SAFETY DATA SHEET

Spotcheck SKD-S2 Aerosol

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name:	Spotcheck SKD-S2 Aerosol
Unique formula identifier (UFI):	PKWV-Q0NU-J005-XJ54

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:	Non-destructive testing Restricted to professional and industrial use.
Uses advised against :	This product is not recommended for any use other than the identified uses above.

1.3. Details of the supplier of the safety data sheet

Company and address:	**Magnaflux® (A Division of ITW Ltd)** Faraday Road, South Dorcan Industrial Estate SN3 5HE Swindon, Wiltshire United Kingdom T +44 (0)1793 524566 https://magnaflux.eu/en
E-mail:	support.eu@magnaflux.com
Revision:	07/04/2026
SDS Version:	11.0
Date of previous version:	02/04/2026 (11.0)

1.4. Emergency telephone number

Emergency phone number: +44(0)203 394 9866
Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)
General public:
England - Dial 111 to reach NHS 111 (24 hour service)
Scotland - Dial 111 to reach NHS 24 (24 hour service)
Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)
See section 4 “First aid measures”.

SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2; H319, Causes serious eye irritation.
STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s):



Signal word: Danger

Hazard statement(s): Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)

Precautionary statement(s):

General: Not applicable.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)
Wear eye protection/protective gloves/protective clothing. (P280)

Response: Not applicable.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal: Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances: propan-2-ol

Additional labelling: EUH066, Repeated exposure may cause skin dryness or cracking.

UFI: PKWV-Q0NU-J005-XJ54

2.3. Other hazards

Additional warnings: In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH: Index No.: 603-117-00-0	25-40%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
butane	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: REACH Exempt (Article 2, 7b) Index No.: 601-004-00-0	15-25%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	[3]
propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: REACH Exempt (Article 2, 7b) Index No.: 601-003-00-5	15-25%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 UK-REACH: REACH Exempt (Article 2, 7b) Index No.: 601-004-00-0	10-15%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
acetone;propan-2-one;propanone	CAS No.: 67-64-1 EC No.: 200-662-2 UK-REACH: Index No.: 606-001-00-8	10-15%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1], [3]
Oxirane, 2-methyl-, polymer with oxirane, mono(2-propylheptyl) ether	CAS No.: 166736-08-9 EC No.: UK-REACH: REACH Exempt (Article 2, 9) Index No.:	<0.1%	Acute Tox. 4, H302 Eye Dam. 1, H318	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.
[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information: In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:	Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.
Skin contact:	IF ON SKIN: Wash with plenty of water and soap. Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
Eye contact:	If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
Ingestion:	If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.
Burns:	Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.
In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.
Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO2)
Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.
Hazchem Code: None

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.
Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 “Disposal considerations” on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid static electricity.
Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition. Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material:	Keep only in original packaging.
Storage conditions:	10 - 30°C
Incompatible materials:	Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

propan-2-ol
Long term exposure limit (8 hours) (ppm): 400
Long term exposure limit (8 hours) (mg/m^3): 999
Short term exposure limit (15 minutes) (ppm): 500
Short term exposure limit (15 minutes) (mg/m^3): 1250

butane
Long term exposure limit (8 hours) (ppm): 600
Long term exposure limit (8 hours) (mg/m^3): 1450
Short term exposure limit (15 minutes) (ppm): 750
Short term exposure limit (15 minutes) (mg/m^3): 1810
Annotations:
Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

acetone;propan-2-one;propanone
Long term exposure limit (8 hours) (ppm): 500
Long term exposure limit (8 hours) (mg/m^3): 1210
Short term exposure limit (15 minutes) (ppm): 1500
Short term exposure limit (15 minutes) (mg/m^3): 3620

Aluminium hydroxide
Long term exposure limit (8 hours) (mg/m^3): 2

Calcium carbonate
Long term exposure limit (8 hours) (mg/m^3): 10(inhalable)/4(respirable)

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

acetone;propan-2-one;propanone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	200 mg/m³
Long term – Systemic effects - Workers	Inhalation	1210 mg/m³
Short term – Local effects - Workers	Inhalation	2420 mg/m³
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day

Calcium carbonate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	1.06 mg/m³
Long term – Local effects - Workers	Inhalation	4.26 mg/m³
Long term – Systemic effects - General population	Inhalation	10 mg/m³
Long term – Systemic effects - Workers	Inhalation	10 mg/m³

propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m³
Long term – Systemic effects - Workers	Inhalation	500 mg/m³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day

PNEC

acetone;propan-2-one;propanone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		10.6 mg/L
Intermittent release (freshwater)		21 mg/L
Marine water		1.06 mg/L
Marine water sediment		3.04 mg/kg
Sewage treatment plant		29.5 mg/L
Soil		33.3 mg/L

propan-2-ol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg

Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios implemented for this product.

Exposure limits: Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures: Apply standard precautions during use of the product. Avoid inhalation of gas or dust.


Hygiene measures: In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure: No specific requirements.

Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:

Work situation	Type	Class	Colour	Standards	
In case of inadequate ventilation	Combination filter AXP2		Brown/White	EN14387, EN143	

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,7	> 480	EN374-2, EN16523-1, EN388	

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	White
Odour / Odour threshold:	Alcohol odor
pH:	7
Density (g/cm^3):	0.88 (20 °C)
Kinematic viscosity:	<10 mm^2/s (38 °C)
Particle characteristics:	No data available

Phase changes

Melting point/Freezing point (°C):	<-89
Softening point/range (°C):	Does not apply to aerosols.
Boiling point (°C):	>55.8
Vapour pressure:	138 mmHg (20 °C)
Relative vapour density:	>1
Decomposition temperature (°C):	No data available

Data on fire and explosion hazards

Flash point (°C):	-6
Flammability (°C):	The material is ignitable.
Auto-ignition temperature (°C):	>399
Lower and upper explosion limit (% v/v):	2 - 15

Solubility

Solubility in water:	85%
n-octanol/water coefficient (LogKow):	No data available
Solubility in fat (g/L):	No data available

9.2. Other information

Note: The above properties are for the bulk product and not the aerosol.
Flash point of the aerosol propellent: -40 °C

Evaporation rate (n-butylacetate = 100):	>100
▼VOC (g/l):	812
Oxidizing properties:	No data available
Other physical and chemical parameters:	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity
No data available.

10.2. Chemical stability
The product is stable under the conditions, noted in section 7 “Handling and storage”.

10.3. Possibility of hazardous reactions
None known.

10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Based on available data, the classification criteria are not met.

Product/substance	propan-2-ol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>5000 mg/kg

Product/substance	propan-2-ol
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	>5000 mg/kg

Product/substance	propan-2-ol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (6 hours)
Result:	>10000 ppm

Product/substance	acetone;propan-2-one;propanone
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5800 mg/kg

Product/substance	acetone;propan-2-one;propanone
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	76 mg/L

Product/substance	acetone;propan-2-one;propanone
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	15800 mg/kg

Product/substance	Aluminium hydroxide
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg

Product/substance	Aluminium hydroxide
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	>2.3 mg/L

Product/substance	Calcium carbonate
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	>2000 mg/kg

Product/substance	Calcium carbonate
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg

Product/substance	Calcium carbonate
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	>3 mg/L

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Product/substance	butane
Species:	Rat
Route of exposure:	Inhalation
Duration:	42 days
Test:	NOAEL
Result:	16000 ppm

Product/substance	isobutane
Species:	Rat
Route of exposure:	Inhalation
Duration:	42 days
Test:	NOAEL
Result:	16000 ppm

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

11.2. Information on other hazards

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data, the classification criteria are not met.

Product/substance	propan-2-ol
Species:	Fish
Duration:	48 hours
Test:	LC50
Result:	>100 mg/L

Product/substance	propan-2-ol
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	>100 mg/L

Product/substance	propan-2-ol
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	>100 mg/L

Product/substance	butane
Test method:	QSAR
Species:	Fish
Test:	LC50
Result:	147.54 mg/L

Product/substance	propane
Test method:	QSAR
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	147.54 mg/L

Product/substance	propane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	49.9 mg/L

Product/substance	propane
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	27.1 mg/L

Product/substance	propane
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	11.9 mg/L

Product/substance	isobutane
Test method:	QSAR
Species:	Fish

Duration:	96 hours
Test:	LC50
Result:	147.54 mg/L

Product/substance	acetone;propan-2-one;propanone
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	5540 mg/L

Product/substance	acetone;propan-2-one;propanone
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	>100 mg/L

Product/substance	acetone;propan-2-one;propanone
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	8800 mg/L

Product/substance	acetone;propan-2-one;propanone
Species:	Bacteria
Result:	1000 mg/L

Product/substance	acetone;propan-2-one;propanone
Species:	Daphnia
Duration:	28 days
Test:	NOEC
Result:	2.212 mg/L

Product/substance	Calcium carbonate
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	>200 mg/L

Product/substance	Calcium carbonate
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	>56000 mg/L

Product/substance	Calcium carbonate
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	>1000 mg/L

Product/substance	Calcium carbonate
Species:	Algae
Duration:	72 hours

Test: IC50
Result: >10000 mg/L

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability
Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential
Based on available data, the classification criteria are not met.

12.4. Mobility in soil
No data available.

12.5. Results of PBT and vPvB assessment
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties
This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects
None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods
Product is covered by the regulations on hazardous waste.
HP 3 - Flammable
HP 4 - Irritant (skin irritation and eye damage)
Dispose of contents/container to an approved waste disposal plant.
Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code
Not applicable.

Specific labelling

Contaminated packing
Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IMDG	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS, flammable	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.
ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.
IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.
IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.
Hazchem Code: None

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:	Restricted to professional users. People under the age of 18 shall not be exposed to this product. Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.
Demands for specific education:	No specific requirements.
Control of Major Accident Hazards (COMAH) -	P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Categories / dangerous substances:	
Regulation on drug precursors:	acetone;propan-2-one;propanone is included (Category 3)
Regulation on explosives precursors:	acetone;propan-2-one;propanone (Annex II)
UK-REACH, Annex XVII:	acetone;propan-2-one;propanone is subject to restrictions, UK-REACH annex XVII (entry 40). propan-2-ol is subject to UK-REACH restrictions (entry 40). butane is subject to UK-REACH restrictions (entry 40). propane is subject to UK-REACH restrictions (entry 40). isobutane is subject to UK-REACH restrictions (entry 40). acetone;propan-2-one;propanone is subject to UK-REACH restrictions (entry 40).
Additional information:	Not applicable.
Sources:	The Health and Safety at Work etc. Act 1974 Regulations 2013. The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29). Control of Major Accident Hazards (COMAH) Regulations 2015. Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law. The Controlled Drugs (Drug Precursors) Regulations 2008. Council Regulation (EC) No 2019/1148 on explosives precursors as retained and amended in UK law. Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law. Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H220, Extremely flammable gas.
H225, Highly flammable liquid and vapour.
H280, Contains gas under pressure; may explode if heated.
H302, Harmful if swallowed.
H318, Causes serious eye damage.
H319, Causes serious eye irritation.
H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = Effective concentration
ED = Effective dose
EINECS = European Inventory of Existing Commercial chemical Substances
EL = Effective Loading
ErC = Concentration associated with x% growth rate response
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
HP = Hazardous Property code
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IC = X maximum inhibitory concentration
IMDG = International Maritime Dangerous Goods
LC = Lethal concentration
LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans
LD = Lethal dose
LOAEC = Lowest Observed Adverse Effect Concentration
LOAEL = Lowest Observed Adverse Effect Level
LOEC = Lowest Observed Effect Concentration
LogKow = logarithm of the n-octanol/water coefficient
LL = Lethal Loading
M = For multiplication factor
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOAEC = No Observed Adverse Effect Concentration
NOAEL = No Observed Adverse Effect Level
NOEC = No Observed Effect Concentration
NOELR = No Observable Effect Loading Rate
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit

SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.
The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Magnaflux

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
It is recommended to hand over this safety data sheet to the actual user of the product.
Information in this safety data sheet cannot be used as a product specification.
Country-language: GB-en