ZMM BULGARIA CU1250 - PERIODIC MAINTENANCE SCHEDULE

Frequency	Maintenance task	Acceptance / action
Weekly	Clean entire machine.	Machine clean; chips and deposits removed.
Weekly	Remove chuck jaws, clean and lubricate them.	Jaws clean, lubricated and operating smoothly.
Monthly	Check main drive V-belts.	Check tension and smooth drive; clean, adjust or replace as necessary.
Monthly	Clean coolant tank.	Tank cleaned and serviceable.
Monthly	Check clutch for spindle forward/reverse rotation.	Check operation; adjust if necessary.
Monthly	Lubricate quadrant gears.	Apply grease as specified by the machine lubrication instructions.
3 Monthly	Check machine levelling in both horizontal directions.	Record result and correct levelling if necessary.
6 Monthly	Gearbox oil change after routine service interval.	Change oil per manufacturer lubrication instructions.
6 Monthly	Feed box oil change.	Change periodically using the same interval described for gearbox.
Annually	Check gearbox and spindle rotation accuracy/run-out; nuts and lock rings.	Inspect and correct defects.
Annually	Check bearings and guide-way clearance.	Inspect and correct excessive clearance.
Annually	Check carriage functioning.	Smooth, correct operation.
Annually	Check tool holder functioning.	Secure and correct operation.
Annually	Check tailstock functioning.	Smooth travel, clamping and correct function.
Annually	Clean and refill quadrant gear bearing housings with grease.	Clean and grease as specified.
Periodic	Electrical cabinet/protection circuit check by authorized electrician.	Power isolated; checks per electrical safety requirements/site procedure.

Safety: Maintenance and checks are to be performed with the machine shut down. Disconnect the main power supply and prevent unintended switching-on before maintenance. Electrical cabinet work is for qualified and authorized personnel only.

Reference basis: ZMM-Sliven CU800RD/CU1000RD/CU1250RD Manual for Machine Installation, Maintenance and Operation, especially Sections 2.6, 3.5, 6.1, 6.2 and 10.4. Verify the exact model/variant and lubricant table against the machine nameplate/manual before servicing.