

Plant calendar — Screen processing design

006_DD-SPD version 1 elaborates SCR-006, FN-037–040 and REQ-070–075. WI-010 approved plan revision 1 step 9. Design only; not implemented.

1. Document control and references

Field		Value	
Document ID / version		006_DD-SPD / 1	
System / subsystem		ProductionManagementAI / Master data	
Work item / author		WI-010 / Agent	
Created / updated		2026-10-02 / 2026-10-02	
Review state		Submitted for review; not implemented	

Version	Date	Author	Change
1	2026-10-02	Agent	Initial client flows, focus/reconciliation behavior and detailed previews

Sources: [requirements](#), [BD](#), [DB](#), [main DD](#), [API](#), [FN](#), [decisions](#) and [plan](#). Prior designs are approved and immutable. Main DD owns the three state diagrams and transition tables; API owns transport, fields/errors; FN owns database algorithms. This document owns client execution, keyboard/focus and detailed state previews; it does not duplicate those catalogs.

2. Screen layout and mockup

Mockup artifact: [English-caption static gallery](#) and [Japanese-caption edition](#). The design/publishing tool is unavailable; local HTML rendered in Chromium is the existing bounded fallback. No external publishing or application API simulation. Twelve artboards: loading/unconfigured; populated month; weekly create/edit; no matching choices; validation; past/retired restrictions; known success with refresh error; conflict; unknown observation; confirmation; retained history; capacity unavailable. Both editions show Japanese UI, with translated captions.

Reuse white/gray surfaces, gray borders, rounded 48px controls, orange primary buttons and Japanese system fonts from existing master screens. Desktop >=640px uses shared navigation and a semantic month table; smaller widths use Menu and an ordered day agenda, stacked fields/actions/history. No new component kit. The sampled October 12 line exception reopens a plant closure for 4 hours; P-1001 at 0.125 min/個 yields 1,920 個. Illustrations are not seed or runtime evidence.

1

生産管理 / 稼働カレンダー

2

保存結果・入力エラー・現在の参照結果

3

表示月 対象ライン 適用 前月/翌月

4

稼働 休業 未設定 / 適用元

5

2026年10月 月/火/水/木/金/土/日
12日 稼働 ライン例外 4時間
17日 休業 週間規則 0時間

6

選択日 適用元・下位の規則・理由
ライン例外 > 工場例外 > 週間規則

7

週間規則 日付例外 履歴

8

参考能力: ライン 製品 日付 確認
現設定による参考値・製造指示の割当なし

9

P-1001 1,920 個 / または表示不可

15

保持版・削除/取消の記録
表示範囲・参照版・前へ/次へ

16

削除後は下位の規則を適用・記録を保持
対象 L-001 / 2026-10-12
キャンセル [初期フォーカス] 削除する

1

稼働カレンダー メニュー

2

読込・エラー・参照結果

3

表示月 対象ライン
適用 前月／翌月

4

稼働 休業 未設定

5

10月12日（月） 稼働
ライン例外 4時間
10月17日（土） 休業

6

選択日 適用元・下位規則
理由はテキストとして表示

7

週間規則 日付例外 履歴

8

参考能力 ライン／製品／日付
確認

9

1,920 個 または表示不可

10

対象 L-001 ／ 2026-10-12

11

週間モード：有効開始日・曜日
月 火 水 木 金 土 日

12

日付モード：稼働／休業
ライン設定を使用 ／ 時間

13

理由（任意）

14

保存 キャンセル 削除
結果不明：現在の状態を確認
入力を破棄して現在の状態を使用

15

保持版・取消／削除の記録
参照範囲・前へ／次へ

16

日付例外を削除しますか？
対象 L-001 ／ 2026-10-12
下位の規則が適用されます。
記録は保持されます。
キャンセル [初期フォーカス]
削除する

The phone sheet has two separate panels: lookup and editor/reconciliation. They represent successive screen modes, not a simultaneous two-column phone layout.

Region	Ownership / visible content
1	Shared header/current CalendarRange navigation; phone Menu
2	Status/error summary, restrictions and read-only unknown observations
3	Draft month/scope, Apply and bounded previous/next month
4	Working/closed/unavailable and source legend
5	Month day buttons / ordered phone agenda
6	Selected date, winning source, fallback and reason
7	Weekly/date/history actions, dependent on observed permissions
8	Independent line/product/date capacity selections and request
9	Exact quantity/unit or unavailable reason; no cross-unit totals
10	Captured date/scope or new weekly effective date
11	Seven weekly checkboxes; all closed valid
12	Working/closed, inherited/explicit hours
13	Optional reason, plain text
14	Save/Cancel/remove/withdraw and reconciliation actions
15	Bounded current/history pages, marker identity and predecessor
16	Centered remove/withdraw/discard confirmation; safe initial focus

3. Process list and shared invariants

All component names below are proposed files under features/plant-calendar/; authored/updated by Agent on 2026-10-02. Includes/ASPX/XML files: not applicable. Existing shared components and the single Japanese catalog are reused.

Block	Owner / purpose	Used components/services	Traceability
P-01	PlantCalendarPage; applied URL and read rendering	AppHeader, GuardedLink, API-PC-01/02/08	FN-037, REQ-070/074/075
P-02	WeeklyPatternEditor; current/retained definitions	DraftValidation, Confirmation, API-PC-03/04/05	FN-038, REQ-071/074
P-03	DateExceptionEditor; exact target and history	DraftValidation, Confirmation, API-PC-02/06/07/11	FN-039, REQ-072/074

Block	Owner / purpose	Used components/services	Traceability
P-04	CapacityPanel; independent current reference result	API-PC-08/09/10, exact display formatter	FN-040, REQ-073/074
P-05	CalendarConfirmation; action and guarded departure	Native dialog, existing navigation guard	REQ-074
P-06	CalendarDraftValidation; normalized draft/errors	DateTextRule, HoursTextRule, ReasonTextRule	REQ-071/072/074
P-07	CalendarApi adapter; cancellation/auth/settlement	Existing same-origin apiClient/session	All requirements

Separate applied key, filter draft, editor baseline, editor draft and request sequence. Read keys include operation, scope/date/range/search/page and requested snapshot token where applicable. Every request also has a monotonic local sequence; accept only the current key/sequence while mounted and authorized. Aborting a superseded read is normal, not a displayed failure. Client sequences are never server revisions. Do not join two responses into a claimed single snapshot.

Baseline stores the exact returned context version and target id, including a removed/withdrawn marker. Never substitute a winning lower-priority source id for the exact editable target. Never borrow a version from a choices/capacity response to upgrade an old draft. No draft, reason, token or history snapshot in storage or URL; memory only. Navigation URLs contain only BD's five allowed parameters.

4. Processing design

4.1 P-01 — PlantCalendarPage

Detail: restore calendar context and present request-keyed lookup. Dependencies are listed in section 3; result is the existing main DD read state.

Step	Processing / branch	Calls	Result / focus
1	Require current Admin/Operator session; strict parse month/lineId/date/mode/productId, reject repeated/unknown keys, invalid combinations or unsupported values	Existing session; local validator	Invalid URL: safe reset action, no calendar request
2	Get server date basis. If month omitted, use valid URL date's month, otherwise server plant month. Day mode requires date; explicit month/date mismatch rejected; product requires line	API-PC-08 supplies context	Never derive plant today from browser clock; heading focus on route entry
3	Apply validated default URL with replace; absent date selects server today if in applied month, otherwise first real date	Router	Applied month/scope/date recorded; canonical UUID casing
4	Fetch month and active line choices; show retained selected line from scope even when absent from active choices	API-PC-01/08	Loading; no old data relabeled; unavailable coverage is HTTP 200, not read error
5	Render 28–31 real dates; desktop padding inert, no adjacent-month day actions. Select date using native button; fetch independent details keyed to date/scope	API-PC-02	Selected-day source/fallback shown as text, not partial hour merge

Step	Processing / branch	Calls	Result / focus
6	If month/day versions differ, mark month older and perform one month refresh. If still different, show refresh-needed notice; do not combine as coherent or auto-loop	API-PC-01	Day remains its own observation; editor baseline always day response
7	Filter edits only change local controls. Apply validates, updates URL, aborts obsolete reads and clears capacity; previous/next directly applies bounded month and a real selected day	API-PC-01/02	At 0001-01/9999-12 respective boundary action disabled; announce month, keep initiating control focus
8	Enter weekly/day/history from successful authoritative context; dirty editor departure uses P-05	Router; P-02/03	Editors initialize via their own read; invalid/past/unactivated restrictions visible
9	Read failure: show safe message and explicit read retry; unknown line offers reset scope. Auth error delegates P-07	API-PC-01/02	No fabricated month, no hidden old successful result under new labels

URL reset is an explicit user action, not silent recovery. Month/day queries omit mode/productId and absent lineId; editors/history send only their endpoint's keys. For retained past days show recorded state/source/explicit hours; any inherited hours are labeled current line settings, not historical actual capacity.

4.2 P-02 — WeeklyPatternEditor

Detail: edit one effective start, inspect retained versions and future withdrawal. Return transitions are main DD Clean/Dirty/Confirming/Saving and settlement states.

Step	Processing / branch	Calls	Result / focus
1	Query selected range <=366 dates, initially applied month. Current view includes markers; show applicableBeforeFrom separately. History selection is read-only	API-PC-03	Empty range does not mean no predecessor; range/page controls remain available
2	For new start, default server today; fetch Current with from=to=chosen date to capture exact target or marker and version. For edit, select current row's immutable start	API-PC-03	Never reuse predecessor id as target; year 9999 safe
3	Initialize weekdays from current nonwithdrawn target; new/withdrawn target uses observed applicable pattern, or Mon–Fri proposal when absent. Creation/re-add is an explicit staged intent	Local draft	New intent counts as a change; existing unchanged payload disables Save
4	Toggle checkboxes in Mon..Sun order, allowing []. Change date on a new intent discards/reinitializes only after dirty confirmation; saved start cannot move	P-05/06; API-PC-03	Baseline and draft distinct; past rows read-only
5	Save valid changed today/future draft once with captured version/id and exact weekday tokens	API-PC-04	Saving; disable write/field changes, keep progress text
6	Future current nonwithdrawn row may request withdrawal; initial activation/today/past disallowed. Confirm captured row, not currently highlighted replacement	P-05; API-PC-05	Append marker; no physical deletion or draft autosave
7	Current/History view, range and paging are read-only; page 2+ carries first page snapshotVersion. Stale paging keeps observation and requires explicit page-1 restart	API-PC-03	No combined revision pages; changing range/view resets page/token

Step	Processing / branch	Calls	Result / focus
8	Settle write through P-07. Known success returns calendar with saved context; conflict/unknown preserves draft	P-07; P-01	Heading/status focus after return; guarded Cancel remains possible

A future date outside the initial month is inspected with its own bounded range; there is no hidden all-future query or added business scheduling horizon.

4.3 P-03 — DateExceptionEditor

Detail: save/remove one plant or line date exception; history independent of draft.

Step	Processing / branch	Calls	Result / focus
1	Read exact scope/date; exception null means never configured, removed marker retained for re-add. Store response context and target	API-PC-02	Existing identity labels immutable; new target opened from selected date/scope
2	Initialize from live exception; new/removed target requires explicit Working/Closed choice. Inherited working stores null hours; plant label explains dependence on selected line	Local draft	No invented eight-hour default or lower-override merging
3	Closed clears hours and inherit control; working/inherit clears explicit hours; switching to explicit requires new valid text. Reason stays independent	P-06	Hidden contradictory values never submitted; focus stays on initiating control
4	Validate normalized draft and ≤ 8 KiB UTF-8 JSON including property/escape overhead; save once with all required nullable properties	API-PC-06	No float coercion; capture exact scope/date/id/version
5	Remove only current nonremoved target today/future; retired line permits existing removal despite disabled create/edit. Confirm fallback and retained history	P-05; API-PC-07	No request on dismissal; no pending draft save
6	Inspect history for exact scope/date, paged token from page 1; show isCurrent, marker, commitRevision/date and plain reason. History is never an editable baseline	API-PC-11	Read-only; stale page restarts explicitly; current snapshot returned independently
7	Past, unactivated or retired restrictions render text; preserve permitted draft after authoritative rejection. Refresh observation separately, never silently rebase	API-PC-02; P-07	Save blocked where restricted; removal eligibility distinct
8	Known success/known rejection/conflict/unknown uses P-07; guarded Cancel returns calendar preserving applied lookup context	P-07/05/01	No blind replay; selected day restored

4.4 P-04 — CapacityPanel

Detail: descriptive current capacity only; never order allocation or load scheduling.

Step	Processing / branch	Calls	Result / focus
1	Require line and today/future date; default applied active line/day if eligible. Past lookup remains available outside this panel	API-PC-08	Active paged choices; no eligible line -> explicit empty guidance
2	Line change clears product/result, aborts obsolete choices/capacity; query literal product search with applied q/page and selected line	API-PC-09	No matches differs from failed read; retained URL product shown as unconfirmed until validated
3	Select current product from eligible pages or retain a requested URL id for server eligibility lookup; do not claim eligibility from identifier alone	Local selection	No silent replacement with first product; no stale quantity
4	Explicit lookup sends line/product/date only. Product/date/search changes invalidate old result; current key/sequence gates completion	API-PC-10	Independent Loading/Ready/Unavailable/ReadError
5	Available result uses server quantity/minutes/hours strings, exact display grouping without binary float arithmetic. Closed valid pair displays 0 with unit	Display formatter	Show current-settings notice, source and unit; no total across products
6	Unavailable shows reason text and no quantity/coefficient; UnitStale directs user to Production lines separately, never auto-reconfirms timing	Display mapping	Invalid pair remains unavailable even on a closed day
7	Read error offers explicit retry; server plantToday can invalidate a now-past date. After any known calendar mutation invalidate prior capacity	API-PC-10; P-07	Request/focus stays in panel; status announced without focus theft

Separate responses may have different contexts; a capacity result explains its own returned day and references, never combines a month day with a later coefficient.

4.5 P-05 — CalendarConfirmation and navigation

Detail: captured destructive intent and discard destination, one dialog at a time. Uses native showModal/top layer, existing navigation guard and GuardedLink.

Step	Processing / branch	Calls	Result / focus
1	Capture action, logical target, target id/version, draft-state and invoker; leave/discard also captures intended route/history destination	Local intent	Dialog title/scope/date/consequence; not mutable current selection
2	Open native centered dialog with labeled title and short description, viewport max width/height and internal overflow	showModal	Initial Cancel focus; background inert; no document-centered absolute positioning
3	Tab/Shift+Tab stay within dialog. Escape/Cancel/backdrop dismissal performs no mutation and retains draft; restore invoker, or editor heading if removed	close	Restore prior Clean/Dirty/Unknown; no stacked dialogs
4	Confirm remove/withdraw only if captured context still matches and permitted; otherwise close with error and no request	API-PC-05/07 via editor	Submit once then dismiss to Saving; duplicate clicks disabled
5	Confirm discard/reload/accept observation clears original draft only explicitly; reload creates new baseline, never replays old request	P-01/02/03	Cancel keeps original values; no payload-equality success inference

Step	Processing / branch	Calls	Result / focus
6	Dirty route/menu/Cancel/Back/Forward uses existing guard; declined pop restores history position, accepted departure reaches captured target once	NavigationGuardProvider	Saving blocks in-app departure; Unknown allows confirmed discard/leave
7	Browser refresh/tab-close uses supported beforeunload warning while dirty/pending/unknown	Browser	Warning is not guaranteed; unloading never proves rollback

Long content remains scrollable above the mobile keyboard; controls are not hidden behind fixed page footers. Follow [WAI dialog_guidance](#) for contained focus and return to the invoker. Runtime keyboard/centering checks are still required; a static illustration cannot establish modal compliance.

4.6 P-06 — CalendarDraftValidation

Detail: synchronous local input checks, never authoritative business permission. No external calls. Required field rules remain main DD/API; no duplicate catalog.

Step	Processing / branch	Result
1	Normalize into a separate payload; preserve visible input until correction/success. Date/month parse Gregorian text, including leap years and full bounds	Structured errors, no timezone conversion
2	Hours trim and exact syntax/range/scale checks, no Number/parseFloat, exponent/grouping/rounding. Closed/inherit emits null	Exact hours string or field error
3	Unicode validate, trim reason, blank null; count code points after trim, internal whitespace unchanged. JSON UTF-8 byte count after serialization	Safe text and exact payload-size check
4	Weekly distinct enum set; [] valid. Validate required explicit new state, reference and observed editable dates	No guessed concurrency acceptance
5	Compare normalized payload plus logical creation/re-add intent to captured baseline. Invalid/unchanged submit makes no API call	Announce linked errors; focus first invalid field in document order

Use form labels/fieldset legends, aria-invalid and aria-describedby for field errors. Known server field errors map only recognized fields/codes; unknown codes use safe page-level text. Reasons render text nodes; no HTML injection or input echo in diagnostic messages. No analytics of keystrokes, raw notes or revision tokens.

4.7 P-07 — CalendarApi adapter and settlement

Detail: same-origin adapter around existing apiClient; feature-only 25s deadline. All requests use established cookies/session, no framework/dependency change.

Step	Processing / branch	Result
1	Build only approved query/body fields, omit absent optional query fields, keep nullable body members. No automatic write retry	Request captured once; string tokens stay opaque

Step	Processing / branch	Result
2	Validate expected response shape and exact enums/strings. Ignore obsolete reads; cleanup aborts readers but does not assert write rollback	Safe read error; malformed write success becomes Unknown
3	401/403: existing login/forbidden handling, abort/clear feature memory and stop; do not persist draft across authentication	No arbitrary returned HTML; authorization cannot be bypassed by route
4	Valid 200 MutationResult: known commit/no-op, clear submitted draft, return calendar and refresh. changed=false announces unchanged, not a new revision	Success remains known if subsequent read fails; show separate refresh error
5	Valid NotApplied: field validation keeps draft; stale/target mismatch enters Conflict and blocks resubmit until explicit discard/reload. Other rejected writes keep safe restriction/busy message	CALENDAR_BUSY manual retry only, respecting Retry-After; no timer write
6	Missing/invalid outcome, timeout, network loss, aborted write, generic 5xx, CALENDAR_WRITE_UNKNOWN or malformed success: enter Unknown	Block all mutations; keep original draft/identity/version; no success or certain failure claim
7	Verify Unknown with exact day + exception-history, or weekly Current/History range containing captured start. Label each read independently if revisions differ	Verifying -> Unknown with observed values/errors; no claim that this client committed
8	After successful observation user may explicitly discard and accept current baseline; failed verification cannot enable Accept. Re-read latest baseline after acceptance	Unknown -> Loading; stale draft never gets a new token silently
9	Unknown Cancel/leave still permitted with discard confirmation; pending verification canceled as read only	No replay, completion endpoint or idempotency promise

Before auth branching, adapter semantics still treat lost/malformed mutation responses as uncertain; session errors terminate the feature rather than display success. In known success refresh-error state, retry calls only reads. Never send the earlier mutation again merely to obtain a clean calendar view.

5. Japanese UI additions and focus contract

Proposed additions to the existing single catalog; not implemented. Existing shared labels stay unchanged. Quoted messages below have exact Japanese and gloss. The Japanese PDF omits English glosses, keeping message keys and code values.

Proposed key	Japanese UI	English gloss / use
calendar.loading	読込中です。	Loading
calendar.notActivated	カレンダーは未設定です。	Calendar not configured
calendar.readError	読込に失敗しました。再読込してください。	Read failed; reload
calendar.noChoices	選択できる項目がありません。	No selectable choices
calendar.noMatches	条件に一致する項目がありません。	No matching choices

Proposed key	Japanese UI	English gloss / use
calendar.validation	入力内容を確認してください。	Check input
calendar.hoursError	稼働時間は0を超え24以下、小数3桁まで入力してください。	Hours >0, <=24, scale <=3
calendar.pastLocked	過去の日付は変更できません。	Past date immutable
calendar.retiredLocked	このラインは停止中です。新規登録・編集はできません。	Retired line; create/edit blocked
calendar.saved	保存しました。	Confirmed save
calendar.unchanged	変更はありませんでした。	Confirmed no-op
calendar.refreshAfterSave	保存は完了しましたが、表示の更新に失敗しました。	Known save, refresh failed
calendar.conflict	カレンダーが更新されています。再読み込みしてください。	Changed; guarded reload
calendar.unknown	保存結果を確認できません。再送せず現在の状態を確認してください。	Unknown result; inspect without resend
calendar.observation	現在の参照結果です。先ほどの保存成功を証明するものではありません。	Observation is not commit proof
calendar.acceptCurrent	入力を破棄して現在の状態を使用	Discard input and use observed state
calendar.removeTitle	日付例外を削除しますか？	Remove exception?
calendar.removeBody	削除後は下位の規則が適用されます。記録は保持されます。	Fallback restored; history retained
calendar.withdrawTitle	予約した週間規則を取り消しますか？	Withdraw future weekly rule?
calendar.discardTitle	入力を破棄しますか？	Discard draft?
calendar.capacityUnavailable	参考能力を表示できません。	Capacity unavailable
calendar.unitStale	単位が変更されています。生産ライン・工程で時間を再確認してください。	Reconfirm timing after unit change
calendar.currentSettings	現設定による参考値です。製造指示の割当ではありません。	Current reference, no allocation
calendar.historyMarker	削除・取消の記録	Removal/withdrawal marker
calendar.invalidUrl	表示条件を確認してください。	Check URL conditions
calendar.notFound	対象が見つかりません。表示条件を確認してください。	Unknown target; check conditions
calendar.busy	処理が混み合っています。しばらく待ってから再試行してください。	Busy; manual retry after waiting
calendar.timeZoneError	カレンダーの日付設定を確認できません。管理者に連絡してください。	Date basis mismatch; contact administrator
calendar.protectedRule	この週間規則は変更・取消できません。	Protected weekly rule
calendar.requestError	送信内容を確認してください。	Request size/media error

Proposed key	Japanese UI	English gloss / use
calendar.unexpected	処理を完了できませんでした。	Unexpected error
calendar.referenceStopped	対象のライン・製品・組合せは停止中です。	Retired reference
calendar.noTiming	このラインと製品の製造時間が未設定です。	Pair missing
calendar.noCalendar	適用できるカレンダーの記録がありません。	Calendar unavailable

API code / unavailable reason	Catalog key / behavior
VALIDATION	validation + recognized linked field errors
REQUEST_TOO_LARGE / UNSUPPORTED_MEDIA_TYPE	requestError; preserve draft
NOT_FOUND	notFound; no silent target substitution
CALENDAR_STALE / CALENDAR_TARGET_CHANGED	conflict; guarded reload
CALENDAR_PAST_DATE	pastLocked; save blocked
CALENDAR_LINE_RETIRED	retiredLocked; existing removal separately eligible
CALENDAR_PROTECTED_RULE	protectedRule
CALENDAR_NOT_ACTIVATED / NotActivated	notActivated
CALENDAR_BUSY	busy; manual retry respecting Retry-After
CALENDAR_TIMEZONE_MISMATCH	timeZoneError; feature unavailable
CALENDAR_WRITE_UNKNOWN / uncertain transport	unknown; mutation blocked
UNEXPECTED	unexpected for reads; unknown for writes
LineRetired / ProductRetired / PairRetired	referenceStopped; no quantity
PairMissing	noTiming; no quantity
UnitStale	unitStale; no quantity
CalendarUnavailable	noCalendar; no quantity

No arbitrary server title/detail is shown as user text. Unknown enum/schema is a protocol failure rather than a guessed unavailable reason. Read/network failure uses readError; valid write success/no-op uses saved/unchanged, followed by a separate refreshAfterSave if needed. Never translate unavailable to zero.

Focus order: shared header/Menu; month/scope/Apply/previous/next; date buttons or agenda; selected-day actions; capacity inputs/request; mode fields; Save/Cancel/ remove; history controls. Weekly checkbox order is Monday through Sunday. Native buttons use Tab and Enter/Space; no custom ARIA grid or undocumented arrow mode. Only rendered PC or SP day controls are focusable, never both hidden copies. Route/editor entry focuses heading; ordinary completed reads announce status politely without stealing focus. Submitted validation focuses first invalid field; page conflict/unknown uses focusable summary. Unknown verification completion announces observation and retains Verify focus; Accept requires discard dialog.

Use text plus color, visible focus rings, adequate text/control contrast, semantic table headers and labeled date buttons (date/state/source), aria-current=date for today and aria-pressed for selected day. Loading containers use aria-busy; assertive errors do not repeatedly announce on every render. Maintain 48px actions and single-column reflow at 320 CSS px, 200% zoom and enlarged text. Reflow intent follows [WCAG reflow guidance](#). Static browser checks are artifact evidence only; screen-reader/keyboard/mobile keyboard and native zoom compliance require later implemented UI verification.

6. Verification viewpoints and unresolved decisions

Requirement	Later implementation verification
REQ-070	Default server month, valid deep links, repeated/mismatched URL, date bounds, superseded reads and PC/SP focus
REQ-071	New-today predecessor vs exact target, marker re-add, all closed, bounded future/history paging and protected withdrawal
REQ-072	Working/closed/null toggles, Unicode/UTF-8 limits, exact target removal, retired-line removal and retained history
REQ-073	Empty vs no matches vs failure, unit-stale eligibility, exact result display, zero vs unavailable, stale response suppression
REQ-074	Admin/Operator, auth teardown, busy manual retry, conflict, unknown observation/discard, known success with read failure, dialog/dirty history/focus/zoom
REQ-075	No new due-date/start/dashboard calendar dependency; existing order/master flows unchanged

Unresolved business decisions: none. No new architecture, schema or dependency choice. Current scope needs no existing-screen impact DD; plan step 10 assessment and full design/security reconciliation remain after this review. Submit SPD with SVGs, EN/JA mockups and PDFs; await explicit review. Application work requires a later presented and explicitly approved implementation-plan revision.