

# Rajalakshmi Engineering College

Name: Sathish R  
Email: 241001234@rajalakshmi.edu.in  
Roll no: 241001234  
Phone: 7010493502  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 14

#### Section 1 : MCQ

1. What will be the output of the following code?

```
class Demo {  
    void printMessage() {  
        System.out.println("Hello from Demo");  
    }  
}
```

```
public class Main {  
    public static void main(String[] args) {  
        Demo d = new Demo();  
        d.printMessage();  
    }  
}
```

**Answer**

Hello from Demo

**Status :** Correct

**Marks :** 1/1

2. What will be the output of the following code?

```
class MathUtils {  
    int add(int x) {  
        return x + x;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        MathUtils m = new MathUtils();  
        System.out.println(m.add(5));  
    }  
}
```

**Answer**

10

**Status :** Correct

**Marks :** 1/1

3. What is the output of the following code?

```
class Box {  
    int height;  
    Box(int height) {  
        this.height = height;  
    }  
    void modifyHeight(Box b) {  
        b.height += 10;  
    }  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Box b1 = new Box(20);  
        b1.modifyHeight(b1);  
    }  
}
```

```
        System.out.println(b1.height);  
    }  
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

4. What will be the output of the following code?

```
class Box {  
    int length = 5;  
    int width = 4;  
  
    int area() {  
        return length * width;  
    }  
  
    public static void main(String[] args) {  
        Box b = new Box();  
        System.out.println("Area = " + b.area());  
    }  
}
```

**Answer**

Area = 20

**Status :** Correct

**Marks :** 1/1

5. What will be the output of the following code?

```
class A {  
    int val = 20;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        A obj1 = new A();  
    }  
}
```

```
A obj2 = obj1;  
obj2.val += 5;  
System.out.println(obj1.val);  
}  
}
```

**Answer**

25

**Status :** Correct

**Marks :** 1/1

6. What will be the output of the following code?

```
class A {  
    int p = 5;  
    int q = 2;  
}  
  
class Main {  
    public static void main(String[] args) {  
        A obj = new A();  
        System.out.println(obj.p + obj.q);  
    }  
}
```

**Answer**

7

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following code?

```
class Alpha {  
    void greet(String name) {  
        System.out.println("Hello " + name);  
    }  
}  
  
public class Main {
```

```
public static void main(String[] args) {  
    Alpha obj = new Alpha();  
    obj.greet("Anu");  
}  
}
```

**Answer**

Hello Anu

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
class A {  
    int x = 50;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        A obj1 = new A();  
        A obj2 = obj1;  
        obj2.x = 100;  
        System.out.println(obj1.x);  
    }  
}
```

**Answer**

100

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
class Person {  
    String name;  
    void setName(String n) {  
        name = n;  
    }  
    void printName() {
```

```
        System.out.println(name);
    }
}

class Test {
    public static void main(String[] args) {
        Person p = new Person();
        p.printName();
    }
}
```

**Answer**

null

**Status :** Correct

**Marks :** 1/1

10. What will be the output of the following code?

```
class A {
    int y = 30;
}

public class Main {
    public static void main(String[] args) {
        A a1 = new A();
        A a2 = new A();
        a1.y = 50;
        System.out.println(a2.y);
    }
}
```

**Answer**

30

**Status :** Correct

**Marks :** 1/1

11. What will be the output of the following code?

```
class Box {
```

```
int volume(int l, int b, int h) {  
    return l * b * h;  
}  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Box b = new Box();  
        System.out.println(b.volume(2, 3, 4));  
    }  
}
```

**Answer**

24

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following code?

```
class Ball {  
    int size = 11;  
}  
  
class Game {  
    public static void main(String[] args) {  
        Ball b1 = new Ball();  
        Ball b2 = new Ball();  
        b2.size = 10;  
        System.out.println(b1.size);  
    }  
}
```

**Answer**

11

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following code?

```
class Sample {
    int x = 10;

    void display() {
        System.out.println("x = " + x);
    }

    public static void main(String[] args) {
        Sample s = new Sample();
        s.display();
    }
}
```

**Answer**

x = 10

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following code?

```
class Test {
    private int value;
    Test(int value) {
        this.value = value;
    }
    public int getValue() {
        return value;
    }
}

public class Main {
    public static void main(String[] args) {
        Test obj = new Test(10);
        System.out.println(obj.value);
    }
}
```

**Answer**

Compile-time error



**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following code?

```
class Person {  
    int age = 18;  
}  
  
public class Main {  
    public static void main(String[] args) {  
        Person p = new Person();  
        p.age += 2;  
        System.out.println("Age: " + p.age);  
    }  
}
```

**Answer**

Age: 18

**Status :** Wrong

**Marks :** 0/1

# Rajalakshmi Engineering College

Name: Sathish R  
Email: 241001234@rajalakshmi.edu.in  
Roll no: 241001234  
Phone: 7010493502  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q2

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are working as a developer for CityBank, which wants to build a basic account management system.

Each customer at the bank has:

An Account Number (integer) A Customer Name (string) An Initial Balance (double)

The bank allows two types of transactions:

Deposit – increases the balance. Withdrawal – decreases the balance only if enough funds are available.

If the withdrawal amount is greater than the balance, the withdrawal should not happen, and the balance should remain the same.

You are required to implement this system using:

A class with attributes for account details. A constructor to initialize account details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's account details after all transactions.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the account number (integer).
- The following line contains the customer name (string).
- The next line contains the initial balance (double).
- The next line contains the deposit amount (double).
- The next line contains the withdrawal amount (double).

### ***Output Format***

For each customer, print the details in the following format:

1. Account Number: <account\_number>
2. Customer Name: <customer\_name>
3. Final Balance: <final\_balance> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Rahul Sharma

5000

2000

3000

Output: Account Number: 1234

Customer Name: Rahul Sharma

Final Balance: 4000.0

**Answer**

```
import java.util.Scanner;
class Account{
    private int accno;
    private String name;
    private double bal;
    public Account(int accno,String name,double bal){
        this.accno=accno;
        this.name=name;
        this.bal=bal;
    }
    void setacc(int accno){
        this.accno=accno;
    }
    void setname(String name){
        this.name=name;
    }
    void setbal(int bal){
        this.bal=bal;
    }
    public int getacc(){
        return accno;
    }
    public String getname(){
        return name;
    }
    public double getbal(){
        return bal;
    }
    public void deposit(double amnt){
        if(amnt>=0){
            bal+=amnt;
        }
    }
    public void withdrawl(double amnt){
        if(amnt<=bal&&amnt>0){
            bal-=amnt;
        }
    }
}
```

```

    public void display() {
        System.out.println("Account Number: " + accno);
        System.out.println("Customer Name: " + name);
        System.out.printf("Final Balance: %.1f%n", bal);
    }
}
class main{
    public static void main(String[] args){
        Scanner sc=new Scanner(System.in);
        int n=Integer.parseInt(sc.nextLine().trim());
        for(int i=0;i<n;i++){
            int accno = Integer.parseInt(sc.nextLine().trim());
            String name = sc.nextLine().trim();
            double inbal = Double.parseDouble(sc.nextLine().trim());
            double dep = Double.parseDouble(sc.nextLine().trim());
            double withd = Double.parseDouble(sc.nextLine().trim());
            Account cus=new Account(accno,name,inbal);
            cus.deposit(dep);
            cus.withdrawl(withd);
            cus.display();
        }
    }
}

```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Sathish R  
Email: 241001234@rajalakshmi.edu.in  
Roll no: 241001234  
Phone: 7010493502  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Neha is working as a developer for CityElectricity Board, which wants to build a household electricity billing system.

Each customer's electricity account has:

A Customer ID (integer) A Customer Name (string) Units Consumed (double)

The electricity bill is calculated based on these rules:

For the first 100 units 5 units charge per unit For the next 100 units (101–200) 7 units charge per unit For units above 200 10 units charge per unit If the total bill exceeds 2000 units, a 5% discount is applied on the final bill.

Neha has been asked to implement this system using:

A class with attributes for customer details. A constructor to initialize customer details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customers.

Finally, display each customer's details and final bill amount.

### ***Input Format***

The first line of input contains an integer N, representing the number of customers.

For each customer:

- The next line contains the Customer ID (integer).
- The following line contains the Customer Name (string).
- The next line contains the Units Consumed (double).

### ***Output Format***

For each customer, print the details in the following format:

Customer ID: <customer\_id>

Customer Name: <customer\_name>

Final Bill: <final\_bill> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1001

Ravi Kumar

80

Output: Customer ID: 1001

Customer Name: Ravi Kumar

Final Bill: 400.0

### ***Answer***

// You are using Java

```
import java.util.Scanner;
```

```
class Cus {
```

```
    private int cid;
```

```
    private String cna;
```

```
    private double cun;
```

```
    public Cus(int cid, String cna, double cun) {
```

```
        this.cid = cid;
```

```
        this.cna = cna;
```

```
        this.cun = cun;
```

```
    }
```

```
    public double cal() {
```

```
        double bil = 0, x = cun;
```

```
        if (x > 0) { double t = Math.min(x,100); bil += t*5; x -= t; }
```

```
        if (x > 0) { double t = Math.min(x,100); bil += t*7; x -= t; }
```

```
        if (x > 0) bil += x*10;
```

```
        if (bil > 2000) bil *= 0.95;
```

```
        return bil;
```

```
    }
```

```
    public void dis() {
```

```
        System.out.println("Customer ID: " + cid);
```

```
        System.out.println("Customer Name: " + cna);
```

```
        System.out.printf("Final Bill: %.1f%n", cal());
```

```
    }
```

```
public class Main {
```

```
    public static void main(String[] args) {
```

```
        Scanner scn = new Scanner(System.in);
```

```
        int n = Integer.parseInt(scn.nextLine().trim());
```

```
        for (int i=0;i<n;i++){
```

```
            int cid = Integer.parseInt(scn.nextLine().trim());
```

```
            String cna = scn.nextLine().trim();
```

```
            double cun = Double.parseDouble(scn.nextLine().trim());
```

```
            Cus c = new Cus(cid,cna,cun);
```

```
            c.dis();
```

```
        }
```

```
        scn.close();
```

```
    }
```



}

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sathish R  
Email: 241001234@rajalakshmi.edu.in  
Roll no: 241001234  
Phone: 7010493502  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q4

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

You are working as a developer for CityCab, a taxi service company that wants to build a ride fare management system.

Each customer booking has:

A Booking ID (integer) A Customer Name (string) A Distance Travelled in km (double)

The fare calculation rules are:

Base Fare = 50 units (flat charge for every ride). Per km charge = 10 units/km. If the distance is greater than 20 km, a 10% discount is applied on the total fare.

You are required to implement this system using:

A class with attributes for booking details. A constructor to initialize booking details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent customer rides.

Finally, display each booking's details and final fare.

### ***Input Format***

The first line of input contains an integer N, representing the number of bookings.

For each booking:

- The next line contains the booking ID (integer).
- The following line contains the customer's name (string).
- The next line contains the distance travelled (double).

### ***Output Format***

For each booking, print the details in the following format:

1. Booking ID: <booking\_id>
2. Customer Name: <customer\_name>
3. Final Fare: <final\_fare> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1  
1234  
Rahul Sharma  
15

Output: Booking ID: 1234  
Customer Name: Rahul Sharma  
Final Fare: 200.0

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
class Booking {
    private int bookingId;
    private String customerName;
    private double distance;
    private double fare;

    public Booking(int bookingId, String customerName, double distance) {
        this.bookingId = bookingId;
        this.customerName = customerName;
        this.distance = distance;
        calculateFare();
    }

    public void setBookingId(int bookingId) {
        this.bookingId = bookingId;
    }

    public void setCustomerName(String customerName) {
        this.customerName = customerName;
    }

    public void setDistance(double distance) {
        this.distance = distance;
        calculateFare();
    }

    public int getBookingId() {
        return bookingId;
    }

    public String getCustomerName() {
        return customerName;
    }

    public double getDistance() {
        return distance;
    }

    public double getFare() {
        return fare;
    }
}
```

```

private void calculateFare() {
    fare = 50 + (distance * 10);
    if (distance > 20) {
        fare = fare - (fare * 0.1);
    }
}

}

class CityCabApp {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);
        int n = Integer.parseInt(sc.nextLine());
        for (int i = 0; i < n; i++) {
            int id = Integer.parseInt(sc.nextLine());
            String name = sc.nextLine();
            double distance = Double.parseDouble(sc.nextLine());
            Booking booking = new Booking(id, name, distance);
            System.out.println("Booking ID: " + booking.getBookingId());
            System.out.println("Customer Name: " + booking.getCustomerName());
            System.out.printf("Final Fare: %.1f\n", booking.getFare());
        }
        sc.close();
    }
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Sathish R  
Email: 241001234@rajalakshmi.edu.in  
Roll no: 241001234  
Phone: 7010493502  
Branch: REC  
Department: IT - Section 2  
Batch: 2028  
Degree: B.E - IT

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 5\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Ram is working as a developer for BrightEdu Coaching Center, which wants to build a student fee management system.

Each student's enrollment has:

An Enrollment ID (integer) A Student Name (string) The Number of Subjects (integer)

The fee calculation rules are:

Registration Fee = 1000 units (flat for every student). Per Subject Fee = 800 units. If the student enrolls in more than 5 subjects, a 20% scholarship (discount) is applied on the total fee.

Ram has been asked to implement this system using:

A class with attributes for student details. A constructor to initialize student details. Setter methods to update details if needed. Getter methods to retrieve details. Objects of the class to represent student enrollments.

Finally, display each student's details and final fee.

### ***Input Format***

The first line of input contains an integer N, representing the number of students.

For each student:

- The next line contains the Enrollment ID (integer).
- The following line contains the student's name (string).
- The next line contains the Number of subjects (integer).

### ***Output Format***

For each student, print the details in the following format:

- Enrollment ID: <enrollment\_id>
- Student Name: <student\_name>
- Final Fee: <final\_fee> (rounded to one decimal place)

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 1

1234

Ravi Kumar

3

Output: Enrollment ID: 1234

Student Name: Ravi Kumar

Final Fee: 3400.0

### ***Answer***

```
// You are using Java
import java.util.Scanner;
```

```
class Stu {
```

```

private int eid;
private String sna;
private int sub;

public Stu(int eid, String sna, int sub) {
    this.eid = eid;
    this.sna = sna;
    this.sub = sub;
}

public double fee() {
    double f = 1000 + sub * 800;
    if (sub > 5) f *= 0.8;
    return f;
}

public void dis() {
    System.out.println("Enrollment ID: " + eid);
    System.out.println("Student Name: " + sna);
    System.out.printf("Final Fee: %.1f%n", fee());
}
}

public class Main {
    public static void main(String[] args) {
        Scanner scn = new Scanner(System.in);
        int n = Integer.parseInt(scn.nextLine().trim());
        for (int i = 0; i < n; i++) {
            int eid = Integer.parseInt(scn.nextLine().trim());
            String sna = scn.nextLine().trim();
            int sub = Integer.parseInt(scn.nextLine().trim());
            Stu s = new Stu(eid, sna, sub);
            s.dis();
        }
        scn.close();
    }
}

```

**Status :** Correct

**Marks : 10/10**