Govt. Public Examination - 2024

COMPUTER SCIENCE - XII STD - ANSWER KEY

PART-I

1. c. Big O
2. c. Abstract data type
3. b. F5
4. a. Interface.
5. a. Access control
6. d. [ ]
7. c. Instantiation
8. d. x % 4 == 0
9. b. σ
10. a. [10, 20, 35, 40, 50]
11. b. Flat file
12. d. Select
13. a. 0134
14. d. Dashboard
15. d. Orderby.

Padasalai.Net

PART - II

16. ABSTRACT DATA TYPE.

* ADT is a type of a class for objects whose behaviour is defined.

17. DIFFERENT OPERATORS IN PYTHON

* It represent computations, conditional matching in programming.
* Arithmetic, Logical, Assignment & conditional

18. SEARCHING - TYPES

* Step by step procedure used to locate, specific data. Ex: Linear, Binary Search.

19. DIFFERENT TYPES OF FUNCTIONS

→ User - defined function.

→ Built - in - function.

→ Lambda function.

→ Recursion function.

20. TYPES OF VISUALIZATION IN MATPLOTLIB.

✓ Line plot

✓ Scatter plot

✓ Histogram

✓ Box plot

✓ pie chart.

Padasalai.Net

21. HIERARCHICAL AND NETWORK DATA MODEL

→ Hierarchical Model, data is represented as a simple tree like structure form.

→ Parent - child relationship.

→ Network Model, extended form of Hierarchical data model.

22. CSV FILE.

* Human readable text file.
* number of fields, separated by commas.

23. FETCH ALL ROWS FROM DATABASE TABLE.

✓ Fetchall() method is used to fetch all rows.

24. POP() FUNCTION IN PYTHON.

→ Removes and returns the last element

→ from a python list by default.

25. PART - III

PURE AND IMPURE FUNCTION.

* Pure functions - have no side effects and always return the same output.
* Impure functions - can have side effects and produce different outputs for the same input.

Padasalai.Net

26. DIFFERENT WAYS TO ACCESS ELEMENTS OF A LIST.

✓ To include an element at your desired position.

✓ Used to insert an element at any position of a list.

```
>>> Mylist = [34, 98, 47, 'kanna', 'Leo', 'mani']
```

27. ASYMPTOTIC NOTATION.

Used to describe the running time of an algorithm.

28.

```
n1 = int(input("Enter the first no:"))
n2 = int(input("Enter the second no:"))
n3 = int(input("Enter the third no:"))
if (n1>=n2) and (n1>=n3):
    biggest=n1;
elif (n2>=n1) and (n2>=n3):
    biggest=n2
else:
    biggest=n3.
print("the biggest no between", n1, ",", "
    "n2, "and", n3, "is" biggest)
```

29. Capitalize()

- It is built-in string function in python.
- Used to modify the case of the characters in a string.
- Swap case()
- Returns a copy of the string.

30. CONSTRUCTOR AND DESTRUCTOR

- They are defined with the __init__ method.

31. APPLICATIONS OF SCRIPTING LANGUAGE.

* To automate certain tasks in a program.
* Extracting information from a data set.

32. WHERE CLAUSE USING.

- It is used to filter records.

33. TCL COMMANDS IN SQL.

* Transaction control Language.
* Used to manage transactions in a database.

- COMMIT
- ROLL BACK
- SAVE POINT.

Padasalai.Net

PART - IV

34. DATA ABSTRACTION WITH EXAMPLE.

- It is supported by defining an abstract data type (ADT). Which is a collection of constructor and selectors.

35. SCOPE OF VARIABLES.

- Enclosed scope.
- Local scope.
- Global scope.
- Built-in-scope.

36. PURPOSE OF RANGE FUNCTION.

✓ Generate series of values in python.

syntax:

range (start value, end value, step value).

37. COMPONENTS OF SQL.

- DML - Data Manipulation Language.
- DDL - Data Definition Language.
- DCL - Data control Language.
- TCL - Transaction control Language
- DQL - Data Query Language.

38. VARIOUS BUTTONS IN MATPLOTLIB.

* Home, Forward/Backward, zoom, Save figure, Pan Axis.

Padasalai.Net

HOME BUTTON.

It will help once you have begun navigating your chart.

FORWARD / BACK BUTTONS.

These buttons canbe used like the Forward and Backward in your browser.

PAN AXIS.

Cross looking buttons you to click it.

ZOOM

Zooming in will require a left click and drag.

N. Vennila.
P.G.T.
(Computer Science/
Computer Application)
Muthuthevar Mukkulathore
Higher Secondary School
Thirunagar.
Madurai-6.

P. ANAND, M.A.,M.Ed.,DCA.,
HEAD MASTER
Muthuthevar Mukkulathore Hr. Sec. School
Thirunagar, MADURAI - 625 006

Padasalai.Net