



**RAJALAKSHMI  
ENGINEERING COLLEGE**

An AUTONOMOUS Institution  
Affiliated to ANNA UNIVERSITY, Chennai



DEPARTMENT OF COMPUTER SCIENCE AND  
ENGINEERING

**Laboratory Manual**

REGULATION 2023

**CS23231 - DATA STRUCTURES**



# RAJALAKSHMI ENGINEERING COLLEGE

An Autonomous Institution, Affiliated to Anna University Rajalakshmi Nagar,  
Thandalam – 602 105



## DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

**CS23231 – DATA STRUCTURES**

***(Regulation 2023)***

**LAB MANUAL**

<b>Name</b>	: SATHISH KUMAR .O
<b>Register No.</b>	: 2116230701297
<b>Year / Branch / Section</b>	: I-YEAR-COMPUTER SCIENCE AND ENGINEERING-E
<b>Semester</b>	: II-SEMESTER
<b>Academic Year</b>	: 2023-2024



# LESSON PLAN

Course Code	Course Title (Laboratory Integrated Theory Course)	L	T	P	C
CS23231	Data Structures	3	0	4	5

LIST OF EXPERIMENTS	
Sl. No	Name of the experiment
Week 1	Implementation of Single Linked List (Insertion, Deletion and Display)
Week 2	Implementation of Doubly Linked List (Insertion, Deletion and Display)
Week 3	Applications of Singly Linked List (Polynomial Manipulation)
Week 4	Implementation of Stack using Array and Linked List implementation
Week 5	Applications of Stack (Infix to Postfix)
Week 6	Applications of Stack (Evaluating Arithmetic Expression)
Week 7	Implementation of Queue using Array and Linked List implementation
Week 8	Implementation of Binary Search Tree
Week 9	Performing Tree Traversal Techniques
Week 10	Implementation of AVL Tree
Week 11	Performing Topological Sorting
Week 12	Implementation of BFS, DFS
Week 13	Implementation of Prim's Algorithm
Week 14	Implementation of Dijkstra's Algorithm
Week 15	Program to perform Sorting
Week 16	Implementation of Open Addressing (Linear Probing and Quadratic Probing)

Week 17	Implementation of Rehashing
---------	-----------------------------

## INDEX

S. No.	Name of the Experiment	Expt. Date	Page No	Faculty Sign
1	Implementation of Single Linked List (Insertion, Deletion and Display)	29/02/2024	6	
2	Implementation of Doubly Linked List (Insertion, Deletion and Display)	07/03/2024	16	
3	Applications of Singly Linked List (Polynomial Manipulation)	14/03/2024	23	
4	Implementation of Stack using Array and Linked List implementation	21/03/2024	32	
5	Applications of Stack (Infix to Postfix)	28/03/2024	39	
6	Applications of Stack (Evaluating Arithmetic Expression)	04/04/2024	44	
7	Implementation of Queue using Array and Linked List implementation	11/04/2024	48	
8	Performing Tree Traversal Techniques	18/04/2024	53	
9	Implementation of Binary Search Tree	25/04/2024	57	
10	Implementation of AVL Tree	02/05/2024	64	
11	Performing Topological Sorting	09/05/2024	78	
12	Implementation of BFS, DFS	09/05/2024	82	
13	Implementation of Prim's Algorithm	16/05/2024	89	
14	Implementation of Dijkstra's Algorithm	16/05/2024	94	
15	Program to perform Sorting	23/05/2024	98	
16	Implementation of Collision Resolution Techniques	30/05/2024	104	

**Note: Students have to write the Algorithms at left side of each problem statements.**

Ex. No.:01	Implementation of Single Linked List	Date:29/02/2024
------------	--------------------------------------	-----------------

**Write a C program to implement the following operations on Singly Linked List.**

- (i) Insert a node in the beginning of a list.
- (ii) Insert a node after P
- (iii) Insert a node at the end of a list
- (iv) Find an element in a list
- (v) FindNext
- (vi) FindPrevious
- (vii) isLast
- (viii) isEmpty
- (ix) Delete a node in the beginning of a list.
- (x) Delete a node after P
- (xi) Delete a node at the end of a list
- (xii) Delete the List

**Algorithm:**

- 1) Start
- 2) Define a Node structure with data and a pointer to the next Node.
- 3) Initialize a head pointer to NULL.
- 4) Create functions for the following operations: a. Insert at the beginning or end:
  - Create a new Node with the given data.
  - Traverse the list to the last Node or update the head pointer accordingly. b. Delete from the beginning or end:
    - Update the head pointer to the next Node or traverse to the second last Node and update its pointer.
  - c. Search for a value:
    - Traverse the list and compare each Node's data with the given value.
    - Return the Node if found, otherwise return NULL.
- 5) Test the operations by inserting, deleting, and searching for elements in the list. 6) Stop

**PROGRAM:**

```
#include <stdio.h>
#include<stdlib.h> void
createfnode(int ele); void
insertfront(int ele); void
insertend(int ele); void
display();
//type declaration of a node struct
node
{ int data; struct
node* next;
};
struct node* head = NULL;
struct node *newnode;
void insertfront(int ele)
{
```

```

newnode=(struct node*)malloc(sizeof(struct node));
if(newnode!=NULL) { newnode->data=ele;
if(head!=NULL)
{ newnode->next=head;
head=newnode;
} else
{
newnode->next=NULL;
head=newnode;

} }
}
void insertend(int ele)
{
newnode=(struct node*)malloc(sizeof(struct node));
if(newnode!=NULL)
{ newnode->data=ele;
newnode->next=NULL;
if(head!=NULL)
{ struct node *t;
t=head; while(t->next!=NULL)
{ t=t->next;
} newnode->next=NULL;
t->next=newnode;
}
else {
head=newnode;
}
} }
int listsize()
{ int c=0;
struct node *t;
t=head;
while(t!=NULL)
{ c=c+1;
t=t->next;
}
printf("\n The size of the list is %d:\n",c); return
c;
}
void insertpos(int ele,int pos)
{ int ls=0; ls=listsize(); if(head ==
NULL && (pos <= 0 || pos > 1))
{
printf("\nInvalid position to insert a node\n"); return;
}
// if the list is not empty and the position is out of range
if(head != NULL && (pos <= 0 || pos > ls))
{
printf("\nInvalid position to insert a node\n"); return;
}
struct node* newnode = NULL;
newnode=(struct node*)malloc(sizeof(struct node)); if(newnode
!= NULL)
{
newnode->data=ele; struct
node* temp = head; //getting

```



```

the position-1 node int count
= 1; while(count < pos-1)
{ temp = temp ->
next; count += 1;
}
//if the position is 1 then insertion at the beginning if(pos
== 1)
{ newnode->next =
head; head = newnode;
} else
{ newnode->next = temp-
>next; temp->next =
newnode;
}
}
}
void findnext(int s)
{ struct node *temp; temp=head;
if(temp==NULL&&temp->next==NULL)
{
printf("No next element ");
} else
{
while(temp->data!=s)
{
temp=temp->next;
}
printf("\nNext Element of %d is %d\n",s,temp->next->data);
} }
void findprev(int s)
{ struct node
*temp; temp=head;
if(temp==NULL)
{
printf("List is empty ");
} else
{
while(temp->next->data!=s)
{
temp=temp->next;
}
printf("\n The previous ele of %d is %d\n",s,temp->data);
} }
void find(int s)
{
struct node *temp;
temp=head; if(head==NULL)
{
printf("\n List is empty");
} else
{
while(temp->data!=s && temp->next!=NULL)
{
temp=temp->next;
}
if(temp!=NULL && temp->data==s)
{
printf("\n Searching ele %d is present in the addr of %p",temp-

```

```

>data,temp);
} else {
printf("\n Searching elem %d is not present",s);
} } } void
isempty() {
if(head==NULL)
{
printf("\nList is empty\n");
} else
{
printf("\nList is not empty\n");
}
}
void deleteAtBeginning()
{ struct node
*t; t=head;
head=t->next; }
void deleteAtEnd()
{ struct node
*temp; temp=head;
if(head==NULL)
{
printf("\n List is empty");
} else
{
while(temp->next->next!=NULL)
{ temp=temp->next;
}
temp->next=NULL;
} } void
display()
{ struct node
*t; t=head;
while(t!=NULL)
{
printf("%d\t",t->data); t=t->next;
}
} void delete(int
ele)
{ struct node
*t; t=head;
if(t->data==ele)
{ head=t->next;
}
else {
while(t->next->data!=ele)
{ t=t->next;
}
t->next=t->next->next;
}
} int
main()
{ do { int
ch,a,pos;
printf("\n Choose any one operation that you would like to perform\n");
printf("\n 1.Insert the element at the beginning"); printf("\n 2.Insert
the element at the end"); printf("\n 3. To insert at the specified
position"); printf("\n 4. To view list"); printf("\n 5.To view list
size"); printf("\n 6.To delete first element"); printf("\n 7.To delete

```

```

last element"); printf("\n 8.To find next element"); printf("\n 9. To
find previous element"); printf("\n 10. To find search for an element");
printf("\n 11. To quit"); printf("\n Enter your choice\n");
scanf("%d",&ch); switch(ch) { case 1: printf("\n Insert an element to be
inserted at the beginning\n"); scanf("%d",&a); insertfront(a); break;
case 2: printf("\n Insert an element to be inserted at the End\n");
scanf("%d",&a); insertend(a); break; case 3: printf("\n Insert an
element and the position to insert in the list\n");
scanf("%d%d",&a,&pos); insertpos(a,pos); break; case 4: display();
break; case 5: listsize(); break; case 6:
printf("\n Delete an element to be in the beginning\n");
deleteAtBeginning(); break; case 7: printf("\n Delete an
element to be at the end\n"); deleteAtEnd(); break;
case 8: printf("\n enter the element to which you need to find next
ele in the list\n");; scanf("%d",&a); findnext(a); break; case 9:
printf("\n enter the element to which you need to find prev ele in the
list\n"); scanf("%d",&a); findprev(a); break; case 10: printf("\n
enter the element to find the address of it\n"); scanf("%d",&a);
find(a); break; case 11: printf("Ended"); exit(0); default:
printf("Invalid option is chosen so the process is quit");
} }while(1);
return 0;
}

```

**OUTPUT:**

```
Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
4
2      5      3
Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
5

The size of the list is 3:

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
6

Delete an element to be in the beginning
```

```

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
6

Delete an element to be in the beginning

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
7

Delete an element to be at the end

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
8

enter the element to which you need to find next ele in the list
2

```

```

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
1

Insert an element to be inserted at the beginning
2

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
2

Insert an element to be inserted at the End
3

Choose any one operation that you would like to perform

1.Insert the element at the beginning
2.Insert the element at the end
3. To insert at the specified position
4. To view list
5.To view list size
6.To delete first element
7.To delete last element
8.To find next element
9. To find previous element
10. To find search for an element
11. To quit
Enter your choice
3

Insert an element and the position to insert in the list
5
2

The size of the list is 2:

```

**RESULT: Thus the program was successfully executed.**

<b>Ex. No.: 02</b>	<b>Implementation of Doubly Linked List</b>	<b>Date:07/03/2024</b>
--------------------	---	------------------------

**Write a C program to implement the following operations on Doubly Linked List.**

- (i) Insertion**
- (ii) Deletion**
- (iii) Search**

**(iv) Display****Algorithm:**

- 1) Start
- 2) Define a Node structure with data, a pointer to the previous Node, and a pointer to the next Node.
- 3) Initialize head and tail pointers to NULL. 4) Create functions for the following operations:
  - a. Insert at the beginning or end:
    - Create a new Node with the given data.
    - Update the head or tail pointer accordingly.
- 5) Delete from the beginning or end:
  - Update the head or tail pointer to the next or previous Node.
- 6) Search for a value:
  - Traverse the list forward or backward and compare each Node's data with the given value.
  - Return the Node if found, otherwise return NULL.
- 7) Test the operations by inserting, deleting, and searching for elements in the list. 8) Stop

**PROGRAM:**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct node
{
    int data; struct
    node *next; struct
    node *prev;
};
```

```
struct node *newnode; struct
node *head = NULL;
```

```
void insertfront(int ele)
{
    newnode = (struct node *)malloc(sizeof(struct node)); if
    (head == NULL)
    {
        newnode->data = ele; newnode->next
        = NULL; newnode->prev = NULL;
        head = newnode;
    }
    else
    {
        newnode->data = ele; newnode-
        >next = head; head->prev =
        newnode;
        head = newnode;
    }
}
```

```
}
```

```
void insertend(int ele)
{
    newnode = (struct node *)malloc(sizeof(struct node));
    newnode->data = ele; newnode->next = NULL;
    if (head != NULL)
    {
        struct node *t; t
        = head;
        while (t->next != NULL)
        {
            t = t->next;
        }
        newnode->prev = t;
        t->next = newnode;
    }
    else
    {
        newnode->prev = NULL;
        head = newnode;
    }
}
```

```
int listsize()
{ int c = 0; struct
  node *t; t = head;
  while (t != NULL)
  {
      c++;
      t = t->next;
  }
  printf("\n The size of the list is %d:\n", c); return
  c;
}
```

```
void insertpos(int ele, int pos)
{ int ls = 0;
  struct node *temp;
  ls = listsize(); if
  (head == NULL)
  {
      printf("\nInvalid position to insert a node\n"); return;
  }
  if (head != NULL && (pos <= 0 || pos > ls))
  {
      printf("\nInvalid position to insert a node\n"); return;
  }
```

```
newnode = (struct node *)malloc(sizeof(struct node));
```



```

if (newnode != NULL)
{
    newnode->data = ele;
    temp = head; int
    count = 1;
    while (count < pos - 1)
    {
        temp = temp->next;
        count++;
    }
    if (pos == 1)
    {
        newnode->next = head; head->prev
        = newnode;
        head = newnode;
    }
else
    {
        newnode->next = temp->next;
        if (temp->next != NULL)
            temp->next->prev = newnode;
        temp->next = newnode; newnode-
>prev = temp;
    }
}
}

```

```

void find(int s)
{ int c = 1; struct
  node *temp; temp
  = head;
  if (head == NULL)
  {
      printf("\n List is empty");
  }
  else
  {
      while (temp->data != s && temp->next != NULL)
      {
          temp = temp->next;
          c++;
      }
      if (temp != NULL && temp->data == s)
      {
          printf("\n Searching ele %d is present in the addr of %p in the pos%d", temp->data,
temp, c);
      }
      else
      {
          printf("\n Searching elem %d is not present", s);
      }
  }
}

```

```
}
```

```
void findnext(int s)
{
    struct node *temp; temp
    = head;
    if (temp == NULL || temp->next == NULL)
    {
        printf("No next element ");
    }
    else
    {
        while (temp->data != s)
        {
            temp = temp->next;
        }
        printf("\nNext Element of %d is %d\n", s, temp->next->data);
    }
}
```

```
void findprev(int s)
{
    struct node *temp;
    temp = head; if
    (temp == NULL)
    {
        printf("List is empty ");
    }
    else
    {
        while (temp->data != s)
        {
            temp = temp->next;
        }
        printf("\n The previous ele of %d is %d\n", s, temp->prev->data);
    }
}
```

```
void deleteAtBeginning()
{
    if (head == NULL)
    {
        printf("List is empty");
    }
    else
    {
        struct node *t = head;
        head = head->next; if
        (head != NULL)
            head->prev = NULL;
        free(t);
    }
}
```

```

    }
}

```

```

void deleteAtEnd()
{
    if (head == NULL)
    {
        printf("\n List is empty");
    }
    else
    {
        struct node *temp = head; while
        (temp->next != NULL)
        {
            temp = temp->next;
        }
        if (temp->prev != NULL)
            temp->prev->next = NULL; free(temp);
    }
}

```

```

void delete(int ele)
{
    struct node *t = head;
    if (t->data == ele)
    {
        head = t->next; if
        (head != NULL)
            head->prev = NULL;
        free(t);
    }
    else
    {
        while (t->data != ele)
        {
            t = t->next;
        }
        if (t->next != NULL)
            t->next->prev = t->prev;
        t->prev->next = t->next;
        free(t);
    }
}

```

```

void display()
{
    struct node *temp; temp
    = head;
    while (temp != NULL)
    {
        printf("%d-->", temp->data); temp
        = temp->next;
    }
}

```

```

    }
}

int main()
{
    insertfront(10);
    insertfront(20);
    insertfront(30); display();
    printf("\n Inserted ele 40 at the end\n");
    insertend(40); display(); insertpos(25,
3); display(); find(25); findnext(25);
findprev(25);
    printf("\n element deleted in the beginning\n");
    deleteAtBeginning(); display();
    deleteAtEnd();
    printf("\n Element deleted at the end\n"); display();
    printf("\n After deleting element 25\n");
    delete(25); display();
    return 0;
}

```

#### OUTPUT:

```

30-->20-->10-->
  Inserted ele 40 at the end
30-->20-->10-->40-->
  The size of the list is 4:
30-->20-->25-->10-->40-->
  Searching ele 25 is present in the addr of 0x55ff3be7d730 in the pos3
Next Element of 25 is 10

  The previous ele of 25 is 20

  element deleted in the beginning
20-->25-->10-->40-->
  Element deleted at the end
20-->25-->10-->
  After deleting element 25
20-->10-->aiml231501167@cse1ab:~$

```

**RESULT:** Thus, the program was successfully executed.

Ex. No.:03	Polynomial Manipulation	Date:21/03/2024
------------	-------------------------	-----------------

**Write a C program to implement the following operations on Singly Linked List.**

**(i) Polynomial Addition**

**(ii) Polynomial Subtraction (iii) Polynomial Multiplication**

**Algorithm:**

- 1) Start
- 2) Define a structure for a polynomial term with coefficients and exponents.
- 3) Create functions for the following operations: a. Polynomial addition:
  - Initialize a result polynomial.
  - Traverse both input polynomials simultaneously.
  - Add coefficients of terms with the same exponent and append to the result.
  - Append any remaining terms from both polynomials to the result.
- 4) Polynomial subtraction:
  - Initialize a result polynomial.
  - Traverse both input polynomials simultaneously.
  - Subtract coefficients of terms with the same exponent and append to the result.
  - Append any remaining terms from both polynomials to the result.
- 5) Polynomial multiplication:
  - Initialize a result polynomial.
  - Multiply each term of the first polynomial with each term of the second polynomial.
  - Add the coefficients of terms with the same exponent and append to the result.
- 6) Test the operations by performing addition, subtraction, and multiplication on sample polynomials.
- 7) Stop

**PROGRAM:**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node
```

```
{
```

```

int coeff;

int pow;

struct node *Next;

};

struct node *Poly1,*Poly2,*Result; void

Create(struct node *List);

void Display(struct node *List);

void Addition(struct node *Poly1,struct node *Poly2,struct node *Result); int

main()

{

Poly1=(struct node*)malloc(sizeof(struct node));

Poly2=(struct node*)malloc(sizeof(struct node));

Result=(struct node*)malloc(sizeof(struct node));


Poly1->Next = NULL; Poly2->Next

= NULL;

printf("Enter the values for first polynomial :\n");

Create(Poly1); printf("The polynomial equation is :

"); Display(Poly1); printf("\nEnter the values for

second polynomial :\n"); Create(Poly2); printf("The

polynomial equation is : "); Display(Poly2);

Addition(Poly1, Poly2, Result);

printf("\nThe polynomial equation addition result is : ");

Display(Result);

return 0;

}

void Create(struct node *List)

```

```

{

int choice;

struct node *Position, *NewNode; Position
= List;

do

{

NewNode = malloc(sizeof(struct node));

printf("Enter the coefficient : ");

scanf("%d", &NewNode->coeff);

printf("Enter the power : "); scanf("%d",

&NewNode->pow); NewNode->Next =

NULL;

Position->Next = NewNode; Position
= NewNode;

printf("Enter 1 to continue : "); scanf("%d",

&choice);

} while(choice == 1);

}

void Display(struct node *List)

{

struct node *Position;

Position = List->Next;

while(Position != NULL)

{

printf("%dx^%d", Position->coeff, Position->pow); Position
= Position->Next;

if(Position != NULL && Position->coeff > 0)

{

```

```

printf("+");

}

}

}

void Addition(struct node *Poly1, struct node *Poly2, struct node *Result)
{
    struct node *Position; struct
    node *NewNode; Poly1 =
    Poly1->Next;
    Poly2 = Poly2->Next;
    Result->Next = NULL; Position
    = Result;
    while(Poly1 != NULL && Poly2 != NULL)
    {
        NewNode = malloc(sizeof(struct node)); if(Poly1->pow
        == Poly2->pow)
        {
            NewNode->coeff = Poly1->coeff + Poly2->coeff;
            NewNode->pow = Poly1->pow;
            Poly1 = Poly1->Next;
            Poly2 = Poly2->Next;
        }
        else if(Poly1->pow > Poly2->pow)
        {
            NewNode->coeff = Poly1->coeff;
            NewNode->pow = Poly1->pow;
            Poly1 = Poly1->Next;

```



```

}

else if(Poly1->pow < Poly2->pow)

{

    NewNode->coeff = Poly2->coeff;

    NewNode->pow = Poly2->pow;

    Poly2 = Poly2->Next;

}

NewNode->Next = NULL;

Position->Next = NewNode;

Position = NewNode;

}

while(Poly1 != NULL || Poly2 != NULL)

{

    NewNode = malloc(sizeof(struct node)); if(Poly1

    != NULL)

    {

        NewNode->coeff = Poly1->coeff;

        NewNode->pow = Poly1->pow;

        Poly1 = Poly1->Next;

    }

    if(Poly2 != NULL)

    {

        NewNode->coeff = Poly2->coeff;

        NewNode->pow = Poly2->pow;

        Poly2 = Poly2->Next;

    }

    NewNode->Next = NULL;

```

```
Position->Next = NewNode;
```

```
Position = NewNode;
```

```
}
```

```
}
```

### Program 2:

```
#include<stdio.h>
```

```
#include<stdlib.h> struct
```

```
node
```

```
{ int coeff;
```

```
    int expo;
```

```
    struct node *next;
```

```
};
```

```
struct node* insert(struct node *head,int co,int exp)
```

```
{
```

```
    struct node *temp;
```

```
    struct node *newnode=malloc(sizeof(struct node));
```

```
    newnode->coeff=co; newnode->expo=exp;
```

```
    newnode->next=NULL; if(head==NULL ||
```

```
    exp>head->expo)
```

```
    {
```

```
        newnode->next=head; head=newnode;
```

```
    }
```

```
    else
```

```
    {
```

```
        temp=head; while(temp->next!=NULL &&temp->next-  
        >expo>=exp)
```

```
            temp=temp->next;
```

```
        newnode->next=temp->next;
```

```
        temp->next=newnode;
```

```
    }
```

```
    return head;
```

```
}
```

```
struct node* create(struct node *head)
```

```
{ int n,i; int coeff; int expo;
```

```
    printf("Enter the no of terms:");
```

```
    scanf("%d",&n);
```

```
    for(i=0;i<n;i++)
```

```
    {
```

```
        printf("Enter the coefficient for term %d:",i+1);
```

```
        scanf("%d",&coeff);
```

```
        printf("Enter the exponent for term %d:",i+1);
```

```
        scanf("%d",&expo);
```

```
        head=insert(head,coeff,expo);
```

```
    }
```

```

return head;
}
void print(struct node* head)
{
    if(head==NULL)
        printf("No Polynomial");
    else
    {
        struct node *temp=head;
        while(temp!=NULL)
        {
            printf("%dx^%d",temp->coeff,temp->expo); temp=temp->next;
            if(temp!=NULL) printf("+");

            else
                printf("\n");
        }
    }
}

void polyAdd(struct node *head1, struct node *head2)
{
    struct node *ptr1=head1; struct
    node *ptr2=head2; struct node
    *head3=NULL; while(ptr1!=NULL
    && ptr2!=NULL)
    {
        if(ptr1->expo == ptr2->expo)
        {
            head3=insert(head3,ptr1->coeff+ptr2->coeff,ptr1->expo);
            ptr1=ptr1->next; ptr2=ptr2->next;
        }
        else if(ptr1->expo > ptr2->expo)
        {
            head3=insert(head3,ptr1->coeff,ptr1->expo); ptr1=ptr1->next;
        }
        else if(ptr1->expo < ptr2->expo)
        {
            head3=insert(head3,ptr2->coeff,ptr2->expo); ptr2=ptr2->next;
        }
    }
    while(ptr1!=NULL)
    {
        head3=insert(head3,ptr1->coeff,ptr1->expo); ptr1=ptr1->next;
    }
    while(ptr2!=NULL)
    {
        head3=insert(head3,ptr2->coeff,ptr2->expo); ptr2=ptr2->next;
    }
}

```

```

    }
    printf("Added Polynomial is: ") ; print(head3);
}
int main()
{
    struct node *head1=NULL; struct
    node *head2=NULL;
    printf("Enter first polynomial\n");
    head1=create(head1);
    printf("Enter second polynomial\n");
    head2=create(head2);
    polyAdd(head1,head2);
    return 0;

}

```

OUTPUT:

```

aiml231501167@cselab:~$ gcc program3.c
aiml231501167@cselab:~$ ./a.out
Enter the values for first polynomial :
Enter the coefficient : 2
Enter the power : 2
Enter 1 to continue : 1
Enter the coefficient : 3
Enter the power : 3
Enter 1 to continue : 0
The polynomial equation is : 2x^2+3x^3
Enter the values for second polynomial :
Enter the coefficient : 2
Enter the power : 2
Enter 1 to continue : 1
Enter the coefficient : 5
Enter the power : 3
Enter 1 to continue : 0
The polynomial equation is : 2x^2+5x^3
The polynomial equation addition result is : 4x^2+8x^3aiml231501167@cselab:~$

```

**RESULT:** Thus the program was successfully executed.

Ex. No.:04	Implementation of Stack using Array and Linked List Implementation	Date:21/03/2024
------------	--	-----------------

**Write a C program to implement a stack using Array and linked List implementation and execute the following operation on stack.**

- (i) Push an element into a stack
- (ii) Pop an element from a stack
- (iii) Return the Top most element from a stack
- (iv) Display the elements in a stack

**Algorithm:**

- 1) Start
- 2) Stack using Array:
- 3) Define a fixed-size array to store the stack elements and initialize a variable top to -1.  
Implement functions for the following operations:
  - Push: Increment top and insert the element at the top index.
  - Pop: Remove the element at the top index and decrement top.
  - Peek: Return the element at the top index without removing it.
  - IsEmpty: Check if top is -1 to determine if the stack is empty.
  - IsFull: Check if top is equal to the maximum array size to determine if the stack is full.
- 4) Stack using Linked List:
  - a. Define a Node structure with data and a pointer to the next Node.
  - b. Initialize a head pointer to NULL.
  - c. Implement functions for the following operations:
    - Push: Create a new Node with the given data and insert it at the beginning of the list.
    - Pop: Remove the first Node from the list.
    - Peek: Return the data of the first Node without removing it.
    - IsEmpty: Check if the head pointer is NULL to determine if the stack is empty.
- 5) Stop

**PROGRAM: ARRAY IMPLEMENTATION**

```
#include <stdio.h>

#include <string.h>

#include <ctype.h>

int top = -1; int

stack[100]; void

push (int data) {

stack[++top] = data;
```

```

} int pop () { int
data; if (top == -
1) return -1; data
= stack[top];
stack[top] = 0;
top--; return
(data);
}
int main()
{
char str[100];
int i, data = -1, operand1, operand2, result;
printf("Enter ur postfix expression:");
fgets(str, 100, stdin);
for (i = 0; i < strlen(str); i++)
{ if
(isdigit(str[i]))
{
data = (data == -1) ? 0 : data; data
= (data * 10) + (str[i] - 48);
continue;
} if (data != -
1)
{
push(data);
}
if (str[i] == '+' || str[i] == '-' || str[i] == '*' || str[i] == '/')
{
operand2 = pop(); operand1 = pop();
if (operand1 == -1 || operand2 == -1)
break; switch (str[i])
{
case '+':

```

```

result = operand1 + operand2;
push(result); break; case '-':
result = operand1 - operand2;
push(result); break; case '*':
result = operand1 * operand2;
push(result); break; case '/':
result = operand1 / operand2;
push(result); break;
}
}
data = -1;
} if (top ==
0)
printf("The answer is:%d\n", stack[top]); else
printf("u have given wrong postfix expression\n");
return 0;
}

```

#### LINKED LIST IMPLEMENTATION:

```

#include <stdio.h>
#include <stdlib.h>
struct Node
{
int Data; struct
Node *next; }*top;
void popStack()
{
struct Node *temp, *var=top;
if(var==top)
{
top = top->next; free(var);
}
else printf("\nStack
Empty");

```

```

}

void push(int value)
{
    struct Node *temp;
    temp=(struct Node *)malloc(sizeof(struct Node)); temp->Data=value; if (top == NULL)
    {
        top=temp; top->next=NULL;
    }
else
    {
        temp->next=top; top=temp;
    }
}

void display()
{
    struct Node *var=top;
    if(var!=NULL)
    {
        printf("\nElements are as:");
        while(var!=NULL)
        {
            printf("\t%d\n",var->Data);
            var=var->next;
        } printf("\n");
    }
    else printf("\nStack is
    Empty"");
}

int main()
{ int
    i=0;
    top=NULL;

    printf("\n1. Push to stack");
    printf("\n2. Pop from Stack");

```



```

printf("\n3. Display data of Stack");
printf("\n4. Exit\n"); while(1)
{
printf ("\nChoose Option:");
scanf("%d",&i); switch(i)
{
case 1:
{
int value;
printf("\nEnter a value to push into Stack:");
scanf("%d",&value); push(value); break;
}
case 2:
{
popStack(); printf("\n The last element
is popped"); break;
}
case 3:
{
display(); break;
}
case 4:
{
struct Node *temp;
while(top!=NULL)
{
temp = top->next;
free(top); top=temp;
} exit(0);
}
default:
{
printf("\nwrong choice for operation");
}}}}

```

OUTPUT:

```

1. Push to stack;
2. Pop from Stack;
3. Display data of Stack
4. Exit

Choose Option:1

Enter a value to push into Stack:10

Choose Option:1

Enter a value to push into Stack:20

Choose Option:1

Enter a value to push into Stack:30

Choose Option:1

Enter a value to push into Stack:40

Choose Option:2

The last element is popped
Choose Option:3

Elements are as:      30
                   20
                   10

Choose Option:4
aiml231501167@cslab:~$

```

**RESULT:** Thus the program was successfully executed.

Ex. No.: 05	Infix to Postfix Conversion	Date:28/03/2024
-------------	-----------------------------	-----------------

**Write a C program to perform infix to postfix conversion using stack.**

**Algorithm:**

- 1) Start
- 2) Initialize an empty stack to hold operators.
- 3) Initialize an empty string to store the postfix expression.
- 4) Iterate through each character in the infix expression:
  - a. If the character is an operand, add it to the postfix string.
  - b. If the character is an operator:
    - i. While the stack is not empty and the precedence of the top operator in the stack is greater than or equal to the current operator, pop operators from the stack and add them to the postfix string.
    - ii. Push the current operator onto the stack.
  - c. If the character is an opening parenthesis '(', push it onto the stack.
  - d. If the character is a closing parenthesis ')':
    - i. Pop operators from the stack and add them to the postfix string until an opening parenthesis is encountered.
    - ii. Discard the opening parenthesis.
- 5) Pop any remaining operators from the stack and add them to the postfix string.
- 6) Return the postfix expression.
- 7) Stop

PROGRAM:

```
#include <stdio.h>

#include <stdlib.h>

int top = 0; int
stack[20];
char infix[40], postfix[40];

void convertToPostfix();
void push(int);
char pop();

int main() {
    printf("Enter the infix expression: ");
    scanf("%s", infix);
    convertToPostfix(); return 0;

}

void convertToPostfix() { int i, j
= 0; for (i = 0; infix[i] != '\0';
i++) { switch (infix[i]) {
    case '+':
        while (stack[top] >= 1)
            postfix[j++] = pop();
        push(1); break;
    case '-':
        while (stack[top] >= 1)
            postfix[j++] =
            pop(); push(2);
        break;
    case '*':
        while (stack[top] >= 3)
            postfix[j++] = pop();
```

```

        push(3);
    break; case
    '/':
        while (stack[top] >= 4)
            postfix[j++] = pop();
        push(4); break;
    case '^': postfix[j++] =
        pop();    push(5);
        break;
    case '(':
        push(0);
        break;
    case ')':
        while (stack[top] != 0)
            postfix[j++] = pop();
        top--; break;
    default:
        postfix[j++] = infix[i];
    }
}

while (top > 0)
    postfix[j++] = pop();

printf("\nPostfix expression is =>\n\t\t%s", postfix);
}

void push(int element) {
    top++; stack[top] =
    element;

}

char pop() { int el;
    char e; el =
    stack[top]; top--;

```

```
switch (el) { case
1:
    e = '+';
    break;
case 2:
    e = '-';
    break;
case 3:
    e = '*'; break;
case 4:
    e = '/'; break;
case 5:
    e = '^'; break;
}
return e;
}
```

OUTPUT:

```
Enter the infix expression: ab+cd+*ef/*g^
Postfix expression is =>
abcd+ef/*g*^+aiml231501179@cse1ab:~$
```

**RESULT: Thus, the program was successfully executed.**

Ex. No.:06	Evaluating Arithmetic Expression	Date:04/04/2024
------------	----------------------------------	-----------------

**Write a C program to evaluate Arithmetic expressions using stack.**

**Algorithm:**

- 1) Start
- 2) Create an empty stack to store operands. 3) Iterate through each character in the expression: a. If the character is a digit, push it onto the stack.  
b. If the character is an operator (+, -, \*, /), pop two operands from the stack, perform the operation, and push the result back onto the stack.
- 4) After processing all characters, the final result will be the only element left in the stack.
- 5) Return this result as the evaluation of the arithmetic expression.
- 6) Stop

PROGRAM:

```
#include <stdio.h>
#include <string.h>
#include <ctype.h>
int top = -1; int
stack[100]; void
push (int data) {
    stack[++top] = data;
} int pop () { int
data; if (top == -
1) return -1; data
= stack[top];
stack[top] = 0;
top--; return
(data);
}
int main()
{
    char str[100];
    int i, data = -1, operand1, operand2, result;
    printf("Enter ur postfix expression:"); fgets(str,
    100, stdin);
    for (i = 0; i < strlen(str); i++)

    { if
    (isdigit(str[i]))
    {
        data = (data == -1) ? 0 : data; data
        = (data * 10) + (str[i] - 48);
        continue;
    } if (data != -
    1)
    {
```

```

push(data);
}
if (str[i] == '+' || str[i] == '-' || str[i] == '*' || str[i] == '/')
{
operand2 = pop(); operand1 = pop();
if (operand1 == -1 || operand2 == -1)
break; switch (str[i])
{
case '+':
result = operand1 + operand2;
push(result); break; case '-':
result = operand1 - operand2;
push(result); break; case '*':
result = operand1 * operand2;
push(result); break; case '/':
result = operand1 / operand2;
push(result); break;
}
}
data = -1;
} if (top ==
0)
printf("The answer is:%d\n", stack[top]); else
printf("u have given wrong postfix expression\n");
return 0;
}

```

OUTPUT:

```

aiml231501167@cse1ab:~$ ./a.out
Enter ur postfix expression:10 20 * 30 40 10 / - +
The answer is:226
aiml231501167@cse1ab:~$

```



**RESULT: Thus, the program was successfully executed.**

<b>Ex. No.:07</b>	<b>Implementation of Queue using Array and Linked List Implementation</b>	<b>Date:11/04/2024</b>
-------------------	---	------------------------

**Write a C program to implement a Queue using Array and linked List implementation and execute the following operation on stack.**

- (i) Enqueue**
- (ii) Dequeue**
- (iii) Display the elements in a Queue Algorithm:**

- 1) Start
- 2) 1. For Queue using Array:
- 3) Initialize an array of fixed size to store the queue elements.
- 4) Maintain two pointers, front and rear, to track the front and rear of the queue.
- 5) Implement the following operations:
  - Enqueue: Add an element to the rear of the queue by incrementing the rear pointer.
  - Dequeue: Remove an element from the front of the queue by incrementing the front pointer.
  - isEmpty: Check if the queue is empty by comparing the front and rear pointers.
  - isFull: Check if the queue is full by comparing the rear pointer with the array size.
- 6) For Queue using Linked List:
- 7) Define a Node structure with data and a pointer to the next Node.
- 8) Maintain pointers to the front and rear Nodes of the queue.

9) Implement the following operations:

- Enqueue: Create a new Node with the given data and update the rear pointer.
- Dequeue: Remove the front Node and update the front pointer.
- isEmpty: Check if the queue is empty by comparing the front pointer with NULL. -
- Display: Traverse the linked list to display all elements in the queue.

10) Stop

PROGRAM:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct queue
```

```
{
```

```
    int data; struct
```

```
    queue *next;
```

```
};
```

```
struct queue *addq(struct queue *front); struct
```

```
queue *delq(struct queue *front);
```

```
int main()
```

```
{
```

```
    struct queue *front = NULL; int
```

```
    option;
```

```
    do
```

```
    {
```

```
        printf("\n1. Add to Queue");
```

```
        printf("\n2. Delete from Queue");
```

```
        printf("\n3. Exit"); printf("\nSelect
```

```
        an option: "); scanf("%d",
```

```
        &option);
```

```
        switch(option)
```

```

{

    case 1:

        front = addq(front); printf("\nElement
        added to the queue."); break;

    case 2: front =
        delq(front); break;

    case 3:
        exit(0);

}

} while(1);

return 0;
}

struct queue *addq(struct queue *front)
{

    struct queue *new_node = (struct queue*)malloc(sizeof(struct queue)); if(new_node
    == NULL)

    {

        printf("Insufficient memory."); return
        front;

    }

printf("\nEnter data: "); scanf("%d",
    &new_node->data); new_node-
    >next = NULL;

    if(front == NULL)

    {

        front = new_node;

    }

```

```

else
{
    struct queue *temp = front;
    while(temp->next != NULL)
    {

        temp = temp->next;
    }

    temp->next = new_node;
}

return front;
}

struct queue *delq(struct queue *front)
{

    if(front == NULL)
    {

        printf("Queue is empty."); return
        front;
    }

    struct queue *temp = front; printf("Deleted
    data: %d", front->data); front = front-
    >next;
    free(temp);

    return front;
}
OUTPUT:

```

```

1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 1

Enter data: 2

Element added to the queue.
1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 1

Enter data: 3

Element added to the queue.
1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 1

Enter data: 4

Element added to the queue.
1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 2
Deleted data: 2
1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 2
Deleted data: 3
1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 4

1. Add to Queue
2. Delete from Queue
3. Exit
Select an option: 3
aiml231501179@cse-lab:~$

```

**RESULT:** Thus, the program was successfully executed.

Ex. No.:08	Tree Traversal	Date:18/04/2024
------------	----------------	-----------------

**Write a C program to implement a Binary tree and perform the following tree traversal operation.**

**(i) Inorder Traversal**

**(ii) Preorder Traversal (iii) Postorder Traversal**

**Algorithm:**

- 1) Start
- 2) Define a Node structure with data, left child pointer, and right child pointer. 3) Create functions for the following traversal methods:
- 4) Inorder traversal:
  - Recursively call the function on the left child.
  - Print the data of the current Node.
  - Recursively call the function on the right child.
- 5) Preorder traversal:
  - Print the data of the current Node.
  - Recursively call the function on the left child.
  - Recursively call the function on the right child.
- 6) Postorder traversal:
  - Recursively call the function on the left child.
  - Recursively call the function on the right child.
  - Print the data of the current Node.
- 7) Initialize the root of the binary tree.
- 8) Call the traversal functions with the root Node to perform inorder, preorder, and postorder traversal.

9) Stop

PROGRAM;

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node { int
element; struct
node* left; struct
node* right;
};
```

```
struct node* createNode(int val)
```

```
{
struct node* Node = (struct node*)malloc(sizeof(struct node));
Node->element = val;
Node->left = NULL;
```

```
Node->right = NULL;
```

```
return (Node);
```

```
}
```

```
void traversePreorder(struct node* root)
```

```
{
```

```
if (root == NULL) return;
```

```
printf(" %d ", root->element); traversePreorder(root->left);
```

```
traversePreorder(root->right);
```

```
}
```

```
void traverseInorder(struct node* root)
```

```
{
```

```
if (root == NULL) return;
```

```
traverseInorder(root->left); printf("
```

```
%d ", root->element);
```

```
traverseInorder(root->right);
```

```
}
```

```
void traversePostorder(struct node* root)
```

```
{
```

```
if (root == NULL) return;
```

```
traversePostorder(root->left);
```

```
traversePostorder(root->right); printf("
```

```
%d ", root->element);
```

```
}
```

```
int main()
```

```
{
```

```
struct node* root = createNode(36); root->
```

```
left = createNode(26); root->right =
```

```
createNode(46); root->left->left =
```

```
createNode(21); root->left->right =
```

```
createNode(31); root->left->left->left =
```

```
createNode(11); root->left->left->right =
```

```
createNode(24); root->right->left =
```

```
createNode(41); root->right->right =  
createNode(56); root->right->right->left =  
createNode(51); root->right->right->right  
= createNode(66);  
  
printf("\n The Preorder traversal of given binary tree is -\n");  
traversePreorder(root);  
printf("\n The Inorder traversal of given binary tree is -\n");  
traverseInorder(root);  
  
printf("\n The Postorder traversal of given binary tree is -\n");  
traversePostorder(root);  
  
return 0;  
}
```

OUTPUT:

```
aiml231501167@cselab:~$ ./a.out  
The Preorder traversal of given binary tree is -  
36 26 21 11 24 31 46 41 56 51 66  
The Inorder traversal of given binary tree is -  
11 21 24 26 31 36 41 46 51 56 66  
The Postorder traversal of given binary tree is -  
11 24 21 31 26 41 51 66 56 46 36 aiml231501167@cselab:~$
```



**RESULT: Thus, the program was successfully executed.**

Ex. No.:09	Implementation of Binary Search tree	Date:25/04/2024
------------	--------------------------------------	-----------------

**Write a C program to implement a Binary Search Tree and perform the following operations.**

- (i) Insert**
- (ii) Delete**
- (iii) Search**
- (iv) Display**

**Algorithm:**

- 1) Start
- 2) Define a Node structure with data, left child pointer, and right child pointer.
- 3) Initialize a root pointer to NULL.
- 4) Create functions for the following operations:
  - a. Insert:
    - If the tree is empty, create a new Node and set it as the root.
    - Otherwise, traverse the tree starting from the root:
      - If the data is less than the current Node's data, move to the left child.
      - If the data is greater than the current Node's data, move to the right child.
    - Repeat until reaching a NULL child pointer, then insert the new Node.
  - b. Search:
    - Start from the root and compare the data with each Node:
      - If the data matches, return the Node.
      - If the data is less than the current Node's data, move to the left child.
      - If the data is greater than the current Node's data, move to the right child.
    - Repeat until finding the data or reaching a NULL child pointer.
- 5) Test the operations by inserting elements into the tree and searching for specific values.
- 6) Stop

PROGRAM;

```
#include <stdio.h>
```

```
#include <stdlib.h> struct
```

```
BinaryTreeNode { int
```

```
key;
```

```
struct BinaryTreeNode *left, *right;
```

```
};
```

```

struct BinaryTreeNode* newNodeCreate(int value)
{
    struct BinaryTreeNode* temp =
    (struct BinaryTreeNode*)malloc(
    sizeof(struct BinaryTreeNode));
    temp->key = value; temp->left =
    temp->right = NULL; return temp;
}

struct BinaryTreeNode*
searchNode(struct BinaryTreeNode* root, int target)
{
    if (root == NULL || root->key == target) { return
    root;
    }
    if (root->key < target) { return
    searchNode(root->right, target);
    }
    return searchNode(root->left, target);
}

struct BinaryTreeNode*
insertNode(struct BinaryTreeNode* node, int value)
{
    if (node == NULL) { return
    newNodeCreate(value);
    }
    if (value < node->key) { node->left =
    insertNode(node->left, value);
    }
    else if (value > node->key) { node->right =
    insertNode(node->right, value);
    }
    return node;
}

```

```

void postOrder(struct BinaryTreeNode* root)
{
    if (root != NULL) {
        postOrder(root->left);
        postOrder(root->right);
        printf(" %d ", root->key);
    }
}

```

```

void inOrder(struct BinaryTreeNode* root)
{
    if (root != NULL) {
        inOrder(root->left); printf("
%d ", root->key);
        inOrder(root->right);
    }
}
v
oi
d
pr
e
O
rd
er
(s
tr
u
ct
Bi
n
ar
y
Tr
e

```

```

e
N
o
d
e*
ro
ot
)

{
if (root != NULL) { printf("
%d ", root->key);
preOrder(root->left);
preOrder(root->right);
}
}

struct BinaryTreeNode* findMin(struct BinaryTreeNode* root)
{
if (root == NULL) { return
NULL;
}
else if (root->left != NULL) { return
findMin(root->left);
}
return root;
}

struct BinaryTreeNode* delete (struct BinaryTreeNode* root,
int x)
{
if (root == NULL) return
NULL;

```

```

if (x > root->key) { root->right =
delete (root->right, x);
}
else if (x < root->key) { root->left
= delete (root->left, x);
}
else {
if (root->left == NULL && root->right == NULL) {
free(root); return NULL;
}
else if (root->left == NULL ||
root->right == NULL) { struct
BinaryTreeNode* temp; if
(root->left == NULL) { temp =
root->right;
} else { temp =
root->left;
}
free(root); return
temp;
} else
{
struct BinaryTreeNode* temp = findMin(root->right);
root->key = temp->key; root->right = delete (root-
>right, temp->key);
}
}
return root;
}

int main()
{
struct BinaryTreeNode* root = NULL;

```

```

root = insertNode(root, 50);
insertNode(root, 30);
insertNode(root, 20);
insertNode(root, 40);
insertNode(root, 70);
insertNode(root, 60);
insertNode(root, 80); if
(searchNode(root, 60) != NULL) {
printf("60 found");
} else { printf("60 not
found");
}

printf("\n");
postOrder(root);
printf("\n");

preOrder(root);
printf("\n"); inOrder(root);
printf("\n");

struct BinaryTreeNode* temp = delete (root, 70); printf("After
Delete: \n");
inOrder(root);

return 0;
}
OUTPUT:

```

```

aiml231501167@cselab:~$ ./a.out

The Preorder traversal of given binary tree is -
36 26 21 11 24 31 46 41 56 51 66
The Inorder traversal of given binary tree is -
11 21 24 26 31 36 41 46 51 56 66
The Postorder traversal of given binary tree is -
11 24 21 31 26 41 51 66 56 46 36 aiml231501167@cselab:~$

```

**RESULT:** Thus, the program was successfully executed.

Ex. No.: 10	Implementation of AVL Tree	Date:02/05/2024
-------------	----------------------------	-----------------

**Write a function in C program to insert a new node with a given value into an AVL tree. Ensure that the tree remains balanced after insertion by performing rotations if necessary. Repeat the above operation to delete a node from AVL tree.**

**Algorithm:**

- 1) Start
- 2) Define the AVL Node Structure.
- 3) Implement Rotation Operations (left and right rotations).
- 4) Insert new nodes into the AVL tree, updating heights and balancing as needed.

- 5) Delete nodes from the AVL tree, updating heights and balancing as needed.
- 6) Implement traversal functions (in-order, pre-order, post-order) to navigate through the tree.
- 7) Implement a search function to find specific elements within the AVL tree.
- 8) Test the AVL tree implementation with various scenarios.
- 9) Optionally, optimize the implementation for better performance.
- 10) Stop



PROGRAM:

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
struct node
```

```
{ int data; struct
node* left; struct
node* right; int ht;
};
```

```
struct node* root = NULL;
```

```
struct node* create(int); struct node*
insert(struct node*, int); struct node*
delete(struct node*, int); struct node*
search(struct node*, int); struct node*
rotate_left(struct node*); struct node*
rotate_right(struct node*); int
balance_factor(struct node*); int
height(struct node*); void
inorder(struct node*); void
preorder(struct node*); void
postorder(struct node*);
```

```
int main()
```

```
{
    int user_choice, data;
    char user_continue = 'y'; struct
    node* result = NULL;
```

```
while (user_continue == 'y' || user_continue == 'Y')
```

```
{
    printf("\n\n----- AVL TREE -----
\n"); printf("\n1. Insert"); printf("\n2.
```

```

Delete"); printf("\n3. Search");
printf("\n4. Inorder"); printf("\n5.
Preorder"); printf("\n6. Postorder");
printf("\n7. EXIT");

printf("\n\nEnter Your Choice: ");
scanf("%d", &user_choice);

switch(user_choice)
{
    case 1:
        printf("\nEnter data: ");
        scanf("%d", &data); root
        = insert(root, data);
        break;

    case 2:
        printf("\nEnter data: ");
        scanf("%d", &data); root
        = delete(root, data);
        break;

    case 3:
        printf("\nEnter data: ");
        scanf("%d", &data); result
        = search(root, data); if
        (result == NULL)
        {
            printf("\nNode not found!");
        } else
        {
            printf("\n Node found");
        }

        break; case 4:
inorder(root);
break;

```

```

case 5: preorder(root);
        break;

case 6: postorder(root);
        break;

case 7:
        printf("\n\tProgram Terminated\n");
        return 1;

default:
        printf("
        \n\tInv
        alid
        Choice
        \n");
    }

    printf("\n\nDo you want to continue? ");
    scanf(" %c", &user_continue);
}

return 0;
}

struct node* create(int data)
{
    struct node* new_node = (struct node*) malloc (sizeof(struct node)); if
    (new_node == NULL)
    {
        printf("\nMemory can&'t be allocated\n");
        return NULL;
    }
    new_node->data = data;
    new_node->left = NULL;
    new_node->right = NULL;
    return new_node;
}

```

```

struct node* rotate_left(struct node* root)
{
    struct node* right_child = root->right;
    root->right = right_child->left;
    right_child->left = root; root->ht =
    height(root); right_child->ht =
    height(right_child); return
    right_child;
}

struct node* rotate_right(struct node* root)
{
    struct node* left_child = root->left; root->left
    = left_child->right; left_child->right = root;

    root->ht    =    height(root);
    left_child->ht = height(left_child);
    return left_child;
}

```

```

int balance_factor(struct node* root)
{ int lh, rh; if (root == NULL)
    return 0; if (root->left ==
    NULL) lh = 0; else lh = 1 +
    root->left->ht; if (root-
    >right == NULL) rh = 0;
    else rh = 1 + root->right-
    >ht; return lh - rh;
}

```

```

int height(struct node* root)
{ int lh, rh;

    if (root == NULL)
    {

```

```

    return 0;
}
if (root->left == NULL)
    lh = 0; else lh = 1 + root-
>left->ht; if (root->right
== NULL) rh = 0; else
    rh = 1 + root->right->ht;

if (lh > rh)
    return  (lh);
    return (rh);
}

struct node* insert(struct node* root, int data)
{
    if (root == NULL)
    {
        struct node* new_node = create(data); if
        (new_node == NULL)
        {
            return NULL;
        }
        root = new_node;
    }
    else if (data > root->data)
    {
        root->right = insert(root->right, data);

        if (balance_factor(root) == -2)
        {
            if (data > root->right->data)

```

```

    {
        root = rotate_left(root);
    } else
    {
        root->right = rotate_right(root->right);
        root = rotate_left(root);
    }
}
} else
{
    root->left = insert(root->left, data); if
    (balance_factor(root) == 2)
    {
        if (data < root->left->data)
        {
            root = rotate_right(root);
        } else
        {
            root->left = rotate_left(root->left); root
            = rotate_right(root);
        }
    }
}
root->ht = height(root); return
root;
}

struct node * delete(struct node *root, int x)
{
    struct node * temp = NULL;

    if (root == NULL)
    {
        return NULL;
    }
}

```

```

}

if (x > root->data)
{
    root->right = delete(root->right, x); if
    (balance_factor(root) == 2)
    {
        if (balance_factor(root->left) >= 0)
        {
            root = rotate_right(root);
        } else
        {
            root->left = rotate_left(root->left); root
            = rotate_right(root);
        }
    }
}
else if (x < root->data)
{
    root->left = delete(root->left, x);
    if (balance_factor(root) == -2)
    {
        if (balance_factor(root->right) <= 0)
        {
            root = rotate_left(root);
        } else
    {
        root->right = rotate_right(root->right); root
        = rotate_left(root);
    }
}
} else
{

```

```

if (root->right != NULL)
{
temp = root->right; while
(temp->left != NULL) temp
= temp->left;

root->data = temp->data; root->right =
delete(root->right, temp->data); if
(balance_factor(root) == 2)
{
if (balance_factor(root->left) >= 0)
{
root = rotate_right(root);
}
else
{
root->left = rotate_left(root->left); root
= rotate_right(root);
}
}
} else
{
return (root->left);
}
}

root->ht = height(root); return
(root);
}

struct node* search(struct node* root, int key)
{
if(root == NULL)
{
return NULL;
}
}

```



```

if(root->data == key)
{
return root;
}
if(key > root->data)
{
search(root->right, key);
}
else
{
    search(root->left, key);
}
}

void inorder(struct node* root)
{
if (root == NULL)
{
return;
}
inorder(root->left); printf("%d
", root->data); inorder(root-
>right);
}

void preorder(struct node* root)
{
    if(root == NULL)
    {
return;
}
printf("%d ", root->data); preorder(root-
>left); preorder(root->right);

```

```

}

void postorder(struct node* root)
{
    if(root == NULL)
    {
        return;
    }
    postorder(root->left);
    postorder(root->right); printf("%d
", root->data);
}

```

OUTPUT:

```

----- AVL TREE -----

1. Insert
2. Delete
3. Search
4. Inorder
5. Preorder
6. Postorder
7. EXIT

Enter Your Choice: 1

Enter data: 15

Do you want to continue? y

----- AVL TREE -----

1. Insert
2. Delete
3. Search
4. Inorder
5. Preorder
6. Postorder
7. EXIT

Enter Your Choice: 1

Enter data: 20

Do you want to continue? y

----- AVL TREE -----

1. Insert
2. Delete
3. Search
4. Inorder
5. Preorder
6. Postorder
7. EXIT

Enter Your Choice: 1

Enter data: 25

Do you want to continue? y

----- AVL TREE -----

1. Insert

```

```
Enter data: 30
Node found
Do you want to continue? y
```

```
----- AVL TREE -----
```

1. Insert
2. Delete
3. Search
4. Inorder
5. Preorder
6. Postorder
7. EXIT

```
Enter Your Choice: 4
15 20 30 30
```

```
Do you want to continue? y
```

```
----- AVL TREE -----
```

1. Insert
2. Delete
3. Search
4. Inorder
5. Preorder
6. Postorder
7. EXIT

```
Enter Your Choice: 5
20 15 30 30
```

```
Do you want to continue? y
```

```
----- AVL TREE -----
```

1. Insert
2. Delete
3. Search
4. Inorder
5. Preorder
6. Postorder
7. EXIT

```
Enter Your Choice: 6
15 30 30 20
```

```
Do you want to continue? y
```

```
----- AVL TREE -----
```

1. Insert
2. Delete
3. Search
4. Inorder

**RESULT:** Thus, the program was successfully executed.

<b>Ex. No.: 11</b>	<b>Topological Sorting</b>	<b>Date:09/05/2024</b>
--------------------	----------------------------	------------------------

**Write a C program to create a graph and display the ordering of vertices.**

**Algorithm:**

- 1) Start
- 2) Initialize an empty stack to store the topologically sorted elements.
- 3) Initialize a set to track visited nodes.
- 4) Start a depth-first search (DFS) from any unvisited node in the graph.
- 5) During DFS traversal:
  - a. Mark the current node as visited.
  - b. Recursively visit all adjacent nodes that are not visited yet.
- 6) Once a node has no unvisited adjacent nodes, push it onto the stack.
- 7) Repeat steps 3-5 until all nodes are visited.
- Pop elements from the stack to get the topologically sorted order.
- 8) Stop

PROGRAM:

```
#include<stdio.h>
```

```
#include<stdlib.h>
```

```
int s[100], j, res[100]; void
AdjacencyMatrix(int a[][100], int n) {
    int i, j; for (i = 0; i < n;
    i++) { for (j = 0; j <=
    n; j++) { a[i][j] = 0;
    } } for (i = 1; i < n;
    i++) { for (j = 0; j < i;
    j++) { a[i][j] = rand()
    % 2; a[j][i] = 0;
    }
    } }
```

```
void dfs(int u, int n, int a[][100]) {
    int v; s[u] = 1; for (v = 0; v < n - 1;
    v++) { if (a[u][v] == 1 && s[v] ==
    0) { dfs(v, n, a);
    }
    } j +=
    1;
    res[j]
    = u;
    }
```

```
void topological_order(int n, int a[][100]) {
    int i, u; for (i = 0; i < n;
    i++) { s[i] = 0; } j = 0;
    for (u = 0; u < n; u++) {
    if (s[u] == 0) { dfs(u, n,
    a);
```

```

}
}
return;
}
int main() { int
a[100][100], n, i, j;

printf("Enter number of vertices\n");
scanf("%d", &n);

AdjacencyMatrix(a, n); printf("\t\tAdjacency Matrix of the graph\n"); /* PRINT
ADJACENCY MATRIX */

for (i = 0; i < n; i++) {
for (j = 0; j < n; j++) {
printf("\t%d", a[i][j]);
}
printf("\n");
}
printf("\nTopological order:\n");

topological_order(n, a);

for (i = n; i >= 1; i--) {
printf("-->%d", res[i]);
}
return 0;
}

```

OUTPUT:

```

aiml231501167@cselab:~$ gcc program12.c
aiml231501167@cselab:~$ ./a.out
Enter number of vertices
2
Adjacency Matrix of the graph
0 0
1 0
Topological order:
-->1-->0aiml231501167@cselab:~$

```

**RESULT:** Thus, the program was successfully executed.

Ex. No.:12	Graph Traversal	Date:09/05/2024
------------	-----------------	-----------------

**Write a C program to create a graph and perform a Breadth First Search and Depth First Search.**

**Algorithm:**

DFS

- 1) Start with an empty stack and a set to track visited nodes.
- 2) Push the starting node onto the stack and mark it as visited.
- 3) While the stack is not empty, do the following:
- 4) If the stack is not empty, pop a node from the stack.  
Process the node.
- 5) For each unvisited neighbor of the node, push the neighbor onto the stack and mark it as visited.
- 6) Repeat steps 3-6 until the stack is empty. 7) Stop

## BFS

- 1) Start with an empty queue and a set to track visited nodes.
- 2) Enqueue the starting node into the queue and mark it as visited.
- 3) While the queue is not empty, do the following:
- 4) If the queue is not empty, dequeue a node from the queue.  
Process the node.
- 5) For each unvisited neighbor of the node, enqueue the neighbor into the queue and mark it as visited.
- 6) Repeat steps 3-6 until the queue is empty.
- 7) Stop

PROGRAM: BFS

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct node { int
    vertex; struct
    node* next;
}; struct adj_list {
struct node* head;
};
```

```
struct graph { int
    num_vertices; struct
    adj_list* adj_lists; int*
    visited;
};
```

```
struct node* new_node(int vertex) { struct node* new_node =
(struct node*)malloc(sizeof(struct node)); new_node->vertex =
vertex; new_node->next = NULL; return new_node;
}
```

```
struct graph* create_graph(int n) { struct graph* graph = (struct
graph*)malloc(sizeof(struct graph)); graph->num_vertices = n;
graph->adj_lists = (struct adj_list*)malloc(n * sizeof(struct adj_list));
graph->visited = (int*)malloc(n * sizeof(int));
```



```

int i; for (i = 0; i < n; i++) { graph-
>adj_lists[i].head = NULL;
graph->visited[i] = 0;
}

return graph;
}

void add_edge(struct graph* graph, int src, int dest) {
struct node* new_node1 = new_node(dest);
new_node1->next = graph->adj_lists[src].head;
graph->adj_lists[src].head = new_node1; struct
node* new_node2 = new_node(src); new_node2-
>next = graph->adj_lists[dest].head; graph-
>adj_lists[dest].head = new_node2;
}

void bfs(struct graph* graph, int v) { int queue[1000]; int
front = -1; int rear = -1; graph->visited[v] = 1;
queue[++rear] = v; while (front != rear) { int
current_vertex = queue[++front]; printf("%d ",
current_vertex); struct node* temp = graph-
>adj_lists[current_vertex].head; while (temp != NULL) { int
adj_vertex = temp->vertex;

if (graph->visited[adj_vertex] == 0) { graph-
>visited[adj_vertex] = 1; queue[++rear] =
adj_vertex;
}
temp = temp->next;
}
}}

int main() { struct graph* graph =
create_graph(6); add_edge(graph, 0, 1);

```

```

add_edge(graph, 0, 2); add_edge(graph, 1, 3);
add_edge(graph, 1, 4); add_edge(graph, 2, 4);
add_edge(graph, 3, 4); add_edge(graph, 3, 5);
add_edge(graph, 4, 5); printf("BFS traversal
starting from vertex 0: "); bfs(graph, 0);

return 0;
}

DFS:
#include <stdio.h>
#include <stdlib.h>

// Globally declared visited array int
vis[100];
struct Graph {
    int V; int
    E; int**
    Adj;
};

struct Graph* adjMatrix()
{

    struct Graph* G = (struct Graph*)
        malloc(sizeof(struct Graph));
    if (!G) {
        printf("Memory Error\n"); return
        NULL;
    }
    G->V = 7;
    G->E = 7;

    G->Adj = (int**)malloc((G->V) * sizeof(int*)); for
    (int k = 0; k < G->V; k++) {

```

```

    G->Adj[k] = (int*)malloc((G->V) * sizeof(int));

}

for (int u = 0; u < G->V; u++) {
    for (int v = 0; v < G->V; v++) {
        G->Adj[u][v] = 0;

    }
}

G->Adj[0][1] = G->Adj[1][0] = 1;
G->Adj[0][2] = G->Adj[2][0] = 1;
G->Adj[1][3] = G->Adj[3][1] = 1; G-
>Adj[1][4] = G->Adj[4][1] = 1; G->Adj[1][5] =
G->Adj[5][1] = 1;

G->Adj[1][6] = G->Adj[6][1] = 1;
G->Adj[6][2] = G->Adj[2][6] = 1;

return G;
}

void DFS(struct Graph* G, int u)

{ vis[u] = 1; printf("%d ", u); for
  (int v = 0; v < G->V; v++) {
    if (!vis[v] && G->Adj[u][v]) {
        DFS(G, v);

    }
  }
}

void DFStraversal(struct Graph* G)
{

```

```

for (int i = 0; i < 100; i++) {
    vis[i] = 0;
} for (int i = 0; i < G->V; i++)
{ if (!vis[i]) {
    DFS(G, i);

    }
}
}

```

```

void main()
{
    struct Graph* G;
    G = adjMatrix();
    DFStraversal(G);
}

```

OUTPUT:

```
BFS traversal starting from vertex 0: 0 2 1 4 3 5 a
```

```
0 1 3 4 5 6 2
```

**RESULT: Thus, the program was successfully executed.**

<b>Ex. No.:13</b>	<b>Graph Traversal</b>	<b>Date:16/05/2014</b>
-------------------	------------------------	------------------------

**Write a C program to create a graph and find a minimum spanning tree using prim's algorithm.**

**Algorithm:**

- 1) Start
- 2) Initialize an empty set to store the minimum spanning tree (MST) and a priority queue to store edges and their weights.
- 3) Choose a starting node and add it to the MST set.
- 4) For each edge connected to the starting node, add the edge to the priority queue.
- 5) While the priority queue is not empty:
  - a. Extract the edge with the smallest weight from the priority queue.
  - b. If adding the edge to the MST set does not create a cycle, add the edge to the MST set.
  - c. For each neighbour of the newly added node in the MST set:
    - i. If the neighbour is not already in the MST set, add the edge connecting the neighbor to the priority queue.
- 6) Repeat step 4 until all nodes are included in the MST set.
- 7) The edges in the MST set form the minimum spanning tree of the graph. 8) Stop

PROGRAM:

```
#include <stdio.h>

#include <stdlib.h>

struct node { int
vertex; struct
node* next;
}; struct adj_list {
struct node* head;
};

struct graph { int
num_vertices; struct
adj_list* adj_lists; int*
visited;
};

struct node* new_node(int vertex) { struct node* new_node =
(struct node*)malloc(sizeof(struct node)); new_node->vertex =
vertex; new_node->next = NULL; return new_node;
}

struct graph* create_graph(int n) { struct graph* graph = (struct
graph*)malloc(sizeof(struct graph)); graph->num_vertices = n;
graph->adj_lists = (struct adj_list*)malloc(n * sizeof(struct adj_list));
graph->visited = (int*)malloc(n * sizeof(int));

int i; for (i = 0; i < n;
i++) { graph->adj_lists[i].head =
NULL; graph->visited[i] = 0;
}

return graph;
}
```

```

void add_edge(struct graph* graph, int src, int dest) {
    struct node* new_node1 = new_node(dest);
    new_node1->next = graph->adj_lists[src].head;
    graph->adj_lists[src].head = new_node1; struct
    node* new_node2 = new_node(src); new_node2-
    >next = graph->adj_lists[dest].head; graph-
    >adj_lists[dest].head = new_node2;
}

void bfs(struct graph* graph, int v) { int queue[1000]; int
    front = -1; int rear = -1; graph->visited[v] = 1;
    queue[++rear] = v; while (front != rear) { int
    current_vertex = queue[++front]; printf("%d ",
    current_vertex); struct node* temp = graph-
    >adj_lists[current_vertex].head; while (temp != NULL) { int
    adj_vertex = temp->vertex; if (graph->visited[adj_vertex]
    == 0) { graph->visited[adj_vertex] = 1; queue[++rear] =
    adj_vertex;
    }
    temp = temp->next;
    }
}

int main() { struct graph* graph =
    create_graph(6); add_edge(graph, 0, 1);
    add_edge(graph, 0, 2); add_edge(graph, 1, 3);
    add_edge(graph, 1, 4); add_edge(graph, 2, 4);
    add_edge(graph, 3, 4); add_edge(graph, 3, 5);
    add_edge(graph, 4, 5); printf("BFS traversal
    starting from vertex 0: "); bfs(graph, 0);

    return 0;
}

```

OUTPUT:

```
Input the number of vertices: 5
Input the adjacency matrix for the graph:
4
1
2
3
5
9
8
6
7
0
11
12
12
14
15
16
17
18
19
20
21
22
23
24
25
Edge    Weight
0 - 1    9
0 - 2   11
0 - 3   16
0 - 4   21
```

**RESULT:** Thus, the program was successfully executed.

Ex. No.:14	Graph Traversal	Date: 16/05/2024
------------	-----------------	------------------

**Write a C program to create a graph and find the shortest path using Dijkstra's Algorithm.**



**Algorithm:**

- 1) Start
- 2) Initialize the distance from the start node to all other nodes as infinity, except for the start node itself which is 0.
- 3) Create a priority queue to store nodes and their distances from the start node.
- 4) Add the start node to the priority queue with a distance of 0.
- 5) While the priority queue is not empty:
  - a. Extract the node with the smallest distance from the priority queue.
  - b. For each neighbor of the extracted node:
    - i. Calculate the distance from the start node to the neighbor through the extracted node.
    - ii. If this distance is smaller than the current distance stored for the neighbor, update the distance.
    - iii. Add the neighbor to the priority queue with the updated distance.
- 6) Repeat step 4 until all nodes have been processed.
- 7) The distances stored for each node after the algorithm completes represent the shortest path from the start node to that node.
- 8) Stop

```

PROGRAM;

#include <stdio.h>

#include <limits.h>

#define MAX_VERTICES 100

int minDistance(int dist[], int sptSet[], int vertices) {
    int min = INT_MAX, minIndex; for (int v = 0; v <
    vertices; v++) { if (!sptSet[v] && dist[v] < min) { min
    = dist[v]; minIndex = v;
    }
    }
    return minIndex;
}

void printSolution(int dist[], int vertices) {
    printf("Vertex \tDistance from Source\n");
    for (int i = 0; i < vertices; i++) { printf("%d
    \t%d\n", i, dist[i]);
    }
}

void dijkstra(int graph[MAX_VERTICES][MAX_VERTICES], int src, int
    vertices) { int dist[MAX_VERTICES]; int sptSet[MAX_VERTICES];
    for (int i = 0; i < vertices; i++) {
        dist[i] = INT_MAX; sptSet[i] =
        0;
    } dist[src] =
    0; for (int
    count = 0;
    count <
    vertices - 1;
    count++) {
        int u =
        minDistance
        (dist, sptSet,
        vertices);

```

```

sptSet[u] =
1;

for (int v = 0; v < vertices; v++) { if (!sptSet[v] &&
graph[u][v] && dist[u] != INT_MAX && dist[u] +
graph[u][v] < dist[v]) { dist[v] = dist[u] + graph[u][v];
}
}
}

printSolution(dist, vertices);
}

int main() { int vertices; printf("Input the
number of vertices: "); scanf("%d", &vertices); if
(vertices <= 0 || vertices > MAX_VERTICES) {
printf("Invalid number of vertices. Exiting...\n");
return 1;
}

int graph[MAX_VERTICES][MAX_VERTICES]; printf("Input the adjacency matrix
for the graph (use INT_MAX for infinity):\n"); for (int i = 0; i < vertices; i++) {

for (int j = 0; j < vertices; j++) {
scanf("%d", &graph[i][j]);
}
}

int source;

printf("Input the source vertex: ");
scanf("%d", &source); if (source < 0 ||
source >= vertices) { printf("Invalid source
vertex. Exiting...\n"); return 1;
}

dijkstra(graph, source, vertices); return
0;
}

```

OUTPUT:

```

a1m1231301167@cse1ab:~$ ./a.out
Input the number of vertices: 3
Input the adjacency matrix for the graph (use INT_MAX for infinity):
1
2
3
4
5
6
7
8
9
Input the source vertex: 1
Vertex Distance from Source
0      4
1      0
2      6

```

**RESULT:** Thus, the program was successfully executed.

Ex. No.:15	Sorting	Date:23/05/2024
------------	---------	-----------------

**Write a C program to take n numbers and sort the numbers in ascending order. Try to implement the same using the following sorting techniques.**

1. Quick Sort
2. Merge Sort

**Algorithm:**

- 1) Start
- 2) If the array has fewer than two elements, return it as it is already sorted.
- 3) Divide the array into two halves.
- 4) Recursively sort the two halves using Merge Sort.
- 5) Merge the sorted halves into a single sorted array.
- 6) Choose a sorting algorithm (e.g., Bubble Sort, Merge Sort, Quick Sort).
- 7) Implement the selected sorting algorithm.
- 8) Pass the unsorted array to the sorting algorithm.

- 9) Execute the sorting algorithm to sort the array. Obtain the sorted array as output.
- 10) stop

PROGRAM:

QUICK SORT: #include

<stdio.h> void

swap(int\* a, int\* b)

{

int temp = \*a; \*a

= \*b;

\*b = temp;

}

int partition(int arr[], int low, int high)

{ int pivot =

arr[low]; int i =

low;

int j = high;

while (i < j) { while (arr[i] <= pivot &&

i <= high - 1) { i++;

}

while (arr[j] > pivot && j >= low + 1) {

j--; } if (i < j) {

swap(&arr[i], &arr[j]);

}

}

swap(&arr[low], &arr[j]); return

j;

}

void quickSort(int arr[], int low, int high)

{ if (low < high)

{

int partitionIndex = partition(arr, low, high);

quickSort(arr, low, partitionIndex - 1); quickSort(arr,

partitionIndex + 1, high);

}

}

```

int main()
{
int arr[] = { 19, 17, 15, 12, 16, 18, 4, 11, 13 };
int n = sizeof(arr) / sizeof(arr[0]);
printf("Original array:"); for (int i = 0; i<n; i++)
{ printf("%d", arr[i]);
}
quickSort(arr, 0, n 0;
printf("\nSorted array:"); for
(int i = 0; i < n; i++) {
printf("%d", arr[i]);
}

```

```

return 0;
}

```

#### MERGE SORT

```

#include <stdio.h> #include
<stdlib.h> void merge(int arr[], int l,
int m, int r)
{ int i, j,
k;
int n1 = m - l + 1; int n2
= r - m; int L[n1], R[n2];
for (i = 0; i < n1; i++) L[i]
= arr[l + i]; for (j = 0; j <
n2; j++) R[j] = arr[m + 1
+ j]; i = 0; j = 0; k = l;
while (i < n1 && j < n2) {
if (L[i] <= R[j]) { arr[k] =
L[i]; i++;
} else {
arr[k] = R[j];
j++;
}
}

```

```

k++;
} while (i < n1)
{ arr[k] = L[i];
i++; k++;
}
while (j < n2) {
arr[k] = R[j]; j++;

k++;
}
}

void mergeSort(int arr[], int l, int r)
{ if (l < r) { int m = l + (r -
l) / 2; mergeSort(arr, l,
m); mergeSort(arr, m +
1, r); merge(arr, l, m, r);
}
}

void printArray(int A[], int size)
{ int i; for (i = 0;
i<size;      i++)
printf("%d ", A[i]);
printf("\n");
}

int main()
{
int arr[] = { 12, 11, 13, 5, 6, 7 }; int
arr_size = sizeof(arr) / sizeof(arr[0]);
printf("Given array is \n"); printArray(arr,
arr_size); mergeSort(arr, 0, arr_size -
1); printf("\nSorted array is \n");
printArray(arr, arr_size); return 0;
}

```



OUTPUT:

```
Original array:19171512161841113  
Sorted array:41112131516171819aim
```

**RESULT:** Thus, the program was successfully executed.

Ex. No.: 16	Hashing	Date:30/05/2024
-------------	---------	-----------------

**Write a C program to create a hash table and perform collision resolution using the following techniques.**

- (i) Open addressing**
- (ii) Closed Addressing**
- (iii) Rehashing Algorithm:**

### 1. Open Addressing:

1. Compute the hash of the key to be inserted.
2. Check the computed hash index in the hash table.
3. If the slot is empty, insert the key.
4. If the slot is occupied, then it means a collision has occurred. In this case, move to the next slot in the hash table.
5. Repeat the process until an empty slot is found.

### 2. Closed Addressing (Separate Chaining):

1. Compute the hash of the key to be inserted.
2. Check the computed hash index in the hash table.
3. If the slot is empty, insert the key.
4. If the slot is occupied, then it means a collision has occurred. In this case, add the new key to the linked list at that slot.

### 3. Rehashing:

1. When the load factor of the hash table reaches a certain threshold (typically  $> 0.7$ ), create a new hash table of larger size.
2. Compute the hash of each key in the old table.
3. Insert each key into the new table.
4. Delete the old table.

## PROGRAM:

### A. OPEN ADDRESSING:

```
#include <stdio.h>
#include <stdlib.h> #define

TSIZE 12

typedef struct Node {
int k; struct Node* n;
} Node;

int hFunc(int k) {
    return k % TSIZE;
}

// Open Addressing Hash Table int
oaHashTable[TSIZE];

void initOA() {
    for (int i = 0; i < TSIZE; i++) {
        oaHashTable[i] = -1;
    }
}

void insOA(int k) { int
    idx = hFunc(k); int
    origIdx = idx; int i
    = 1;
```

```
while (oaHashTable[idx] != -1) {
    idx = (origIdx + i) % TSIZE;
    i++;
}
oaHashTable[idx] = k;
}

void dispOA() {
    printf("OA Hash Table:\n"); for
    (int i = 0; i < TSIZE; i++) {
        if (oaHashTable[i] != -1) {
            printf("%d ", oaHashTable[i]);
        } else { printf("-
            ");
        }
    } printf("\n");
}
}
```



**B. CLOSED ADDRESSING;**

```
#include <stdio.h> #define
```

```
max 10
```

```
int a[11] = { 10, 14, 19, 26, 27, 31, 33, 35, 42, 44, 0 }; int
b[10];
```

```
void merging(int low, int mid, int high) {
int l1, l2, i;
```

```
for(l1 = low, l2 = mid + 1, i = low; l1 <= mid && l2 <= high; i++) {
if(a[l1] <= a[l2]) b[i] = a[l1++]; else b[i] = a[l2++];
}
while(l1 <= mid) b[i++]
= a[l1++]; while(l2 <=
high)
b[i++] = a[l2++];
```

```
for(i = low; i <= high; i++)
a[i] = b[i];
}
```

```
void sort(int low, int high) { int
mid;
```

```
if(low < high) { mid =
(low + high) / 2; sort(low,
mid); sort(mid+1, high);
merging(low, mid, high);
} else { return;
}
}
```

```
int main() {
int i;
```

```
printf("List before sorting\n");
```

```
for(i = 0; i <= max; i++)
printf("%d ", a[i]);
```

```
sort(0, max);
```

```
printf("\nList after sorting\n");
```

```
for(i = 0; i <= max; i++) printf("%d
", a[i]);
}
```

**C. REHASHING:**

```

#include <stdio.h>
#include <stdlib.h>

typedef struct Node {
int key; int value;
struct Node* next;
} Node;

typedef struct HashTable {
int size; int count; Node**
table;
} HashTable;

Node* createNode(int key, int value) { Node*
newNode = (Node*)malloc(sizeof(Node));
newNode->key = key; newNode->value = value;
newNode->next = NULL; return newNode;
}

HashTable* createTable(int size) {
HashTable* newTable = (HashTable*)malloc(sizeof(HashTable));
newTable->size = size; newTable->count = 0;
newTable->table = (Node**)malloc(sizeof(Node*) * size);
for (int i = 0; i < size; i++) {

newTable->table[i] = NULL;
}
return newTable;
}

int hashFunction(int key, int size) { return
key % size;
}

void insert(HashTable* hashTable, int key, int value);

void rehash(HashTable* hashTable) {
int oldSize = hashTable->size; Node**
oldTable = hashTable->table;

// New size is typically a prime number or double the old size int
newSize = oldSize * 2;
hashTable->table = (Node**)malloc(sizeof(Node*) * newSize);
hashTable->size = newSize; hashTable->count = 0;
for (int i = 0; i < newSize; i++) { hashTable->table[i]
= NULL;
}
}

```

```

for (int i = 0; i < oldSize; i++) {
    Node* current = oldTable[i]; while
    (current != NULL) {
        insert(hashTable, current->key, current->value); Node*
        temp = current;

        current = current->next;
        free(temp);
    }

    free(oldTable);
}

void insert(HashTable* hashTable, int key, int value) { if
((float)hashTable->count / hashTable->size >= 0.75) {
    rehash(hashTable);
}

    int hashIndex = hashFunction(key, hashTable->size);
    Node* newNode = createNode(key, value); newNode->next
    = hashTable->table[hashIndex]; hashTable-
    >table[hashIndex] = newNode; hashTable->count++;
}

    int search(HashTable* hashTable, int key) { int
    hashIndex = hashFunction(key, hashTable->size);
    Node* current = hashTable->table[hashIndex]; while
    (current != NULL) { if (current->key == key) { return
    current->value;
    }
    current = current->next;
}

    return -1;
}

void delete(HashTable* hashTable, int key) { int
hashIndex = hashFunction(key, hashTable->size);
Node* current = hashTable->table[hashIndex]; Node*
prev = NULL;
while (current != NULL && current->key != key) { prev
= current;
current = current->next;
}
if (current == NULL) { return;
}
if (prev == NULL) {
    hashTable->table[hashIndex] = current->next;
} else {
    prev->next = current->next;
}
}

```

```

}
free(current); hashTable->count--;
}

void freeTable(HashTable* hashTable) {
for (int i = 0; i < hashTable->size; i++) {
Node* current = hashTable->table[i];
while (current != NULL) { Node* temp =
current; current = current->next;

free(temp);
}
}
free(hashTable->table);
free(hashTable);
}

int main() {
HashTable* hashTable = createTable(5);

insert(hashTable, 1, 10); insert(hashTable,
2, 20); insert(hashTable, 3, 30);
insert(hashTable, 4, 40); insert(hashTable,
5, 50);
insert(hashTable, 6, 60); // This should trigger rehashing

printf("Value for key 1: %d\n", search(hashTable, 1)); printf("Value
for key 2: %d\n", search(hashTable, 2)); printf("Value for key 3:
%d\n", search(hashTable, 3)); printf("Value for key 4: %d\n",
search(hashTable, 4)); printf("Value for key 5: %d\n",
search(hashTable, 5));
printf("Value for key 6: %d\n", search(hashTable, 6));

delete(hashTable, 3);
printf("Value for key 3 after deletion: %d\n", search(hashTable, 3));

freeTable(hashTable); return
0;

}

```

**OUTPUT:**



```

aiml231501167@cselab:~$ gcc program16C.c
aiml231501167@cselab:~$ ./a.out
Value for key 1: 10
Value for key 2: 20
Value for key 3: 30
Value for key 4: 40
Value for key 5: 50
Value for key 6: 60
Value for key 3 after deletion: -1
aiml231501167@cselab:~$

```

```

aiml231501167@cselab:~$ ./a.out
Value for key 1: 10
Value for key 2: 20
Value for key 12: 30
Value for key 3: -1
Value for key 2 after deletion: -1
aiml231501167@cselab:~$

```

```

aiml231501167@cselab:~$ gcc program16A.c
aiml231501167@cselab:~$ ./a.out
List before sorting
10 14 19 26 27 31 33 35 42 44 0
List after sorting
0 10 14 19 26 27 31 33 35 42 44 aiml231501167@cselab:~$

```

**RESULT:** Thus, the program was successfully executed.



**Rajalakshmi Engineering College**  
**Rajalakshmi Nagar Thandalam, Chennai - 602 105.**  
**Phone : +91 -44 -67181111 , 67181112**  
**Website : [www.rajalakshmi.org](http://www.rajalakshmi.org)**