Task - 1:

IP address of particular domain -> to retrieve the IP address of a domain we can use “nslookup”, to get more details we can use “dig” command.

nslookup guvi.in

EC2

```
ubuntu@ip-172-31-38-111:~$ nslookup guvi.in
Server:         127.0.0.53
Address:        127.0.0.53#53

Non-authoritative answer:
Name:   guvi.in
Address: 104.26.4.88
Name:   guvi.in
Address: 172.67.70.207
Name:   guvi.in
Address: 104.26.5.88
Name:   guvi.in
Address: 2606:4700:20::ac43:46cf
Name:   guvi.in
Address: 2606:4700:20::681a:558
Name:   guvi.in
Address: 2606:4700:20::681a:458

ubuntu@ip-172-31-38-111:~$ dig guvi.in

; <<>> DiG 9.18.39-0ubuntu0.24.04.2-Ubuntu <<>> guvi.in
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 1501
;; flags: qr rd ra; QUERY: 1, ANSWER: 3, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 65494
;; QUESTION SECTION:
;guvi.in.                       IN      A

;; ANSWER SECTION:
guvi.in.                213     IN      A       172.67.70.207
guvi.in.                213     IN      A       104.26.5.88
guvi.in.                213     IN      A       104.26.4.88

;; Query time: 0 msec
;; SERVER: 127.0.0.53#53(127.0.0.53) (UDP)
;; WHEN: Wed Apr 08 10:35:11 UTC 2026
;; MSG SIZE  rcvd: 84
```

Check CPU and Memory usage of the server

For real time monitoring of CPU usage and Memory usage of the server we can use commands like “**top**” and “**htop**”

```
EC2

  0[                                                          0.0%] Tasks: 31, 38 thr, 78 kthr; 1 running
  1[                                                          0.0%] Load average: 0.00 0.00 0.00
Mem[||||||
```