TheTesting Academy
QUALITY ENGINEERING & TEST CONSULTING

Client: VWO (Wingify)
Prepared for QA review

Test Plan — KAN-4: Add Passkey & SSO Login Options to VWO Login Page

Drafted from JIRA story KAN-4 (Epic: Authentication Enhancements) — pending human review.

Document	Test Plan
JIRA Ticket	KAN-4 — [VWO] Add Passkey and SSO Login Options to VWO Login Page
Issue Type / Epic	Story · Epic: *Authentication Enhancements*
Priority	High (per ticket description) · JIRA field: Medium
Product / Feature	VWO Login Page — new *Sign in using SSO* & *Sign in with Passkey* options
Prepared By	TheTesting Academy — QA Team
Version	1.0 (Draft)
Date	3 November 2026
Status	**Draft — For Approval**

PREPARED BY THETESTING ACADEMY

TheTesting Academy is a quality-engineering and test-consulting partner specialising in authentication, A/B testing and digital-experience platforms. This plan was produced for VWO, a **Wingify** product used for A/B testing, conversion-rate optimisation and behavioural analytics across thousands of brands worldwide.

Client context: **VWO / Wingify** · Domain: **A/B testing platform** · Approx. scale: **~5,000 employees** · Focus: **secure, frictionless authentication**

CONTENTS

1. Scope & Objectives
2. Gaps & Questions for the Author
3. Test Scenarios (P0/P1/P2)
4. Test Data & Environment
5. Risks & Assumptions
6. Entry / Exit Criteria
7. Resource Allocation
8. Timelines & Sprint Details
9. Human Review Gate

1. Scope & Objectives

In scope

- **UI visibility & placement (AC1):** presence and position of the "Sign in using SSO" and "Sign in with Passkey" options on the login page, including their placement below the "Sign in with Google" option.
- **SSO login flow (AC2):** happy path (valid SSO credentials → authenticated → dashboard) and negative path (invalid credentials → appropriate error message).
- **Passkey login flow (AC3):** happy path (registered & verified passkey → logged in → dashboard), and the "no passkey available" fallback / guidance path.
- **Error handling (AC4):** failed SSO authentication, passkey authentication failure, and unsupported browser/device for passkeys.
- **Compatibility (AC5):** passkey flow across supported browsers/devices; SSO across all configured identity providers.
- **Security (AC6):** secure protocols (OAuth / SAML / WebAuthn) and no exposure of sensitive data in the UI or network logs.
- **Regression of existing auth:** email/password and "Sign in with Google" must remain unaffected.

Out of scope (per ticket)

- Passkey *registration* flow — covered in a separate story.
- SSO provider configuration / IdP setup.
- Redesign of existing authentication methods beyond verifying no regression.

Objective

"Tested" for this ticket means every acceptance criterion is demonstrated as an observable pass/fail; both new login flows are verified secure, reliable and usable across supported environments; the three defined error states behave correctly and leak no sensitive data; and existing login methods continue to work without regression.

Tech / platform context

WebAuthn (Passkey) · OAuth / SAML (SSO) · Web login page · Redirect to Dashboard

> **Note:** Protocol details (SAML vs OAuth per IdP, which WebAuthn platform authenticators are supported) are not stated in the ticket and are flagged in Section 2 as gaps.

2. Gaps & Questions for the Author

Each row scores KAN-4 against the requirement gap-analysis checklist (✓ **present** · ⚠ **ambiguous** · ✗ **missing**). Every ⚠/✗ becomes an open question.

#	Area	Status	Finding & question to the author
G1	Acceptance criteria testability	⚠	ACs describe outcomes at a high level but not observable specifics. *What are the exact button labels, and is the passkey option hidden, disabled, or shown-with-explanatory-text when the device lacks WebAuthn?*
G2	Error messaging	⚠	AC4 says "proper error messages" without text or behaviour. *Please provide the exact error copy and behaviour for: failed SSO, passkey failure, and unsupported browser/device.*
G3	Boundary & empty states	✗	No boundary/empty states defined. *What happens with: expired/revoked passkey, cancelled OS biometric prompt, timed-out SSO assertion, user with no passkeys registered, or 0 configured IdPs?*
G4	User cancellation	✗	No path for a user abandoning/cancelling the SSO redirect or passkey prompt. *Should the user return to the login page with a neutral message and no partial session?*
G5	State / session behaviour	✗	Post-login session lifecycle is unstated. *How do SSO and passkey sessions interact with session timeout, logout, "remember me", and existing MFA/2FA?*
G6	Test data	✗	No test data specified. *Can we be provided: SSO test accounts per IdP, a user with a registered passkey, a user without one, and invalid/revoked credentials?*
G7	Environment / flags	✗	No environment or feature-flag details. *Which environment (QA/Staging) hosts this, and is there a feature flag to toggle SSO/passkey independently?*
G8	IdP & dependencies	⚠	AC5 says "all configured identity providers" but none are named. *Which IdPs (SAML/OAuth: Azure AD, Okta, Google Workspace…) must SSO be validated against?*
G9	Browser/device matrix	⚠	"Supported browsers/devices only" is undefined. *What is the supported matrix for passkeys (Chrome/Edge/Safari versions, Windows Hello, Touch ID, Android biometrics, hardware keys)?*
G10	Non-functional – performance	✗	No performance expectations. *Any target for SSO redirect round-trip or passkey assertion latency under load?*
G11	Accessibility (a11y)	✗	A11y not mentioned explicitly. *Should the two new options meet WCAG 2.1 AA — keyboard operable, correct focus order, accessible names? (Ticket lists "responsiveness and accessibility" in its scenarios only.)*
G12	Security / roles	⚠	AC6 is generic. *Which roles/tenants may use SSO; must we test session-fixation, replay, and token/PII leakage in logs explicitly?*
G13	Regression surface	⚠	Impact on existing login is not stated. *Confirm that email/password and Google login must be regression-tested, including layout shifts from the new buttons.*
G14	Designs / mockups	✗	No designs linked (ticket has no attachments, components or Figma link). *Can the Figma/mockup and the intended visual spec for the two options be shared?*

#	Area	Status	Finding & question to the author
G15	Wording clarity	✗	Vague terms: “seamlessly”, “smooth user experience”, “appropriate/proper error messages”. *Can these be quantified so two engineers read them the same way?*
G16	Rollback / feature flag	✗	No rollback path defined. *If SSO/passkey misbehaves in production, can it be disabled without redeploy, and what is the fallback login experience?*

3. Test Scenarios

Priority is risk-based: **P0** critical / release-blocking · **P1** important · **P2** lower risk. Every scenario maps to an AC or an open gap (see Section 2).

ID	Pri	Type	Scenario	Maps to
TS-01	P0	Positive	Both “Sign in using SSO” and “Sign in with Passkey” options are visible on the login page on first load.	AC1
TS-02	P0	Positive	The two new options are positioned *below* “Sign in with Google”, in the intended order and styling.	AC1
TS-03	P1	Boundary	New options render correctly at minimum/maximum supported viewport widths and with long/localized labels (no overlap/truncation).	AC1 / G9 / G11
TS-04	P1	Regression	Existing email/password fields and “Sign in with Google” remain visible, correctly ordered and functional.	G13
TS-05	P0	Positive	Clicking “Sign in using SSO” with valid SSO credentials authenticates the user and redirects to the dashboard.	AC2
TS-06	P0	Negative	SSO login with invalid credentials shows an appropriate error and does *not* grant dashboard access.	AC2 / G2
TS-07	P1	Negative	SSO with an expired/revoked IdP account (or de-provisioned user) is rejected with a clear message.	G3 / G8
TS-08	P1	Negative	User cancels the SSO login at the IdP screen → returns to login page with a neutral message and no partial session.	G4
TS-09	P1	Boundary	SSO succeeds against *each* configured identity provider (every supported IdP / protocol).	AC5 / G8
TS-10	P1	Negative	After SSO login the correct tenant/account is mapped; no cross-account or cross-tenant data is exposed.	AC6 / G12
TS-11	P0	Positive	Clicking “Sign in with Passkey” with a registered, verified passkey logs the user in and redirects to the dashboard.	AC3
TS-12	P0	Negative	Passkey authentication failure (mismatch / failed biometric) shows an appropriate error and blocks access.	AC4 / G2
TS-13	P0	Negative	User with *no* registered passkey sees the defined fallback/guidance message (not a broken state).	AC3 / G3
TS-14	P1	Negative	Passkey that was deleted/revoked on the device produces a graceful error and guidance.	G3
TS-15	P1	Boundary	On an unsupported browser/device (no WebAuthn), the passkey option shows the defined message and cannot be used.	AC4 / AC5 / G1
TS-16	P1	Boundary	Passkey login works with multiple/roaming authenticators (security key, cross-device) where supported.	AC5 / G9
TS-17	P2	Boundary	Expired passkey challenge / assertion timeout is handled with a retry-able error, not a crash.	G3

ID	Pri	Type	Scenario	Maps to
TS-18	P0	Negative	All three error states (failed SSO, passkey failure, unsupported device) render the correct, non-sensitive message.	AC4 / AC6
TS-19	P1	Negative	Network failure / interrupted redirect mid-authentication surfaces a recoverable error and leaves no stuck session.	G3 / G5
TS-20	P0	Negative	No sensitive data (credentials, tokens, PII) appears in the UI, URLs, or network/browser logs during either flow.	AC6
TS-21	P0	Positive	SSO and passkey flows use secure protocols end-to-end (OAuth/SAML/WebAuthn over HTTPS).	AC6
TS-22	P1	Negative	Session-fixation / replay attempts after SSO or passkey login are rejected (new session issued on login).	AC6 / G12
TS-23	P1	Compatibility	Both flows verified across the agreed browser/OS/device matrix for the login page.	AC5 / G9
TS-24	P1	Accessibility	New options are keyboard operable with a logical focus order and accessible names/labels (WCAG 2.1 AA).	G11
TS-25	P2	Boundary	User can retry after a failed SSO/passkey attempt without page reload or lockout.	G3 / G4

> **Traceability:** AC1→TS-01..03, AC2→TS-05/06, AC3→TS-11/13, AC4→TS-12/15/18, AC5→TS-09/16/23, AC6→TS-10/20/21/22. Remaining scenarios cover the flagged gaps.

4. Test Data & Environment

Test data required (to be supplied — see G6)

Data set	Purpose
SSO test account per IdP	Valid SSO credentials for each configured identity provider (AC5).
Invalid / revoked SSO account	Negative SSO path and de-provisioned user (AC2, G3).
User with registered passkey	Successful passkey login (AC3).
User without any passkey	Fallback/guidance message (AC3).
Revoked / migrated passkey	Graceful failure after device change (G3).
Unsupported browser/device	No-WebAuthn behaviour (AC4).

Environment & configuration

- Target environment: QA / Staging (per ticket DoD — "deployed to staging") — *exact URL to confirm (G7)*.
- Feature flags to independently enable SSO and Passkey — *availability to confirm (G7/G16)*.

- At least one configured IdP with valid credentials for SSO testing.
- Devices/authenticators: passkey-capable laptop (Windows Hello / Touch ID), mobile (Android/iOS), and an unsupported device.

Roles / permissions

- Standard user, enterprise SSO user, and (if applicable) admin — *role matrix to confirm (G12)*.

Browsers / devices (indicative matrix — pending G9)

- Windows 10/11 – Chrome, Edge (passkey + SSO)
- macOS – Safari, Chrome (passkey + SSO)
- Android – Chrome (passkey + SSO)
- iOS – Safari (passkey + SSO)
- Legacy/unsupported browser – negative passkey path

5. Risks & Assumptions

Assumptions made

- A staging build with the feature deployed and enabled is available for testing.
- At least one SSO identity provider is configured with usable test credentials.
- A passkey-capable device/authenticator is available; error copy/design will be provided.
- "Dashboard" is the authenticated landing page reached after a successful login.

Risks

Risk	Mitigation
Passkey testing depends on specific hardware/OS/browser support.	Prepare a device matrix up front; use virtual/emulated authenticators where valid.
SSO availability relies on external IdP uptime.	Confirm IdP status before cycles; schedule around IdP maintenance.
Undefined error copy / design could cause rework.	Raise G2/G14 early; draft scenarios now, finalise assertions after answers.
Unclear supported-browser matrix (G9) risks under/over-testing.	Get the matrix agreed before execution; prioritise P0 on primary browsers.
Security scope (AC6) is broad and generic.	Agree explicit security checks (TS-20..22) with the author.

6. Entry / Exit Criteria

Entry criteria

- Feature deployed to staging and reachable; SSO/passkey flags enabled.
- Test data available (SSO accounts, passkey-registered users, invalid/revoked accounts).
- At least one IdP configured with credentials.
- Error copy and design spec available (or explicit waiver agreed).
- This test plan reviewed and approved by the QA owner.

Exit criteria

- All P0 scenarios pass; no open Critical/High defects (per ticket DoD).

- All acceptance criteria (AC1–AC6) demonstrated as pass.
- Regression of existing email/password and Google login confirmed green.
- Test summary report produced; open questions in Section 2 resolved or explicitly waived.
- QA sign-off recorded (per ticket DoD: "QA sign-off completed").

7. Resource Allocation

Role	Count	Responsibility
QA Lead / Test Manager	1	Plan sign-off, coverage ownership, defect triage, client communication.
Manual Test Engineer(s)	2	Execute UI, SSO, passkey, error, security and compatibility scenarios.
Automation Engineer	1	Automate P0 flows (Playwright) where feasible after approval.
Dev POCs (Frontend / Backend / DevOps)	≈3	Environment, IdP setup, defect fixes and clarifications.
Business Analyst / Product Owner	1	Resolve gaps in Section 2 and confirm acceptance.

8. Timelines & Sprint Details

- **Epic:** Authentication Enhancements · **Sprint:** current (KAN-4 created 31 Oct 2026) — sprint name/number to confirm.
- **Estimated effort:** ~1 sprint of test execution across 2 engineers, with contingency for device/IdP setup.

Task	Dates
Test plan review & gap resolution (Section 2)	To schedule
Test data & environment / IdP setup	To schedule
Test case design & review	To schedule
Test execution (P0 → P1 → P2)	To schedule
Regression & security validation	To schedule
Test summary report & sign-off	To schedule

> **Dates are intentionally left blank** — scheduling depends on the sprint plan and answers to Section 2.

HUMAN REVIEW GATE — MANDATORY

This plan is a DRAFT and is not approved.

I assumed: a staging build with SSO/passkey deployed and enabled; at least one IdP configured with usable credentials; a passkey-capable device is available; "dashboard" is the post-login landing page; error copy/design will be provided.

I could not confirm (the KAN-4 ticket contained no attachments, Figma links, components, labels or fix version, and left the following unstated): exact button labels & styling; exact error text; boundary/empty/cancellation states; session behaviour vs. MFA/logout; test data; environment & feature flags; the list of configured IdPs; the supported browser/device matrix; performance targets; accessibility expectations; role/permission rules; rollback behaviour.

Open questions blocking sign-off: G1–G16 in Section 2 — in priority order: G2 (error copy), G6/G7 (data & environment), G8/G9 (IdPs & browser matrix), G12 (security roles), G14 (designs), G16 (rollback).

→ Please **approve or edit** this plan before I write detailed test cases or any automation. I will not proceed to test-case creation until a human signs off.