
Dialogs:

By default, **dialogs are auto-dismissed by Playwright**, so you don't have to handle them.

However, you can register a dialog handler before the action that triggers the dialog to either `dialog.accept()` or `dialog.dismiss()` it.

Dialogs are JavaScript pop-ups like `alert`, `confirm`, and `prompt`.

Common Dialog Types

- `alert()`: Displays a message with an OK button.
- `confirm()`: Displays a message with OK and Cancel buttons.
- `prompt()`: Asks for user input.

How to Handle a Dialog

You need to **listen** for the dialog event and then **accept** or **dismiss** it.

Example – Handling an `alert()` Dialog

```
import { test, expect } from '@playwright/test';

test('handle alert dialog', async ({ page }) => {
  // Listen for the dialog
  page.on('dialog', async (dialog) => {
    console.log('Dialog message:', dialog.message());
    await dialog.accept(); // or dialog.dismiss();
  });

  await page.goto('https://example.com');
  await page.click('#trigger-alert'); // Assume this triggers an alert
});
```

Example – Handling a `confirm()` Dialog

```
page.on('dialog', async (dialog) => {
  console.log(dialog.message());
  await dialog.accept(); // Click OK
  // await dialog.dismiss(); // Click Cancel
});
```

Example – Handling a prompt() Dialog with Input

```
page.on('dialog', async (dialog) => {  
  console.log(dialog.message());  
  await dialog.accept('My input text'); // Provide input and click OK  
});
```

Frames:

An **iframe** (inline frame) is an HTML element that allows one HTML document to be embedded inside another.

Commonly used to include:

- YouTube videos
- Google Maps
- Other webpages inside the current page

page.frames()

- Returns a list of all frames on the current page.
- Helps in understanding how many iframes exist.

page.frame()

- Used to access a specific frame by its **URL** or **name**.
- Returns a Frame object that allows us to interact with elements inside the iframe.

page.frameLocator()

- A newer and preferred way to work with frames.
- Allows you to directly locate elements inside an iframe using Playwright's powerful locators.
- More **stable** than page.frame().

childFrames()

- If a frame contains **another nested frame**, you can access it using frame.childFrames().