

[← Mobile Testing with WebDriverIO](#)[AWS for Test Automation →](#)

# BrowserStack Integration

## Table of Contents

1. Cross-Browser and Cross-Device Testing Strategy
2. Integrating Playwright with BrowserStack
3. Integrating Cypress with BrowserStack
4. Integrating WebDriverIO with BrowserStack
5. Parallel Test Execution
6. Debugging Cloud Test Failures
7. Practice Exercises

## Cross-Browser and Cross-Device Testing Strategy

### Why Cloud Testing?

#### Challenges of Local Testing:

- Limited device/browser availability
- Maintenance overhead



- Scalability issues
- No parallel execution

### **Benefits of Cloud Testing:**

- Access to 3000+ real devices
- All browser versions
- No maintenance
- Parallel execution
- Instant scalability
- Videos and screenshots
- Network simulation
- Debugging tools

## **BrowserStack Overview**

**BrowserStack** provides cloud infrastructure for testing across browsers, operating systems, and mobile devices.

### **Features:**

- Real devices (not emulators)
- Live testing
- Automated testing
- Local testing
- Visual testing
- Accessibility testing
- Performance monitoring

### **Products:**

- **Live:** Manual interactive testing
- **Automate:** Web automation
- **App Automate:** Mobile app automation



## Testing Strategy

### Browser Coverage:

#### Desktop Browsers:

- **Chrome** (latest, latest-1, latest-2)
- **Firefox** (latest, latest-1)
- **Safari** (latest, latest-1)
- **Edge** (latest, latest-1)
- **Opera** (latest)

#### Mobile Browsers:

- **Safari** (iOS latest, latest-1)
- **Chrome** (Android latest, latest-1)
- Samsung Internet

### Device Coverage:

#### Popular Devices:

- iPhone **15**, **14**, **13**
- Samsung Galaxy **S23**, **S22**, **S21**
- Google Pixel **7**, **6**
- iPad Pro, Air

#### Screen Resolutions:

- **1920x1080** (Desktop)
- **1366x768** (Laptop)
- **768x1024** (Tablet)
- **375x667** (Mobile)

### Test Matrix:

#### Priority **1** (Critical):

- Chrome latest + Windows
- Safari latest + macOS
- Chrome latest + Android
- Safari latest + iOS

#### Priority **2** (High):



Priority **3** (Medium):

- All latest-**1** versions
- Popular devices

## Account Setup

### 1. Sign up:

- Visit [browserstack.com](https://browserstack.com)
- Create account (free trial available)
- Get credentials

### 2. Get credentials:

Username: `your_username`  
Access Key: `your_access_key`

### 3. Store securely:

```
# .env file (add to .gitignore)
BROWSERSTACK_USERNAME=your_username
BROWSERSTACK_ACCESS_KEY=your_access_key
```

# Integrating Playwright with BrowserStack

## Installation

### Install BrowserStack SDK:

```
npm install --save-dev @browserstack/playwright-helper
```



```
# browserstack.yml
auth:
  username: ${BROWSERSTACK_USERNAME}
  access_key: ${BROWSERSTACK_ACCESS_KEY}

browsers:
  - os: Windows
    osVersion: 11
    browserName: Chrome
    browserVersion: latest
  - os: OS X
    osVersion: Ventura
    browserName: Safari
    browserVersion: latest
  - os: Windows
    osVersion: 11
    browserName: Edge
    browserVersion: latest

run_settings:
  timeout: 0
  project: My Project
  build: Build 1
  name: Playwright Test
  buildIdentifier: ${BUILD_NUMBER}
  parallels: 5
```

### playwright.config.ts:

```
import { defineConfig } from '@playwright/test'
import { config as dotenvConfig } from 'dotenv'

dotenvConfig()

export default defineConfig({
  testDir: './tests',
  timeout: 30000,
  retries: 1,
  workers: 5,

  use: {
```



```
video: 'retain-on-failure',
trace: 'retain-on-failure',
},

projects: [
  {
    name: 'chrome-windows',
    use: {
      browserName: 'chromium',
      channel: 'chrome',
      connectOptions: {
        wsEndpoint: 'wss://cdp.browserstack.com/playwright',
      },
    },
  },
  {
    name: 'safari-mac',
    use: {
      browserName: 'webkit',
      connectOptions: {
        wsEndpoint: 'wss://cdp.browserstack.com/playwright',
      },
    },
  },
],
})
```

## Using BrowserStack with Playwright

### Basic test:

```
import { test, expect } from '@playwright/test'

test('BrowserStack test', async ({ page }) => {
  await page.goto('https://www.browserstack.com')

  const title = await page.title()
  expect(title).toContain('BrowserStack')

  await page.screenshot({ path: 'browserstack-home.png' })
})
```



```
import { chromium } from 'playwright'

const caps = {
  'browser': 'chrome',
  'browser_version': 'latest',
  'os': 'Windows',
  'os_version': '11',
  'name': 'Playwright Test',
  'build': 'Build 1',
  'browserstack.username': process.env.BROWSERSTACK_USERNAME,
  'browserstack.accessKey': process.env.BROWSERSTACK_ACCESS_KEY,
}

const browser = await chromium.connect({
  wsEndpoint: `wss://cdp.browserstack.com/playwright?caps=${encodeURIComponent(
const page = await browser.newPage()
await page.goto('https://example.com')

// Your test code

await browser.close()
```

## Session Management

### Mark test status:

```
import { test } from '@playwright/test'

test.afterEach(async ({ page }, testInfo) => {
  const status = testInfo.status === 'passed' ? 'passed' : 'failed'
  const reason = testInfo.error?.message || ''

  await page.evaluate(() => {}, `browserstack_executor: ${JSON.stringify({
    action: 'setSessionStatus',
    arguments: { status, reason }
  })}`)
})
```

### Set session name:



```
    arguments: { name: testInfo.title }  
  })})`  
})
```

## Local Testing

Test apps on localhost or private networks:

**Install BrowserStack Local:**

```
npm install --save-dev browserstack-local
```

**Start local connection:**

```
// setup-browserstack-local.ts  
import * as browserstack from 'browserstack-local'  
  
export async function startBrowserStackLocal() {  
  const bs_local = new browserstack.Local()  
  
  return new Promise((resolve, reject) => {  
    bs_local.start({  
      key: process.env.BROWSERSTACK_ACCESS_KEY,  
      force: 'true',  
      onlyAutomate: 'true',  
    }, (error: any) => {  
      if (error) reject(error)  
      else resolve(bs_local)  
    })  
  })  
}  
  
export async function stopBrowserStackLocal(bs_local: any) {  
  return new Promise((resolve) => {  
    bs_local.stop() => resolve(true)  
  })  
}
```

**Use in tests:**





```
let bsLocal: any

test.beforeAll(async () => {
  bsLocal = await startBrowserStackLocal()
})

test.afterAll(async () => {
  await stopBrowserStackLocal(bsLocal)
})

test('local test', async ({ page }) => {
  await page.goto('http://localhost:3000')
  // Test local application
})
```

## Parallel Execution

### Configure parallel workers:

```
// playwright.config.ts
export default defineConfig({
  workers: 5, // Run 5 tests in parallel

  projects: [
    { name: 'chrome-win11' },
    { name: 'safari-monterey' },
    { name: 'edge-win11' },
    { name: 'firefox-win10' },
    { name: 'chrome-mac' },
  ]
})
```

### Run tests:

```
npx playwright test --project=chrome-win11 --project=safari-monterey
```



## Installation

### Install plugin:

```
npm install --save-dev browserstack-cypress-cli
```

## Configuration

### Create browserstack.json:

```
{
  "auth": {
    "username": "${BROWSERSTACK_USERNAME}",
    "access_key": "${BROWSERSTACK_ACCESS_KEY}"
  },
  "browsers": [
    {
      "browser": "chrome",
      "os": "Windows 11",
      "versions": ["latest", "latest-1"]
    },
    {
      "browser": "firefox",
      "os": "Windows 10",
      "versions": ["latest"]
    },
    {
      "browser": "edge",
      "os": "Windows 11",
      "versions": ["latest"]
    },
    {
      "browser": "safari",
      "os": "OS X Ventura",
      "versions": ["latest"]
    }
  ],
  "run_settings": {
    "cypress_proj_dir": ".",
    "project_name": "My Cypress Project",
  }
}
```



```
"@faker-js/faker": "^7.6.0"
},
"package_config_options": {
  "video": true,
  "screenshotsFolder": "cypress/screenshots",
  "videosFolder": "cypress/videos"
},
"connection_settings": {
  "local": false,
  "local_identifier": null
},
"disable_usage_reporting": false
}
```

### **cypress.config.js:**

```
const { defineConfig } = require('cypress')

module.exports = defineConfig({
  e2e: {
    baseUrl: 'http://localhost:3000',
    specPattern: 'cypress/e2e/**/*.cy.{js,jsx,ts,tsx}',
    supportFile: 'cypress/support/e2e.js',

    setupNodeEvents(on, config) {
      // BrowserStack setup
      return config
    },
  },
})
```

## **Running Tests on BrowserStack**

### **Initialize:**

```
npx browserstack-cypress init
```

### **Run tests:**



### Run specific browsers:

```
npx browserstack-cypress run --browser chrome
```

### Run with local testing:

```
npx browserstack-cypress run --local
```

## BrowserStack Commands

### Install Cypress plugin:

```
npm install --save-dev cypress-browserstack
```

### cypress/support/e2e.js:

```
require('cypress-browserstack')
```

### Mark test status:

```
describe('BrowserStack Tests', () => {  
  afterEach(function() {  
    cy.browserstack('setSessionStatus', {  
      status: this.currentTest.state === 'passed' ? 'passed' : 'failed',  
      reason: this.currentTest.err?.message || ''  
    })  
  })  
  
  it('test example', () => {  
    cy.visit('https://example.com')  
    cy.get('h1').should('contain', 'Example')  
  })  
})
```



```
{
  "connection_settings": {
    "local": true,
    "local_identifier": "my-project"
  }
}
```

### Run with local:

```
npx browserstack-cypress run --local
```

## Parallel Execution

### Configure parallels:

```
{
  "run_settings": {
    "parallels": 10
  }
}
```

### Run:

```
npx browserstack-cypress run --parallels 10
```

---

# Integrating WebDriverIO with BrowserStack

---

## Installation

### Install service:



## Configuration

### wdio.conf.ts:

```
export const config = {
  user: process.env.BROWSERSTACK_USERNAME,
  key: process.env.BROWSERSTACK_ACCESS_KEY,

  services: [
    ['browserstack', {
      browserstackLocal: false,
      opts: {
        forceLocal: false,
      }
    }]
  ],

  capabilities: [
    {
      browserName: 'Chrome',
      'bstack:options': {
        os: 'Windows',
        osVersion: '11',
        browserVersion: 'latest',
        projectName: 'WebDriverIO Tests',
        buildName: 'Build 1',
        sessionName: 'Chrome Test',
        debug: true,
        networkLogs: true,
        consoleLogs: 'verbose',
        video: true,
      }
    },
    {
      browserName: 'Safari',
      'bstack:options': {
        os: 'OS X',
        osVersion: 'Ventura',
        browserVersion: 'latest',
        projectName: 'WebDriverIO Tests',
        buildName: 'Build 1',
        sessionName: 'Safari Test',
      }
    }
  ]
}
```



```
maxInstances: 5,
logLevel: 'info',
bail: 0,
waitForTimeout: 10000,
connectionRetryTimeout: 120000,
connectionRetryCount: 3,

framework: 'mocha',
reporters: ['spec'],

mochaOpts: {
  ui: 'bdd',
  timeout: 60000
},

afterTest: async function(test, context, { error, result, passed }) {
  if (!passed) {
    await browser.execute(
      'browserstack_executor: {"action": "setSessionStatus", "arguments"
      error.message + '"}}'
    )
  } else {
    await browser.execute(
      'browserstack_executor: {"action": "setSessionStatus", "arguments"
    )
  }
}
```

## Mobile Testing Configuration

### wdio.conf.ts for mobile:

```
capabilities: [
  {
    'bstack:options': {
      deviceName: 'Samsung Galaxy S23',
      platformVersion: '13.0',
      platformName: 'Android',
      app: process.env.BROWSERSTACK_APP_ID,
      projectName: 'Mobile App Tests',
      buildName: 'Android Build 1',
      sessionName: 'Galaxy S23 Test',
    },
  },
]
```



```
}
},
{
  'bstack:options': {
    deviceName: 'iPhone 15',
    platformVersion: '17',
    platformName: 'iOS',
    app: process.env.BROWSERSTACK_APP_ID,
    projectName: 'Mobile App Tests',
    buildName: 'iOS Build 1',
    sessionName: 'iPhone 15 Test',
  }
}
]
```

## Local Testing

### wdio.conf.ts:

```
services: [
  ['browserstack', {
    browserstackLocal: true,
    opts: {
      key: process.env.BROWSERSTACK_ACCESS_KEY,
      forceLocal: true,
      localIdentifier: 'my-project',
    }
  }]
]
```

## Custom Executors

### Mark session status:

```
it('test example', async () => {
  await browser.url('https://example.com')

  // Your test code

  // Mark as passed
})
```





```
} )
```

### Set session name:

```
beforeEach(async function() {  
  await browser.execute(  
    `browserstack_executor: {"action": "setSessionName", "arguments": {"na  
  })  
})
```

## Parallel Test Execution

### Strategy for Parallel Execution

#### Parallel levels:

1. Suite level - Different test suites
2. File level - Different spec files
3. Test level - Individual tests
4. Browser level - Same tests, different browsers

### Playwright Parallel Execution

#### playwright.config.ts:

```
export default defineConfig({  
  workers: 10, // 10 parallel workers  
  fullyParallel: true, // All tests run in parallel  
  
  projects: [  
    {  
      name: 'chrome-win11',  
      use: { /* ... */ },  
    },  
  ],  
})
```



```
    },  
    {  
      name: 'safari-ventura',  
      use: { /* ... */ },  
    },  
  ],  
}  
})
```

### Run command:

```
# All projects in parallel  
npx playwright test  
  
# Specific projects  
npx playwright test --project=chrome-win11 --project=safari-ventura  
  
# With custom workers  
npx playwright test --workers=5
```

## Cypress Parallel Execution

### browserstack.json:

```
{  
  "run_settings": {  
    "parallels": 10  
  }  
}
```

### Run:

```
npx browserstack-cypress run --parallels 10
```

### With Cypress Cloud:

```
cypress run --record --parallel --group "Chrome Tests"
```



```
export const config = {
  maxInstances: 10, // Max parallel instances

  capabilities: [
    { browserName: 'chrome' },
    { browserName: 'firefox' },
    { browserName: 'safari' },
    { browserName: 'edge' },
  ],

  specs: [
    './test/specs/**/*.ts'
  ]
}
```

### Run:

```
npx wdio run wdio.conf.ts
```

## Optimizing Parallel Execution

### Best practices:

```
// 1. Independent tests
// Each test should be able to run in isolation

// 2. No shared state
// Avoid global variables or shared data

// 3. Unique test data
// Generate unique data per test
const uniqueEmail = `test-${Date.now()}@example.com`

// 4. Cleanup
afterEach(async () => {
  // Clean up test data
})
```



### Calculate optimal workers:

```
workers = min(  
    number_of_tests / average_test_duration,  
    browserstack_parallel_limit,  
    available_memory / memory_per_worker  
)
```

#### Example:

- 100 tests
- Average duration: 30 seconds
- BrowserStack limit: 5 parallel
- Optimal workers: 5

## Debugging Cloud Test Failures

### BrowserStack Dashboard

#### Access dashboard:

1. Login to browserstack.com
2. Go to Automate/App Automate
3. View test sessions
4. Click on session for details

#### Session details include:

- Video recording
- Screenshots
- Console logs
- Network logs
- Selenium/Appium logs
- Test commands



## Video Recording

### Enable video:

```
// Playwright
screenshot: 'only-on-failure',
video: 'retain-on-failure',

// Cypress (browserstack.json)
"package_config_options": {
  "video": true
}

// WebDriverIO
'bstack:options': {
  video: true
}
```

### Download video:

```
# Via API
curl -u "USERNAME:ACCESS_KEY" \
  "https://api.browserstack.com/automate/sessions/SESSION_ID/video.mp4" \
  -o video.mp4
```

## Console Logs

### Enable console logs:

```
// WebDriverIO
'bstack:options': {
  consoleLogs: 'verbose'
}
```

### Access logs:

```
const logs = await browser.getLogs('browser')
console.log(logs)
```



## Enable network logs:

```
'bstack:options': {  
  networkLogs: true  
}
```

## Access via dashboard:

- Click on session
- Go to "Network" tab
- View all requests/responses
- Filter by type, status, etc.

## Screenshots on Failure

### Playwright:

```
import { test } from '@playwright/test'  
  
test.afterEach(async ({ page }, testInfo) => {  
  if (testInfo.status !== 'passed') {  
    const screenshot = await page.screenshot()  
    await testInfo.attach('screenshot', {  
      body: screenshot,  
      contentType: 'image/png'  
    })  
  }  
})
```

### Cypress:

```
afterEach(function() {  
  if (this.currentTest.state === 'failed') {  
    cy.screenshot(`FAILED-${this.currentTest.title}`)  
  }  
})
```



```
afterTest: async function(test, context, { passed }) {  
  if (!passed) {  
    await browser.saveScreenshot(  
      `./screenshots/FAILED-${test.title}.png`  
    )  
  }  
}
```

## Debug Mode

### Enable debug:

```
'bstack:options': {  
  debug: true,  
  networkLogs: true,  
  consoleLogs: 'verbose'  
}
```

## Common Issues and Solutions

### 1. Element not found:

```
// Issue: Element timing  
// Solution: Add explicit wait  
await page.waitForSelector('.element', { timeout: 10000 })  
  
// Solution: Use retry logic  
await browser.waitUntil(async () => {  
  return await $('.element').isDisplayed()  
}, { timeout: 10000 })
```

### 2. Flaky tests:

```
// Issue: Race conditions  
// Solution: Wait for page load  
await page.waitForLoadState('networkidle')  
  
// Solution: Wait for specific condition
```



### 3. Timeout errors:

```
// Issue: Default timeout too short
// Solution: Increase timeout
timeout: 60000, // 60 seconds

// Solution: Wait for specific state
await page.waitForSelector('.element', {
  state: 'visible',
  timeout: 30000
})
```

### 4. Session not found:

```
// Issue: Session expired
// Solution: Use session keep-alive
'bstack:options': {
  idleTimeout: 300 // 5 minutes
}
```

## REST API for Debugging

### Get session details:

```
curl -u "USERNAME:ACCESS_KEY" \
  "https://api.browserstack.com/automate/sessions/SESSION_ID.json"
```

### Get session logs:

```
curl -u "USERNAME:ACCESS_KEY" \
  "https://api.browserstack.com/automate/sessions/SESSION_ID/logs"
```

### Delete session:





# Practice Exercises

## Exercise 1: Multi-Browser Playwright Setup

**Task: Configure and run Playwright on multiple browsers**

```
// playwright.config.ts
// Configure for:
// - Chrome (Windows 11)
// - Firefox (Windows 10)
// - Safari (macOS Ventura)
// - Edge (Windows 11)

// Create test that:
// 1. Runs on all browsers
// 2. Takes screenshots
// 3. Records video on failure
// 4. Marks session status

// Your implementation
```

## Exercise 2: Cypress Parallel Execution

**Task: Setup Cypress with BrowserStack parallel testing**

```
// browserstack.json
// Configure for:
// - 5 parallel executions
// - Chrome, Firefox, Safari, Edge
// - Video recording enabled
// - Local testing enabled

// Create tests that:
// 1. Run independently
```



```
// Your implementation
```

## Exercise 3: Mobile App Testing

### Task: Test mobile app on multiple devices

```
// wdio.conf.ts
// Configure for:
// - Samsung Galaxy S23 (Android 13)
// - iPhone 15 (iOS 17)
// - Google Pixel 7 (Android 13)

// Create tests that:
// 1. Test app on all devices
// 2. Handle device-specific UI
// 3. Test both orientations
// 4. Capture screenshots on failure

// Your implementation
```

## Exercise 4: Local Testing Setup

### Task: Test local application on cloud browsers

```
// Setup local testing for:
// - Playwright
// - Cypress
// - WebDriverIO

// Test localhost:3000 application
// Verify local tunnel works
// Run tests on cloud browsers
// Debug any connection issues

// Your implementation
```

## Exercise 5: Comprehensive Test Suite



```
// Create test suite that:  
// 1. Tests on 5 browsers  
// 2. Runs 10 tests in parallel  
// 3. Includes web and mobile  
// 4. Captures all debugging info  
// 5. Reports to dashboard  
// 6. Marks all session statuses  
  
// Tests should cover:  
// - Login flow  
// - Form submission  
// - Navigation  
// - Data validation  
// - Error handling  
  
// Your implementation
```

## Exercise 6: Debugging Practice

### Task: Debug failing cloud tests

```
// Given a failing test:  
// 1. Review video recording  
// 2. Check console logs  
// 3. Analyze network logs  
// 4. Review screenshots  
// 5. Identify root cause  
// 6. Fix the issue  
// 7. Verify fix on cloud  
  
// Document your debugging process  
  
// Your implementation
```

## Exercise 7: Performance Testing

### Task: Measure parallel execution performance

```
// Measure and compare:  
// 1. Sequential execution time
```



```
// Calculate:  
// - Time saved  
// - Optimal worker count  
// - Cost efficiency  
// - Resource usage  
  
// Create report with findings  
  
// Your implementation
```

## Summary

In Day 11, you mastered:

### ✅ **Cloud Testing Strategy**

- Cross-browser coverage
- Device selection
- Test matrix design
- Priority planning

### ✅ **Playwright + BrowserStack**

- Configuration setup
- Capabilities management
- Session control
- Local testing
- Parallel execution

### ✅ **Cypress + BrowserStack**

- Plugin installation
- JSON configuration
- CLI usage



## ✓ **WebDriverIO + BrowserStack**

- Service integration
- Mobile capabilities
- Custom executors
- Debug options

## ✓ **Parallel Execution**

- Strategy design
- Worker optimization
- Independent tests
- Resource management

## ✓ **Debugging**

- Dashboard navigation
- Video analysis
- Log inspection
- Network debugging
- Screenshot capture
- API usage

## **Key Takeaways**

- **Cloud testing** eliminates device maintenance
- **BrowserStack** provides comprehensive coverage
- **Parallel execution** dramatically reduces test time
- **Proper configuration** is critical for success
- **Debugging tools** are essential for troubleshooting
- **Session management** provides test traceability



2. Use data-testid for stable selectors
3. Enable all debugging features
4. Mark session status always
5. Implement retry logic
6. Use local testing for staging
7. Monitor BrowserStack usage/costs
8. Keep credentials secure
9. Use build identifiers
10. Review failed sessions immediately

## Integration Checklist

- ☐ BrowserStack account setup
- ☐ Credentials stored securely
- ☐ Configuration files created
- ☐ Tests run locally first
- ☐ Capabilities configured correctly
- ☐ Parallel execution tested
- ☐ Local testing working
- ☐ Session status marked
- ☐ Debugging enabled
- ☐ Dashboard accessible

## Cost Optimization

### Tips to reduce costs:

- Use parallel wisely (don't over-parallelize)
- Set appropriate timeouts
- Clean up sessions
- Use local testing for dev



- 
- Delete old builds
  - Optimize test duration

## Next Steps

- **Day 12:** AWS for Test Automation
- **Day 13:** CI/CD & Test Reporting
- **Day 14:** AI in Test Automation
- **Day 15:** Framework Design & Capstone

**Only 4 more days to complete the program!** 🎯

---

### End of Day 11 Documentation

---

---

[← Mobile Testing with WebDriverIO](#)

[AWS for Test Automation →](#)

---

© 2026 VibeTestQ. All rights reserved.