

Practical(Q2)

Name: K.Vaishali

Rollno: 2520030117

Section: 8

Title: File Copying Using Linux System Calls and System Call Tracing Using strace

Aim: To develop a C program that uses the Linux system calls `open()`, `read()`, `write()`, and `close()` to copy the contents of one file to another.

Also, to use the `strace` utility to trace the system calls generated by the command:

`cat sample.txt`

and analyse the sequence of system calls and identify the kernel services involved.

Objective:

- To understand file handling using Linux system calls.
- To learn how `open()` opens a file.
- To learn how `read()` reads data from a file.
- To learn how `write()` writes data to another file.
- To learn how `close()` closes an opened file.
- To understand the transition between **user space and kernel space**.
- To use `strace` for tracing system calls.
- To identify the kernel services involved in executing

```
cat sample.txt.
```

Theory:

Linux provides system calls that allow user programs to request services from the kernel.

For file operations, the important system calls are: **1. open()**

The `open()` system call opens a file and returns a **file descriptor**. Example:

```
int fd = open("source.txt", O_RDONLY);
```

Here, `O_RDONLY` opens the file in read-only mode.

2. read()

The `read()` system call reads data from an opened file into a buffer.

```
read(fd, buffer, sizeof(buffer));
```

It returns the number of bytes actually read.

3. write()

The `write()` system call writes data from a buffer to a file. `write(fd, buffer, bytes);`

4. close()

The `close()` system call closes the file descriptor after the

file operation is completed.

```
close(fd);
```

User Space and Kernel Space

Linux divides execution into two important areas:

User Space

This is where normal applications such as our C program and the `cat` command execute.

Kernel Space

This is where the Linux kernel manages:

- Files
- Memory
- Processes
- Hardware
- Input/output operations
- File systems

When a C program calls `open()`, `read()`, `write()`, or `close()`, control transitions from **user space to kernel space**.

Control Flow

User Program

|

| `open()`

↓

Kernel

|

| File System

↓

Disk /

Storage |

↓

Kernel

|

↓

User

Program For

example: C

Program

↓

open()

↓

Kernel

↓

File

System ↓

Source File



Kernel



C Program

The same process occurs for read(), write(), and close().

Algorithm:

1. Start the program.
2. Open the source file using open() in read-only mode.
3. Open/create the destination file using open().
4. Read data from the source file using read().
5. Write the data to the destination file using write().
6. Repeat the read and write operations until the complete file is copied.
7. Close the source file using close().
8. Close the destination file using close().
9. Display a success message.
10. Stop.

System Calls Used:

System Call Purpose

open() Opens or creates a file

read() Reads data from a file

System Call Purpose

write() Writes data to a file close()

Closes a file descriptor

C Program:

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
#include <fcntl.h>
```

```
#include <unistd.h>
```

```
int main()
```

```
{
```

```
    int source, destination;
```

```
    char buffer[1024];
```

```
    ssize_t bytesRead;
```

```
    // Open source file for reading source =
```

```
    open("source.txt", O_RDONLY); if
```

```
    (source == -1)
```

```
{
```

```
perror("Error opening source file");
return 1;
}

// Open destination file for writing
// Create it if it does not exist

// Give read and write permissions to the
owner destination = open("destination.txt",
O_WRONLY | O_CREAT | O_TRUNC,
0644);

if (destination == -1)
{
perror("Error opening destination file");
close(source);
return 1;
}

// Read and write until the complete file is copied while
((bytesRead = read(source, buffer, sizeof(buffer))) > 0) {
if (write(destination, buffer, bytesRead) != bytesRead)
{
perror("Error writing to destination file");
close(source);
close(destination);
}
```

```
return 1;

}

}if (bytesRead == -1)

{
perror("Error reading source file");
}

else{

printf("File copied successfully.\n");

}

// Close both files

close(source);

close(destination);

return 0;

}
```

OUTPUT:

```
simra@simran315:~$ cd OSSP
simra@simran315:~/OSSP$ nano file1.c
simra@simran315:~/OSSP$ nano source.txt
simra@simran315:~/OSSP$ gcc file1.c -o file1
simra@simran315:~/OSSP$ ./file1
File copied successfully.
simra@simran315:~/OSSP$ cat destination.txt
Hello Linux!
This is a system call experiment.
File copying is performed using open, read, write and close.
simra@simran315:~/OSSP$ diff source.txt destination.txt
simra@simran315:~/OSSP$ echo "Hello from strace!" > sample.txt
simra@simran315:~/OSSP$ cat sample.txt
Hello from strace!
```

Part 2: strace System Call Tracing

Aim: To trace all system calls generated by the

command: `cat sample.txt`

using the `strace` utility and analyze the kernel services involved.

What is strace?

`strace` is a Linux debugging and diagnostic utility used to monitor the **system calls made by a process**.

For example:

`strace cat sample.txt`

This shows the system calls made by the `cat` command.

Important System Calls in `cat sample.txt`

When you execute:

`cat sample.txt`

the exact output varies depending on your Ubuntu version, libraries, architecture, and environment. However, the important file-related sequence is typically similar to:

`execve("../cat", ...)`

`openat(..., "sample.txt", O_RDONLY)`

`read(..., ...)`

`write(1, ...)`

`read(..., ...)`

`close(...)`

`exit_group(0)`

You may also see many additional calls related to program startup and shared libraries.

Sequence of Important System Calls:

1. `execve()`

`execve(...)`

The shell starts the cat program using `execve()`.

Kernel service: Process/program execution.

2. `openat()`

`openat(..., "sample.txt", O_RDONLY)`

cat asks the kernel to open `sample.txt`.

The kernel checks the file and returns a file

descriptor. **Kernel service:** File-system access.

On modern Linux systems, cat commonly uses `openat()` rather than the older `open()` system call.

3. `read()`

`read(fd, "Hello Linux!\n", ...)`

The cat program requests the kernel to read the contents of `sample.txt`.

Kernel service: File input / storage access.

4. write()

```
write(1, "Hello Linux!\n", ...)
```

File descriptor 1 represents **standard output**, normally the terminal.

The kernel writes the contents to the terminal. **Kernel service:** Output/I/O.

5. close()

```
close(fd)
```

After reading the file, cat closes the file descriptor.

Kernel service: File descriptor/resource management.

6. exit_group()

```
exit_group(0)
```

The process terminates successfully.

Kernel service: Process termination.

Simplified strace Flow:

Shell

|

| execve()



cat program



| openat()



Kernel



| Opens

sample.txt ↓

File System



| read()



Kernel



| write()



Terminal



| close()



Kernel

|

| exit_group()

↓

Process terminates

Observation:

- The C program successfully copied the contents of source.txt to destination.txt.
- open() was used to open the source and destination files.
- read() was used to read data from the source file. .
- write() was used to write data to the destination file. .
- close() was used to release the file descriptors.
- The strace utility successfully displayed the system calls generated by cat sample.txt.
- The cat command uses kernel services for opening, reading, writing, and closing files.
- System calls provide the interface between **user-space applications and the Linux kernel**.

Result:

The C program was successfully implemented using the open(), read(), write(), and close() system calls to copy a file.

The strace utility was also successfully used to trace the

system calls generated by `cat sample.txt`. The experiment demonstrated how user-space programs request file and process-related services from the Linux kernel through system calls.