

Design and apply context-aware access controls based on user identity, device posture, location, and application risk.

List of teammates:

S.no	Name	Collage	Mail ID
01	Sathya K	Shri Nehru Maha Vidyalaya College of Arts & Science	Sathya30082005@gmail.com
02	Pavithra M	Shri Nehru Maha Vidyalaya College of Arts & Science	pavimariduari@gmail.com
03	Rithik Rahul S	Shri Nehru Maha Vidyalaya College of Arts & Science	rithikrahul2005@gmail.com
04	Pragadeeswaran B	Shri Nehru Maha Vidyalaya College of Arts & Science	
05	Rameez M	Shri Nehru Maha Vidyalaya College of Arts & Science	

Introduction:

Modern organizations depend heavily on digital platforms, cloud services, and distributed networks to perform everyday operations. Employees now access corporate resources not only from office networks but also from homes, public networks, and mobile devices. Because of this transformation, traditional security models that rely only on network boundaries are no longer reliable. Organizations require smarter security approaches that verify every request before allowing access.

Context-aware access control is an advanced security approach that evaluates multiple factors before granting access to applications or sensitive information. Instead of trusting users simply because they are inside the corporate network, the system continuously examines contextual attributes such as the user's identity, the security status of their device, their geographic location, and the sensitivity of the application they are trying to access.

By analyzing these parameters together, organizations can enforce stronger security policies and reduce the risk of unauthorized access. This approach ensures that users receive only the permissions they truly require while protecting critical systems from potential threats.

In today's digital world, cyber threats are becoming more sophisticated and frequent. Organizations are increasingly dependent on digital infrastructure, which makes security one of the most important priorities for businesses and institutions. Protecting confidential information, financial data, and internal systems requires modern and adaptive security mechanisms.

Previously, organizations relied on perimeter-based security models where anyone inside the internal network was considered trustworthy. However, the rapid adoption of cloud technologies, mobile computing, and remote working environments has made this model ineffective. Employees now access company resources from different devices, networks, and locations, making traditional security strategies insufficient.

To address this challenge, organizations are shifting toward identity-based and context-aware security models. In this system, access decisions are not based solely on usernames and passwords. Instead, the system evaluates several contextual factors before granting permission. These include the user's role in the organization, the health and security of the device they are using, the location from which they are accessing the system, and the risk level of the application they are attempting to use.

The goal of this project is to design a system that applies context-aware access controls to protect enterprise resources. By continuously analyzing contextual data, the system ensures that only legitimate users with trusted devices and appropriate permissions can access sensitive applications.

Abstract:

The rapid growth of cloud computing, remote work environments, and mobile technologies has changed how organizations manage access to their digital resources. Traditional access control systems, which rely mainly on network location or simple authentication methods, are no longer capable of protecting modern enterprise environments.

Context-aware access control introduces a smarter and more dynamic approach to security. Instead of making simple allow-or-deny decisions, the system evaluates multiple contextual parameters before granting access. These parameters include user identity verification, device security status, geographical location, and the sensitivity of the requested application.

This project proposes the implementation of a context-aware access control system that enhances security while maintaining usability for authorized users. By integrating identity management systems, device posture checks, and risk-based policies, the solution ensures that access decisions are made intelligently and securely.

The system improves security by reducing the possibility of unauthorized access and minimizing the exposure of critical resources. It also supports modern workplace environments where employees frequently access corporate services from various devices and locations.

Another important advantage of context-aware access control is its ability to adapt security policies according to changing conditions. Instead of applying the same level of access to every user and device, the system dynamically evaluates risk levels and adjusts permissions accordingly. For example, access from a trusted office device may be granted immediately, while access from an unknown device or unusual location may require additional verification steps.

The implementation of context-aware policies also improves visibility and control for system administrators. Security teams can monitor access requests, detect suspicious activities, and enforce policies that align with organizational security requirements. This proactive approach helps reduce the likelihood of data breaches and unauthorized access.

Furthermore, integrating context-aware security with modern identity management systems allows organizations to support flexible work environments without compromising security. Employees can safely access enterprise applications from different devices and locations while the system continuously evaluates potential risks.

Overall, context-aware access control represents an effective solution for modern cybersecurity challenges by combining identity verification, device security validation, and contextual risk assessment to protect sensitive organizational resources.

Use Case Scenarios:

Scenario 1: Remote Employee Accessing Internal HR Portal

An employee working from home wants to access the organization's HR management portal to check leave balance and update personal information.

The system first authenticates the employee using their organizational credentials. After verifying the identity, the context-aware access control system checks the device posture to ensure the laptop has updated security patches and antivirus protection. It also verifies that the login location matches the user's normal working region.

If all security conditions are satisfied, the system allows secure access to the HR portal while blocking access to other sensitive internal systems.

Output:

- User identity verified successfully.
- Device posture checked and validated
- Access granted only to HR portal
- Other internal resources remain restricted

Scenario 2: Login from an Unrecognized Device

Access to Company Database from Untrusted Device

A user attempts to access a company database using a device that is not registered with the organization.

The context-aware access control system evaluates the device posture and detects that the device does not meet the organization's security policies. Because of this, the system blocks access to the database and notifies the user to use a trusted or compliant device.

Output:

- Device identified as untrusted
- Security policy violation detected
- Access to the database denied.
- User instructed to use a compliant device.

Scenario 3: Login Attempt from Unknown Geographic Location

A user attempts to log in to a sensitive business application from a geographic location that has never been used before by that account.

The system identifies this as a potential security risk and triggers additional verification measures. The user is required to complete multi-factor authentication before access can be granted.

If the verification fails or appears suspicious, the system blocks the login attempt.

Output:

- Login attempt detected from unusual location.
- Additional authentication required
- User identity re-verified
- Access granted only after successful verification.

Scenario 4: Accessing Cloud Storage from Public Network

An employee tries to access the organization's cloud storage service while connected to a public Wi-Fi network in a café.

The context-aware access control system recognizes that the network is not secure and applies stricter access policies. The system may allow the user to view files but restrict downloading or modifying sensitive documents.

Output:

- Public network detected
- Security risk level increased
- Limited access granted to cloud storage
- Sensitive data protected from download

Scenario 5: Administrator Access to Critical Application

A system administrator needs to access a critical internal application for maintenance.

Before granting access, the context-aware system verifies the administrator's identity, confirms the device security status, and checks that the request is coming from an approved network location. Only after all conditions are satisfied does the system allow administrative access to the application.

Output:

- Administrator identity verified.
- Device compliance confirmed.
- Network location validated.
- Secure administrative access granted.

Stage – 1

Title of the project:

Design and apply context-aware access controls based on user identity, device posture, location, and application risk.

Overview:

With the rapid growth of cloud computing, remote work, and mobile devices, traditional network security methods are becoming less effective. Earlier security models relied heavily on VPN-based access where users connected to the internal network and were trusted once authenticated. However, this approach often provides broad network access, which increases the possibility of cyberattacks and unauthorized movement within the network.

To overcome these limitations, modern organizations are moving towards a Zero Trust security approach. This model is based on the principle that no user or device should be trusted automatically, even if they are inside the network. Every access request must be continuously verified using multiple security factors before permission is granted.

In this project, a context-aware access control system is designed to strengthen security by evaluating several contextual parameters during every login attempt. These parameters include the identity of the user, the security condition of the device being used, the location from which the request is made, and the sensitivity level of the application that the user wants to access. By analysing these factors together, the system can make accurate decisions such as allowing access, limiting certain functions, requesting additional authentication, or blocking the request entirely.

The implementation uses Zscaler Private Access (ZPA) to establish secure, application-specific connections between users and internal resources. Unlike traditional VPN connections that expose the entire network, ZPA creates direct and secure connections only to the required applications. This method hides internal systems from the public internet and prevents attackers from discovering or targeting them.

Through this approach, the project aims to implement a least-privilege access model, where users receive only the minimum level of access necessary to perform their tasks. This significantly reduces the attack surface and prevents threats such as unauthorized access, credential misuse, and lateral movement across systems. The overall goal is to build a flexible and intelligent security framework that protects organizational resources while still allowing users to work efficiently in modern digital environments.

List of Vulnerability:

S.no	Category	Vulnerability Name	CWE/CVE - No
O1	Broken Access Control	Windows Hard Link	CWE-65
02	Security Misconfiguration	Active Debug Code	CWE-489
03	Software Supply Chain Failures	Use of Unmaintained Third-Party Components	CWE-1104
04	Cryptographic Failures	Use of Weak Hash	CWE-328
05	Injection	Improper Input Validation	CWE-20
06	Insecure Design	Permissive List of Allowed Inputs	CWE-183
07	Authentication Failures	Improper Authentication	CWE-287
08	Software or Data Integrity Failures	Untrusted Search Path	CWE-426
09	Security Logging and Alerting Failures	Information Loss or Omission	CWE-221
10	Mishandling of Exceptional Conditions	Uncaught Exception	CWE-248

Report:

1. **Vulnerability Name:** Windows Hard Link

CWE/CVE: 65

OWASP/SANS Category: Broken Access Control

Description: - Windows Hard Link vulnerability occurs when the operating system allows the creation of hard links that point to sensitive files. Attackers can exploit this weakness to manipulate file access or modify system files without proper authorization.

Business Impact: -If exploited, this vulnerability may allow attackers to alter important files, escalate privileges, or disrupt system operations. This can lead to unauthorized access to confidential data and compromise system integrity.

CWE-65: Windows Hard Link

Weakness ID: 65
Vulnerability Mapping: ALLOWED
Abstraction: Variant

View customized information:

Conceptual Operational Mapping Friendly Complete Custom

Description

The product, when opening a file or directory, does not sufficiently handle when the name is associated with a hard link to a target that is outside of the intended control sphere. This could allow an attacker to cause the product to operate on unauthorized files.

Extended Description

Failure for a system to check for hard links can result in vulnerability to different types of attacks. For example, an attacker can escalate their privileges if a file used by a privileged program is replaced with a hard link to a sensitive file (e.g. AUTOEXEC.BAT). When the process opens the file, the attacker can assume the privileges of that process, or prevent the program from accurately processing data.

Common Consequences

Impact	Details
Read Files or Directories; Modify Files or Directories	Scope: Confidentiality, Integrity

Recommendations:

- Restrict the creation of hard links to authorized users only.
- Implement proper file permission controls.
- Regularly monitor file system activities for suspicious changes.

2. Vulnerability Name: Active Debug Code

CWE/CVE: 489

OWASP/SANS Category: Security Misconfiguration

Description: - Debugging code is sometimes left in the application during development. If this code remains active in the production environment, it may expose sensitive information such as internal system paths, application logic, or database details.

Business Impact: - Attackers may use this information to understand the system architecture and exploit additional vulnerabilities, potentially leading to data leakage or system compromise.

CWE-489: Active Debug Code

Weakness ID: 489
Vulnerability Mapping: **ALLOWED**
Abstraction: Base

View customized information:

Conceptual

Operational


Mapping
Friendly

Complete

Custom

▼ Description

The product is released with debugging code still enabled or active.



Recommendations:

- Remove all debugging statements before deployment.
- Disable verbose error messages in production environments.
- Perform code reviews before releasing applications.

3.Vulnerability Name: Use of Unmaintained Third-Party Components

CWE/CVE: 1104

OWASP/SANS Category: Software Supply Chain Failures

Description: - Applications sometimes depend on external libraries or frameworks that are no longer maintained. These outdated components may contain known security flaws that attackers can exploit.

Business Impact: - Using outdated libraries increases the risk of exploitation, which may lead to system compromise, malware injection, or unauthorized data access.

CWE-1104: Use of Unmaintained Third Party Components

Weakness ID: 1104
Vulnerability Mapping: ALLOWED
Abstraction: Base

View customized information:

Conceptual

Operational


Mapping
Friendly

Complete

Custom

Description

The product relies on third-party components that are not actively supported or maintained by the original developer or a trusted proxy for the original developer.



Recommendations:

- Regularly update third-party components.
- Use dependency management tools to track vulnerabilities.
- Replace unsupported libraries with secure alternatives.

4.Vulnerability Name: Use of Weak Hash

CWE/CVE: 328

OWASP/SANS Category: Cryptographic Failures

Description: - Weak hashing algorithms such as MD5 or SHA1 may be used to store passwords or secure data. These algorithms are vulnerable to brute-force and collision attacks.

Business Impact: - Attackers may be able to crack hashed passwords and gain unauthorized access to user accounts or sensitive information.

CWE-328: Use of Weak Hash

Weakness ID: 328

Vulnerability Mapping: ALLOWED

Abstraction: Base

View customized information:

Conceptual

Operational

Mapping
Friendly

Complete

Custom

▼ Description

The product uses an algorithm that produces a digest (output value) that does not meet security expectations for a hash function that allows an adversary to reasonably determine the original input (preimage attack), find another input that can produce the same hash (2nd preimage attack), or find multiple inputs that evaluate to the same hash (birthday attack).

▼ Extended Description

A hash function is defined as an algorithm that maps arbitrarily sized data into a fixed-sized digest (output) such that the following properties hold:

1. The algorithm is not invertible (also called "one-way" or "not reversible")
2. The algorithm is deterministic; the same input produces the same digest every time

Building on this definition, a cryptographic hash function must also ensure that a malicious actor cannot leverage the hash function to have a reasonable chance of success at determining any of the following:

1. the original input (preimage attack), given only the digest
2. another input that can produce the same digest (2nd preimage attack), given the original input
3. a set of two or more inputs that evaluate to the same digest (birthday attack), given the actor can arbitrarily choose the inputs to be hashed and can do so a reasonable amount of times

What is regarded as "reasonable" varies by context and threat model, but in general, "reasonable" could cover any attack that is more efficient than brute force (i.e., on average, attempting half of all possible combinations). Note that some attacks might be more efficient than brute force but are still not regarded as achievable in the real world.

Recommendations:

- Use strong hashing algorithms like **bcrypt**, **Argon2**, or **SHA-256**.
- Implement salting techniques to strengthen password storage.
- Regularly review cryptographic configurations.

5.Vulnerability Name: Improper Input Validation

CWE/CVE: 20

OWASP/SANS Category: Injection

Description: - Improper input validation occurs when user inputs are not properly verified before being processed by the application. This can allow attackers to inject malicious data or scripts.

Business Impact: - Failure to validate inputs can result in multiple attacks such as SQL injection, cross-site scripting, or command injection, leading to data theft or application compromise.

CWE-20: Improper Input Validation

Weakness ID: 20

Vulnerability Mapping: **DISCOURAGED**

Abstraction: Class

View customized information:

Conceptual

Operational


Mapping
Friendly

Complete

Custom

▼ Description

The product receives input or data, but it does not validate or incorrectly validates that the input has the properties that are required to process the data safely and correctly.



▼ Extended Description

Input validation is a frequently-used technique for checking potentially dangerous inputs in order to ensure that the inputs are safe for processing within the code, or when communicating with other components.

Input can consist of:

- raw data - strings, numbers, parameters, file contents, etc.
- metadata - information about the raw data, such as headers or size

Recommendations:

- Validate all user inputs before processing.
- Use input filtering and encoding techniques.
- Implement server-side validation.

6.Vulnerability Name: Permissive List of Allowed Inputs

CWE/CVE: 183

OWASP/SANS Category: Insecure Design

Description: When an application allows overly broad input values without proper restrictions, attackers may exploit this behavior to bypass validation mechanisms.

Business Impact: - This weakness can enable unauthorized actions within the system and may lead to security breaches or manipulation of application data.

CWE-183: Permissive List of Allowed Inputs

Weakness ID: 183

Vulnerability Mapping: ALLOWED

Abstraction: Base

View customized information:

Conceptual

Operational

Mapping
Friendly

Complete

Custom

▼ Description

The product implements a protection mechanism that relies on a list of inputs (or properties of inputs) that are explicitly allowed by policy because the inputs are assumed to be safe, but the list is too permissive - that is, it allows an input that is unsafe, leading to resultant weaknesses.

▼ Alternate Terms

Allowlist / Allow List

This is used by CWE and CAPEC instead of other commonly-used terms. Its counterpart is denylist.

Safelist / Safe List

This is often used by security tools such as firewalls, email or web gateways, proxies, etc.

Whitelist / White List

This term is frequently used, but usage has been declining as organizations have started to adopt other terms.

▼ Common Consequences



Impact

Details

Bypass Protection

Scope: Access Control

Recommendations:

- Implement strict allow-list validation for user inputs.
- Define clear rules for acceptable data formats.
- Reject unexpected input values.

7.Vulnerability Name: Improper Authentication

CWE/CVE: 287

OWASP/SANS Category: Authentication Failures

Description: Improper authentication occurs when the system fails to properly verify user identity. Weak login mechanisms or flawed authentication logic can allow unauthorized users to access protected resources.

Business Impact: - Attackers may bypass authentication controls and gain access to confidential systems or sensitive data.

CWE-287: Improper Authentication

Weakness ID: 287
Vulnerability Mapping: **DISCOURAGED**
Abstraction: Class

View customized information:

Conceptual

Operational


Mapping
Friendly

Complete

Custom

▼ Description

When an actor claims to have a given identity, the product does not prove or insufficiently proves that the claim is correct.



▼ Alternate Terms

authentication

An alternate term is "authentification", which appears to be most commonly used by people from non-English-speaking countries.

AuthN

"AuthN" is typically used as an abbreviation of "authentication" within the web application security community. It is also distinct from "AuthZ," which is an abbreviation of "authorization." The use of "Auth" as an abbreviation is discouraged, since it could be used for either authentication or authorization.

Recommendations:

- Implement strong authentication mechanisms.
- Use **Multi-Factor Authentication (MFA)**.
- Apply secure password policies.

8.Vulnerability Name: Untrusted Search Path

CWE/CVE: 426

OWASP/SANS Category: Software or Data Integrity Failures

Description: An untrusted search path vulnerability occurs when an application loads files or executables from directories that attackers can control. This may allow malicious code to be executed.

Business Impact: - Attackers may replace legitimate files with malicious ones, leading to system compromise or unauthorized command execution.

CWE-426: Untrusted Search Path

Weakness ID: 426
Vulnerability Mapping: ALLOWED (with careful review of mapping notes)
Abstraction: Base

View customized information:

Conceptual

Operational

Mapping
Friendly

Complete

Custom

▼ Description

The product searches for critical resources using an externally-supplied search path that can point to resources that are not under the product's direct control.

▼ Extended Description

This might allow attackers to execute their own programs, access unauthorized data files, or modify configuration in unexpected ways. If the product uses a search path to locate critical resources such as programs, then an attacker could modify that search path to point to a malicious program, which the targeted product would then execute. The problem extends to any type of critical resource that the product trusts.

Some of the most common variants of untrusted search path are:

- In various UNIX and Linux-based systems, the PATH environment variable may be consulted to locate executable programs, and LD_PRELOAD may be used to locate a separate library.
- In various Microsoft-based systems, the PATH environment variable is consulted to locate a DLL, if the DLL is not found in other paths that appear earlier in the search order.

▼ Alternate Terms

Untrusted Path

▼ Common Consequences

Impact Details

Gain Privileges or
Assume Identity;

Scope: Integrity, Confidentiality, Availability, Access Control

Recommendations:

- Restrict search paths to trusted directories only.
- Avoid loading executable files from user-controlled locations.
- Validate file paths before execution.

9.Vulnerability Name: Information Loss or Omission

CWE/CVE: 221

OWASP/SANS Category: Security Logging and Alerting Failures

Description: This vulnerability occurs when important information required for proper system operation is not logged or recorded correctly. Missing logs may hide malicious activities.

Business Impact: - Without proper logging, security teams may not detect attacks in time, leading to delayed response and greater system damage.

CWE-221: Information Loss or Omission

Weakness ID: 221
Vulnerability Mapping: ALLOWED (with careful review of mapping notes)
Abstraction: Class

View customized information:

Conceptual

Operational

Mapping Friendly

Complete

Custom

Description

The product does not record, or improperly records, security-relevant information that leads to an incorrect decision or hampers later analysis.

Common Consequences

Impact

Details

Hide Activities

Scope: Non-Repudiation

Relationships

Relevant to the view "Research Concepts" (View-1000)

Nature	Type	ID	Name
ChildOf	P	664	Improper Control of a Resource Through its Lifetime
ParentOf	Ⓢ	222	Truncation of Security-relevant Information
ParentOf	Ⓢ	223	Omission of Security-relevant Information
ParentOf	Ⓢ	224	Obscured Security-relevant Information by Alternate Name
ParentOf	Ⓢ	356	Product UI does not Warn User of Unsafe Actions
ParentOf	Ⓢ	396	Declaration of Catch for Generic Exception
ParentOf	Ⓢ	397	Declaration of Throws for Generic Exception
ParentOf	Ⓢ	451	User Interface (UI) Misrepresentation of Critical Information

Recommendations:

- Implement comprehensive logging mechanisms.
- Monitor logs regularly for suspicious activities.
- Use automated alerting systems.

10.Vulnerability Name: Uncaught Exception

CWE/CVE: 248

OWASP/SANS Category: Mishandling of Exceptional Conditions

Description: An uncaught exception occurs when an application fails to handle unexpected errors properly. This may expose system details through error messages or cause application crashes

Business Impact: - Attackers may gain insights into the application structure through error messages, which can help them launch further attacks.

CWE-248: Uncaught Exception

Weakness ID: 248

Vulnerability Mapping: ALLOWED

Abstraction: Base

View customized information:

Conceptual

Operational

Mapping
Friendly

Complete

Custom

Description

An exception is thrown from a function, but it is not caught.

Extended Description

When an exception is not caught, it may cause the program to crash or expose sensitive information.

Common Consequences

Impact

DoS: Crash, Exit,
or Restart; Read
Application Data

Details

Scope: Availability, Confidentiality

An uncaught exception could cause the system to be placed in a state that could lead to a crash, exposure of sensitive information or other unintended behaviors.

Relationships

Relevant to the view "Research Concepts" (View-1000)

Nature	Type	ID	Name
ChildOf	🟢	705	Incorrect Control Flow Scoping
ChildOf	🟢	755	Improper Handling of Exceptional Conditions
ParentOf	🟡	600	Uncaught Exception in Servlet

Recommendations:

- Implement proper exception handling mechanisms.
- Avoid displaying detailed error messages to users.
- Log errors securely for debugging purposes.

Stage – 3

Title:

Design and apply context-aware access controls based on user identity, device posture, location, and application risk.

Context-aware access control represents the practical implementation of the **Zero Trust security architecture**, where no user or device is automatically trusted even if it originates from inside the network. Traditional security systems relied heavily on perimeter-based protection where users who successfully authenticated were granted broad access to internal resources. However, modern organizations operate in distributed environments where employees access applications from remote locations, personal devices, and cloud environments. Because of these changes, relying only on usernames and passwords is no longer sufficient to protect sensitive systems.

In this stage, a context-aware access control framework is designed to evaluate multiple security parameters before allowing a user to access an application. Instead of granting network-level access like traditional VPN solutions, the system uses **application-level access policies** that verify several contextual attributes. Technologies such as **Zscaler Private Access (ZPA)** help implement this model by creating secure connections between users and specific applications without exposing the internal network infrastructure.

Zero Trust Security Model

The **Zero Trust model** is based on the principle of “never trust, always verify.” In this approach, every access request is continuously verified regardless of where it originates. Users are only granted the minimum level of access required to perform their tasks. This principle reduces the attack surface and prevents attackers from moving laterally within the network if a system becomes compromised.

Zero Trust security enforces strict identity verification, device compliance checks, and contextual policy evaluation before allowing access to internal resources. By adopting this model, organizations can significantly improve their ability to detect and prevent unauthorized access attempts.

Zscaler Private Access (ZPA)

Zscaler Private Access (ZPA) is a cloud-based security solution that enables secure access to private applications without exposing them to the internet. Unlike traditional VPNs that provide network-level access, ZPA connects authenticated users directly to the specific application they are authorized to use.

This approach hides internal applications from public visibility and prevents attackers from discovering internal systems through network scanning. ZPA also integrates with identity

providers and endpoint security solutions to enforce context-aware access policies based on user identity, device posture, location, and application sensitivity.

User Identity Verification

User identity is the primary factor in determining whether access should be granted. Identity verification is typically performed through identity providers such as **Azure Active Directory** or **Okta**, which authenticate users and provide important identity attributes.

Additional security measures such as **Multi-Factor Authentication (MFA)** ensure that only legitimate users can access protected applications. The system also retrieves user attributes such as department, role, and group membership to enforce role-based access policies.

Device Posture Evaluation

In addition to verifying the user's identity, the system evaluates the **security status of the device** being used to access the application. Device posture checks ensure that the device complies with organizational security policies.

These checks may include verifying operating system updates, antivirus status, firewall configuration, and disk encryption. If the device does not meet security requirements, the system may limit or deny access to sensitive applications.

Location-Based Access Control

The **location of the user** is another important contextual factor considered in access control decisions. The system evaluates whether the user is accessing the application from a trusted corporate network, a home network, or a public internet connection.

Access requests from trusted locations may be allowed with minimal restrictions, while requests from unknown or high-risk locations may trigger additional authentication requirements or be blocked entirely.

Application Risk Assessment

Not all applications within an organization require the same level of security. Some applications may contain sensitive information such as financial data or administrative controls, making them high-risk systems.

Applications are therefore categorized based on their **risk level and sensitivity**. Access to critical systems requires stricter authentication and device compliance checks, ensuring that sensitive information remains protected.

Policy-Based Access Decision

All contextual information—including user identity, device posture, location, and application risk—is evaluated by a **policy decision engine**. This engine applies predefined security policies to determine whether a user should be granted access to a particular application.

For example, a policy may allow access only if the user belongs to a specific department, uses a compliant device, and connects from a trusted location during working hours. By applying such policies, organizations can enforce the **least-privilege access principle**, ensuring that users only receive the permissions necessary for their role.

Conclusion

Stage 1

Stage-1 emphasized the importance of **web application security testing** in identifying vulnerabilities that could compromise the integrity and reliability of web-based systems. The testing process involved evaluating different aspects of the application, including authentication mechanisms, input validation procedures, and configuration settings. Detecting vulnerabilities at an early stage helps organizations address security flaws before attackers can exploit them. This stage highlighted how proactive security testing contributes to building secure and reliable applications.

Stage 2

In Stage-2, the security assessment identified several vulnerabilities present in the web application environment. These findings demonstrated that even well-designed applications may contain security weaknesses if proper validation and configuration practices are not followed. The analysis emphasized the importance of implementing corrective measures such as patching vulnerable components, improving input validation, and strengthening access control mechanisms. The stage also reinforced the value of continuous monitoring and adherence to recognized security standards to maintain a secure system environment.

Stage 3

Stage-3 focuses on implementing a **Zero Trust-based access control model** that prevents unauthorized access to internal applications. Instead of exposing applications to the internet through traditional VPN systems, technologies such as **Zscaler Private Access (ZPA)** allow users to connect securely to specific applications without revealing the internal network infrastructure. This approach significantly reduces the risk of cyberattacks while providing users with secure and reliable access to organizational resources. By adopting a context-aware security framework, organizations can strengthen their security posture while supporting flexible work environments.

Future Scope

Stage 1: Future scope of web application testing

The field of web application testing is continuously evolving due to the rapid growth of digital platforms and web technologies.

- **Increasing demand:** As businesses increasingly rely on online services, the need for effective security testing and vulnerability detection will continue to grow.
- **Advanced technologies:** Modern web applications integrate technologies such as artificial intelligence, cloud computing, and blockchain, which introduce new security challenges that require specialized testing methods.
- **Stronger security requirements:** With the rise in cyberattacks and data breaches, organizations will place greater emphasis on continuous vulnerability testing and proactive security assessments.
- **Mobile and cross-browser compatibility:** As mobile usage continues to expand, ensuring secure functionality across different devices and browsers will become increasingly important.
- **Performance and load testing:** Future testing methodologies will focus more on evaluating system performance under heavy workloads to ensure reliability during peak usage.

Stage 2: Future scope of the testing process

The future of vulnerability assessment is promising, particularly with the increasing complexity of digital systems.

- **AI-based testing tools:** Artificial intelligence and machine learning technologies can automate vulnerability detection by analysing large volumes of code and identifying patterns that indicate potential security risks.
- **Expansion of IoT environments:** As Internet of Things devices become more common, security testing will need to extend beyond traditional web applications to include connected devices and networks.
- **Blockchain security:** With the growing use of blockchain technology in financial and digital systems, testing techniques will evolve to address vulnerabilities in blockchain-based applications.

- **Serverless architectures:** The adoption of serverless computing will require new testing approaches to ensure that serverless components remain secure and free from vulnerabilities.
- **Container security:** With the widespread use of container technologies such as Docker and Kubernetes, security testing will also focus on container environments and orchestration platforms.

Stage 3: Future scope of aware access control

The implementation of **Zscaler Private Access (ZPA)** provides a strong foundation for developing more advanced security capabilities in the future.

- **Integration with Zscaler Internet Access (ZIA):** Combining ZPA with ZIA can create a unified security platform that manages both private and internet traffic through a single policy framework.
- **Advanced device posture verification:** Future systems may integrate endpoint detection tools that provide detailed risk assessments of devices before granting access.
- **Secure access for third-party users:** Organizations may extend secure access capabilities to vendors and contractors using controlled and time-limited permissions.
- **Protection of IoT and operational technology:** Zero Trust principles can be applied to IoT devices to ensure that only authorized systems can communicate with critical infrastructure.
- **AI-based anomaly detection:** Machine learning technologies can analyze user behavior and detect suspicious activity such as unusual login patterns or abnormal data access.
- **Cloud workload security:** Secure access technologies can be expanded to protect cloud-based applications and services across multiple cloud environments.
- **Automated user provisioning:** Identity management systems can automatically assign or revoke access privileges based on changes in employee roles or responsibilities.
- **Digital experience monitoring:** Monitoring tools can be used to track network performance and user connectivity to ensure smooth and secure application access.

Topics Explored

1. Zscaler
2. Zero Trust
3. ZPA

4. VPN
5. MISP
6. College Network Information
7. Deployment of SOC in the College
8. Threat Intelligence
9. Incident Response

Tools Explored

- Nessus Scanner