

# HTML PRACTICE-II

# HTML RGB COLORS

- An RGB color value represents RED, GREEN, and BLUE light sources.
- An RGBA color value is an extension of RGB with an Alpha channel (opacity).
- In HTML, a color can be specified as an RGB value, using this formula:  
**`rgb(red, green, blue)`**
- Each parameter (red, green, and blue) defines the intensity of the color with a value between 0 and 255.

# HTML RGB COLORS

- This means that there are  $256 \times 256 \times 256 = 16777216$  possible colors!
- For example, `rgb(255, 0, 0)` is displayed as red, because red is set to its highest value (255), and the other two (green and blue) are set to 0.
- Another example, `rgb(0, 255, 0)` is displayed as green, because green is set to its highest value (255), and the other two (red and blue) are set to 0.
- To display black, set all color parameters to 0, like this: `rgb(0, 0, 0)`.
- To display white, set all color parameters to 255, like this: `rgb(255, 255, 255)`.

# EXAMPLE

rgb(255, 0, 0)

rgb(0, 0, 255)

rgb(60, 179, 113)

rgb(238, 130, 238)

rgb(255, 165, 0)

rgb(106, 90, 205)

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h1 style="background-color:rgb(255, 0, 0);">rgb(255, 0, 0)</h1>
```

```
<h1 style="background-color:rgb(0, 0, 255);">rgb(0, 0, 255)</h1>
```

```
<h1 style="background-color:rgb(60, 179, 113);">rgb(60, 179, 113)</h1>
```

```
<h1 style="background-color:rgb(238, 130, 238);">rgb(238, 130, 238)</h1>
```

```
<h1 style="background-color:rgb(255, 165, 0);">rgb(255, 165, 0)</h1>
```

```
<h1 style="background-color:rgb(106, 90, 205);">rgb(106, 90, 205)</h1>
```

```
</body>
```

```
</html>
```

# EXAMPLE-SHADES OF GREY

rgb(60, 60, 60)

rgb(100, 100, 100)

rgb(140, 140, 140)

rgb(180, 180, 180)

rgb(200, 200, 200)

rgb(240, 240, 240)

```
<!DOCTYPE html>
<html>
<body>
```

```
<h1 style="background-color:rgb(60, 60, 60);">rgb(60, 60, 60)</h1>
<h1 style="background-color:rgb(100, 100, 100);">rgb(100, 100, 100)</h1>
<h1 style="background-color:rgb(140, 140, 140);">rgb(140, 140, 140)</h1>
<h1 style="background-color:rgb(180, 180, 180);">rgb(180, 180, 180)</h1>
<h1 style="background-color:rgb(200, 200, 200);">rgb(200, 200, 200)</h1>
<h1 style="background-color:rgb(240, 240, 240);">rgb(240, 240, 240)</h1>
```

```
</body>
</html>
```

# HTML HEX Colors

- A hexadecimal color is specified with: #RRGGBB, where the RR (red), GG (green) and BB (blue) hexadecimal integers specify the components of the color.
- In HTML, a color can be specified using a hexadecimal value in the form:  
*#rrggbb*
- Where rr (red), gg (green) and bb (blue) are hexadecimal values between 00 and ff (same as decimal 0-255).
- For example, #ff0000 is displayed as red, because red is set to its highest value (ff), and the other two (green and blue) are set to 00.
- Another example, #00ff00 is displayed as green, because green is set to its highest value (ff), and the other two (red and blue) are set to 00.
- To display black, set all color parameters to 00, like this: #000000. To display white, set all color parameters to ff, like this: #ffffff.

# EXAMPLE

#ff0000

#0000ff

#3cb371

#ee82ee

#ffa500

#6a5acd

```
<!DOCTYPE html>
```

```
<html>
```

```
<body>
```

```
<h1 style="background-color:#ff0000;">#ff0000</h1>
```

```
<h1 style="background-color:#0000ff;">#0000ff</h1>
```

```
<h1 style="background-color:#3cb371;">#3cb371</h1>
```

```
<h1 style="background-color:#ee82ee;">#ee82ee</h1>
```

```
<h1 style="background-color:#ffa500;">#ffa500</h1>
```

```
<h1 style="background-color:#6a5acd;">#6a5acd</h1>
```

```
</body>
```

```
</html>
```

# EXAMPLE-SHADES OF GREY

#404040

#686868

#a0a0a0

#bebebe

#dcdcdc

#f8f8f8

```
<!DOCTYPE html>  
<html>  
<body>
```

```
<h1 style="background-color:#404040;">#404040</h1>  
<h1 style="background-color:#686868;">#686868</h1>  
<h1 style="background-color:#a0a0a0;">#a0a0a0</h1>  
<h1 style="background-color:#bebebe;">#bebebe</h1>  
<h1 style="background-color:#dcdcdc;">#dcdcdc</h1>  
<h1 style="background-color:#f8f8f8;">#f8f8f8</h1>
```

```
</body>  
</html>
```



# Tags

- Block tags
- Inline tags
- Container tags
- Semantic tags

# Block Elements & Inline Elements

- **Block Elements**

Block elements appear on the screen as if they have a line break before and after them. For example, the `<p>`, `<h1>`, `<h2>`, `<h3>`, `<h4>`, `<h5>`, `<h6>`, `<ul>`, `<ol>`, `<dl>`, `<pre>`, `<hr />`, `<blockquote>`, and `<address>` elements are all block level elements. They all start on their own new line, and anything that follows them appears on its own new line.

- **Inline Elements**

Inline elements, on the other hand, can appear within sentences and do not have to appear on a new line of their own. The `<b>`, `<i>`, `<u>`, `<em>`, `<strong>`, `<sup>`, `<sub>`, `<big>`, `<small>`, `<li>`, `<ins>`, `<del>`, `<code>`, `<cite>`, `<dfn>`, `<kbd>`, and `<var>` elements are all inline elements.

# Grouping HTML Elements- (Container tags)

- There are two important tags which we use very frequently to group various other HTML tags
  - ❑ `<div>` tag
  - ❑ `<span>` tag

It is used to group other HTML elements

It usually contains content like text, images, headings and other divs

# The <div> tag

- This is the very important block level tag which plays a big role in grouping various other HTML tags and applying CSS on group of elements.
- <div> tag can be used to create webpage layout where we define different parts (Left, Right, Top etc.) of the page using <div> tag.
- This tag does not provide any visual change on the block but this has more meaning when it is used with CSS.

# DIV TAG

```
<!DOCTYPE html>
<html>

  <head>
    <title>HTML div Tag</title>
  </head>

  <body>
    <!-- First group of tags -->
    <div style = "color:red">
      <h4>This is first group</h4>
      <p>Following is a list of vegetables</p>

      <ul>
        <li>Beetroot</li>
        <li>Ginger</li>
        <li>Potato</li>
        <li>Radish</li>
      </ul>
    </div>

    <!-- Second group of tags -->
    <div style = "color:green">
      <h4>This is second group</h4>
      <p>Following is a list of fruits</p>

      <ul>
        <li>Apple</li>
        <li>Banana</li>
        <li>Mango</li>
        <li>Strawberry</li>
      </ul>
    </div>
  </body>

</html>
```

# DIV tag Exercise

```
<!DOCTYPE html>
<html>
<head>
  <title>DIV Container Layout</title>
</head>

<body bgcolor="#F2F2F2">

  <!-- Header -->
  <div style="background-color: lightblue; border:2px solid blue; padding:10px; text-align:center;">
    <h1>Header Section</h1>
    <p>This is the header container</p>
  </div>

  <br>

  <!-- Main Content Area -->
  <div style="border:2px solid black; background-color:white; padding:10px;">

    <!-- Left Content -->
    <div style="background-color: lightyellow; border:2px solid orange; width: 45%; float:left; padding:10px;">
      <h3>Left Content</h3>
      <p>This is left aligned div.</p>
    </div>

    <!-- Right Content -->
    <div style="background-color: red; border:2px solid green; width:45%; float:right; padding:10px;">
      <h3>Right Content</h3>
      <p>This is right aligned div.</p>
    </div>

    <!-- Clear float -->
    <div style="clear:both;"></div>

  </div>
```

# Continuation..

```
<!-- Center Div -->
<div style="width:50%; margin:auto; background-color: pink; border:2px solid red; padding:10px; text-align:center;">
  <h3>Center Container</h3>
  <p>This div is centered on the page</p>
</div>

<br>

<!-- Footer -->
<div style="background-color: lightgray; border:2px solid gray; padding:10px; text-align:center;">
  <p>Footer Section</p>
</div>

</body>
</html>
```

# The `<span>` tag

- The HTML `<span>` is an inline element and it can be used to group inline-elements in an HTML document. This tag also does not provide any visual change on the block but has more meaning when it is used with CSS.
- The difference between the `<span>` tag and the `<div>` tag is that the `<span>` tag is used with inline elements whereas the `<div>` tag is used with block-level elements.



# SPAN TAG

```
<!DOCTYPE html>
<html>

  <head>
    <title>HTML span Tag</title>
  </head>

  <body>
    <p>This is <span style = "color:red">red</span> and this is
      <span style = "color:green">green</span></p>
  </body>

</html>
```