

HTML FORMS

Practice codes

Practice exercise-6

HTML VS CSS VS JAVA SCRIPT

- HTML:
- HTML makes up this web page's skeleton and structure, and almost every other web page you'll ever visit.
- It's a markup language that "marks up" and forms the backbone to online content, putting the site structure in place for the web browser to understand.
-  **CSS**
- Whereas HTML makes up the structure, or bones, of the site, CSS adds the skin - the aesthetics you see and navigate.
- The CSS on a webpage designs it and makes it look more attractive for the visitor reading the page.
- CSS, or Cascading Style Sheets, shape the HTML and affects how it's displayed to the website visitor.
- These forms of styling include font color, background color, border-radius (rounded corners on boxes), the position of columns, hue, opacity, and separation. New CSS features even allow for animations, flexbox gaps, and much more responsive design.
-  **JavaScript**
- JavaScript (JS) is another key language for web page design and inserts dynamic text into HTML client-side.



HTML FORM

- An **HTML form** is *a section of a document* which contains controls such as text fields, password fields, checkboxes, radio buttons, submit button, menus etc.
 - An HTML form facilitates the user to enter data that is to be sent to the server for processing such as name, email address, password, phone number, etc. .
-
- **Why use HTML Form**
 - HTML forms are required if you want to collect some data from of the site visitor.
 - For example: If a user want to purchase some items on internet, he/she must fill the form such as shipping address and credit/debit card details so that item can be sent to the given address.



SYNTAX FOR HTML FORMS

USING ELEMENT <FORM>

<form action="server url" method="get | post">

//input controls e.g. textfield, textarea,
radiobutton, button etc.

</form>



HTML 5 FORM TAGS

Tag	Description
<form>	It defines an HTML form to enter inputs by the used side.
<input>	It defines an input control.
<textarea>	It defines a multi-line input control.
<label>	It defines a label for an input element.
<fieldset>	It groups the related element in a form.
<legend>	It defines a caption for a <fieldset> element.
<select>	It defines a drop-down list.
<optgroup>	It defines a group of related options in a drop-down list.
<option>	It defines an option in a drop-down list.
<button>	It defines a clickable button.



HTML 5 FORM TAGS (CONTINUED..)

Tag	Description
<datalist>	It specifies a list of pre-defined options for input control.
<keygen>	It defines a key-pair generator field for forms.
<output>	It defines the result of a calculation.



HTML <INPUT> ELEMENT -TO CREATE TEXT FIELDS

```
<body>
  <form>
    Enter your name <br>
    <input type="text" name="username">
  </form>
</body>
```

Output:

Enter your name



CONTROLLING HTML TEXT FIELD

```
<form>  
  First Name: <input type="text" name="firstname"/> <br/>  
  Last Name: <input type="text" name="lastname"/> <br/>  
</form>
```

- The type="text" attribute of input tag creates textfield control also known as single line textfield control.

The name attribute is optional, but it is required for the server side component such as JSP, ASP, PHP etc.



Output:

A screenshot of a web browser window titled "Form in HTML". The address bar shows the file path "file:///D:/HTML/JTP.html". The browser displays the rendered HTML form with two text input fields. The first field is labeled "First Name:" and the second field is labeled "Last Name:". Both fields are empty and have a light gray border.

First Name:

Last Name:

<TEXTAREA> TAG

```
<!DOCTYPE html>
<html>
<head>
  <title>Form in HTML</title>
</head>
<body>
  <form>
    Enter your address:<br>
    <textarea rows="2" cols="20"></textarea>
  </form>
</body>
</html>
```

- The <textarea> tag in HTML is used to insert multiple-line text in a form.
- The size of <textarea> can be specify either using "rows" or "cols" attribute or by CSS.

Enter your address:



<LABEL> TAG IN HTML FORM

```
<form>
  <label for="firstname">First Name: </label> <br/>
    <input type="text" id="firstname" name="firstname"/> <br/>
  <label for="lastname">Last Name: </label>
    <input type="text" id="lastname" name="lastname"/> <br/>
</form>
```

First Name:

Last Name:

- It is considered better to have label in form. As it makes the code parser/browser/user friendly.
- If you click on the label tag, it will focus on the text control.
- To do so, you need to have “for” attribute in label tag that must be same as “id” attribute of input tag.



HTML PASSWORD FIELD CONTROL

THE PASSWORD IS NOT VISIBLE TO THE USER IN
PASSWORD FIELD CONTROL

```
<form>  
  <label for="password">Password: </label>  
  <input type="password" id="password" name="password"/> <br/>  
</form>
```



HTML 5 EMAIL FIELD CONTROL

- The new HTML5 email field validates the text for correct email address.
- You must use @ and . in this field.
- If correct email is not entered, it will display

```
<form>  
  <label for="email">Email: </label>  
  <input type="email" id="email" name="email"/> <br/>  
</form>
```

Email:



Please include an '@' in the email address.
'example.com' is missing an '@'.

RADIO BUTTON CONTROL

CREATING RADIO BUTTONS USING HTML

- The radio button is used to select one option from multiple options. It is used for selection of gender, quiz questions etc.
- If you use one name for all the radio buttons, only one radio button can be selected at a time.
- Using radio buttons for multiple options, you can only choose a single option at a time.



RADIO BUTTON CONTROL

```
<form>
  <label for="gender">Gender: </label>
    <input type="radio" id="gender" name="gender" value="male"/>Male
    <input type="radio" id="gender" name="gender" value="female"/>Female <br/>
</form>
```

Gender: ☐ Male ☒ Female



CHECKBOX CONTROL

-CREATING “CHECKBOX” INPUT TYPE TO CHECK MULTIPLE OPTIONS FROM GIVEN CHECKBOXES (UNLIKE BUTTONS WE SELECT MULTIPLE OPTIONS)

```
<form>
Hobby:<br>
  <input type="checkbox" id="cricket" name="cricket" value="cricket"/>
  <label for="cricket">Cricket</label> <br>
  <input type="checkbox" id="football" name="football" value="football"/>
  <label for="football">Football</label> <br>
  <input type="checkbox" id="hockey" name="hockey" value="hockey"/>
  <label for="hockey">Hockey</label>
</form>
```

Output:

Hobby:

☒ Cricket

☒ Football

☐ Hockey

SELECT AND OPTION

- Used for **dropdown lists**.

```
<select>
```

```
<option>CSE</option>
```

```
<option>ECE</option>
```

```
<option>EEE</option>
```

```
</select>
```



SUBMIT BUTTON CONTROL

submit

- HTML uses **<input type="submit">** to add a submit button on web page.
- When user clicks on submit button, then form get submit to the server.
- Syntax: `<input type="submit" value="submit">`
- The type = submit , specifies that it is a submit button
- The value attribute can be anything which we write on button on web page.
- The name attribute can be omitted here.



EXAMPLE- TO CREATE A FORM

```
<form>  
  <label for="name">Enter name</label> <br>  
  <input type="text" id="name" name="name"> <br>  
  <label for="pass">Enter Password</label> <br>  
  <input type="Password" id="pass" name="pass"> <br>  
  <input type="submit" value="submit">  
</form>
```



HTML <FIELDSET> ELEMENT

```
1  <form>
2      <fieldset>
3          <legend>User Information:</legend>
4          <label for="name">Enter name</label><br>
5          <input type="text" id="name" name="name"><br>
6          <label for="pass">Enter Password</label><br>
7          <input type="Password" id="pass" name="pass"><br>
8          <input type="submit" value="submit">
9      </fieldset>
10 </form>
```

User Information: _____

Enter name

Enter Password

submit

- The <fieldset> element in HTML is used to group the related information of a form.
- This element is used with <legend> element which provide caption for the grouped elements.



CREATE A REGISTRATION FORM IN THE HTML WEBSITE

```
<!DOCTYPE html>
<html>
<head>
<title>Form in HTML</title>
</head>
<body>
  <h2>Registration form</h2>
  <form>
    <fieldset>
      <legend>User personal information</legend>
      <label>Enter your full name</label><br>
      <input type="text" name="name"><br>
      <label>Enter your email</label><br>
      <input type="email" name="email"><br>
      <label>Enter your password</label><br>
      <input type="password" name="pass"><br>
      <label>confirm your password</label><br>
      <input type="password" name="pass"><br>
      <br><label>Enter your gender</label><br>
      <input type="radio" id="gender" name="gender" value="male"/>Male <br>
      <input type="radio" id="gender" name="gender" value="female"/>Female <br/>
      <input type="radio" id="gender" name="gender" value="others"/>others <br/>
      <br>Enter your Address:<br>
      <textarea></textarea><br>
      <input type="submit" value="sign-up">
    </fieldset>
  </form>
</body>
</html>
```



FORM EXAMPLE-2

```
<!DOCTYPE>
<html>
  <head>
    <style>
      .tdLabel{
        font-style: italic;
        background-color: #aliceblue;
      }
      .label{
        font-style: italic;
        background-color: #azure;
      }
    </style>
  </head>
  <body>
    <form action="main1.jsp" method = "GET">
    <table>
    <tr>
      <td class="tdLabel"><label for="register_name" class="label">Enter name:</label></td>
      <td><input type="text" name="name" value="" id="register_name" style="width:160px"/></td>
    </tr>
    <tr>
      <td class="tdLabel"><label for="register_password" class="label">Enter password:</label></td>
      <td><input type="password" name="password" id="register_password" style="width:160px"/></td>
    </tr>
    <tr>
      <td class="tdLabel"><label for="register_email" class="label">Enter Email:</label></td>
      <td><input type="email" name="email" value="" id="register_email" style="width:160px"/></td>
    </tr>
```



FORM EXAMPLE-2 (CONTINUED..)

```
<tr>
|   <td class="tdLabel"><label for="register_gender" class="label">Enter Gender:</label></td>
|   <td>
|       <input type="radio" name="gender" id="register_gendermale" value="male"/>
|       <label for="register_gendermale">male</label>
|       <input type="radio" name="gender" id="register_genderfemale" value="female"/>
|       <label for="register_genderfemale">female</label>
|   </td>
| </tr>
| <tr>
|   <td class="tdLabel"><label for="register_country" class="label">Select Country:</label></td>
|   <td><select name="country" id="register_country" style="width:160px">
|       <option value="india">india</option>
|       <option value="pakistan">pakistan</option>
|       <option value="africa">africa</option>
|       <option value="china">china</option>
|       <option value="other">other</option>
|   </select>
| </td>
| </tr>
| <tr>
|   <td colspan="2"><div align="right"><input type="submit" id="register_0" value="register"/>
|   </div></td>
| </tr>
| </table>
| </form>
| </body>
| </html>
```



HTML FORM INPUT TYPES

- In HTML `<input type=" ">` is an important element of HTML form.
- The "type" attribute of input element can be various types, which defines information field. Such as `<input type="text" name="name">` gives a text box.



LIST OF ALL TYPES OF <INPUT> ELEMENT OF HTML

(FEW ARE DISCUSSED IN PREVIOUS SLIDES)

type=" "	Description
text	Defines a one-line text input field
password	Defines a one-line password input field
submit	Defines a submit button to submit the form to server
reset	Defines a reset button to reset all values in the form.
radio	Defines a radio button which allows select one option.
checkbox	Defines checkboxes which allow select multiple options form.
button	Defines a simple push button, which can be programmed to perform a task on an event.
file	Defines to select the file from device storage.
image	Defines a graphical submit button.



LIST OF TYPES OF ELEMENTS OF HTML5

type=" "	Description
color	Defines an input field with a specific color.
date	Defines an input field for selection of date.
datetime-local	Defines an input field for entering a date without time zone.
email	Defines an input field for entering an email address.
month	Defines a control with month and year, without time zone.
number	Defines an input field to enter a number.
url	Defines a field for entering URL
week	Defines a field to enter the date with week-year, without time zone.
search	Defines a single line text field for entering a search string.
tel	Defines an input field for entering the telephone number.



<INPUT TYPE="RESET">

(TRY THE CODE FOR OUTPUT)

```
<!DOCTYPE html>
<html>
<body>
  <h3>Input "reset" type:</h3>
  <form>
    <label>User id: </label>
    <input type="text" name="user-id" value="user">
    <label>Password: </label>
    <input type="password" name="pass" value="pass"><br><br>
    <input type="submit" value="login">
    <input type="reset" value="Reset">
  </form>
  <p>Try to change the input values of user id and password, then when you click on
  reset, it will reset input fields with default values. </p>
</body>
</html>
```



CHECKBOX TYPE INPUT EXAMPLE

```
<!DOCTYPE html>
<html>
<body>
<h2>Input "checkbox" type</h2><br>
<h3>Registration Form</h3>
<form>
    <label>Enter your Name:</label>
    <input type="text" name="name">
    <p>Kindly Select your favorite sports</p>
    <input type="checkbox" name="sport1" value="cricket">Cricket<br>
    <input type="checkbox" name="sport2" value="tennis">Tennis<br>
    <input type="checkbox" name="sport3" value="football">Football<br>
    <input type="checkbox" name="sport4" value="baseball">Baseball<br>
    <input type="checkbox" name="sport5" value="badminton">Badminton<br><br>
    <input type="submit" value="submit">
</form>
</body>
</html>
```



<INPUT TYPE="BUTTON">

```
<!DOCTYPE html>
<html>
<body>
    <h2>Input "button" type.</h2>
    <p>Click the button to see the result: </p>
    <form>
        <input type="button" value="Click me" onclick="alert('you are learning HTML')">
    </form>
</body>
</html>
```

- The <input> type "button" defines a simple push button, which can be programmed to control a functionality on any event such as click event.
- **Note: It mainly works with JavaScript.**
- In the above example we have used the "alert" of JS, which can be learnt in the JS concepts. It is used to show a pop window.



<INPUT TYPE="FILE">

```
<!DOCTYPE html>
<html>
<body>
    <h2>Input "file" type.</h2>
    <p>We can choose any type of file until we do not specify it! The selected file
will appear at next to "choose file" option</p>
    <form>
        <label>Select file to upload:</label>
        <input type="file" name="newfile">
        <input type="submit" value="submit">
    </form>
</body>
</html>
```

- The <input> element with type "file" is used to select one or more files from user device storage.
- Once you select the file, and after submission, this file can be uploaded to the server with the help of JS code and file API.



<INPUT TYPE="IMAGE">

THE <INPUT> TYPE "IMAGE" IS USED TO REPRESENT A SUBMIT BUTTON IN THE FORM OF IMAGE.

```
<!DOCTYPE html>
<html>
<body>
<h2>Input "image" type.</h2>
<p>We can create an image as submit button</p>
  <form>
    <label>User id:</label> <br>
    <input type="text" name="name"> <br> <br>
    <input type="image" alt="Submit" src="login.png" width="100px">
  </form>

</body>
</html>
```



THE `<INPUT>` TYPE "COLOR" IS USED TO DEFINE AN INPUT FIELD WHICH CONTAINS A COLOUR. IT ALLOWS A USER TO SPECIFY THE COLOUR BY THE VISUAL COLOUR INTERFACE ON A BROWSER.

```
<!DOCTYPE html>
<html>
<body>
    <h3>Input "color" types:</h3>
    <form>
        Pick your Favorite color: <br><br>
        <input type="color" name="upclick" value="#a52a2a"> Up-click<br><br>
        <input type="color" name="downclick" value="#f5f5dc"> Down-click
    </form>
    <p><strong>Note:</strong>The default value of "color" type is #000000 (black). It only
    supports color value in hexadecimal format.</p>
</body>
</html>
```



<INPUT TYPE="DATE">

THE <INPUT> ELEMENT OF TYPE "DATE" GENERATES AN INPUT FIELD, WHICH ALLOWS A USER TO INPUT THE DATE IN A GIVEN FORMAT. A USER CAN ENTER THE DATE BY TEXT FIELD OR BY DATE PICKER INTERFACE.

```
<form>
```

```
  Select Start and End Date: <br><br>
```

```
    <input type="date" name="Startdate"> Start date:<br><br>
```

```
    <input type="date" name="Enddate"> End date:<br><br>
```

```
    <input type="submit">
```

```
</form>
```



<INPUT TYPE="DATETIME-LOCAL">

```
<form>
```

```
  <label>
```

```
    Select the meeting schedule: <br><br>
```

```
    Select date & time: <input type="datetime-local" name="meetingdate"> <br><br>
```

```
  </label>
```

```
    <input type="submit">
```

```
</form>
```



<INPUT TYPE="EMAIL">

```
<!DOCTYPE html>
<html>

<body>
  <h3>Input "email" type</h3>
  <form>
    <label><b>Enter your Email-address</b></label>
    <input type="email" name="email" required>
    <input type="submit">
    <p><strong>Note:</strong>User can also enter multiple email addresses separating
by comma or whitespace as following: </p>
    <label><b>Enter multiple Email-addresses</b></label>
    <input type="email" name="email" multiple>
    <input type="submit">
  </form>

</body>
</html>
```



<INPUT TYPE="MONTH">

```
<form>  
  <label>Enter your Birth Month-year: </label>  
  <input type="month" name="newMonth">  
  <input type="submit">  
</form>
```



EXAMPLES FOR OTHER INPUT TYPES LIKE: NUMBER, URL

```
<form>
  <label>Enter your age: </label>
  <input type="number" name="num" min="50" max="80">
  <input type="submit">
</form>
```

```
<form>
  <label>Enter your website URL: </label>
  <input type="url" name="website" placeholder="http://example.com"> <br>
  <input type="submit" value="send data">
</form>
```



EXAMPLES FOR OTHER INPUT TYPES LIKE: WEEK, MOBILE NUMBER

```
<form>
```

```
  <label> <b>Select your best week of year:</b> </label> <br> <br>
```

```
  <input type="week" name="bestweek">
```

```
  <input type="submit" value="Send data">
```

```
</form>
```

```
<form>
```

```
  <label>Search here:</label>
```

```
  <input type="search" name="q">
```

```
  <input type="submit" value="search">
```

```
</form>
```

```
<form>
```

```
  <label> <b>Enter your Telephone Number(in format of xxx-xxx-xxxx):</b> </label>
```

```
  <input type="tel" name="telephone" pattern="[0-9]{3}-[0-9]{3}-[0-9]{4}" required>
```

```
  <input type="submit"> <br> <br>
```

```
</form>
```



PATTERNS

- **Basic Syntax**

- `<input type="text" pattern="regex">`

-

Example 1: Only Alphabets Allowed

`<input type="text" pattern="[A-Za-z]+" placeholder="Only letters">`

Accepts: Deepthi, HTML

Rejects: 123, abc123

Example 2: 10-Digit Mobile Number

`<input type="text" pattern="[0-9]{10}" placeholder="10-digit mobile number">`

Accepts: 9876543210

Rejects: 98765, 98abc43210

Example 3: College Roll Number Format

(Example: CSE123)

`input type="text" pattern="[A-Z]{3}[0-9]{3}" placeholder="CSE123">`

- **Using pattern with required**

`<input type="text" pattern="[A-Za-z]+" required>`

pattern works **only when input is not empty** → use required to make it mandatory.



HTML <FORM> ELEMENT ATTRIBUTES

IN HTML THERE ARE VARIOUS ATTRIBUTES AVAILABLE FOR <FORM> ELEMENT

HTML action attribute

- The action attribute of <form> element defines the process to be performed on form when form is submitted, or it is a URL to process the form information.
- The action attribute value defines the web page where information proceed. It can be .php, .jsp, .asp, etc. or any URL where you want to process your form.
- If action attribute value is blank then form will be processed to the same page.

```
<form action="action.html" method="post">  
<label>User Name:</label><br>  
<input type="text" name="name"><br><br>  
<label>User Password</label><br>  
<input type="password" name="pass"><br><br>  
<input type="submit">  
</form>
```



HTML METHOD ATTRIBUTE

- The method attribute defines the HTTP method which browser used to submit the form. The possible values of method attribute can be:
- **post:** We can use the post value of method attribute when we want to process the sensitive data as it does not display the submitted data in URL.
- **get:** The get value of method attribute is default value while submitting the form. But this is not secure as it displays data in URL after submitting the form.

```
<form action="action.html" method="post">
```

```
<form action="action.html" method="get">
```

When submitting the data, it will display the entered data in the form of:

file:///D:/HTML/action.html?name=FWD&pass=123



HTML TARGET ATTRIBUTE

- The target attribute defines where to open the response after submitting the form. The following are the keywords used with the target attribute.

- **_self:** If we use _self as an attribute value, then the response will display in current page only.

```
<form action="action.html" method="get" target="_self">
```

- **_blank:** If we use _blank as an attribute it will load the response in a new page.

```
<form action="action.html" method="get" target="_blank">
```

HTML <INPUT> ELEMENT ATTRIBUTE

- The HTML name attribute defines the name of an input element.
- The name and value attribute are included in HTTP request when we submit the form.
- **One should not omit the name attribute as when we submit the form the HTTP request includes both name-value pair and if name is not available it will not process that input field.**

```
<!DOCTYPE html>
<html>
  <body>

    <h2>Fill the form</h2>
    <form action = "action.html" method = "get">
      Enter name:<br><input type="name" name="uname"><br>
      Enter age:<br><input type="number" name="age"><br>
      Enter email:<br><input type="email"><br>
      <input type="submit" value="Submit">
    </form>
    <p><b>Note: If you will not use name attribute in any input field, then that input field
    will not be submitted, when submit the form.</b></p>
    <p>Click on submit and see the URL where email is not included in HTTP request as we have
    not used name attribute in the email input field</p>
  </body>
</html>
```



HTML VALUE ATTRIBUTE

- The HTML value attribute defines the initial value or default value of an input field

```
<form>
  <label>Enter your Name</label> <br>
  <input type="text" name="uname" value="Enter Name"> <br> <br>
  <label>Enter your Email-address</label> <br>
  <input type="text" name="uname" value="Enter email"> <br> <br>
  <label>Enter your password</label> <br>
  <input type="password" name="pass" value=""> <br> <br>
  <input type="submit" value="login">
</form>
```



HTML AUTOFOCUS ATTRIBUTE HTML5

THE AUTOFOCUS IS A BOOLEAN ATTRIBUTE WHICH ENABLES A FIELD AUTOMATICALLY FOCUSED WHEN A WEBPAGE LOADS.

```
<form>
  <label>Enter your Email-address</label> <br>
  <input type="text" name="uname" autofocus> <br> <br>
  <label>Enter your password</label> <br>
  <input type="password" name="pass"> <br> <br>
  <input type="submit" value="login">
</form>
```



FORM VALIDATION

○ Form Validation

Form validation is the process of **checking user input** before submitting the form.

○ It ensures:

Correct data format

Mandatory fields are filled

Invalid data is prevented

○ Types of Form Validation

HTML5 Built-in Validation (No JavaScript)

JavaScript Validation (covered later)



HTML REQUIRED ATTRIBUTE

HTML REQUIRED IS A BOOLEAN ATTRIBUTE WHICH SPECIFIES THAT USER MUST FILL THAT FIELD BEFORE SUBMITTING THE FORM.

```
<form>  
  <label>Enter your Email-address</label> <br>  
  <input type="text" name="uname" required> <br> <br>  
  <label>Enter your password</label> <br>  
  <input type="password" name="pass"> <br> <br>  
  <input type="submit" value="login">  
</form>
```



HTML PLACEHOLDER ATTRIBUTE

- The placeholder attribute specifies a text within an input field which informs the user about the expected input of that field.
- The placeholder attribute can be used with text, password, email, and URL values.
- When the user enters the value, the placeholder will be automatically removed.

```
<form>
  <label>Enter your name</label> <br>
  <input type="text" name="uname" placeholder="Your name"> <br> <br>
  <label>Enter your Email address</label> <br>
  <input type="email" name="email" placeholder="example@gmail.com"> <br> <br>
  <label>Enter your password</label> <br>
  <input type="password" name="pass" placeholder="your password"> <br> <br>
  <input type="submit" value="login">
</form>
```



HTML READ ONLY & DISABLED ATTRIBUTE

- Read only: User **can see but cannot edit**.
- DISABLED: Input is **inactive and not submitted**.
- The HTML disabled attribute when applied then it disable that input field. The disabled field does not allow the user to interact with that field.
- The disabled input filed does not receive click events, and these input value will not be sent to the server when submitting the form.
- `<input type="text" value="India" readonly>`
- `<input type="text" value="India" disabled>`



MIN LENGTH, MAX LENGTH & STEP

Length Validation (Password):

```
<form>
  <label>Password:</label>
  <input type="password" minlength="6"
maxlength="12" required>
  <br><br>
  <input type="submit">
</form>
```

This max length ensures password length is valid

STEP:

Specifies valid intervals.

```
<input type="number" step="5">
```

It Accepts: 5, 10, 15 & Rejects: 7



HTML SIZE ATTRIBUTE

THE SIZE ATTRIBUTE CONTROLS THE SIZE OF THE INPUT FIELD IN TYPED CHARACTERS.

```
<!DOCTYPE html>
<html>
<body>
  <h3>Registration form with disbaled attribute</h3>
  <form>
    <label>Account holder name</label><br>
    <input type="text" name="uname" size="40" required><br><br>
    <label>Account number</label><br>
    <input type="text" name="an" size="30" required><br><br>
    <label>CVV</label><br>
    <input type="text" name="cvv" size="1" required><br><br>
    <input type="submit" value="login">
  </form>
</body>
</html>
```



HTML FORM ATTRIBUTE

HTML FORM ATTRIBUTE ALLOWS A USER TO SPECIFY AN INPUT FIELD OUTSIDE THE FORM BUT REMAINS THE PART OF THE PARENT FORM.

```
<!DOCTYPE html>
<html>

  <body>
    <form id="fcontrol">
      User Name:<br><input type="text" name="uname"><br><br>
      User password:<br><input type="password" name="pass"><br><br>
    </form>
    <p>The email field is outside the form but still it will remain part of the
form</p>
    User email: <br><input type="email" name="email" form="fcontrol" required><br>
    <input type="submit" form="fcontrol">
  </body>
</html>
```



SUMMARY:

COMMON FORM ELEMENTS

- Input
- Label
- Textarea
- Select
- Option
- Button



ADVANCE INPUT ATTRIBUTES

- Required
- Place holder
- Readonly
- Disabled
- Min and max
- Maxlength
- Pattern
- Autofocus
- Autocomplete
- multiple



INPUT TYPES

- Text
- Password
- Email
- Number
- Radio
- Checkbox
- Date
- File
- Submit
- Reset
- Tel
- url



FORM VALIDATION:

IN-BUILT FORM VALIDATION

- Required
- Type-based validation. Ex: email, number, url etc
- Pattern
- Min and max
- Max length
- Min length
- Step
- Readonly
- Disabled



DISABLE HTML5 VALIDATION

- **Disable HTML5 Validation**

`<form novalidate>`

- Used when **custom JavaScript validation** is required.

