

Smart Lead Bot API Testing Documentation

This document outlines the API testing suite built for the AI Sales Copilot & Lead Intelligence Console. It details the endpoints tested, their purposes, expected request payloads (inputs), response structures (outputs), and instructions for executing the tests on your local machine using the custom test runner and Postman.

SETUP: How to Execute the API Tests

We have provided two methods to test the APIs locally and maintain a visible test history.

Method 1: Custom Node CLI Test Runner (`test_apis.js`)

A automated test runner has been created at [test_apis.js](file:///home/satish/Desktop/Frontend/test_apis.js). It dynamically signs up a temporary user, authenticates to retrieve a JWT bearer token, and runs through the 12 key CRM and Integration endpoints in sequence.

To run the suite:

1. Ensure your local server is running (e.g., `PORT=5173 node server.js` or `npm run dev`).
2. Run the script from the project root:

```
node test_apis.js http://localhost:5173
```

Method 2: Postman Collection (`smart_lead_bot_api_tests.postman_collection.json`)

For a persistent visual test history:

1. Open your **Postman** desktop application or web interface.
2. Click **Import** in the top-left corner.
3. Select the file [smart_lead_bot_api_tests.postman_collection.json](file:///home/satish/Desktop/Frontend/smart_lead_bot_api_tests.postman_collection.json) from your local project directory.
4. Set the collection environment variable `baseUrl` to `http://localhost:5173` (or your active server URL).
5. Click **Run Collection** to execute all 12 tests sequentially.

SPEC: Detailed API Specifications

Here is the reference list of all tested API endpoints:

1. User Registration / Signup

- **Endpoint:** **POST /api/auth/signup**
- **Purpose:** Register a new user account on the CRM.
- **Headers:** **Content-Type: application/json**
- **Request Input:**

```
{
  "firstName": "Automated",
  "lastName": "Runner",
  "email": "testrunner_1718000000@smartleadbot.com",
  "password": "runnerpassword123",
  "company": "Runner Automation"
}
```

- **Response Output (201 Created):**

```
{
  "message": "User registered successfully",
  "userId": "usr_7a4f9e8b"
}
```

2. User Authentication / Signin

- **Endpoint:** **POST /api/auth/signin**
- **Purpose:** Validate credentials and receive a JWT Bearer Token for protected routes.
- **Headers:** **Content-Type: application/json**
- **Request Input:**

```
{
  "email": "testrunner_1718000000@smartleadbot.com",
  "password": "runnerpassword123"
}
```

- **Response Output (200 OK):**

```
{
  "token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJpZCI6IjFhMmIzYyIsImVtYWlsIjoic2F0aXNoQGFKbWluLmIvIn0...",
  "user": {
    "id": "usr_7a4f9e8b",
    "firstName": "Automated",
    "lastName": "Runner",
    "email": "testrunner_1718000000@smartleadbot.com",
    "company": "Runner Automation",
    "role": "user"
  }
}
```

3. Retrieve Ingestion Templates

- **Endpoint:** **GET /api/ingest-templates**
- **Purpose:** Retrieve user-defined dynamic ingestion templates containing custom field configurations.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**
- **Request Input:** None (empty body)
- **Response Output (200 OK):**

```
[
  {
    "id": 1,
    "name": "B2B Outreach Template",
    "fields": [
      {"key": "revenue", "label": "Annual Revenue", "type": "number", "required": false},
      {"key": "linkedin", "label": "LinkedIn Profile", "type": "url", "required": true}
    ]
  }
]
```

4. Create Single Lead (Manual Ingestion)

- **Endpoint:** **POST /api/leads**
- **Purpose:** Insert a new lead profile into the directory database.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**, **Content-Type: application/json**
- **Request Input:**

```
{
  "company": "Showroom Kolkata Test 1718",
  "industry": "Car Dealership",
  "location": "Kolkata",
  "phone": "+91 98765 43211",
  "email": "test@showroomkolkata.in",
  "website": "http://showroomkolkata.in",
  "ai_score": 8,
  "source": "CLI Test Runner"
}
```

- **Response Output (200 OK):**

```
{
  "message": "Leads uploaded successfully",
  "ids": [24]
}
```

5. Get Active Leads Directory List

- **Endpoint:** **GET /api/leads**
- **Purpose:** Retrieve the full list of active B2B leads from the database.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**
- **Request Input:** None (empty body)
- **Response Output (200 OK):**

```
[
  {
    "id": 24,
    "company": "Showroom Kolkata Test 1718",
    "industry": "Car Dealership",
    "location": "Kolkata",
    "phone": "+91 98765 43211",
    "email": "test@showroomkolkata.in",
    "website": "http://showroomkolkatatest.in",
    "ai_score": 8,
    "assigned_user_id": null,
    "custom_fields": null,
    "grade": "Warm",
    "created_at": "2026-06-10T13:00:00Z"
  }
]
```

6. Get Registered CRM Teammates List

- **Endpoint:** **GET /api/users**
- **Purpose:** Fetch a list of user profiles in the system to support lead and task assignment.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**
- **Request Input:** None (empty body)
- **Response Output (200 OK):**

```
[
  {
    "id": "usr_7a4f9e8b",
    "first_name": "Automated",
    "last_name": "Runner",
    "email": "testrunner_1718000000@smartleadbot.com",
    "company": "Runner Automation",
    "role": "user"
  }
]
```


7. Assign Lead to CRM Teammate

- **Endpoint:** **PUT /api/leads/assign**
- **Purpose:** Allocate lead ownership/follow-up to a teammate.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**, **Content-Type: application/json**
- **Request Input:**

```
{  
  "leadId": 24,  
  "userId": "usr_7a4f9e8b"  
}
```

- **Response Output (200 OK):**

```
{  
  "message": "Lead assigned successfully"  
}
```

8. Get Tasks Timeline

- **Endpoint:** **GET /api/tasks**
- **Purpose:** List all CRM activities, priorities, and deadlines.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**
- **Request Input:** None (empty body)
- **Response Output (200 OK):**

```
[
  {
    "id": 12,
    "lead_id": 24,
    "title": "Initial Review",
    "description": "Establish first contact with Kolkata Showroom",
    "status": "Pending",
    "priority": "High",
    "due_date": "2026-06-20T00:00:00.000Z"
  }
]
```

9. Create / Delegate Task to User

- **Endpoint:** **POST /api/tasks**
- **Purpose:** Create a new task and associate it with a lead and one or more assigned users.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**, **Content-Type: application/json**
- **Request Input:**

```
{
  "leadId": 24,
  "assignedUserIds": ["usr_7a4f9e8b"],
  "title": "Review test showroom lead",
  "description": "Verify details and send customized pitch.",
  "priority": "Medium",
  "dueDate": "2026-06-25"
}
```

- **Response Output (201 Created):**

```
{
  "message": "Task created successfully",
  "taskId": 13
}
```

10. Get Google Forms OAuth Status

- **Endpoint:** **GET /api/google/status**
- **Purpose:** Check the state of the Google Integration setup, token expiration, and whether system environment variables are active.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**
- **Request Input:** None (empty body)
- **Response Output (200 OK):**

```
{
  "configured": true,
  "authenticated": true,
  "profile": {
    "email": "satish.leads.integration@gmail.com",
    "name": "Satish Kumar"
  },
  "usingSystemCredentials": true
}
```

11. Send Email (AI Sales Copilot Outreach Proxy)

- **Endpoint:** **POST /api/send-emails**
- **Purpose:** Deliver personalized email drafts to leads (integrated with n8n workflow or Resend proxy, and logged to **sent_emails** DB outbox).
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**, **Content-Type: application/json**
- **Request Input:**

```
{
  "recipients": [
    {
      "email": "test@showroomkolkata.in",
      "company": "Showroom Kolkata"
    }
  ],
  "subject": "Test email from automated runner",
  "body": "Hello, this is a test email sent from the automated test script."
}
```

- **Response Output (200 OK):**

```
{
  "message": "Done",
  "results": [
    {
      "email": "test@showroomkolkata.in",
      "status": "sent",
      "method": "mock"
    }
  ]
}
```

12. Find Leads (NLP Prospector Webhook Proxy)

- **Endpoint:** **POST /api/find-leads**
- **Purpose:** Execute natural language queries to search the web for new leads (falls back to resilient rule-based OSM/Groq generation if blocked).
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**, **Content-Type: application/json**
- **Request Input:**

```
{
  "query": "car showrooms in west bengal",
  "limit": 10
}
```

- **Response Output (200 OK):**

```
[
  {
    "company": "Kolkata Hyundai",
    "location": "Kolkata, West Bengal",
    "industry": "car showrooms",
    "website": "http://kolkatahyundai.com",
    "phone": "+91 33 2444 8888",
    "email": "info@kolkatahyundai.com",
    "ai_score": 9,
    "grade": "Hot"
  }
]
```

13. Retrieve Outbox History (Newly Added)

- **Endpoint:** **GET /api/outbox**
- **Purpose:** Fetch the history logs of all emails sent by the AI Sales Copilot.
- **Headers:** **Authorization: Bearer <JWT_TOKEN>**
- **Request Input:** None (empty body)
- **Response Output (200 OK):**

```
[
  {
    "id": 1,
    "sender_id": "usr_7a4f9e8b",
    "sender_name": "Automated Runner",
    "recipient_email": "test@showroomkolkata.in",
    "recipient_company": "Showroom Kolkata",
    "subject": "Test email from automated runner",
    "body": "Hello, this is a test email sent from the automated test script.",
    "status": "sent",
    "method": "mock",
    "sent_at": "2026-06-10T13:04:15.000Z"
  }
]
```