

## {CS310-DBMS}

Name: P. SATWIK

Roll.No: - 19BCS083

- ① Using emp name as a clustered index is possible only when every employee will have a unique name. If this is ensured, the tuples will be organized according empname ~~at~~ alphabetically

Using empid a clustered index is definitely possible considering everyone already has a unique id assigned to them. The tuples will be organized ~~at~~ accordingly to empid.

Using both empname & empid as a clustered indexes may not be possible but it is possible two hand one clustered index & one non-clustered index.

P.SATWIK

19BCS083

- (2.) (i.) DDL is important in representing information in DBMS because it is used to describe External & Logical ~~schemes~~ schemes
- (ii) DML is used to access and update data, It is not important for representing the data.

- ③ It is true, because A DBMS is typically shared among many users. Transactions from these users can be interleaved to improve the execution time of user's queries. By interleaving queries, users do not have to wait for other user's transactions to complete fully before their own transaction begins. Without interleaving, if user A begins a transaction that'll take 10 ~~minutes~~ seconds to complete & user B wants to begin transaction, user B would have to wait an additional 10 seconds for user's A transaction to complete before the database would begin processing user B's request.
- ④ a) A user must guarantee that his (or) her transaction doesn't corrupt data (or) insert nonsense in the database. For example, in a banking database, a user must guarantee that a cash withdraw transaction that will accurately model the amount a person removes from his/her account. A dB application would be worthless if a person removed 20 \$ from an ATM but transaction set their balance to zero.

(b) A DBMS must guarantee that ~~the~~ transactions are executed fully and independently of other transactions. An essential property of a DBMS is that a transaction should execute automatically, (d) as if it is the only transaction running. Also, transactions will either complete fully, & will be aborted and the database returned to its initial state. This ensures that the database remains constant.

P. SATWIK

19BCS083

- (5.) Yes, we can determine the key of relation with the help of instance. Eg.  
In a one to many relation we can consider the column attribute with unique values as a primary key.

⑦. for the given schema:-

Relational Algebra query:-

$\rho(R_1, \text{catalog})$

$\rho(R_2, \text{catalog})$

$$\pi_{R_1.pid} \sigma_{R_1.pid = R_2.pid \wedge R_1.sid \neq R_2.sid} (R_1 \times R_2)$$

SQL Query:-

SELECT C.sid  
FROM Catalog C

WHERE EXISTS (SELECT C1.sid  
FROM Catalog C1

WHERE C1.pid = C.pid AND C1.sid  $\neq$  C.sid)



P. SATWIK

19BCS083

- ⑧ It is an Invalid query. Error is "Invalid query" because, the given R.A statement does not return anything because of the sequence of projection operators. Once the sid is projected, it is the only field in the set. Therefore, projecting on the same will not return anything.