

Material/Process

DENSO FLASHING TAPE PRIMER

Supplier

WINN & COALES (DENSO) LTD

Keyword

Primer

Signal Word

Warning

MEDIUM HAZARD

LIQUID



Method

Hand applying

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR VITON



BS EN166



AND



LEV OR



FILTER TYPE A2



WASH AFTER EXPOSURE



IF SOILED



CLOSE ALL CONTAINERS



FLAMMABLE / ACUTE

Health Hazards

Flammable liquid and vapour
Causes serious eye irritation
May cause respiratory irritation
Causes skin irritation
May cause damage to organs through prolonged or repeated exposure
Potential for ototoxic effects that may cause hearing loss
May cause ill health if ingested in quantity

Material/Process

IKOPRO SELF ADHESIVE BITUMEN PRIMER

Supplier

IKO PLC

Keyword

Primer (Bitumen)

Signal Word

Warning

MEDIUM HAZARD

LIQUID



Method

Hand applying

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



POLYTHENE OR NITRILE



BS EN166



AND



LEV OR



FILTER TYPE A2



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



FLAMMABLE / SENSITISER

Health Hazards

Flammable liquid and vapour
Causes serious eye irritation
May cause respiratory irritation
Causes skin irritation
May cause an allergic skin reaction
May cause drowsiness or dizziness
Toxic to aquatic life with long lasting effects
May cause ill health if ingested in quantity

Material/Process
READY - MIXED CONCRETE

SupplierTARMAC
KeywordCement
Signal WordDanger

HIGH HAZARD
SEMI-SOLID



MethodHand applyingAreaOutsideExposureUp to 1/2 hour per shiftActivity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE	MEDIUM CHRONIC RISK - FULL EXPOSURE	Application of wet cement.
-----------------------------------	-------------------------------------	----------------------------

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY	MEDIUM CHRONIC RISK
---	---------------------



IMPERVIOUS OVERALLS



HEAVYDUTY IMPERVIOUS



WET CEMENT



BS EN166 GRADE 3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



WHEN CURED

Health Hazards

Causes serious eye damage
Causes skin irritation
May cause an allergic skin reaction
Prolonged skin contact can cause burns/skin ulceration
May cause ill health if ingested in quantity

Material/Process
READY - MIXED CONCRETE

SupplierTARMAC
KeywordCement
Signal WordDanger

HIGH HAZARD
SEMI-SOLID



MethodCutting (Mechanical)AreaOutsideExposureUp to 1/2 hour per shiftActivity Comments

MEDIUM ACUTE RISK - FULL EXPOSUREMEDIUM CHRONIC RISK - FULL EXPOSURE

Cured material.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITYMEDIUM CHRONIC RISK



IMPERVIOUS
OVERALLS



HEAVYDUTY
IMPERVIOUS



PROTECTIVE
FOOTWEAR



IF CONTACT
POSSIBLE



AND



WATER
SUPPRESSION AND



FILTER TYPE P3



WASH AFTER USE



IF SOILED



SWEEP OR
VACUUM



CONTROLLED
STORE /WASTE

Health Hazards

Causes serious eye damage
Causes skin irritation
May cause an allergic skin reaction
Prolonged skin contact can cause burns/skin ulceration
May cause ill health if ingested in quantity

Material/Process
READY - MIXED CONCRETE

SupplierTARMAC
KeywordCement
Signal WordDanger

HIGH HAZARD
SEMI-SOLID



MethodPouringAreaOutsideExposureUp to 1/2 hour per shiftActivity Comments
MEDIUM ACUTE RISK - FULL EXPOSUREMEDIUM CHRONIC RISK - FULL EXPOSUREApplication of wet cement.

Control MeasuresMEDIUM ACUTE RISK - INDIVIDUAL ACTIVITYMEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



HEAVYDUTY IMPERVIOUS



WET CEMENT



BS EN166 GRADE 3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



SENSITISER/ACUTE HAZARD

Health Hazards
Causes serious eye damage
Causes skin irritation
May cause an allergic skin reaction
Prolonged skin contact can cause burns/skin ulceration
May cause ill health if ingested in quantity

Material/Process

DENSO PASTE

Supplier

WINN & COALES (DENSO) LTD

Keyword

Rust Preventative

Signal Word

Warning

LOW HAZARD

SEMI-SOLID



Method	Hand applying	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE		LOW CHRONIC RISK - FULL EXPOSURE				

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY





WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



ECOTOXIC

Health Hazards

Very toxic to aquatic life

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Sypol

Part of EcoOnline Global

This assessment was compiled by EcoOnline Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 26/01/2026

M GROUP

Assessment Reviewed

07/11/2024

Next Review

07/11/2029

Latest SDS Reference

05/07/2024

Material/Process

GENERIC - WHITE SPIRIT

Supplier

VARIOUS

Keyword

White Spirit

Signal Word

Danger

MEDIUM HAZARD

LIQUID









Method

Hand applying

Area

Inside Well Ventilated

Exposure

Less than 5 minutes per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



CLOSE ALL CONTAINERS



FLAMMABLE / ACUTE

Health Hazards

Flammable liquid and vapour

May be fatal if swallowed and enters airways

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

May cause eye irritation

Toxic to aquatic life with long lasting effects

Material/Process

GENERIC - WHITE SPIRIT

Supplier

VARIOUS

Keyword

White Spirit

Signal Word

Danger

MEDIUM HAZARD

LIQUID









Method

Hand applying

Area

Outside

Exposure

Less than 5 minutes per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



CLOSE ALL CONTAINERS



FLAMMABLE / ACUTE

Health Hazards

Flammable liquid and vapour

May be fatal if swallowed and enters airways

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

May cause eye irritation

Toxic to aquatic life with long lasting effects

Material/Process
GENERIC - DIESEL

Supplier
VARIOUS

Keyword
Fuel (Diesel)

Signal Word
Danger

MEDIUM HAZARD

LIQUID



Method Filling Area Outside Exposure Up to 1/2 hour per shift Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF SOILED



CLOSE ALL CONTAINERS



FLAMMABLE / ACUTE

Health Hazards

Flammable liquid and vapour

May be fatal if swallowed and enters airways

Harmful if inhaled

Causes skin irritation

Suspected of causing cancer

May cause damage to organs through prolonged or repeated exposure

Toxic to aquatic life with long lasting effects

May cause eye irritation

Material/Process
GENERIC - MINERAL OIL BASED GREASE

MEDIUM HAZARD

SEMI-SOLID



Supplier
VARIOUS
Keyword
Grease (Mineral Oil)
Signal Word

Method
Gun applying
Area
Outside
Exposure
Up to 1/2 hour per shift
Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN
CONTACT



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



CONTROLLED
STORE /WASTE

Health Hazards
Mechanically degraded mineral oil may cause skin cancer
May cause ill health if ingested in quantity
May cause eye irritation

Material/Process
GENERIC - SILICONE SEALANT

LOW HAZARD

SEMI-SOLID



Supplier
VARIOUS
Keyword
Sealant (Silicone)
Signal Word

Method
Gun applying
Area
Outside
Exposure
Up to 1/2 hour per shift
Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN
CONTACT



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



CONTROLLED
STORE /WASTE

Health Hazards
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Material/Process
GENERIC - SILICONE SEALANT

Supplier
Keyword
Signal Word

VARIOUS
Sealant (Silicone)

LOW HAZARD
SEMI-SOLID



Method Hand applying Area Outside Exposure Up to 1/2 hour per shift Activity Comments

LOW ACUTE RISK - FULL EXPOSURE LOW CHRONIC RISK - FULL EXPOSURE

Control Measures LOW ACUTE RISK - INDIVIDUAL ACTIVITY LOW CHRONIC RISK



AVOID SKIN
CONTACT



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



CONTROLLED
STORE /WASTE

Health Hazards
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Material/Process
ALL SEASONS SCREENWASH

LOW HAZARD

LIQUID



SupplierTETROSYL LIMITED
KeywordScreen Wash
Signal WordWarning

MethodPouringAreaOutsideExposureLess than 5 minutes per shiftActivity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN
CONTACT



POLYTHENE OR
NITRILE



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



FLAMMABLE

Health Hazards
Flammable liquid and vapour
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Material/Process
GENERIC - LPG CYLINDERS

Supplier
NOT APPLICABLE
Keyword
Gas
Signal Word
Danger

MEDIUM HAZARD

GAS



Method	Connecting	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE			LOW CHRONIC RISK - FULL EXPOSURE			Refer to Pressure Systems Safety Regulations 2000 / DSEA Regulations for further precautions.

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED

Health Hazards
Asphyxiant properties
Extremely flammable gas
Contains gas under pressure; may explode if heated
May cause eye irritation

Material/Process

BOSTIK COLOURS FOR CEMENT

Supplier

BOSTIK LIMITED

Keyword

Additive

Signal Word

LOW HAZARD

SOLID



Method	Mixing	Area	Outside	Exposure	Less than 5 minutes per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE			LOW CHRONIC RISK - FULL EXPOSURE			Assessment covers the mixing of material with cement. Refer to assessment for cement for any further precautions.

Control Measures	LOW ACUTE RISK - INDIVIDUAL ACTIVITY	LOW CHRONIC RISK
------------------	--------------------------------------	------------------



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



SWEEP OR VACUUM



CONTROLLED STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Material/Process

FLASH PRO ALL-PURPOSE CLEANER LEMON

Supplier

PROCTER & GAMBLE UK

Keyword

Cleaner

Signal Word

Danger

HIGH HAZARD

LIQUID



Method

Diluting

Area

Inside Well Ventilated

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



BS EN166



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



ACUTE HAZARD

Health Hazards

Causes serious eye damage

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Material/Process

FLASH PRO ALL-PURPOSE CLEANER LEMON

Supplier

PROCTER & GAMBLE UK

Keyword

Cleaner

Signal Word

Danger

HIGH HAZARD

LIQUID



Method

Spraying (Trigger Bottle)

Area

Inside Well Ventilated

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Intermittent use of low pressure trigger spray bottle.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



BS EN166 GRADE 3



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



ACUTE HAZARD

Health Hazards

Causes serious eye damage
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact

Material/Process

FLASH PRO ALL-PURPOSE CLEANER LEMON

Supplier

PROCTER & GAMBLE UK

Keyword

Cleaner

Signal Word

Danger

HIGH HAZARD

LIQUID



Method

Hand applying

Area

Inside Well Ventilated

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



BS EN166 GRADE 3



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



ACUTE HAZARD

Health Hazards

Causes serious eye damage
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact

Material/Process

FLASH PRO ALL-PURPOSE CLEANER LEMON

Supplier

PROCTER & GAMBLE UK

Keyword

Cleaner

Signal Word

Danger

HIGH HAZARD

LIQUID

Method	Mopping	Area	Inside Well Ventilated	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE			MEDIUM CHRONIC RISK - FULL EXPOSURE			Use of diluted material, minimal contact envisaged

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

AVOID SKIN CONTACT

IF OVEREXPOSURE LIKELY

IF CONTACT POSSIBLE

WASH AFTER EXPOSURE

IF HEAVILY SOILED

CLOSE ALL CONTAINERS

ACUTE HAZARD

Health Hazards

Causes serious eye damage

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Material/Process

FLASH PRO ALL-PURPOSE CLEANER LEMON

SupplierPROCTER & GAMBLE UK
KeywordCleaner
Signal WordDanger

HIGH HAZARD
LIQUID



Method	Mopping	Area	Inside Well Ventilated	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE			MEDIUM CHRONIC RISK - FULL EXPOSURE			Use of diluted material, minimal eye contact envisaged

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITYLOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT POSSIBLE



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



ACUTE HAZARD

Health Hazards

Causes serious eye damage
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact

Material/Process
PURECHLOR / ULTRACHLOR >=10 -<=15%

Supplier
BRENNTAG UK LIMITED
Keyword
Cleaner
Signal Word
Danger

HIGH HAZARD
LIQUID



Method
Spraying (Trigger Bottle)
Area
Outside
Exposure
Up to 1/2 hour per shift
Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE
MEDIUM CHRONIC RISK - FULL EXPOSURE
Intermittent use of low pressure trigger spray bottle.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY
MEDIUM CHRONIC RISK



IMPERVIOUS
OVERALLS



NITRILE OR
NEOPRENE



BS EN166 GRADE 3



WASH AFTER
EXPOSURE



IF SOILED



OR STORE WITH
ACIDS



CLOSE ALL
CONTAINERS



ACID
REACTIVE/CORROSI
VE

Health Hazards

Causes severe skin burns and eye damage
Ingestion may be fatal if not treated promptly
Contact with acids liberates toxic gas
Very toxic to aquatic life
Toxic to aquatic life with long lasting effects

Material/Process
PURECHLOR / ULTRACHLOR >=10 -<=15%

Supplier
BRENNTAG UK LIMITED
Keyword
Cleaner
Signal Word
Danger

HIGH HAZARD
LIQUID



Method
Pouring
Area
Outside
Exposure
Up to 1/2 hour per shift
Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE
MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures
MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY
MEDIUM CHRONIC RISK



IMPERVIOUS
OVERALLS



NITRILE OR
NEOPRENE



BS EN166 GRADE 3



WASH AFTER
EXPOSURE



IF SOILED



OR STORE WITH
ACIDS



CLOSE ALL
CONTAINERS



ACID
REACTIVE/CORROSI
VE

Health Hazards
Causes severe skin burns and eye damage
Ingestion may be fatal if not treated promptly
Contact with acids liberates toxic gas
Very toxic to aquatic life
Toxic to aquatic life with long lasting effects

Material/Process
GENERIC - ETHANOL/ISOPROPANOL DEICER

Supplier
Keyword
Signal Word

VARIOUS
De-Icer
Danger

MEDIUM HAZARD
LIQUID



Method
Spraying (Pressurised/Gun)

Area
Outside

Exposure
Less than 5 minutes per shift

Activity Comments

HIGH ACUTE RISK - FULL EXPOSURE

HIGH CHRONIC RISK - FULL EXPOSURE

Control Measures

HIGH ACUTE RISK - INDIVIDUAL ACTIVITY

HIGH CHRONIC RISK - INDIVIDUAL ACTIVITY



KEEP SKIN COVERED

POLYTHENE OR NITRILE

PROTECTIVE FOOTWEAR

BS EN166

AND

LEV AND

FILTER TYPE P2

WASH AFTER EXPOSURE



IF HEAVILY SOILED

CLOSE ALL CONTAINERS

HIGHLY FLAMM /ACUTE HAZ

Health Hazards

Highly flammable liquid and vapour
Causes serious eye irritation
May cause damage to organs through prolonged or repeated exposure if swallowed
May cause drowsiness or dizziness
Skin - irritation and dermatitis may result from prolonged contact

Material/Process

POCKET ROCKET

SupplierAEROSOL SOLUTIONS LTD

KeywordLubricant (Aerosol)

Signal WordDanger

MEDIUM HAZARD

AEROSOL



MethodSpraying (Aerosol)

AreaInside Well Ventilated

ExposureLess than 5 minutes per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER USE



IF SOILED



PRESSURISED

Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes damage to organs through prolonged or repeated exposure

Causes skin irritation

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

May cause ill health if ingested in quantity

May cause eye irritation

May cause allergic reaction in susceptible individuals in contact with skin

Material/Process

POCKET ROCKET

SupplierAEROSOL SOLUTIONS LTD

KeywordLubricant (Aerosol)

Signal WordDanger

MEDIUM HAZARD

AEROSOL



MethodSpraying (Aerosol)

AreaOutside

ExposureLess than 5 minutes per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER USE



IF SOILED



PRESSURISED

Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes damage to organs through prolonged or repeated exposure

Causes skin irritation

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

May cause ill health if ingested in quantity

May cause eye irritation

May cause allergic reaction in susceptible individuals in contact with skin

Material/Process
AEROSOL SOLUTIONS KWIK TAK.

SupplierAEROSOL SOLUTIONS LIMITED
KeywordAdhesive (Aerosol)
Signal WordDanger

MEDIUM HAZARD

AEROSOL



MethodSpraying (Aerosol)AreaInside Well VentilatedExposureLess than 5 minutes per shiftActivity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR VITON



BS EN166



AND



LEV OR



FILTER TYPE AXP3



WASH AFTER EXPOSURE



IF SOILED



PRESSURISED

Health Hazards

Extremely flammable aerosol
Pressurised container: May burst if heated.
Causes serious eye irritation
Causes skin irritation
Suspected of causing cancer
May cause drowsiness or dizziness
Harmful to aquatic life with long lasting effects
May cause ill health if ingested in quantity



This assessment was compiled by EcoOnline Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 26/01/2026



Material/Process

DENSO TAPE .

Supplier

WINN & COALES (DENSO) LTD

Keyword

Tape

Signal Word

LOW HAZARD

SOLID

Method	Handling	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE			LOW CHRONIC RISK - FULL EXPOSURE			Handling materials unlikely to result in occupational exposure due to physical form or to release contents from sealed containers; minimal contact envisaged. In the event of a spill please refer to spillage section.

Control Measures	LOW ACUTE RISK - INDIVIDUAL ACTIVITY	LOW CHRONIC RISK
------------------	--------------------------------------	------------------



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED

Health Hazards

Minimal risk of exposure when intact

If dust produced see below

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Method

Hand applying

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER EXPOSURE



AT END OF SHIFT



CLOSE ALL CONTAINERS



SWEEP OR VACUUM



CONTROLLED STORE /WASTE

Health Hazards

May be harmful if vapour/mists/fumes from heated bitumen are inhaled

Skin - possible irreversible effects from prolonged contact if personal cleanliness ignored

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Material/Process
GENERIC - SHARP SAND

Supplier
Keyword
Signal Word

VARIOUS
Sand

MEDIUM HAZARD

SOLID



Method	Pouring	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE				MEDIUM CHRONIC RISK - FULL EXPOSURE		Pouring solid material.

Control Measures	MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY	MEDIUM CHRONIC RISK
------------------	---	---------------------



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



IF CONTACT LIKELY



AND



LEV OR



FILTER TYPE P3



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



SWEEP OR VACUUM



CONTROLLED STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Prolonged inhalation may lead to long term lung damage

May cause eye irritation

Material/Process
GENERIC - SHARP SAND

Supplier
Keyword
Signal Word

VARIOUS
Sand

MEDIUM HAZARD

SOLID



Method Sweeping Area Outside Exposure Up to 1/2 hour per shift Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN
CONTACT



HEAVYDUTY
IMPERVIOUS



IF CONTACT LIKELY



AND



LEV OR



FILTER TYPE P3



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



DO NOT DRY
SWEEP



CONTROLLED
STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Prolonged inhalation may lead to long term lung damage

May cause eye irritation

Method

Hand applying

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

Health Hazards

Mechanically degraded mineral oil may cause skin cancer

May cause ill health if ingested in quantity

May cause eye irritation

Material/Process
GENERIC - ROCK SALT

Supplier
Keyword
Signal Word

VARIOUS
Salt

LOW HAZARD

SOLID



Method Spreading Area Outside Exposure Up to 1/2 hour per shift Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN
CONTACT



HEAVYDUTY
IMPERVIOUS



PROTECTIVE
FOOTWEAR



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



CONTROLLED
STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Method

Diluting

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Material/Process

SEWAGE EFFLUENTS

MEDIUM HAZARD

LIQUID



Supplier

NOT APPLICABLE

Keyword

Sewage Process

Signal Word

Method

Direct Exposure

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



HEAVYDUTY IMPERVIOUS



PROTECTIVE FOOTWEAR



BS EN166



WASH AFTER EXPOSURE



IF SOILED



BIOHAZARD

Health Hazards

Biological hazard

May cause human disease

Effective prophylaxis or treatment usually available

Disease unlikely to spread to the community

Material/Process

SEWAGE EFFLUENTS

MEDIUM HAZARD

LIQUID



Supplier

NOT APPLICABLE

Keyword

Sewage Process

Signal Word

Method

Excavating

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



HEAVYDUTY IMPERVIOUS



PROTECTIVE FOOTWEAR



IF CONTACT LIKELY



AND



FILTER TYPE P3



WASH AFTER EXPOSURE



IF SOILED



BIOHAZARD

Health Hazards

Biological hazard

May cause human disease

Effective prophylaxis or treatment usually available

Disease unlikely to spread to the community

Material/Process

TARMAC TRUPAK

MEDIUM HAZARD

SOLID



Supplier

TARMAC TRUPAK

Keyword

Aggregate

Signal Word

Method

Shovelling

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



PROTECTIVE FOOTWEAR



IF CONTACT LIKELY



AND



LEV OR



FILTER TYPE P3



WASH AFTER EXPOSURE



IF HEAVILY SOILED



SWEEP OR VACUUM



CONTROLLED STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Prolonged inhalation may lead to long term lung damage

May cause eye irritation

Method	Mixing	Area	Outside	Exposure	Less than 5 minutes per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE		LOW CHRONIC RISK - FULL EXPOSURE				Refer to assessment for material to be mixed for any further precautions
Control Measures		LOW ACUTE RISK - INDIVIDUAL ACTIVITY		LOW CHRONIC RISK		
						
AVOID SKIN CONTACT		POLYTHENE OR NITRILE		IF CONTACT LIKELY		
						
WASH AFTER EXPOSURE		IF HEAVILY SOILED		CLOSE ALL CONTAINERS		
		CONTROLLED STORE /WASTE				

Health Hazards

Mechanically degraded mineral oil may cause skin cancer

May cause ill health if ingested in quantity

May cause eye irritation

Material/Process

WICKES PIPE FREEZER

LOW HAZARD

AEROSOL



Supplier

ARTIC PRODUCTS LTD

Keyword

Aerosol

Signal Word

Warning

Method

Spraying (Aerosol)

Area

Inside Poorly Ventilated

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Intermittent use of aerosol spray.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



POLYTHENE OR NITRILE



IF CONTACT LIKELY



AND



LEV OR



FILTER TYPE P2



WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Health Hazards

Pressurised container: May burst if heated.
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Method	Spraying (Aerosol)	Area	Inside Well Ventilated	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE			MEDIUM CHRONIC RISK - FULL EXPOSURE			Intermittent use of aerosol spray.

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



POLYTHENE OR NITRILE



IF CONTACT LIKELY





WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Health Hazards

Pressurised container: May burst if heated.

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Material/Process

SIKA-4 A

HIGH HAZARD

LIQUID



Supplier SIKA LIMITED

Keyword Admixture

Signal Word Danger

Method Mixing

Area **Outside**

Exposure

Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Refer to assessment for material to be mixed for any further precautions

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



NITRILE OR PVC



BS EN166 GRADE 3



WASH AFTER
EXPOSURE



IF SOILED



CLOSE ALL
CONTAINERS



CORROSIVE

Health Hazards

- Causes severe skin burns and eye damage
- Ingestion may be fatal if not treated promptly
- Corrosive to the respiratory tract

This assessment was compiled by EcoOnline Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 26/01/2026



Material/Process

SIKA-4 A

HIGH HAZARD

LIQUID



Supplier
Keyword
Signal Word

SIKA LIMITED
Admixture
Danger

Method
Pouring

Area
Outside

Exposure
Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



IMPERVIOUS
OVERALLS



NITRILE OR PVC



BS EN166 GRADE 3



WASH AFTER
EXPOSURE



IF SOILED



CLOSE ALL
CONTAINERS



CORROSIVE

Health Hazards

Causes severe skin burns and eye damage
Ingestion may be fatal if not treated promptly
Corrosive to the respiratory tract

Material/Process

SOUDAFOAM SMX

Supplier

SOUDAL N.V

Keyword

Sealant

Signal Word

Danger

LOW HAZARD

AEROSOL



Method	Spraying (Aerosol)	Area	Inside Well Ventilated	Exposure	Up to 1/2 hour per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE			LOW CHRONIC RISK - FULL EXPOSURE			Intermittent use of aerosol spray.

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



NEOPRENE OR VITON



IF CONTACT LIKELY





WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

 **Sypol**
Part of EcoOnline Global

This assessment was compiled by EcoOnline Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 26/01/2026



M GROUP

Assessment Reviewed

05/12/2024

Next Review

05/12/2029

Latest SDS Reference

01/06/2021

Material/Process

SOUDAFOAM SMX

Supplier

SOUDAL N.V

Keyword

Sealant

Signal Word

Danger

LOW HAZARD

AEROSOL



Method

Spraying (Aerosol)

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Intermittent use of aerosol spray.

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



NEOPRENE OR VITON



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Health Hazards

Extremely flammable aerosol
Pressurised container: May burst if heated.
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Method	Mixing	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE			MEDIUM CHRONIC RISK - FULL EXPOSURE			Mixing with water prior to application.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

IMPERVIOUS OVERALLS

HEAVYDUTY IMPERVIOUS

WET CEMENT

BS EN166 GRADE 3

AND

LEV OR

FILTER TYPE P3

WASH AFTER USE

IF SOILED

CLOSE ALL CONTAINERS

SWEEP OR VACUUM

SENSITISER/ACUTE HAZARD

Health Hazards

Causes serious eye damage

Causes skin irritation

May cause respiratory irritation

May cause an allergic skin reaction

Prolonged skin contact can cause burns/skin ulceration

May cause ill health if ingested in quantity

Method	Pouring	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments				
		MEDIUM ACUTE RISK - FULL EXPOSURE		MEDIUM CHRONIC RISK - FULL EXPOSURE		Application of mixed material.				
Control Measures		MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY		MEDIUM CHRONIC RISK						
										
		IMPERVIOUS OVERALLS	HEAVYDUTY IMPERVIOUS	WET CEMENT	BS EN166 GRADE 3		WASH AFTER USE	IF SOILED	CLOSE ALL CONTAINERS	WHEN CURED

Health Hazards

Causes serious eye damage

Causes skin irritation

May cause respiratory irritation

May cause an allergic skin reaction

Prolonged skin contact can cause burns/skin ulceration

May cause ill health if ingested in quantity

Method	Handling	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE		LOW CHRONIC RISK - FULL EXPOSURE				Handling materials unlikely to result in occupational exposure due to physical form or to release contents from sealed containers; minimal contact envisaged. In the event of a spill please refer to spillage section.
Control Measures		LOW ACUTE RISK - INDIVIDUAL ACTIVITY		LOW CHRONIC RISK		
						
AVOID SKIN CONTACT		IF OVEREXPOSURE LIKELY		IF CONTACT LIKELY		
						
						WASH AFTER EXPOSURE
						IF HEAVILY SOILED

Health Hazards

Minimal risk of exposure when intact

If dust produced see below

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Material/Process

MAPP

Supplier

ROTHENBERGER WERKZEUGE GMBH.

Keyword

Fuel (Gas)

Signal Word

Danger

MEDIUM HAZARD

GAS



Method

Cylinder Changing

Area

Inside Well Ventilated

Exposure

Less than 5 minutes per shift

Activity Comments

Refer to Pressure Systems Safety Regulations 2000 / DSEA Regulations for further precautions.

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



IF CONTACT LIKELY





WASH AFTER EXPOSURE

Health Hazards

Extremely flammable gas

Contains gas under pressure; may explode if heated

May cause eye irritation

Material/Process

MAPP

Supplier

ROTHENBERGER WERKZEUGE GMBH.

Keyword

Fuel (Gas)

Signal Word

Danger

MEDIUM HAZARD

GAS



Method

Cylinder Changing

Area

Outside

Exposure

Less than 5 minutes per shift

Activity Comments

Refer to Pressure Systems Safety Regulations 2000 / DSEA Regulations for further precautions.

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



IF CONTACT LIKELY





WASH AFTER EXPOSURE

Health Hazards

Extremely flammable gas
Contains gas under pressure; may explode if heated
May cause eye irritation

Material/Process

WELDING WIPES / 90% ALCOHOL SOLUTION

SupplierKLENZEEN LTD
KeywordCleaner (Wipes)
Signal WordDanger

MEDIUM HAZARD

LIQUID



MethodHand applyingAreaOutsideExposureUp to 1/2 hour per shiftActivity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



HIGHLY FLAMM /ACUTE HAZ

Health Hazards

Highly flammable liquid and vapour
Causes serious eye irritation
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact

Material/Process

NEW-WAY WEED SPRAY

Supplier

HEADLAND AMENITY LTD

Keyword

Plant Protection Product

Signal Word

Danger

HIGH HAZARD

LIQUID



Method

Spraying (Knapsack)

Area

Outside

Exposure

1/2 to 2 hours per shift

HIGH ACUTE RISK - FULL EXPOSURE

HIGH CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

Activity Comments

Diluted/prepared for use in accordance with manufacturer’s instructions. Controlled spray of measured quantities knapsack/Lance sprayer or hand trigger sprayer reduces likelihood of exposure.

Control Measures



TYPE 4



NITRILE OR PVC



PROTECTIVE
FOOTWEAR



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



AFTER USE



CLOSE ALL
CONTAINERS



ACUTE HAZARD

Health Hazards

To avoid risks to human health and the environment, comply with the instructions for use.

Causes serious eye damage

Causes skin irritation

May cause ill health if ingested in quantity

Method

Diluting

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

HIGH ACUTE RISK - FULL EXPOSURE

HIGH CHRONIC RISK - FULL EXPOSURE

Control Measures

HIGH ACUTE RISK - INDIVIDUAL ACTIVITY

HIGH CHRONIC RISK - INDIVIDUAL ACTIVITY



TYPE 4



NITRILE OR PVC



PROTECTIVE FOOTWEAR



BS EN166





WASH AFTER EXPOSURE



AT END OF SHIFT



CLOSE ALL CONTAINERS



ACUTE HAZARD

Health Hazards

To avoid risks to human health and the environment, comply with the instructions for use.

Causes serious eye damage

Causes skin irritation

May cause ill health if ingested in quantity

Method

Indirect Exposure

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Activity covers exposure to products diluted/prepared for use in accordance with manufacturer’s instructions.

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

















TYPE 5/6

NITRILE OR PVC

PROTECTIVE FOOTWEAR

IF CONTACT LIKELY

IF CONTACT HAS OCCURRED

IF SOILED

Health Hazards

To avoid risks to human health and the environment, comply with the instructions for use.

Causes serious eye damage

Causes skin irritation

May cause ill health if ingested in quantity

Material/Process

NEW-WAY WEED SPRAY

Supplier

HEADLAND AMENITY LTD

Keyword

Plant Protection Product

Signal Word

Danger

HIGH HAZARD

LIQUID



Method	Indirect Exposure	Area	Outside	Exposure	1/2 to 2 hours per shift
LOW ACUTE RISK - FULL EXPOSURE			LOW CHRONIC RISK - FULL EXPOSURE		
LOW ACUTE RISK - INDIVIDUAL ACTIVITY			LOW CHRONIC RISK		

Control Measures



TYPE 5/6



NITRILE OR PVC



PROTECTIVE
FOOTWEAR



IF CONTACT LIKELY



IF CONTACT HAS
OCCURRED



IF SOILED

Activity Comments

Activity covers exposure to products diluted/prepared for use in accordance with manufacturer’s instructions.

Health Hazards

To avoid risks to human health and the environment, comply with the instructions for use.

Causes serious eye damage

Causes skin irritation

May cause ill health if ingested in quantity

Method

Indirect Exposure

Area

Outside

Exposure

1/2 to 2 hours per shift

Activity Comments

Activity covers exposure to products diluted/prepared for use in accordance with manufacturer’s instructions.

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

TYPE 5/6

NITRILE OR PVC

PROTECTIVE FOOTWEAR

IF CONTACT LIKELY

IF CONTACT HAS OCCURRED

IF SOILED

Health Hazards

To avoid risks to human health and the environment, comply with the instructions for use.

Causes serious eye damage

Causes skin irritation

May cause ill health if ingested in quantity

Method

Hand applying

Area

Inside Well Ventilated

Exposure

Up to 1/2 hour per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

May cause allergic reaction in susceptible individuals in contact with skin

Material/Process

CHLORINE TABLETS

Supplier

MERLIN CHEMICALS LTD

Keyword

Chlorine Tablets

Signal Word

Warning

MEDIUM HAZARD

SOLID



Method

Dissolving

Area

Outside

Exposure

Less than 5 minutes per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



AND



WASH AFTER EXPOSURE



IF HEAVILY SOILED



OR STORE WITH ACIDS



ACID REACT/ACUTE HAZARD

Health Hazards

- Minimal risk of exposure when intact
- Harmful if swallowed
- Causes serious eye irritation
- May cause respiratory irritation
- Contact with acids liberates toxic gas
- Very toxic to aquatic life with long lasting effects
- Very toxic to aquatic life
- If dust produced see below
- Skin - irritation and dermatitis may result from prolonged contact

Material/Process
SODIUM BISULPHITE 22%

Supplier
Keyword
Signal Word

VARIOUS
Chemical

MEDIUM HAZARD

LIQUID



Method Pouring Area Outside Exposure Up to 1/2 hour per shift Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN
CONTACT



POLYTHENE OR
NITRILE



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



OR STORE WITH
ACIDS



CLOSE ALL
CONTAINERS



ACID REACTIVE

Health Hazards

Contact with acids liberates toxic gas
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Material/Process

UNIPAK MORTAR POWDER & RESIN SOLUTION

Supplier

WREKIN PRODUCTS LTD

Keyword

Mortar (Styrene)

Signal Word

Danger

MEDIUM HAZARD

MULTI PACK



Method	Hand applying	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE			MEDIUM CHRONIC RISK - FULL EXPOSURE			Application of mixed material

Control Measures	MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY	MEDIUM CHRONIC RISK
------------------	---	---------------------



IMPERVIOUS OVERALLS



BUTYL OR VITON



BS EN166



AND



LEV OR



FILTER TYPE A2



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



SENSITISER/ACUTE HAZARD

Health Hazards

Causes damage to organs through prolonged or repeated exposure

Harmful if inhaled

Causes serious eye irritation

May cause respiratory irritation

Causes skin irritation

May cause an allergic skin reaction

Suspected of damaging the unborn child

Potential for ototoxic effects that may cause hearing loss

Very toxic to aquatic life with long lasting effects

Very toxic to aquatic life

May cause ill health if ingested in quantity

Material/Process

UNIPAK MORTAR POWDER & RESIN SOLUTION

Supplier

WREKIN PRODUCTS LTD

Keyword

Mortar (Styrene)

Signal Word

Danger

MEDIUM HAZARD

MULTI PACK



Method

Mixing

Area

Outside

Exposure

Up to 1/2 hour per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Activity Comments

Mixing components of multipack material prior to use

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



BUTYL OR VITON



BS EN166



AND



LEV OR



FILTER TYPE A2P3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



SWEEP OR VACUUM



SENSITISER/ACUTE HAZARD

Health Hazards

Causes damage to organs through prolonged or repeated exposure

Harmful if inhaled

Causes serious eye irritation

May cause respiratory irritation

Causes skin irritation

May cause an allergic skin reaction

Suspected of damaging the unborn child

Potential for ototoxic effects that may cause hearing loss

Very toxic to aquatic life with long lasting effects

Very toxic to aquatic life

May cause ill health if ingested in quantity

Method	Hand applying	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity	Comments
MEDIUM ACUTE RISK - FULL EXPOSURE			MEDIUM CHRONIC RISK - FULL EXPOSURE				

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



HEAVYDUTY IMPERVIOUS



IF CONTACT LIKELY



AND



LEV OR



FILTER TYPE P3



WASH AFTER USE



AT END OF SHIFT



CLOSE ALL CONTAINERS



SWEEP OR VACUUM



CONTROLLED STORE /WASTE

Health Hazards

Skin - possible irreversible effects from prolonged contact if personal cleanliness ignored

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Prolonged inhalation may lead to long term lung damage

May cause eye irritation

May cause allergic reaction in susceptible individuals

Material/Process
REDEX ADBLUE

Supplier
Key Word
Signal Word

HOLTS AUTO
Fuel Additive

LOW HAZARD

LIQUID



Method Decanting Area Outside Exposure Less than 5 minutes per shift Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN
CONTACT



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



CONTROLLED
STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Material/Process
HAWK WHITE 400G (61024)

Supplier
Key Word
Signal Word

FERNOX UK LTD
Sealant

LOW HAZARD
SEMI-SOLID



Method
Hand applying

Area
Inside Well Ventilated

Exposure
Less than 5 minutes per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



AVOID SKIN
CONTACT



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



WASH AFTER
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL
CONTAINERS



CONTROLLED
STORE /WASTE

Health Hazards

May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Material/Process
HAND GEL SANITISER - 70% ALCOHOL

SupplierCHEMANGLIA LTD T/A ANGLIAN CHE
KeywordHand Cleanser
Signal WordDanger

MEDIUM HAZARD
LIQUID



MethodHand applyingAreaInside Well VentilatedExposureLess than 5 minutes per shiftActivity Comments

LOW ACUTE RISK - FULL EXPOSURELOW CHRONIC RISK - FULL EXPOSURE

Control MeasuresLOW ACUTE RISK - INDIVIDUAL ACTIVITYLOW CHRONIC RISK



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



CLOSE ALL
CONTAINERS



HIGHLY FLAMM
/ACUTE HAZ

Health Hazards
Highly flammable liquid and vapour
Causes serious eye irritation
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact

Material/Process

HAND GEL SANITISER - 70% ALCOHOL

Supplier

CHEMANGLIA LTD T/A ANGLIAN CHE

Keyword

Hand Cleanser

Signal Word

Danger

MEDIUM HAZARD

LIQUID



Method

Hand applying

Area

Outside

Exposure

Less than 5 minutes per shift

Activity Comments

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



IF OVEREXPOSURE
LIKELY



IF CONTACT LIKELY



CLOSE ALL
CONTAINERS



HIGHLY FLAMM
/ACUTE HAZ

Health Hazards

Highly flammable liquid and vapour

Causes serious eye irritation

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

Material/Process
SAFE STEP 100 - ALL COLOURS.

Supplier
Keyword
Signal Word

ROCOL A DIVISION OF ITW LTD
Paint (Coating)
Warning

MEDIUM HAZARD
LIQUID



Method
Hand applying (Roller)

Area
Inside Well Ventilated

Exposure
Up to 1/2 hour per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



POLYETHYLENE



BS EN166



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



FLAMMABLE / ACUTE

Health Hazards

Flammable liquid and vapour
Causes serious eye irritation
May cause respiratory irritation
Causes skin irritation
May cause damage to organs through prolonged or repeated exposure
Potential for ototoxic effects that may cause hearing loss
May cause ill health if ingested in quantity
May cause allergic reaction in susceptible individuals in contact with skin

Material/Process
READY MIXED CONCRETE

SupplierAggregate Industries UK Ltd
KeywordReady Mix Concrete
Signal WordDanger

HIGH HAZARD
SEMI-SOLID



MethodHand applyingAreaOutsideExposureUp to 1/2 hour per shiftActivity Comments

MEDIUM ACUTE RISK - FULL EXPOSUREMEDIUM CHRONIC RISK - FULL EXPOSUREApplication of mixed material.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITYMEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



HEAVYDUTY IMPERVIOUS



WET CEMENT



BS EN166 GRADE 3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



WHEN CURED

Health Hazards

Causes serious eye damage
Causes skin irritation
May cause an allergic skin reaction
Prolonged skin contact can cause burns/skin ulceration
May cause ill health if ingested in quantity

Material/Process
READY MIXED CONCRETE

SupplierAggregate Industries UK Ltd
KeywordReady Mix Concrete
Signal WordDanger

HIGH HAZARD
SEMI-SOLID



MethodMixingAreaOutsideExposureUp to 1/2 hour per shiftActivity Comments

MEDIUM ACUTE RISK - FULL EXPOSUREMEDIUM CHRONIC RISK - FULL EXPOSURE

Mixing with water.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITYMEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



HEAVYDUTY IMPERVIOUS



WET CEMENT



BS EN166 GRADE 3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



SENSITISER/ACUTE HAZARD

Health Hazards

Causes serious eye damage
Causes skin irritation
May cause an allergic skin reaction
Prolonged skin contact can cause burns/skin ulceration
May cause ill health if ingested in quantity

Material/Process

CLEANLINE ACID TOILET DESCALER

HIGH HAZARD

LIQUID



SupplierPRIME SOURCE

KeywordDescaler (Acid)

Signal WordDanger

MethodPouring

AreaInside Well Ventilated

ExposureLess than 5 minutes per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



BS EN166 GRADE 3



WASH AFTER EXPOSURE



IF SOILED



OR STORE WITH ALKALI



CLOSE ALL CONTAINERS



CORROSIVE

Health Hazards

Causes severe skin burns and eye damage

Ingestion may be fatal if not treated promptly

Material/Process

MR MUSCLE SINK & DRAIN FOAMER

HIGH HAZARD

LIQUID



Supplier

SC JOHNSON LTD

Keyword

Drain Cleaner (Alkali)

Signal Word

Danger

Method

Spraying (Trigger Bottle)

Area

Inside Well Ventilated

Exposure

Less than 5 minutes per shift

Activity Comments

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



KEEP SKIN COVERED



NITRILE



BS EN166 GRADE 3



WASH AFTER EXPOSURE



IF SOILED



OR STORE WITH ACIDS



CLOSE ALL CONTAINERS



CORROSIVE / ECOTOXIC

Health Hazards

Causes severe skin burns and eye damage

Ingestion may be fatal if not treated promptly

Very toxic to aquatic life

Toxic to aquatic life with long lasting effects



This assessment was compiled by EcoOnline Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 26/01/2026



Material/Process
PLYWOOD HARDWOOD EXTERIOR

HIGH HAZARD

SOLID



SupplierSKLEJKA-PISZ PAGED S.A.
KeywordHardwood
Signal WordDanger

Method	Handling	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
LOW ACUTE RISK - FULL EXPOSURE			LOW CHRONIC RISK - FULL EXPOSURE			Handling plywood; minimal contact envisaged. In the event of a spill please refer to spillage section.

Control Measures	LOW ACUTE RISK - INDIVIDUAL ACTIVITY	LOW CHRONIC RISK
------------------	--------------------------------------	------------------



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED

Health Hazards
Minimal risk of exposure when intact
If dust produced see below
May cause cancer by inhalation
May cause allergy or asthma symptoms or breathing difficulties if inhaled
May cause ill health if ingested in quantity
Skin - irritation and dermatitis may result from prolonged contact
May cause eye irritation

Method

Hand applying

Area

Outside

Exposure

Up to 1/2 hour per shift

Activity Comments

Application of mixed material.

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



HEAVYDUTY IMPERVIOUS



WET CEMENT



BS EN166 GRADE 3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



WHEN CURED

Health Hazards

Causes serious eye damage

Causes skin irritation

May cause respiratory irritation

May cause an allergic skin reaction

Prolonged skin contact can cause burns/skin ulceration

May cause ill health if ingested in quantity

Method	Mixing	Area	Outside	Exposure	Up to 1/2 hour per shift	Activity Comments
MEDIUM ACUTE RISK - FULL EXPOSURE				MEDIUM CHRONIC RISK - FULL EXPOSURE		Mixing with water prior to application.

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



IMPERVIOUS OVERALLS



HEAVYDUTY IMPERVIOUS



WET CEMENT



BS EN166 GRADE 3



AND



LEV OR



FILTER TYPE P3



WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



SWEEP OR VACUUM



SENSITISER/ACUTE HAZARD

Health Hazards

Causes serious eye damage

Causes skin irritation

May cause respiratory irritation

May cause an allergic skin reaction

Prolonged skin contact can cause burns/skin ulceration

May cause ill health if ingested in quantity