

Material/Process

RENEWABLE HYDROCARBON (DIESEL TYPE FRACT

MEDIUM HAZARD

LIQUID

Supplier

Green Biofuels Ltd

Keyword

Fuel (Diesel)

Contents

Renewable hydrocarbons (diesel type fraction)

Signal Word

Danger

Exp Limit



Health Hazards

May be fatal if swallowed and enters airways

Repeated exposure may cause skin dryness or cracking

May cause eye irritation

Considerations

Method

Dispensing

Area

Outside

Exposure

Less than 5 minutes per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

Control Measures



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



CLOSE ALL CONTAINERS



ACUTE HAZARD

Spillage

Ventilate area

Wear nitrile or pvc gloves

Wear eye protection if contact likely

Wear respiratory protection for large spills in poorly ventilated areas

Wear protective overalls and footwear for large spillages

Absorb in sand or inert absorbent material

Small spills - wipe up with cloth

Collect into a container, close lid

Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

Ingestion - give plenty of water in sips, obtain immediate medical attention

Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:

Water fog - carbon dioxide - powder - foam - inert material

Do not use water jet

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Activity Comments

Material/Process

PROMARKER AEROSOL PAINT

MEDIUM HAZARD

AEROSOL

Supplier MHL Group

Keyword Paint (Aerosol)

Contents

n-Butane: 10 - < 25%, Propane: 10 - < 25%, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: 2.5 - < 10%, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics: 2.5 - < 10%, Titanium dioxide: 2.5 - < 10%, Isobutane: 2.5 - < 10%, Ethyl acetate: 2.5 - < 10%, Fatty acid

Signal Word Danger

Exp Limit Propane 1800mg/m3 8hTWA 7200mg/m3 15mSTEL OEL, Ethyl acetate 200ppm Vap8hTWA 734mg/m3 8hTWA 400ppm Vap15mSTEL 1468mg/m3 15mSTEL WEL, n-



Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes serious eye irritation

May cause an allergic skin reaction

Inhalation of dusts/mists released during use may have possible irreversible effects

May cause damage to organs through prolonged or repeated exposure

Repeated exposure may cause skin dryness or cracking

Harmful to aquatic life with long lasting effects

May cause ill health if ingested in quantity

Considerations

|                                   |                    |      |                                     |          |                          |
|-----------------------------------|--------------------|------|-------------------------------------|----------|--------------------------|
| Method                            | Spraying (Aerosol) | Area | Outside                             | Exposure | 1/2 to 2 hours per shift |
| MEDIUM ACUTE RISK - FULL EXPOSURE |                    |      | MEDIUM CHRONIC RISK - FULL EXPOSURE |          |                          |

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

IMPERVIOUS OVERALLS

BUTYL OR NITRILE

BS EN166

AND

LEV OR

FILTER TYPE A1P2

WASH AFTER USE

IF SOILED

PRESSURISED

Spillage

Not applicable when intact

In case of leakage or loss of containment:

Ventilate area and exclude all sources of ignition

Wear protective clothing if whole container is spilt

Allow to dissipate

Wear butyl or nitrile gloves

Ensure area is safe before re-entry

First Aid

In case of allergic reaction/anaphylactic shock call for immediate assistance from trained first aiders

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Water fog - carbon dioxide - powder - foam - inert material

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Keep containers cool with water spray

Risk of explosion if involved in a fire

Activity Comments

Intermittent use of aerosol spray.

Material/Process

PROMARKER AEROSOL PAINT

MEDIUM HAZARD

AEROSOL

Supplier MHL Group

Keyword Paint (Aerosol)

Contents

n-Butane: 10 - < 25%, Propane: 10 - < 25%, Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics: 2.5 - < 10%, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics: 2.5 - < 10%, Titanium dioxide: 2.5 - < 10%, Isobutane: 2.5 - < 10%, Ethyl acetate: 2.5 - < 10%, Fatty acid

Signal Word Danger

Exp Limit Propane 1800mg/m3 8hTWA 7200mg/m3 15mSTEL OEL, Ethyl acetate 200ppm Vap8hTWA 734mg/m3 8hTWA 400ppm Vap15mSTEL 1468mg/m3 15mSTEL WEL, n-



Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes serious eye irritation

May cause an allergic skin reaction

Inhalation of dusts/mists released during use may have possible irreversible effects

May cause damage to organs through prolonged or repeated exposure

Repeated exposure may cause skin dryness or cracking

Harmful to aquatic life with long lasting effects

May cause ill health if ingested in quantity

Considerations



| Method                            | Spraying (Aerosol) | Area | Outside                             | Exposure | Up to 1/2 hour per shift |
|-----------------------------------|--------------------|------|-------------------------------------|----------|--------------------------|
| MEDIUM ACUTE RISK - FULL EXPOSURE |                    |      | MEDIUM CHRONIC RISK - FULL EXPOSURE |          |                          |

| Control Measures | MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY |  |  | MEDIUM CHRONIC RISK |  |
|------------------|-----------------------------------------|--|--|---------------------|--|
|------------------|-----------------------------------------|--|--|---------------------|--|

IMPERVIOUS OVERALLS

BUTYL OR NITRILE

BS EN166

AND

LEV OR

FILTER TYPE A1P2

WASH AFTER USE

IF SOILED

PRESSURISED

Spillage

Not applicable when intact

In case of leakage or loss of containment:

Ventilate area and exclude all sources of ignition

Wear protective clothing if whole container is spilt

Allow to dissipate

Wear butyl or nitrile gloves

Ensure area is safe before re-entry

First Aid

In case of allergic reaction/anaphylactic shock call for immediate assistance from trained first aiders

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Water fog - carbon dioxide - powder - foam - inert material

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Keep containers cool with water spray

Risk of explosion if involved in a fire

Activity Comments

Intermittent use of aerosol spray.

This assessment was compiled by EcoOnline Sypol Limited from supplier's safety data sheets where appropriate. Safety in the use of assessments is the responsibility of the subscriber. For advice call the helpdesk on 01296 678464

Date Printed 26/01/2026

Material/Process

VIAFIX/VIAFIXQUICK

MEDIUM HAZARD

SOLID

Supplier

Start Traffic Uk

Keyword

Asphalt

Contents

Asphalt



Health Hazards

Skin - possible irreversible effects from prolonged contact if personal cleanliness ignored  
May cause ill health if ingested in quantity  
Skin - irritation and dermatitis may result from prolonged contact  
May cause eye irritation

Considerations



Signal Word

Exp Limit

Asphalt 5mg/m3 8hTWA 10mg/m3 15mSTEL

Method

Filling

Area

Outside

Exposure

Up to 1/2 hour per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

Control Measures

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK



KEEP SKIN COVERED



POLYTHENE OR NITRILE



IF CONTACT LIKELY



WASH AFTER EXPOSURE



AT END OF SHIFT



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

Spillage

Ventilate area  
Wear polythene or nitrile gloves  
Wear eye protection if contact likely  
Wear respiratory protection for large spills in poorly ventilated areas  
Wear protective overalls and footwear for large spillages  
Scoop or scrape up and place in suitable container  
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor  
Do not try to remove any adhering bitumen.

Fire

Isolated small scale fire:  
Water fog - carbon dioxide - powder - foam - inert material  
Do not use water jet  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing

Activity Comments

Material/Process

GENERIC UNLEADED PETROL WITH 10% ETHANOL

HIGH HAZARD

LIQUID

Supplier

VARIOUS

Keyword

Petrol (Unleaded)

Contents

Gasoline-: 90%, Ethanol: 10%

Signal Word

Danger

Exp Limit

Ethanol 1920mg/m3 8hTWA WEL, Gasoline- 1ppm 8hTWA



Health Hazards

Highly flammable liquid and vapour

May be fatal if swallowed and enters airways

May cause cancer

May cause genetic defects

Causes skin irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

Toxic to aquatic life with long lasting effects

May cause eye irritation

Considerations



Method

Filling

Area

Outside

Exposure

Less than 5 minutes per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

Control Measures



KEEP SKIN COVERED

POLYTHENE OR NITRILE

IF CONTACT LIKELY

WASH AFTER USE



IF SOILED

CLOSE ALL CONTAINERS

HIGHLY FLAMM /ACUTE HAZ

Spillage

Large spillage-evacuate area & refer to emergency spillage procedure

Ventilate area and exclude all sources of ignition

Wear polythene or nitrile gloves

Wear eye protection if contact likely

Suitable respiratory protection must be worn

Wear protective overalls & chemical proof footwear

Absorb in sand or inert absorbent material

Small spills - wipe up with cloth

Collect into a container, close lid

Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

Ingestion - give plenty of water in sips, obtain immediate medical attention

Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Carbon dioxide - powder - inert material, sand, earth, etc.

Do not use water

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing



Material/Process

7300 COMBI-COLOUR FINISHES

MEDIUM HAZARD

LIQUID

Supplier TOR COATINGS LIMITED

Keyword Paint (Solvent)

Contents

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics: 25 - 50%, Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics: <= 3%, Trizinc bis (orthophosphate): <= 2%, Zinc oxide: <= 0.3%, Neodecanoic acid, cobalt salt: <= 0.3%, Titanium dioxide: >= 1%

Signal Word Warning

Exp Limit Titanium dioxide 10mg/m3 Inhal8hTWA 4mg/m3 Resp8hTWA WEL, Neodecanoic acid, cobalt salt 0.1mg/m3 8hTWA WEL, Hydrocarbons, C9-C11, n-alkanes, isoalkanes,



Health Hazards

Flammable liquid and vapour

Inhalation of dusts/mists released during use may have possible irreversible effects

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

Harmful to aquatic life with long lasting effects

May cause ill health if ingested in quantity

May cause eye irritation

May cause allergic reaction in susceptible individuals in contact with skin



| Method                         | Hand applying (Roller) | Area | Outside                          | Exposure | Up to 1/2 hour per shift |
|--------------------------------|------------------------|------|----------------------------------|----------|--------------------------|
| LOW ACUTE RISK - FULL EXPOSURE |                        |      | LOW CHRONIC RISK - FULL EXPOSURE |          |                          |

|                                      |  |  |                  |  |  |
|--------------------------------------|--|--|------------------|--|--|
| LOW ACUTE RISK - INDIVIDUAL ACTIVITY |  |  | LOW CHRONIC RISK |  |  |
|--------------------------------------|--|--|------------------|--|--|



KEEP SKIN COVERED



BUTYL OR NITRILE



IF CONTACT LIKELY





WASH AFTER USE



IF SOILED



CLOSE ALL CONTAINERS



FLAMMABLE / ACUTE

Spillage

Mark the area and warn all personnel

Ventilate area and exclude all sources of ignition

Wear butyl or nitrile gloves

Wear eye protection if contact likely

Wear respiratory protection if spill is in a poorly ventilated space

Wear respiratory protection if whole container is spilt

Wear protective overalls and footwear for large spillages

Absorb in sand or inert absorbent material

Small spills - wipe up with cloth

Collect into a container, close lid

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:

Water fog - carbon dioxide - powder - foam

Do not use water jet

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Material/Process

TEMPO TP SHORT-TERM HI-VIS AEROSOL MARKE

MEDIUM HAZARD

AEROSOL

Supplier

Meon Ltd.

Keyword

Paint (Aerosol)

Contents

n-Butane: 10 - < 25%, Isobutane: 25 - < 50%, Propane: 25 - < 50%, Ethyl acetate: 10 - < 25%, Naphtha (petroleum), hydrotreated heavy: 10 - < 25%, Titanium dioxide: 2.5 - < 10%, White mineral oil (petroleum): 2.5 - < 10%

Signal Word

Danger

Propane 1800mg/m3 8hTWA 7200mg/m3 15mSTEL OEL, Ethyl acetate 200ppm Vap8hTWA 734mg/m3 8hTWA 400ppm Vap15mSTEL 1468mg/m3 15mSTEL WEL, Naphtha



Health Hazards

Extremely flammable aerosol  
Pressurised container: May burst if heated.  
Causes serious eye irritation  
Causes skin irritation  
Inhalation of dusts/mists released during use may have possible irreversible effects  
May cause drowsiness or dizziness  
Harmful to aquatic life with long lasting effects  
May cause ill health if ingested in quantity

Considerations



Method

Spraying (Aerosol)

Area

Outside

Exposure

1/2 to 2 hours per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



KEEP SKIN COVERED



POLYTHENE OR NITRILE



BS EN166



AND



LEV OR



FILTER TYPE A1P2



WASH AFTER EXPOSURE



IF SOILED



PRESSURISED

Spillage

Not applicable when intact  
In case of leakage or loss of containment:  
Ventilate area and exclude all sources of ignition  
Wear protective clothing if whole container is spilt  
Allow to dissipate  
Wear polythene or nitrile gloves  
Ensure area is safe before re-entry

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal  
Isolated small scale fire:  
Vapour may spread - distant ignition is possible  
Inert material - powder  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing  
Keep containers cool with water spray  
Risk of explosion if involved in a fire

Activity Comments

Intermittent use of aerosol spray.

Material/Process

TEMPO TP SHORT-TERM HI-VIS AEROSOL MARKE

MEDIUM HAZARD

AEROSOL

Supplier Meon Ltd.

Keyword Paint (Aerosol)

Contents

n-Butane: 10 - < 25%, Isobutane: 25 - < 50%, Propane: 25 - < 50%, Ethyl acetate: 10 - < 25%, Naphtha (petroleum), hydrotreated heavy: 10 - < 25%, Titanium dioxide: 2.5 - < 10%, White mineral oil (petroleum): 2.5 - < 10%

Signal Word

Exp Limit

Danger

Propane 1800mg/m3 8hTWA 7200mg/m3 15mSTEL OEL, Ethyl acetate 200ppm Vap8hTWA 734mg/m3 8hTWA 400ppm Vap15mSTEL 1468mg/m3 15mSTEL WEL, Naphtha



Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes serious eye irritation

Causes skin irritation

Inhalation of dusts/mists released during use may have possible irreversible effects

May cause drowsiness or dizziness

Harmful to aquatic life with long lasting effects

May cause ill health if ingested in quantity

Considerations



Method Spraying (Aerosol)

Area Outside

Exposure Up to 1/2 hour per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



KEEP SKIN COVERED



POLYTHENE OR NITRILE



BS EN166



AND



LEV OR



FILTER TYPE A1P2



WASH AFTER EXPOSURE



IF SOILED



PRESSURISED

Spillage

Not applicable when intact

In case of leakage or loss of containment:

Ventilate area and exclude all sources of ignition

Wear protective clothing if whole container is spilt

Allow to dissipate

Wear polythene or nitrile gloves

Ensure area is safe before re-entry

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Inert material - powder

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Keep containers cool with water spray

Risk of explosion if involved in a fire

Activity Comments

Intermittent use of aerosol spray.



Material/Process

ZINC

MEDIUM HAZARD

AEROSOL

Supplier CRC Industries Europe BV  
Keyword Coating (Aero)

Contents

dimethyl ether: 50 - 75%, Zinc (powder or dust- stabilised): 25 - 50%, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics: 5 - 10%, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane: 5 - 10%, Butan-2-one: 5 - 10%, Zinc oxide: 1 - 5%

Signal Word Danger

Exp Limit Butan-2-one 600mg/m3 8hTWA 899mg/m3 15mSTEL WEL, dimethyl ether 766mg/m3 8hTWA 958mg/m3 15mSTEL WEL, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,



Health Hazards

- Extremely flammable aerosol
- Pressurised container: May burst if heated.
- Causes serious eye irritation
- Causes skin irritation
- May cause drowsiness or dizziness
- Very toxic to aquatic life with long lasting effects
- Very toxic to aquatic life
- May cause ill health if ingested in quantity

Considerations



Method Spraying (Aerosol) Area Inside Well Ventilated Exposure Less than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



KEEP SKIN COVERED



POLYETHYLENE



BS EN166



WASH AFTER EXPOSURE



IF SOILED



PRESSURISED

Spillage

- Not applicable when intact
- In case of leakage or loss of containment:
  - Ventilate area and exclude all sources of ignition
  - Wear protective clothing if whole container is spilt
  - Allow to dissipate
  - Wear polythene gloves
  - Ensure area is safe before re-entry

First Aid

- Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
- Ingestion - do not induce vomiting, wash out mouth with water
- If feeling unwell consult your doctor immediately
- Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor
- Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

- Keep aerosol cans cool, do not burn for disposal
- Isolated small scale fire:
  - Vapour may spread - distant ignition is possible
  - Water fog - carbon dioxide - powder - foam
  - Do not use water jet
- Large fire: evacuate area, call fire brigade or follow site procedure
- Wear self-contained breathing apparatus and protective clothing
- Keep containers cool with water spray
- Risk of explosion if involved in a fire

Material/Process

ZINC

MEDIUM HAZARD

AEROSOL

Supplier CRC Industries Europe BV  
Keyword Coating (Aero)

Contents

dimethyl ether: 50 - 75%, Zinc (powder or dust- stabilised): 25 - 50%, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics: 5 - 10%, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane: 5 - 10%, Butan-2-one: 5 - 10%, Zinc oxide: 1 - 5%

Signal Word Danger  
Exp Limit Butan-2-one 600mg/m3 8hTWA 899mg/m3 15mSTEL WEL, dimethyl ether 766mg/m3 8hTWA 958mg/m3 15mSTEL WEL, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,



Health Hazards

- Extremely flammable aerosol
- Pressurised container: May burst if heated.
- Causes serious eye irritation
- Causes skin irritation
- May cause drowsiness or dizziness
- Very toxic to aquatic life with long lasting effects
- Very toxic to aquatic life
- May cause ill health if ingested in quantity

Considerations



Method Spraying (Aerosol) Area Outside Exposure Less than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures

KEEP SKIN COVERED

POLYETHYLENE

BS EN166

WASH AFTER EXPOSURE

IF SOILED

PRESSURISED

Spillage

- Not applicable when intact
- In case of leakage or loss of containment:
  - Ventilate area and exclude all sources of ignition
  - Wear protective clothing if whole container is spilt
  - Allow to dissipate
  - Wear polythene gloves
  - Ensure area is safe before re-entry

First Aid

- Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
- Ingestion - do not induce vomiting, wash out mouth with water
- If feeling unwell consult your doctor immediately
- Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor
- Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

- Keep aerosol cans cool, do not burn for disposal
- Isolated small scale fire:
  - Vapour may spread - distant ignition is possible
  - Water fog - carbon dioxide - powder - foam
  - Do not use water jet
- Large fire: evacuate area, call fire brigade or follow site procedure
- Wear self-contained breathing apparatus and protective clothing
- Keep containers cool with water spray
- Risk of explosion if involved in a fire

Material/Process

AIRLINE LUBRICANT KO10

LOW HAZARD

LIQUID

Supplier

AZTEC OILS LTD

Keyword

Anti-Freeze

Contents

IONIC MIXTURE ANNEX V – AMINE CARBOXYLATE: 1 - < 9%,  
1,2-propanediol: 1 - < 10%

Signal Word

Exp Limit

1,2-propanediol 474mg/m3 Vap8hTWA 10mg/m3  
Part8hTWA



Health Hazards

May cause ill health if ingested in quantity  
Skin - irritation and dermatitis may result from prolonged contact  
May cause eye irritation

Considerations

Method

Pouring

Area

Outside

Exposure

Less than 5 minutes per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

Control Measures



AVOID SKIN  
CONTACT



POLYTHENE OR  
NITRILE



IF CONTACT LIKELY



WASH AFTER  
EXPOSURE



IF HEAVILY SOILED



CLOSE ALL  
CONTAINERS



CONTROLLED  
STORE /WASTE

Spillage

Ventilate area  
Wear polythene or nitrile gloves  
Wear eye protection if contact likely  
Wear respiratory protection for large spills in poorly ventilated areas  
Wear protective overalls and footwear for large spillages  
Absorb in sand or inert absorbent material  
Small spills - wipe up with cloth  
Collect into a container, close lid  
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:  
Water fog - carbon dioxide - powder - foam - inert material  
Do not use water jet  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing

Material/Process

GENERIC - CONTAMINATED SOIL

MEDIUM HAZARD

SOLID

Supplier

NOT APPLICABLE

Keyword

Contaminated Land/Soil

Contents

Contaminated land/soil

Signal Word

Exp Limit

10mg/m3(inh),4mg/m3(resp) dust OEL EH



Health Hazards

Toxicological properties of material not fully investigated

Contaminants present may have an adverse impact on human health

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation



MethodHandlingAreaOutsideExposureUp to 1/2 hour per shift

MEDIUM ACUTE RISK - FULL EXPOSUREMEDIUM CHRONIC RISK - FULL EXPOSURE

Control MeasuresMEDIUM ACUTE RISK - INDIVIDUAL ACTIVITYMEDIUM CHRONIC RISK

KEEP SKIN COVERED

POLYTHENE OR NITRILE

BS EN166

WASH AFTER USE

IF SOILED

Spillage

If dust produced see below:

Wear respirator with particulate filter type p3 or equivalent

Wear eye protection if contact likely

Wear protective overalls and footwear for large spillages

Do not dry sweep - either suppress dust or clear using hepa vacuum

Scoop up, sweep or vacuum residue (h type), avoid dust creation.

Collect into suitable container avoiding dust generation

Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

Wear polythene or nitrile gloves

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:

Use extinguishers suitable for other materials involved in fire

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Material/Process

TANGO AIR FRESHENER

LOW HAZARD

AEROSOL

Supplier

KOZMO KIMYA SAN. VE DIS. TIC.L

Keyword

Air Freshener

Contents

Ethanol: 1.2 - 1.5%, Petroleum gases, liquefied: 18 - 22%, Sodium nitrite: 0.1 - 0.12%, Sodium Benzoate: 0.1 - 0.4%

Signal Word

Danger

Exp Limit

Ethanol 1920mg/m3 8hTWA WEL, Petroleum gases, liquefied 1750mg/m3 8hTWA 2180mg/m3 15mSTEL



Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

May cause ill health if ingested in quantity

Skin - irritation and dermatitis may result from prolonged contact

May cause eye irritation

Considerations



Method

Spraying (Aerosol)

Area

Inside Well Ventilated

Exposure

Less than 5 minutes per shift

LOW ACUTE RISK - FULL EXPOSURE

LOW CHRONIC RISK - FULL EXPOSURE

LOW ACUTE RISK - INDIVIDUAL ACTIVITY

LOW CHRONIC RISK

Control Measures



AVOID SKIN CONTACT



NITRILE



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Spillage

Not applicable when intact

In case of leakage or loss of containment:

Ventilate area and exclude all sources of ignition

Wear protective clothing if whole container is spilt

Allow to dissipate

Wear nitrile gloves

Ensure area is safe before re-entry

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Water fog - carbon dioxide - powder - foam - inert material

Do not use water jet

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Keep containers cool with water spray

Risk of explosion if involved in a fire

Activity Comments



Material/Process

NADCC EFFERVESCENT CHLORINE TABLETS

MEDIUM HAZARD

SOLID

Supplier

HY-RAM ENGINEERING

Keyword

Chlorine Tablets

Contents

Troclosene sodium: 40 - 60%, Adipic acid: 15 - 25%, Sodium carbonate: 3 - 5%

Signal Word

Warning

Exp Limit

Sodium carbonate 10mg/m3 Inhal8hTWA 4mg/m3 Resp8hTWA



Health Hazards

- Minimal risk of exposure when intact
- Harmful if swallowed
- Causes serious eye irritation
- May cause respiratory irritation
- Contact with acids liberates toxic gas
- Very toxic to aquatic life with long lasting effects
- Very toxic to aquatic life
- If dust produced see below
- Skin - irritation and dermatitis may result from prolonged contact

Considerations



Method

Dissolving

Area

Outside

Exposure

Less than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



AVOID SKIN CONTACT



IF OVEREXPOSURE LIKELY



IF CONTACT LIKELY



WASH AFTER EXPOSURE



IF HEAVILY SOILED



OR STORE WITH ACIDS



ACID REACT/ACUTE HAZARD

Spillage

- Avoid excessive exposure to hands/skin - use suitable gloves if necessary
- Contain and collect material
- Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

- Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill
- Ingestion - do not induce vomiting, wash out mouth with water
- Ingestion - give plenty of water in sips, obtain immediate medical attention
- Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor
- Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

- Isolated small scale fire:
- Water - carbon dioxide - powder - foam - inert material
- Large fire: evacuate area, call fire brigade or follow site procedure
- Wear self-contained breathing apparatus and protective clothing

Material/Process

ALL TYPES OF SAND, GRAVEL, GRANITE,

MEDIUM HAZARD

SOLID

SupplierTARMAC TRUPAK  
KeywordAggregate

Contents

Quartz (SiO2) (non respirable fraction): 30 - 100%, Respirable silica: < 10%

Signal Word

Exp Limit

Respirable silica 0.1mg/m3 8hTWA WEL, Quartz (SiO2) (non respirable fraction) 10mg/m3 Inhal8hTWA 4mg/m3 Resp8hTWA



Health Hazards

May cause ill health if ingested in quantity  
Skin - irritation and dermatitis may result from prolonged contact  
Prolonged inhalation may lead to long term lung damage  
May cause eye irritation

Considerations



MethodExcavatingAreaOutsideExposureLess than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



PROTECTIVE FOOTWEAR



IF CONTACT LIKELY



AND



FILTER TYPE P3



WASH AFTER EXPOSURE



IF HEAVILY SOILED



SWEEP OR VACUUM



CONTROLLED STORE /WASTE

Spillage

Ventilate area  
Wear heavy duty impervious gloves  
Wear eye protection if contact likely  
Suitable respiratory protection must be worn  
Wear protective overalls and footwear for large spillages  
Scoop or scrape up and place in suitable container  
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:  
Water - carbon dioxide - powder - foam - inert material  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing

Activity Comments

Material/Process

ALL TYPES OF SAND, GRAVEL, GRANITE,

MEDIUM HAZARD

SOLID

Supplier

TARMAC TRUPAK

Keyword

Aggregate

Contents

Quartz (SiO2) (non respirable fraction): 30 - 100%, Respirable silica: < 10%

Signal Word

Exp Limit

Respirable silica 0.1mg/m3 8hTWA WEL, Quartz (SiO2) (non respirable fraction) 10mg/m3 Inhal8hTWA 4mg/m3 Resp8hTWA

Health Hazards

May cause ill health if ingested in quantity  
Skin - irritation and dermatitis may result from prolonged contact  
Prolonged inhalation may lead to long term lung damage  
May cause eye irritation

Considerations

Method

Loading/Unloading

Area

Outside

Exposure

Less than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

AVOID SKIN CONTACT

IF OVEREXPOSURE LIKELY

IF CONTACT LIKELY

AND

FILTER TYPE P3

WASH AFTER EXPOSURE

IF HEAVILY SOILED

Spillage

Ventilate area  
Wear heavy duty impervious gloves  
Wear eye protection if contact likely  
Suitable respiratory protection must be worn  
Wear protective overalls and footwear for large spillages  
Scoop or scrape up and place in suitable container  
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:  
Water - carbon dioxide - powder - foam - inert material  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing

Material/Process

ALL TYPES OF SAND, GRAVEL, GRANITE,

MEDIUM HAZARD

SOLID

SupplierTARMAC TRUPAK  
KeywordAggregate

Contents

Quartz (SiO2) (non respirable fraction): 30 - 100%, Respirable silica: < 10%

Signal Word

Exp Limit

Respirable silica 0.1mg/m3 8hTWA WEL, Quartz (SiO2) (non respirable fraction) 10mg/m3 Inhal8hTWA 4mg/m3 Resp8hTWA



Health Hazards

May cause ill health if ingested in quantity  
Skin - irritation and dermatitis may result from prolonged contact  
Prolonged inhalation may lead to long term lung damage  
May cause eye irritation

Considerations



MethodSpreadingAreaOutsideExposureLess than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

Control Measures

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK



AVOID SKIN CONTACT



HEAVYDUTY IMPERVIOUS



PROTECTIVE FOOTWEAR



IF CONTACT LIKELY



AND



LEV OR



FILTER TYPE P3



WASH AFTER EXPOSURE



IF HEAVILY SOILED



CLOSE ALL CONTAINERS



CONTROLLED STORE /WASTE

Spillage

Ventilate area  
Wear heavy duty impervious gloves  
Wear eye protection if contact likely  
Suitable respiratory protection must be worn  
Wear protective overalls and footwear for large spillages  
Scoop or scrape up and place in suitable container  
Dispose or recycle of spillages in a controlled manner - Refer to Hazardous Waste Regulations if appropriate

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill  
Ingestion - do not induce vomiting, wash out mouth with water  
If feeling unwell consult your doctor immediately  
Eye - irrigate with water until irritation subsides; if irritation persists then consult a doctor  
Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Isolated small scale fire:  
Water - carbon dioxide - powder - foam - inert material  
Large fire: evacuate area, call fire brigade or follow site procedure  
Wear self-contained breathing apparatus and protective clothing

Activity Comments

Material/Process

SOPPEC- PAK DETECTOR

MEDIUM HAZARD

AEROSOL

Supplier Technima Central GmbH.

Keyword Paint (Aerosol)

Contents

Acetone: 25 - < 50%, Ethyl acetate: 10 - < 25%, n-Butane: 10 - < 25%, Solvent naphtha (petroleum) light aromatic: 2.5 - < 10%, Titanium dioxide: 2.5 - < 10%, Ethanol: 0.1 - < 1%

Signal Word Danger

Exp Limit Acetone 1210mg/m3 8hTWA 3620mg/m3 15mSTEL WEL, Ethanol 1920mg/m3 8hTWA WEL, Ethyl acetate 200ppm Vap8hTWA 734mg/m3 8hTWA 400ppm Vap15mSTEL



Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes serious eye irritation

Inhalation of dusts/mists released during use may have possible irreversible effects

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

Harmful to aquatic life with long lasting effects

May cause ill health if ingested in quantity

Considerations



Method Spraying (Aerosol) Area Outside Exposure Less than 5 minutes per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



AVOID SKIN CONTACT



NEOPRENE/ POLYTHENE



BS EN166



WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Spillage

Not applicable when intact

In case of leakage or loss of containment:

Ventilate area and exclude all sources of ignition

Wear protective clothing if whole container is spilt

Allow to dissipate

Wear neoprene or polythene gloves

Ensure area is safe before re-entry

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Carbon dioxide - powder - inert material, sand, earth, etc.

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Keep containers cool with water spray

Risk of explosion if involved in a fire

Activity Comments

Material/Process

SOPPEC- PAK DETECTOR

MEDIUM HAZARD

AEROSOL

Supplier

Technima Central GmbH.

Keyword

Paint (Aerosol)

Contents

Acetone: 25 - < 50%, Ethyl acetate: 10 - < 25%, n-Butane: 10 - < 25%, Solvent naphtha (petroleum) light aromatic: 2.5 - < 10%, Titanium dioxide: 2.5 - < 10%, Ethanol: 0.1 - < 1%

Signal Word

Danger

Exp Limit

Acetone 1210mg/m3 8hTWA 3620mg/m3 15mSTEL WEL, Ethanol 1920mg/m3 8hTWA WEL, Ethyl acetate 200ppm Vap8hTWA 734mg/m3 8hTWA 400ppm Vap15mSTEL



Health Hazards

Extremely flammable aerosol

Pressurised container: May burst if heated.

Causes serious eye irritation

Inhalation of dusts/mists released during use may have possible irreversible effects

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking

Harmful to aquatic life with long lasting effects

May cause ill health if ingested in quantity

Considerations



Method

Spraying (Aerosol)

Area

Outside

Exposure

Up to 1/2 hour per shift

MEDIUM ACUTE RISK - FULL EXPOSURE

MEDIUM CHRONIC RISK - FULL EXPOSURE

MEDIUM ACUTE RISK - INDIVIDUAL ACTIVITY

MEDIUM CHRONIC RISK

Control Measures



KEEP SKIN COVERED



NEOPRENE/ POLYTHENE



BS EN166



WASH AFTER EXPOSURE



IF HEAVILY SOILED



PRESSURISED

Spillage

Not applicable when intact

In case of leakage or loss of containment:

Ventilate area and exclude all sources of ignition

Wear protective clothing if whole container is spilt

Allow to dissipate

Wear neoprene or polythene gloves

Ensure area is safe before re-entry

First Aid

Inhalation - remove to fresh air; get immediate medical attention after significant exposure or if feeling ill

Ingestion - do not induce vomiting, wash out mouth with water

If feeling unwell consult your doctor immediately

Eye - rinse thoroughly with water - take care not to affect uncontaminated eye. If irritation persists then consult a doctor

Skin - wash with soap/cleanser and rinse with water; if irritation persists then consult a doctor

Fire

Keep aerosol cans cool, do not burn for disposal

Isolated small scale fire:

Vapour may spread - distant ignition is possible

Carbon dioxide - powder - inert material, sand, earth, etc.

Large fire: evacuate area, call fire brigade or follow site procedure

Wear self-contained breathing apparatus and protective clothing

Keep containers cool with water spray

Risk of explosion if involved in a fire

Activity Comments

Intermittent use of aerosol spray.