

On this page



Manage Endpoints

`gpuIds`, `name`, and `templateId` are required arguments; all other arguments are optional, and default values will be used if unspecified.

Create a new Serverless Endpoint

[cURL](#)[GraphQL](#)[Output](#)

```
curl --request POST \
  --header 'content-type: application/json' \
  --url 'https://api.runpod.io/graphql?api_key=${YOUR_API_KEY}' \
  --data '{"query": "mutation { saveEndpoint(input: { gpuIds: \"AMPERE_16\"
```

Modify an existing Serverless Endpoint

[cURL](#)[GraphQL](#)[Output](#)

```
curl --request POST \
  --header 'content-type: application/json' \
  --url 'https://api.runpod.io/graphql?api_key=${YOUR_API_KEY}' \
  --data '{"query": "mutation { saveEndpoint(input: { id: \"i02xupws21hp6:
```

View your Endpoints

[cURL](#)[GraphQL](#)[Output](#)

Ask AI

```
curl --request POST \  
  --header 'content-type: application/json' \  
  --url 'https://api.runpod.io/graphql?api_key=${YOUR_API_KEY}' \  
  --data '{"query": "query Endpoints { myself { endpoints { gpuIds id :
```

Delete a Serverless Endpoints


Note that your endpoint's min and max workers must both be set to zero for your call to work.

cURL

GraphQL

Output

```
curl --request POST \  
  --header 'content-type: application/json' \  
  --url 'https://api.runpod.io/graphql?api_key=${YOUR_API_KEY}' \  
  --data '{"query": "mutation { deleteEndpoint(id: \"i02xupws21hp6i\") }"}
```

 [Edit this page](#)

Previous

« [Manage Templates](#)

Next

[Overview](#) »

Docs


[Overview](#)

[Tutorials](#)

[AI APIs](#)

Community

[Discord](#) 


[Contact us](#) 



Ask AI

More

[Blog](#) 

[GitHub](#) 

Copyright © 2024 RunPod



Ask AI