



Serverless

References

**Endpoint operations** 

## **Endpoint operations**

RunPod's endpoints facilitate submitting jobs and retrieving outputs.

To use these endpoints, you will need to have your endpoint ID. The constructed URL will start with https://api.runpod.ai/v2/{endpoint\_id}/{operation} followed by an operation.

Operations available to all users are:

- /run: Asynchronous endpoint for submitting jobs. Returns a unique Job ID.
  - o Payload capacity: 10 MB
  - Rate limit: 1000 per second
  - Job availability: Successful job results are accessible for 30 minutes after completion
- /runsync: Synchronous endpoint for shorter running jobs, returning immediate results.
  - o Payload capacity: 20 MB
  - Rate limit: 2000 per second
  - Job availability: Successful job results are accessible for 60 seconds after completion
- /stream/{job\_id}: For streaming results from generator-type handlers.
- /status/{job\_id}: To check the job status and retrieve outputs upon completion.
- /cancel/{job\_id}: To cancel a job prematurely.
- /health: Provides worker statistics and endpoint health.
  - Only accepts GET methods
- /purge-queue: Clears all queued jobs, it will not cancel jobs in progress.

## Edit this page

Previous 
« Endpoint configurations

Next Job states »



Ask Al

Overview	
Tutorials	
Al APIs	
Community	
Discord ☑	
Contact us ☐	
More	
Blog ☑	
GitHub ⊡	
	Copyright © 2024 RunPod

