

08 Amazon Fine Food Reviews Analysis_Decision Trees

June 26, 2019

1 Amazon Fine Food Reviews Analysis

Data Source: <https://www.kaggle.com/snap/amazon-fine-food-reviews>

EDA: <https://nycdatascience.com/blog/student-works/amazon-fine-foods-visualization/>

The Amazon Fine Food Reviews dataset consists of reviews of fine foods from Amazon.

Number of reviews: 568,454 Number of users: 256,059 Number of products: 74,258 Timespan: Oct 1999 - Oct 2012 Number of Attributes/Columns in data: 10

Attribute Information:

1. Id
2. ProductId - unique identifier for the product
3. UserId - unique identifier for the user
4. ProfileName
5. HelpfulnessNumerator - number of users who found the review helpful
6. HelpfulnessDenominator - number of users who indicated whether they found the review helpful or not
7. Score - rating between 1 and 5
8. Time - timestamp for the review
9. Summary - brief summary of the review
10. Text - text of the review

Objective: Given a review, determine whether the review is positive (rating of 4 or 5) or negative (rating of 1 or 2).

[Q] How to determine if a review is positive or negative? [Ans] We could use Score/Rating. A rating of 4 or 5 can be considered as a positive review. A rating of 1 or 2 can be considered as negative one. A review of rating 3 is considered neutral and such reviews are ignored from our analysis. This is an approximate and proxy way of determining the polarity (positivity/negativity) of a review.

2 [1]. Reading Data

2.1 [1.1] Loading the data

The dataset is available in two forms 1. .csv file 2. SQLite Database

In order to load the data, We have used the SQLITE dataset as it is easier to query the data and visualise the data efficiently.

Here as we only want to get the global sentiment of the recommendations (positive or negative), we will purposefully ignore all Scores equal to 3. If the score is above 3, then the recommendation will be set to "positive". Otherwise, it will be set to "negative".

```
[1]: %matplotlib inline
import warnings
warnings.filterwarnings("ignore")

import sqlite3
import pandas as pd
import numpy as np
import nltk
import string
import matplotlib.pyplot as plt
import seaborn as sns
# from sklearn.feature_extraction.text import TfidfTransformer
from sklearn.feature_extraction.text import TfidfVectorizer

from sklearn.feature_extraction.text import CountVectorizer
from sklearn.metrics import confusion_matrix
from sklearn import metrics
from sklearn.metrics import roc_curve, auc
# from nltk.stem.porter import PorterStemmer

import re
# Tutorial about Python regular expressions: https://pymotw.com/2/re/
import string
from nltk.corpus import stopwords
# from nltk.stem import PorterStemmer
# from nltk.stem.wordnet import WordNetLemmatizer

from gensim.models import Word2Vec
from gensim.models import KeyedVectors
import pickle

from tqdm import tqdm
import os

[2]: # Using prettyTable for showing the observations
from prettytable import PrettyTable
table = PrettyTable()
table.field_names= ["Vectorizer", "Model", "Hyperparameters", "AUC Score"]
print(table)
```

```
+-----+-----+-----+-----+
| Vectorizer | Model | Hyperparameters | AUC Score |
+-----+-----+-----+-----+
+-----+-----+-----+-----+
```

```
[3]: dir_path = '../'
print(os.listdir(dir_path))
```

```
['Assignment1_Habermans', 'models', 'database.sqlite',
'Assignment5_LogisticRegression', 'Assignment4_NaiveBayes',
'Assignment2_AmazonFoodReviews', 'Assignment8_DT', 'Assignment3_kNN',
'Assignment6_SGD', 'Assignment7_SVM']
```

```
[4]: # using SQLite Table to read data.
con = sqlite3.connect(dir_path+'database.sqlite')

# filtering only positive and negative reviews i.e.
# not taking into consideration those reviews with Score=3
# SELECT * FROM Reviews WHERE Score != 3 LIMIT 500000, will give top
# 500000 data points you can change the number to any other number
# based on your computing power

filtered_data = pd.read_sql_query(
    "SELECT * FROM Reviews WHERE Score < 3 LIMIT 55000"
    , con)
filtered_data = filtered_data.append(
    pd.read_sql_query(
        "SELECT * FROM Reviews WHERE Score > 3 LIMIT 55000"
        , con))

# Give reviews with Score>3 a positive rating(1), and reviews with a
# score<3 a negative rating(0).
def partition(x):
    if x < 3:
        return 0
    return 1

#changing reviews with score less than 3 to be positive and vice-versa
actualScore = filtered_data['Score']
positiveNegative = actualScore.map(partition)
filtered_data['Score'] = positiveNegative
print("Number of data points in our data", filtered_data.shape)
filtered_data.head(3)
```

Number of data points in our data (110000, 10)

```
[4]:
```

	Id	ProductId	UserId	ProfileName	HelpfulnessNumerator	\
0	2	B00813GRG4	A1D87F6ZCVE5NK	dll pa	0	
1	4	B000UA0QIQ	A395BORC6FGVXV	Karl	3	
2	13	B0009XLVG0	A327PCT23YH90	LT	1	

	HelpfulnessDenominator	Score	Time \
0	0	0	1346976000
1	3	0	1307923200
2	1	0	1339545600

	Summary \
0	Not as Advertised
1	Cough Medicine
2	My Cats Are Not Fans of the New Food

	Text
0	Product arrived labeled as Jumbo Salted Peanut...
1	If you are looking for the secret ingredient i...
2	My cats have been happily eating Felidae Plati...

```
[5]: display = pd.read_sql_query("""
SELECT UserId, ProductId, ProfileName, Time, Score, Text, COUNT(*)
FROM Reviews
GROUP BY UserId
HAVING COUNT(*)>1
""", con)
```

```
[6]: print(display.shape)
display.head()
```

(80668, 7)

	UserId	ProductId	ProfileName	Time	Score \
0	#oc-R115TNMSPFT9I7	B005ZBZLT4	Breyton	1331510400	2
1	#oc-R11D9D7SHXIJB9	B005HG9ESG	Louis E. Emory "hoppy"	1342396800	5
2	#oc-R11DNU2NBKQ23Z	B005ZBZLT4	Kim Cieszykowski	1348531200	1
3	#oc-R1105J5ZVQE25C	B005HG9ESG	Penguin Chick	1346889600	5
4	#oc-R12KPBODL2B5ZD	B007OSBEV0	Christopher P. Presta	1348617600	1

	Text	COUNT(*)
0	Overall its just OK when considering the price...	2
1	My wife has recurring extreme muscle spasms, u...	3
2	This coffee is horrible and unfortunately not ...	2
3	This will be the bottle that you grab from the...	3
4	I didnt like this coffee. Instead of telling y...	2

```
[7]: display[display['UserId']=='AZY10LLTJ71NX']
```

	UserId	ProductId	ProfileName	Time \
80638	AZY10LLTJ71NX	B001ATMQK2	undertheshrine "undertheshrine"	1296691200

	Score	Text	COUNT(*)
80638	5	I bought this 6 pack because for the price tha...	5

```
[8]: display['COUNT(*)'].sum()
```

[8]: 393063

3 [2] Exploratory Data Analysis

3.1 [2.1] Data Cleaning: Deduplication

It is observed (as shown in the table below) that the reviews data had many duplicate entries. Hence it was necessary to remove duplicates in order to get unbiased results for the analysis of the data. Following is an example:

```
[9]: display= pd.read_sql_query("""
SELECT *
FROM Reviews
WHERE Score != 3 AND UserId="AR5J8UI46CURR"
ORDER BY ProductID
""", con)
display.head()
```

```
[9]:      Id  ProductId      UserId  ProfileName  HelpfulnessNumerator  \
0   78445  B000HDL1RQ  AR5J8UI46CURR  Geetha Krishnan                2
1  138317  B000HDOPYC  AR5J8UI46CURR  Geetha Krishnan                2
2  138277  B000HDOPYM  AR5J8UI46CURR  Geetha Krishnan                2
3   73791  B000HDOPZG  AR5J8UI46CURR  Geetha Krishnan                2
4  155049  B000PAQ75C  AR5J8UI46CURR  Geetha Krishnan                2
```

```
      HelpfulnessDenominator  Score      Time  \
0                        2      5  1199577600
1                        2      5  1199577600
2                        2      5  1199577600
3                        2      5  1199577600
4                        2      5  1199577600
```

```
      Summary  \
0  LOACKER QUADRATINI VANILLA WAFERS
1  LOACKER QUADRATINI VANILLA WAFERS
2  LOACKER QUADRATINI VANILLA WAFERS
3  LOACKER QUADRATINI VANILLA WAFERS
4  LOACKER QUADRATINI VANILLA WAFERS
```

```
      Text
0  DELICIOUS WAFERS. I FIND THAT EUROPEAN WAFERS ...
1  DELICIOUS WAFERS. I FIND THAT EUROPEAN WAFERS ...
2  DELICIOUS WAFERS. I FIND THAT EUROPEAN WAFERS ...
3  DELICIOUS WAFERS. I FIND THAT EUROPEAN WAFERS ...
4  DELICIOUS WAFERS. I FIND THAT EUROPEAN WAFERS ...
```

As it can be seen above that same user has multiple reviews with same values for HelpfulnessNumerator, HelpfulnessDenominator, Score, Time, Summary and Text and on doing analysis it was found that ProductId=B000HDOPZG was Loacker Quadratini Vanilla Wafer Cookies,

8.82-Ounce Packages (Pack of 8) ProductId=B000HDL1RQ was Loacker Quadratini Lemon Wafer Cookies, 8.82-Ounce Packages (Pack of 8) and so on

It was inferred after analysis that reviews with same parameters other than ProductId belonged to the same product just having different flavour or quantity. Hence in order to reduce redundancy it was decided to eliminate the rows having same parameters.

The method used for the same was that we first sort the data according to ProductId and then just keep the first similar product review and delete the others. for eg. in the above just the review for ProductId=B000HDL1RQ remains. This method ensures that there is only one representative for each product and deduplication without sorting would lead to possibility of different representatives still existing for the same product.

```
[10]: #Sorting data according to ProductId in ascending order
sorted_data=filtered_data.sort_values('ProductId', axis=0,
                                       ascending=True, inplace=False,
                                       kind='quicksort',
                                       na_position='last')
```

```
[11]: #Deduplication of entries
final=sorted_data.drop_duplicates(subset={"UserId","ProfileName",
                                          "Time","Text"},
                                 keep='first', inplace=False)

final.shape
```

```
[11]: (90187, 10)
```

```
[12]: #Checking to see how much % of data still remains
(final['Id'].size*1.0)/(filtered_data['Id'].size*1.0)*100
```

```
[12]: 81.98818181818181
```

Observation:- It was also seen that in two rows given below the value of HelpfulnessNumerator is greater than HelpfulnessDenominator which is not practically possible hence these two rows too are removed from calculations

```
[13]: display= pd.read_sql_query("""
SELECT *
FROM Reviews
WHERE Score != 3 AND Id=44737 OR Id=64422
ORDER BY ProductID
""", con)

display.head()
```

```
[13]:      Id  ProductId      UserId      ProfileName \
0  64422  B000MIDROQ  A161DK06JJMCYF  J. E. Stephens "Jeanne"
1  44737  B001EQ55RW  A2V0I904FH7ABY                      Ram

      HelpfulnessNumerator  HelpfulnessDenominator  Score      Time \
0                        3                        1      5  1224892800
1                        3                        2      4  1212883200
```

Summary \

```

0           Bought This for My Son at College
1 Pure cocoa taste with crunchy almonds inside

```

Text

```

0 My son loves spaghetti so I didn't hesitate or...
1 It was almost a 'love at first bite' - the per...

```

```
[14]: final=final[final.HelpfulnessNumerator<=final.HelpfulnessDenominator]
```

```
[15]: #Before starting the next phase of preprocessing lets see the number of entries
      → left
      print(final.shape)

      #How many positive and negative reviews are present in our dataset?
      final['Score'].value_counts()
```

```
(90185, 10)
```

```
[15]: 1    49643
      0    40542
      Name: Score, dtype: int64
```

4 [3] Preprocessing

4.1 [3.1]. Preprocessing Review Text

Now that we have finished deduplication our data requires some preprocessing before we go on further with analysis and making the prediction model.

Hence in the Preprocessing phase we do the following in the order below:-

1. Begin by removing the html tags
2. Remove any punctuations or limited set of special characters like , or . or # etc.
3. Check if the word is made up of english letters and is not alpha-numeric
4. Check to see if the length of the word is greater than 2 (as it was researched that there is no adjective in 2-letters)
5. Convert the word to lowercase
6. Remove Stopwords
7. Finally Snowball Stemming the word (it was observed to be better than Porter Stemming)

After which we collect the words used to describe positive and negative reviews

```
[16]: # printing some random reviews
      sent_0 = final['Text'].values[0]
      print(sent_0)
      print("="*50)

      sent_1000 = final['Text'].values[1000]
      print(sent_1000)
      print("="*50)
```

```

sent_1500 = final['Text'].values[1500]
print(sent_1500)
print("="*50)

sent_4900 = final['Text'].values[4900]
print(sent_4900)
print("="*50)

```

This is one of the best children's books ever written but it is a mini version of the book and was not portrayed as one. It is over priced for the product. I sent an email regarding my bewilderment to Amazon and got no response.

=====

The tree and pot which arrived were not the ones pictured. Also, the trunk has several indentions and rust spots from where improper wire was left on the trunk too long. I expected better.

=====

I did my research before deciding to spend \$30+ on a bottle of vanilla, granted a very large one. After reading all the comments, I expected the pleasant aroma of vanilla wafting from the bottle upon opening, but what I got instead was this murky, smokey smell that doesn't even remotely resemble vanilla. There is absolutely no vanilla aroma when I added it to my custards, even with additional amount. Sure, the vanilla specks are there, but what good would they do if they give nothing to the flavor of the dish? I must have gotten a bad bottle or something (is that even possible, for vanilla bean paste to go bad?). I'm quite disappointed, looks like I'll just have to stick with Costco vanilla extract from now on.

=====

I had purchased 48 3 oz. cans of tuna, upon opening some of the tuna I had to throw out 20 cans, because the product was spoiled (dark meat and fowl smell). I purchased this product in the past with no problems.

=====

[17]: *# remove urls from text python: <https://stackoverflow.com/a/40823105/4084039>*

```

sent_0 = re.sub(r"http\S+", "", sent_0)
sent_1000 = re.sub(r"http\S+", "", sent_1000)
sent_150 = re.sub(r"http\S+", "", sent_1500)
sent_4900 = re.sub(r"http\S+", "", sent_4900)

print(sent_0)

```

This is one of the best children's books ever written but it is a mini version of the book and was not portrayed as one. It is over priced for the product. I sent an email regarding my bewilderment to Amazon and got no response.


```
[18]: # https://stackoverflow.com/questions/16206380/
      ↪python-beautifulsoup-how-to-remove-all-tags-from-an-element
from bs4 import BeautifulSoup

soup = BeautifulSoup(sent_0, 'lxml')
text = soup.get_text()
print(text)
print("="*50)

soup = BeautifulSoup(sent_1000, 'lxml')
text = soup.get_text()
print(text)
print("="*50)

soup = BeautifulSoup(sent_1500, 'lxml')
text = soup.get_text()
print(text)
print("="*50)

soup = BeautifulSoup(sent_4900, 'lxml')
text = soup.get_text()
print(text)
```

This is one of the best children's books ever written but it is a mini version of the book and was not portrayed as one. It is over priced for the product. I sent an email regarding my bewilderment to Amazon and got no response.

=====

The tree and pot which arrived were not the ones pictured. Also, the trunk has several indentions and rust spots from where improper wire was left on the trunk too long. I expected better.

=====

I did my research before deciding to spend \$30+ on a bottle of vanilla, granted a very large one. After reading all the comments, I expected the pleasant aroma of vanilla wafting from the bottle upon opening, but what I got instead was this murky, smokey smell that doesn't even remotely resemble vanilla. There is absolutely no vanilla aroma when I added it to my custards, even with additional amount. Sure, the vanilla specks are there, but what good would they do if they give nothing to the flavor of the dish? I must have gotten a bad bottle or something (is that even possible, for vanilla bean paste to go bad?). I'm quite disappointed, looks like I'll just have to stick with Costco vanilla extract from now on.

=====

I had purchased 48 3 oz. cans of tuna, upon opening some of the tuna I had to throw out 20 cans, because the product was spoiled (dark meat and fowl smell). I purchased this product in the past with no problems.

```
[19]: # https://stackoverflow.com/a/47091490/4084039
import re

def decontracted(phrase):
    # specific
    phrase = re.sub(r"won't", "will not", phrase)
    phrase = re.sub(r"can't", "can not", phrase)

    # general
    phrase = re.sub(r"n't", " not", phrase)
    phrase = re.sub(r"\ 're", " are", phrase)
    phrase = re.sub(r"\ 's", " is", phrase)
    phrase = re.sub(r"\ 'd", " would", phrase)
    phrase = re.sub(r"\ 'll", " will", phrase)
    phrase = re.sub(r"\ 't", " not", phrase)
    phrase = re.sub(r"\ 've", " have", phrase)
    phrase = re.sub(r"\ 'm", " am", phrase)
    return phrase
```

```
[20]: sent_1500 = decontracted(sent_1500)
print(sent_1500)
print("="*50)
```

I did my research before deciding to spend \$30+ on a bottle of vanilla, granted a very large one. After reading all the comments, I expected the pleasant aroma of vanilla wafting from the bottle upon opening, but what I got instead was this murky, smokey smell that does not even remotely resemble vanilla. There is absolutely no vanilla aroma when I added it to my custards, even with additional amount. Sure, the vanilla specks are there, but what good would they do if they give nothing to the flavor of the dish? I must have gotten a bad bottle or something (is that even possible, for vanilla bean paste to go bad?). I am quite disappointed, looks like I will just have to stick with Costco vanilla extract from now on.

=====

```
[21]: #remove words with numbers python:
# https://stackoverflow.com/a/18082370/4084039
sent_0 = re.sub(r"\S*\d\S*", "", sent_0).strip()
print(sent_0)
```

This is one of the best children's books ever written but it is a mini version of the book and was not portrayed as one. It is over priced for the product. I sent an email regarding my bewilderment to Amazon and got no response.

```
[22]: #remove spacial character:
# https://stackoverflow.com/a/5843547/4084039
sent_1500 = re.sub(r'[^A-Za-z0-9]+', ' ', sent_1500)
```

```
print(sent_1500)
```

I did my research before deciding to spend 30 on a bottle of vanilla granted a very large one After reading all the comments I expected the pleasant aroma of vanilla wafting from the bottle upon opening but what I got instead was this murky smokey smell that does not even remotely resemble vanilla There is absolutely no vanilla aroma when I added it to my custards even with additional amount Sure the vanilla specks are there but what good would they do if they give nothing to the flavor of the dish I must have gotten a bad bottle or something is that even possible for vanilla bean paste to go bad I am quite disappointed looks like I will just have to stick with Costco vanilla extract from now on

```
[23]: # https://gist.github.com/sebleier/554280
# we are removing the words from the stop words list: 'no', 'nor', 'not'
# <br /><br /> ==> after the above steps, we are getting "br br"
# we are including them into stop words list
# instead of <br /> if we have <br/> these tags would have been removed in the 1st
→step

stopwords= set(['br', 'the', 'i', 'me', 'my', 'myself', 'we', 'our', 'ours', \
               'ourselves', 'you', "you're", "you've", \
               "you'll", "you'd", 'your', 'yours', 'yourself', 'yourselves', 'he', \
→\
               'him', 'his', 'himself', \
               'she', "she's", 'her', 'hers', 'herself', 'it', "it's", 'its', \
               'itself', 'they', 'them', 'their', \
               'theirs', 'themselves', 'what', 'which', 'who', 'whom', 'this', \
               'that', "that'll", 'these', 'those', \
               'am', 'is', 'are', 'was', 'were', 'be', 'been', 'being', 'have', \
               'has', 'had', 'having', 'do', 'does', \
               'did', 'doing', 'a', 'an', 'the', 'and', 'but', 'if', 'or', \
→'because', \
               'as', 'until', 'while', 'of', \
               'at', 'by', 'for', 'with', 'about', 'against', 'between', 'into', \
               'through', 'during', 'before', 'after', \
               'above', 'below', 'to', 'from', 'up', 'down', 'in', 'out', 'on', \
               'off', 'over', 'under', 'again', 'further', \
               'then', 'once', 'here', 'there', 'when', 'where', 'why', 'how', \
               'all', 'any', 'both', 'each', 'few', 'more', \
               'most', 'other', 'some', 'such', 'only', 'own', 'same', 'so', \
               'than', 'too', 'very', \
               's', 't', 'can', 'will', 'just', 'don', "don't", 'should', \
→"should've", \
               'now', 'd', 'll', 'm', 'o', 're', \
               've', 'y', 'ain', 'aren', "aren't", 'couldn', "couldn't", 'didn', \
               "didn't", 'doesn', "doesn't", 'hadn', \
```

```

        "hadn't", 'hasn', "hasn't", 'haven', "haven't", 'isn', "isn't", \
        → 'ma', \
        'mightn', "mightn't", 'mustn', \
        "mustn't", 'needn', "needn't", 'shan', "shan't", 'shouldn', \
        → "shouldn't", \
        'wasn', "wasn't", 'weren', "weren't", \
        'won', "won't", 'wouldn', "wouldn't"])

```

```

[24]: # Combining all the above students
from tqdm import tqdm
preprocessed_reviews = []
review_score = []
# tqdm is for printing the status bar
for sentence, score in tqdm(final[['Text', 'Score']].values):
    sentence = re.sub(r"http\S+", "", sentence)
    sentence = BeautifulSoup(sentence, 'lxml').get_text()
    sentence = decontracted(sentence)
    sentence = re.sub("\S*\d\S*", "", sentence).strip()
    sentence = re.sub('[^A-Za-z]+', ' ', sentence)
    # https://gist.github.com/sebleier/554280
    sentence = ' '.join(e.lower() for e in sentence.split() \
        if e.lower() not in stopwords)
    preprocessed_reviews.append(sentence.strip())
    review_score.append(score)

```

100%|| 90185/90185 [00:31<00:00, 2848.98it/s]

```

[25]: preprocessed_reviews[1500]

```

```

[25]: 'research deciding spend bottle vanilla granted large one reading comments
expected pleasant aroma vanilla wafting bottle upon opening got instead murky
smokey smell not even remotely resemble vanilla absolutely no vanilla aroma
added custards even additional amount sure vanilla specks good would give
nothing flavor dish must gotten bad bottle something even possible vanilla bean
paste go bad quite disappointed looks like stick costco vanilla extract'

```

```

[26]: len(preprocessed_reviews)

```

```

[26]: 90185

```

[3.2] Preprocessing Review Summary

```

[27]: ## Similarly you can do preprocessing for review summary also.
# Combining all the above students
preprocessed_summary = []
for summary in tqdm(final['Summary'].values):
    summary = re.sub(r"http\S+", "", summary)
    summary = BeautifulSoup(summary, 'lxml').get_text()
    summary = decontracted(summary)
    summary = re.sub("\S*\d\S*", "", summary).strip()

```

```
summary = re.sub('[^A-Za-z0-9]+', ' ', summary) # adding 0-9 in the regex
summary = ' '.join(e.lower() for e in summary.split()\
                    if e.lower() not in stopwords)
preprocessed_summary.append(summary.strip())
```

100%|| 90185/90185 [00:18<00:00, 4910.05it/s]

```
[28]: len(preprocessed_summary)
```

[28]: 90185

```
[29]: preprocessed_text = [str(rev+' '+summ) for rev, summ in \
                        zip(preprocessed_reviews, preprocessed_summary)]
print(preprocessed_text[:5])
```

['one best children books ever written mini version book not portrayed one
 priced product sent email regarding bewilderment amazon got no response awesome
 book poor size', 'give five stars maurice sendak story one star printed edition
 book children older copy book familiar previous softcover version ordered
 granddaughters embarrassed give gift looks puny book size postcard think
 overpriced learned lesson not buying softcover children books next time get used
 copy story great softcover book disappointing', 'dogs loves chicken product
 china wont buying anymore hard find chicken products made usa one isnt bad good
 product wont take chances till know going china imports made china', 'dogs love
 saw pet store tag attached regarding made china satisfied safe dog lover
 delites', 'selected company even though price higher hoping pieces would
 consistent size tuened container filled smaller crum like pieces worse company
 never buy anything company should get crumbs']

```
[30]: # importing train_test_split to split data
from sklearn.model_selection import train_test_split
```

```
[31]: # this is random splitting into train, test and cross validation set
ppText_train, ppText_test, rs_train, rs_test = train_test_split(
    preprocessed_text, review_score,
    test_size=0.30, random_state = 0,
    stratify = review_score)
```

```
[32]: print("Train data length ", len(ppText_train))
print("Test data length ", len(ppText_test))
```

Train data length 63129
 Test data length 27056

```
[33]: ppText_train[:3]
```

```
[33]: ['best sauce boneless chicken wings also great bone wings closest thing favorite
wings great restaurant visit frequently gold fever',
'sauce taste like italian dressing not good one salty hard find chipotle not
```

```
like flavor artificial like blend not well made salty',
'like use energy time time help self get energy not replace poor diet no
exercise mind remember eat healthy get exercise sometimes need little something
something instead ho hum coffee good option lot better soda definitely picks
perks think even better coffee good late afternoon need keep working kind tired
gives energy keep going tastes great not sweet keep one stashed purse
emergencies received free sample energy energy berry good give zip']
```

5 [4] Featurization

5.1 [4.1] BAG OF WORDS

```
[34]: #BoW
fullPath = dir_path+'models/Decision_Trees/'+ 'bow_vectors.pickle'
useOldData = False
count_vect = CountVectorizer(ngram_range=(1,2), min_df=10,
                             max_features=5000) #in scikit-learn
count_vect.fit(ppText_train)
print("some feature names ", count_vect.get_feature_names()[:10])
print('='*50)
if os.path.isfile(fullPath) and useOldData:
    print("Reading vectors from drive..")
    with open(fullPath, 'rb') as f:
        bow_train, bow_test = pickle.load(f)
else:
    bow_train = count_vect.transform(ppText_train)
    bow_test = count_vect.transform(ppText_test)

    # Save the vectors
    with open(fullPath, 'wb') as f:
        pickle.dump((bow_train, bow_test), f)

print("\nShapes After Vectorization ")
print("Train shape ", bow_train.shape, len(rs_train))
print("Test shape  ", bow_test.shape, len(rs_test))
print("Unique words in training : ", bow_train.get_shape()[1])
```

```
some feature names  ['able', 'able find', 'able get', 'absolute', 'absolutely',
'absolutely delicious', 'absolutely love', 'absolutely loves', 'absolutely no',
'absorb']
```

```
=====
```

```
Shapes After Vectorization
Train shape  (63129, 5000) 63129
Test shape   (27056, 5000) 27056
Unique words in training : 5000
```

5.2 [4.2] Bi-Grams and n-Grams.

```
[43]: #bi-gram, tri-gram and n-gram

#removing stop words like "not" should be avoided before building n-grams
# count_vect = CountVectorizer(ngram_range=(1,2))
# please do read the CountVectorizer documentation
#http://scikit-learn.org/stable/modules/generated/
#sklearn.feature_extraction.text.CountVectorizer.html

count_vect_bi = CountVectorizer(ngram_range=(1,2), min_df=10,
                               max_features=5000)
final_bigram_counts = count_vect_bi.fit_transform(preprocessed_text)
print("the type of count vectorizer ",type(final_bigram_counts))
print("the shape of out text BOW vectorizer ",final_bigram_counts.get_shape())
print("the number of unique words including both unigrams and bigrams ",
      final_bigram_counts.get_shape()[1])
```

the type of count vectorizer <class 'scipy.sparse.csr.csr_matrix'>
the shape of out text BOW vectorizer (90185, 5000)
the number of unique words including both unigrams and bigrams 5000

5.3 [4.3] TF-IDF

```
[35]: fullPath = dir_path+'models/Decision_Trees/'+ 'tfIdf_vectors.pickle'
useOldData=True
tf_idf_vect = TfidfVectorizer(ngram_range=(1,2), min_df=10,
                             max_features=5000)

tf_idf_vect.fit(ppText_train)
print("Some sample features(unique words in the training corpus)",
      tf_idf_vect.get_feature_names()[0:10])
print('='*50)
if os.path.isfile(fullPath) and useOldData:
    print("Reading vectors from drive..")
    with open(fullPath, 'rb') as f:
        tfIdf_train, tfIdf_test = pickle.load(f)

else:
    tfIdf_train = tf_idf_vect.transform(ppText_train)
    tfIdf_test = tf_idf_vect.transform(ppText_test)

    # Save the vectors
    with open(fullPath, 'wb') as f:
        pickle.dump((tfIdf_train, tfIdf_test), f)

print("\nShapes After Vectorization ")
print("Train shape ", tfIdf_train.shape, len(rs_train))
```

```
print("Test shape ", tfIdf_test.shape, len(rs_test))
print("Unique words in training : ", tfIdf_train.get_shape()[1])
```

Some sample features(unique words in the training corpus) ['able', 'able find', 'able get', 'absolute', 'absolutely', 'absolutely delicious', 'absolutely love', 'absolutely loves', 'absolutely no', 'absorb']

=====

Reading vectors from drive..

Shapes After Vectorization

Train shape (63129, 5000) 63129

Test shape (27056, 5000) 27056

Unique words in training : 5000

5.4 [4.4] Word2Vec

```
[62]: # Train your own Word2Vec model using your own text corpus
i=0

# list of sentences divided into train and test set
train_sentences = [sentence.split() for sentence in ppText_train]
test_sentences = [sentence.split() for sentence in ppText_test]
```

```
[63]: # Using Google News Word2Vectors

# in this project we are using a pretrained model by google
# its 3.3G file, once you load this into your memory
# it occupies ~9Gb, so please do this step only if you have >12G of ram
# we will provide a pickle file wich contains a dict ,
# and it contains all our courpus words as keys and model[word] as values
# To use this code-snippet, download "GoogleNews-vectors-negative300.bin"
# from https://drive.google.com/file/d/0B7XkCwpI5KDYNlNUTTlSS21pQmM/edit
# it's 1.9GB in size.

# http://kavita-ganesan.com/gensim-word2vec-tutorial-starter-code/#.W17SRFAzZPY
# you can comment this whole cell
# or change these variable according to your need

is_your_ram_gt_16g=False
want_to_use_google_w2v = False
want_to_train_w2v = True
fullPath = dir_path+'models/Decision_Trees/'+ 'w2V_model.pickle'
useOldData=True

if want_to_train_w2v:
```



```

# min_count = 5 considers only words that occurred at least 5 times
if os.path.isfile(fullPath) and useOldData:
    with open(fullPath, 'rb') as f:
        w2v_model = pickle.load(f)
else:
    w2v_model=Word2Vec(train_sentences,min_count=5,size=128, workers=4)
    # Save word2Vec model
    with open(fullPath,'wb') as f:
        pickle.dump(w2v_model, f)
print(w2v_model.wv.most_similar('great'))
print('='*50)
print(w2v_model.wv.most_similar('worst'))

elif want_to_use_google_w2v and is_your_ram_gt_16g:
    if os.path.isfile('GoogleNews-vectors-negative300.bin'):
        w2v_model=KeyedVectors.load_word2vec_format(
            'GoogleNews-vectors-negative300.bin', binary=True)
        print(w2v_model.wv.most_similar('great'))
        print(w2v_model.wv.most_similar('worst'))
    else:
        print("you don't have google's word2vec file, keep \
            want_to_train_w2v = True, to train your own w2v ")

```

```

[('excellent', 0.7690900564193726), ('awesome', 0.7675778269767761),
 ('fantastic', 0.7632836699485779), ('terrific', 0.7358640432357788),
 ('wonderful', 0.7027043104171753), ('good', 0.6942657232284546), ('fabulous',
 0.6401124596595764), ('amazing', 0.6338384747505188), ('nice',
 0.6248286366462708), ('perfect', 0.6173133850097656)]
=====
[('nastiest', 0.8176918625831604), ('greatest', 0.6959682106971741), ('weakest',
 0.6874932646751404), ('best', 0.657362163066864), ('disgusting',
 0.6410381197929382), ('grossest', 0.628602147102356), ('weirdest',
 0.577441930770874), ('vile', 0.5741907954216003), ('terrible',
 0.5731832981109619), ('smoothest', 0.5719156861305237)]

```

```

[64]: w2v_words = list(w2v_model.wv.vocab)
print("number of words that occurred minimum 5 times ",len(w2v_words))
print("sample words ", w2v_words[0:50])

```

```

number of words that occurred minimum 5 times 16053
sample words ['best', 'sauce', 'boneless', 'chicken', 'wings', 'also', 'great',
'bone', 'closest', 'thing', 'favorite', 'restaurant', 'visit', 'frequently',
'gold', 'fever', 'taste', 'like', 'italian', 'dressing', 'not', 'good', 'one',
'salty', 'hard', 'find', 'chipotle', 'flavor', 'artificial', 'blend', 'well',
'made', 'use', 'energy', 'time', 'help', 'self', 'get', 'replace', 'poor',
'diet', 'no', 'exercise', 'mind', 'remember', 'eat', 'healthy', 'sometimes',
'need', 'little']

```

5.5 [4.4.1] Converting text into vectors using Avg W2V, TFIDF-W2V

[4.4.1.1] Avg W2v

```
[65]: fullPath = dir_path+'models/Decision_Trees/'+ 'avg_W2V.pickle'
      useOldData=True

      # average Word2Vec

      avgW2V_train, avgW2V_test = [], []
      c = 0

      if os.path.isfile(fullPath) and useOldData:
          print("Vectors loaded from drive..")
          with open(fullPath, 'rb') as f:
              avgW2V_train, avgW2V_test = pickle.load(f)

      else:
          for i, sent_set in enumerate([train_sentences, test_sentences]):
              for sent in sent_set:
                  c += 1
                  if c % 1000==0:
                      print("Progress : {:3d} % ".format(
                          int(c/len(preprocessed_reviews)*100)),
                          end='\r')
                  sent_vec = np.zeros(128)
                  cnt_words = 0
                  for word in sent:
                      if word in w2v_words:
                          vec = w2v_model.wv[word]
                          sent_vec += vec
                          cnt_words += 1
                  if cnt_words != 0:
                      sent_vec /= cnt_words
                  if i==0:
                      avgW2V_train.append(sent_vec)
                  if i==1:
                      avgW2V_test.append(sent_vec)

          print("Saving to drive..")
          with open(fullPath, 'wb') as f:
              pickle.dump((avgW2V_train, avgW2V_test), f)

      print("Dims of Train : ({}, {})".format(len(avgW2V_train),
                                              len(avgW2V_train[0])))
      print("Dims of Test : ({}, {})".format(len(avgW2V_test),
                                              len(avgW2V_test[0])))
```

Vectors loaded from drive..

Dims of Train : (63129, 128)

Dims of Test : (27056, 128)

[4.4.1.2] TFIDF weighted W2v

```
[66]: # S = ["abc def pqr", "def def def abc", "pqr pqr def"]
model = TfidfVectorizer(min_df=5)
tf_idf_matrix = model.fit_transform(ppText_train)
# we are converting a dictionary with word as a key, and the idf as a value
dictionary = dict(zip(model.get_feature_names(), list(model.idf_)))

[67]: # TF-IDF weighted Word2Vec
tfidf_feat = model.get_feature_names() # tfidf words/col-names
# final_tf_idf is the sparse matrix with row= sentence,
# col=word and cell_val = tfidf

fullPath = dir_path+'models/Decision_Trees/'+ 'tfIdf_avg_W2V.pickle'
useOldData=True

tfidf_avgW2V_train, tfidf_avgW2V_test = [], []
c = 0

if os.path.isfile(fullPath) and useOldData:
    print("Vectors loaded from drive..")
    with open(fullPath, 'rb') as f:
        tfidf_avgW2V_train, tfidf_avgW2V_test = pickle.load(f)
else:
    for i, sent_set in enumerate([train_sentences, test_sentences]):
        for sent in sent_set:
            c += 1
            if c % 1000==0:
                print("Progress : {:3d} % ".format(
                    int(c/len(preprocessed_reviews)*100)),
                    end='\r')
            sent_vec = np.zeros(128)
            weight_sum = 0
            for word in sent:
                if word in w2v_words and word in tfidf_feat:
                    vec = w2v_model.wv[word]
                    tf_idf = dictionary[word]*(sent.count(word)/len(sent))
                    sent_vec += (vec * tf_idf)
                    weight_sum += tf_idf
            if weight_sum != 0:
                sent_vec /= weight_sum
            if i==0:
                tfidf_avgW2V_train.append(sent_vec)
            if i==1:
```

```

        tfidf_avgW2V_test.append(sent_vec)

    print("Saving to drive..")
    with open(fullPath, 'wb') as f:
        pickle.dump((tfidf_avgW2V_train, tfidf_avgW2V_test), f)

print("Dims of Train : ({}, {})".format(len(tfidf_avgW2V_train),
                                         len(tfidf_avgW2V_train[0])))
print("Dims of Test : ({}, {})".format(len(tfidf_avgW2V_test),
                                         len(tfidf_avgW2V_test[0])))

```

Vectors loaded from drive..
 Dims of Train : (63129, 128)
 Dims of Test : (27056, 128)

6 [5] Assignment 8: Decision Trees

Apply Decision Trees on these feature sets

SET 1: Review text, preprocessed one converted into vectors using (BOW)

SET 2: Review text, preprocessed one converted into vectors using (TFIDF)

SET 3: Review text, preprocessed one converted into vectors using (AVG W2v)

SET 4: Review text, preprocessed one converted into vectors using (TFIDF W2v)

The hyper parameter tuning (best depth in range [1, 5, 10, 50, 100, 500, 100], and the best min_samples_split in range [5, 10, 100, 500])

Find the best hyper parameter which will give the maximum AUC value

Find the best hyper parameter using k-fold cross validation or simple cross validation data

Use gridsearch cv or randomsearch cv or you can also write your own for loops to do this task of hyperparameter tuning

Graphviz

Visualize your decision tree with Graphviz. It helps you to understand how a decision is made

Since feature names are not obtained from word2vec related models, visualize only BOW & TFIDF

Make sure to print the words in each node of the decision tree instead of printing its index

Just for visualization purpose, limit max_depth to 2 or 3 and either embed the generated image

Feature importance

Find the top 20 important features from both feature sets Set 1 and


```

<br>
<li><strong>Feature engineering</strong>
  <ul>
<li>To increase the performance of your model, you can also experiment with with feature engineering
    <ul>
      <li>Taking length of reviews as another feature.</li>
      <li>Considering some features from review summary as well.</li>
    </ul>
  </ul>
</li>
<br>
<li><strong>Representation of results</strong>
  <ul>
<li>You need to plot the performance of model both on train data and cross validation data for
    <img src='train_cv_auc.JPG' width=300px></li>
<li>Once after you found the best hyper parameter, you need to train your model with it, and find
    <img src='train_test_auc.JPG' width=300px></li>
<li>Along with plotting ROC curve, you need to print the <a href='https://www.appliedaicourse.com/roc-curve/'>ROC curve</a>
    <img src='confusion_matrix.png' width=300px></li>
  </ul>
</li>
<br>
<li><strong>Conclusion</strong>
  <ul>
<li>You need to summarize the results at the end of the notebook, summarize it in the table for
    <img src='summary.JPG' width=400px>
  </li>
</ul>

```

Note: Data Leakage

1. There will be an issue of data-leakage if you vectorize the entire data and then split it into train/cv/test.
2. To avoid the issue of data-leakage, make sure to split your data first and then vectorize it.
3. While vectorizing your data, apply the method `fit_transform()` on your train data, and apply the method `transform()` on cv/test data.
4. For more details please go through this link.

7 Applying Decision Trees

```

[36]: from sklearn.tree import DecisionTreeClassifier, export_graphviz
      from sklearn.calibration import CalibratedClassifierCV
      from sklearn.metrics import roc_auc_score, roc_curve, auc \
          , accuracy_score, classification_report
      import matplotlib.pyplot as plt
      from sklearn.model_selection import GridSearchCV
      import seaborn as sns

```

```
from IPython.display import Image
import pydotplus
```

```
[37]: def DT_Classifier(X_train, y_train):
    max_depth = np.array([1, 5, 10, 50, 100, 500, 100])
    min_samples_split = np.array([5, 10, 100, 500])
    params_dict = [{'max_depth': max_depth,
                    'min_samples_split': min_samples_split}]
    dt_optimal = DecisionTreeClassifier(random_state=1)

    grid = GridSearchCV(estimator=dt_optimal,
                        param_grid=params_dict,
                        scoring='roc_auc', n_jobs=4, cv=5,
                        return_train_score=True)

    grid_result = grid.fit(X_train, y_train)
    train_auc = grid_result.cv_results_['mean_train_score']
    train_auc_std = grid_result.cv_results_['std_train_score']
    cv_auc = grid_result.cv_results_['mean_test_score']
    cv_auc_std = grid_result.cv_results_['std_test_score']

    print("Optimal Parameters : ", grid_result.best_estimator_.get_params())

    plt.figure(figsize=(10.0, 8.0))
    ax = sns.heatmap(train_auc.reshape(len(max_depth), len(min_samples_split)),
                    annot=True, square=False, cmap="Oranges",
                    xticklabels=["mss = "+str(mss) for mss in min_samples_split],
                    yticklabels=["md = "+str(md) for md in max_depth])

    plt.title("Training scores for max_depth and min_sample_split")
    plt.show()
    print('')

    plt.figure(figsize=(10.0, 8.0))
    ax = sns.heatmap(cv_auc.reshape(len(max_depth), len(min_samples_split)),
                    annot=True, square=False, cmap="Blues",
                    xticklabels=["mss = "+str(mss) for mss in min_samples_split],
                    yticklabels=["md = "+str(md) for md in max_depth])
    plt.title("Cross-val scores for max_depth and min_sample_split")
    plt.show()
```

```
[38]: def DT_Classifier_Test(minSampleSplit, maxDepth, X_train, y_train, X_test,
    ↪y_test):
    # Setting up the classifier using optimal params

    dt_optimal = DecisionTreeClassifier(max_depth=maxDepth,
                                        min_samples_split=minSampleSplit,
                                        random_state=1)
```

```

# we have to fit the SGDClassifier so that we can access the coef_
dt_optimal.fit(X_train, y_train)

# Prediction on training and test set using optimal classifier
logProb_train = dt_optimal.predict_proba(X_train)
logProb_test = dt_optimal.predict_proba(X_test)
pred_train = np.argmax(logProb_train, axis =1)
pred_test = np.argmax(logProb_test, axis =1)
print("Using max depth value for tree - ", maxDepth)
print("Using min sample split for tree - ", minSampleSplit)
print("Train accuracy for optimal Decision Tree ", round(
    accuracy_score(y_train, pred_train)*100, 2))
print("Test accuracy for optimal Decision Tree ", round(
    accuracy_score(y_test, pred_test) * 100, 2))

# ROC-AUC on train & test data
train_fpr, train_tpr, thresholds = roc_curve(y_train,
    logProb_train[:, 1], pos_label=1)
test_fpr, test_tpr, thresholds = roc_curve(y_test,
    logProb_test[:, 1], pos_label=1)

# Draw ROC curve
plt.plot(train_fpr, train_tpr, label="Train AUC = "+str(round(
    auc(train_fpr, train_tpr), 2)))
auc_score = round(auc(test_fpr, test_tpr), 2)
plt.plot(test_fpr, test_tpr, label="Test AUC = "+str(auc_score))
plt.legend()
plt.xlabel("False Pos Rate")
plt.ylabel("True Pos Rate")
plt.title("ROC Curve of Train and Test")
plt.show()

return dt_optimal, pred_train, pred_test, auc_score

```

```


[39]: def draw_Confusion_Matrix(actual, predicted):
    class_label = ["negative", "positive"]
    conf_matrix = confusion_matrix(actual, predicted)
    df_cm = pd.DataFrame(conf_matrix, index = class_label, columns =
→class_label)
    hm = sns.heatmap(df_cm, annot = True, fmt = "d")
    plt.xlabel("Predicted Label")
    plt.ylabel("True Label")
    plt.show()


```

7.1 [5.1] Applying Decision Trees on BOW, SET 1

```
[103]: # Please write all the code with proper documentation
DT_Classifier(bow_train, rs_train)
```


Optimal Parameters : {'class_weight': None, 'criterion': 'gini', 'max_depth': 50, 'max_features': None, 'max_leaf_nodes': None, 'min_impurity_decrease': 0.0, 'min_impurity_split': None, 'min_samples_leaf': 1, 'min_samples_split': 500, 'min_weight_fraction_leaf': 0.0, 'presort': False, 'random_state': 1, 'splitter': 'best'}





```
[40]: # Please write all the code with proper documentation
maxDepth, minSampleSplit = 50, 500
classifier, pred_train, pred_test, auc_score = DT_Classifier_Test(
    minSampleSplit, maxDepth,
    bow_train, rs_train,
    bow_test, rs_test)
```


Using max depth value for tree - 50
 Using min sample split for tree - 500
 Train accuracy for optimal Decision Tree 84.71
 Test accuracy for optimal Decision Tree 80.85




```
[41]: print("Training Confusion Matrix")
draw_Confusion_Matrix(rs_train, pred_train)
print('\n\n')

print("Test Confusion Matrix")
draw_Confusion_Matrix(rs_test, pred_test)
table.add_row(["bow", "Decision Tree",
               "maxDepth: {0} minSampleSplit: {1}".format(
                   maxDepth, minSampleSplit), auc_score])
```

Training Confusion Matrix



Test Confusion Matrix



```
[42]: # Classification report
print(classification_report(rs_test, pred_test))
```

	precision	recall	f1-score	support
0	0.78	0.80	0.79	12163
1	0.83	0.82	0.82	14893
accuracy			0.81	27056
macro avg	0.81	0.81	0.81	27056
weighted avg	0.81	0.81	0.81	27056

7.1.1 [5.1.1] Top 20 important features from SET 1

```
[41]: # Please write all the code with proper documentation
# Top 20 important features
print("Top 20 important features are : ")
print(np.take(count_vect.get_feature_names(),
              classifier.feature_importances_.argsort()[::-21:-1]))
```

Top 20 important features are :

```
['not' 'great' 'best' 'delicious' 'good' 'love' 'perfect' 'disappointed'
 'loves' 'excellent' 'not good' 'bad' 'favorite' 'tasty' 'terrible'
 'awful' 'nice' 'horrible' 'worst' 'not great']
```

7.1.2 [5.1.2] Graphviz visualization of Decision Tree on BOW, SET 1

```
[122]: # https://chrisalbon.com/machine\_learning/trees\_and\_forests/visualize\_a\_decision\_tree/


# Create DOT data
dot_data = export_graphviz(classifier, out_file=None,
                           max_depth=3, filled=True, node_ids=True,
                           feature_names=count_vect.get_feature_names(),
                           class_names=['Negative', 'Positive'])

# Replacing indexes with actual feature names
feature_names = count_vect.get_feature_names()
for strIdx, idx in re.findall(r'(node #[\d]+\)\)', dot_data):
    dot_data = dot_data.replace(strIdx, feature_names[int(idx)].title()+'\')

# Draw graph
graph = pydotplus.graph_from_dot_data(dot_data)
```

```
# Show graph
Image(graph.create_png())
```


[122]:




7.2 [5.2] Applying Decision Trees on TFIDE, SET 2

```
[123]: # Please write all the code with proper documentation
DT_Classifier(tfIdf_train, rs_train)
```


```
Optimal Parameters : {'class_weight': None, 'criterion': 'gini', 'max_depth':
50, 'max_features': None, 'max_leaf_nodes': None, 'min_impurity_decrease': 0.0,
'min_impurity_split': None, 'min_samples_leaf': 1, 'min_samples_split': 500,
'min_weight_fraction_leaf': 0.0, 'presort': False, 'random_state': 1,
'splitter': 'best'}
```





```
[42]: # Please write all the code with proper documentation
maxDepth, minSampleSplit = 50, 500
classifier, pred_train, pred_test, auc_score = DT_Classifier_Test(
    minSampleSplit, maxDepth,
    tfIdf_train, rs_train,
    tfIdf_test, rs_test)
```


Using max depth value for tree - 50
 Using min sample split for tree - 500
 Train accuracy for optimal Decision Tree 85.44
 Test accuracy for optimal Decision Tree 80.39




```
[125]: print("Training Confusion Matrix")
draw_Confusion_Matrix(rs_train, pred_train)
print('\n\n')

print("Test Confusion Matrix")
draw_Confusion_Matrix(rs_test, pred_test)
table.add_row(["tf-Idf", "Decision Tree",
               "maxDepth: {0} minSampleSplit: {1}".format(
                   maxDepth, minSampleSplit), auc_score])
```

Training Confusion Matrix



Test Confusion Matrix



```
[128]: # Classification report
print(classification_report(rs_test, pred_test))
```

	precision	recall	f1-score	support
0	0.78	0.78	0.78	12163
1	0.82	0.82	0.82	14893
accuracy			0.80	27056
macro avg	0.80	0.80	0.80	27056
weighted avg	0.80	0.80	0.80	27056

7.2.1 [5.2.1] Top 20 important features from SET 2

```
[43]: # Please write all the code with proper documentation
# Top 20 important features
print("Top 20 important features are : ")
print(np.take(tf_idf_vect.get_feature_names(),
              classifier.feature_importances_.argsort()[::-21:-1]))
```

Top 20 important features are :

```
['not' 'great' 'best' 'delicious' 'love' 'good' 'loves' 'excellent'
 'disappointed' 'perfect' 'bad' 'favorite' 'not good' 'tasty' 'nice'
 'terrible' 'not great' 'worst' 'horrible' 'awful']
```

7.2.2 [5.2.2] Graphviz visualization of Decision Tree on TFIDF, SET 2

```
[135]: # Please write all the code with proper documentation
# https://chrisalbon.com/machine_learning/trees_and_forests/
# visualize_a_decision_tree/


# Create DOT data
dot_data = export_graphviz(classifier, out_file=None,
                           max_depth=3, filled=True, node_ids=True,
                           feature_names=tf_idf_vect.get_feature_names(),
                           class_names=['Negative', 'Positive'])

# Replacing indexes with actual feature names
feature_names = tf_idf_vect.get_feature_names()
for strIdx, idx in re.findall(r'(node #[\d]+\)\s)', dot_data):
    dot_data = dot_data.replace(strIdx, feature_names[int(idx)].title()+'\\')

# Draw graph
graph = pydotplus.graph_from_dot_data(dot_data)
```

```
# Show graph
Image(graph.create_png())
```


[135]:




7.3 [5.3] Applying Decision Trees on AVG W2V, SET 3

```
[136]: # Please write all the code with proper documentation
DT_Classifier(avgW2V_train, rs_train)
```


```
Optimal Parameters : {'class_weight': None, 'criterion': 'gini', 'max_depth': 10, 'max_features': None, 'max_leaf_nodes': None, 'min_impurity_decrease': 0.0, 'min_impurity_split': None, 'min_samples_leaf': 1, 'min_samples_split': 500, 'min_weight_fraction_leaf': 0.0, 'presort': False, 'random_state': 1, 'splitter': 'best'}
```





```
[137]: # Please write all the code with proper documentation
maxDepth, minSampleSplit = 10, 500
classifier, pred_train, pred_test, auc_score = DT_Classifier_Test(
    minSampleSplit, maxDepth,
    avgW2V_train, rs_train,
    avgW2V_test, rs_test)
```


```
Using max depth value for tree - 10
Using min sample split for tree - 500
Train accuracy for optimal Decision Tree 81.53
Test accuracy for optimal Decision Tree 79.47
```




```
[138]: print("Training Confusion Matrix")
draw_Confusion_Matrix(rs_train, pred_train)
print('\n\n')

print("Test Confusion Matrix")
draw_Confusion_Matrix(rs_test, pred_test)
table.add_row(["Avg W2V", "Decision Tree",
               "maxDepth: {0} minSampleSplit: {1}".format(
                   maxDepth, minSampleSplit), auc_score])
```

Training Confusion Matrix



Test Confusion Matrix




```
[139]: # Classification report
print(classification_report(rs_test, pred_test))
```


	precision	recall	f1-score	support
0	0.77	0.78	0.77	12163
1	0.82	0.81	0.81	14893
accuracy			0.79	27056
macro avg	0.79	0.79	0.79	27056
weighted avg	0.79	0.79	0.79	27056

7.4 [5.4] Applying Decision Trees on TFIDF W2V, SET 4

```
[140]: # Please write all the code with proper documentation
DT_Classifier(tfidf_avgW2V_train, rs_train)
```

Optimal Parameters : {'class_weight': None, 'criterion': 'gini', 'max_depth': 10, 'max_features': None, 'max_leaf_nodes': None, 'min_impurity_decrease': 0.0, 'min_impurity_split': None, 'min_samples_leaf': 1, 'min_samples_split': 100, 'min_weight_fraction_leaf': 0.0, 'presort': False, 'random_state': 1, 'splitter': 'best'}






[]:

```
[141]: # Please write all the code with proper documentation
maxDepth, minSampleSplit = 10, 100
classifier, pred_train, pred_test, auc_score = DT_Classifier_Test(
    minSampleSplit, maxDepth,
    tfidf_avgW2V_train, rs_train,
    tfidf_avgW2V_test, rs_test)
```


Using max depth value for tree - 10
 Using min sample split for tree - 100
 Train accuracy for optimal Decision Tree 83.51
 Test accuracy for optimal Decision Tree 77.57




```
[142]: print("Training Confusion Matrix")
draw_Confusion_Matrix(rs_train, pred_train)
print('\n\n')

print("Test Confusion Matrix")
draw_Confusion_Matrix(rs_test, pred_test)
table.add_row(["tfIdf-Avg W2V", "Decision Tree",
               "maxDepth: {0} minSampleSplit: {1}".format(
                   maxDepth, minSampleSplit), auc_score])
```

Training Confusion Matrix



Test Confusion Matrix



```
[143]: # Classification report
print(classification_report(rs_test, pred_test))
```

	precision	recall	f1-score	support
0	0.75	0.75	0.75	12163
1	0.79	0.80	0.80	14893
accuracy			0.78	27056
macro avg	0.77	0.77	0.77	27056
weighted avg	0.78	0.78	0.78	27056

8 [6] Conclusions

```
[144]: # Please compare all your models using Prettytable library
print(table)
```

Vectorizer	Model	Hyperparameters	AUC Score
bow	Decision Tree	maxDepth: 50 minSampleSplit: 500	0.88
tf-Idf	Decision Tree	maxDepth: 50 minSampleSplit: 500	0.87
Avg W2V	Decision Tree	maxDepth: 10 minSampleSplit: 500	0.88
tfIdf-Avg W2V	Decision Tree	maxDepth: 10 minSampleSplit: 100	0.85

- Our immediate observation is that decision tree classifier is far low in performance (for AUC) compared to kNN, LR, SVM for this dataset
- The tree classifier is almost same performance wise for all the vectors (bow, tf-Idf, average word2Vec and tf-Idf weighted word2Vec), but the word2Vec will have an edge as it achieves the same AUC score for a much lower tree depth compared to bow and tf-Idf
- We also observe that the features(especially the negative classes) are not as much clear and interpretable compared to the ones we got using logistic

```
regression.
```

```
[ ]:
```