

WTPR8

Problem Statement

Design a login page with entries for name, mobile number email id and login button-Use struts

Directly structure

```
WTPR8/
├── src/com/wtpr8/
│   ├── action/LoginAction.java
│   └── form/LoginForm.java
├── WEB-INF/
│   ├── classes/           # Compiled .class files
│   ├── lib/               # struts-core JARs
│   ├── struts-config.xml
│   └── web.xml
├── login.jsp              # Login form
├── success.jsp            # Success page after login
└── style.css              # CSS styling
```

LoginAction.java

```
package com.wtpr8.action;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import com.wtpr8.form.LoginForm;
import org.apache.struts.action.*;

public class LoginAction extends Action {
    public ActionForward execute(ActionMapping mapping, ActionForm form,
        HttpServletRequest request, HttpServletResponse response) throws Exception {
        LoginForm loginForm = (LoginForm) form;
        String name = loginForm.getName();
        String mobile = loginForm.getMobile();
        String email = loginForm.getEmail();
        request.setAttribute("user", name);
        return mapping.findForward("success");
    }
}
```

LoginForm.java

```
package com.wtpr8.form;
import org.apache.struts.action.ActionForm;

public class LoginForm extends ActionForm {
    private String name;
    private String mobile;
    private String email;
    public String getName() {
        return name;
    }
    public void setName(String name) {
        this.name = name;
    }
    public String getMobile() {
        return mobile;
    }
    public void setMobile(String mobile) {
        this.mobile = mobile;
    }
    public String getEmail() {
        return email;
    }
    public void setEmail(String email) {
        this.email = email;
    }
}
```

struts-config.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE struts-config PUBLIC
    "-//Apache Software Foundation//DTD Struts Configuration 1.3//EN"
    "http://struts.apache.org/dtds/struts-config_1_3.dtd">
<struts-config>
    <form-beans>
        <form-bean name="loginForm" type="com.wtpr8.form.LoginForm"/>
    </form-beans>
    <action-mappings>
        <action path="/login"
            type="com.wtpr8.action.LoginAction"
            name="loginForm"
            scope="request"
            input="/login.jsp">
            <forward name="success" path="/success.jsp"/>
        </action>
    </action-mappings>
</struts-config>
```

web.xml

```
<web-app>
    <display-name>WTPR8 Login App</display-name>
    <servlet>
        <servlet-name>action</servlet-name>
        <servlet-class>org.apache.struts.action.ActionServlet</servlet-class>
        <init-param>
            <param-name>config</param-name>
            <param-value>/WEB-INF/struts-config.xml</param-value>
        </init-param>
        <load-on-startup>1</load-on-startup>
    </servlet>
    <servlet-mapping>
        <servlet-name>action</servlet-name>
        <url-pattern>*.do</url-pattern>
    </servlet-mapping>
    <welcome-file-list>
        <welcome-file>login.jsp</welcome-file>
    </welcome-file-list>
</web-app>
```

login.jsp

```
<%@ taglib uri="http://struts.apache.org/tags-html" prefix="html" %>
<!DOCTYPE html>
<html>
<head>
    <title>Login Page</title>
    <link rel="stylesheet" href="style.css">
</head>
<body><div class="container login-container">
    <h2>User Login</h2>
    <html:form action="/login">
        <div class="form-group">
            <label for="name">Name:</label>
            <html:text property="name" styleId="name"/>
        </div>
        <div class="form-group">
            <label for="mobile">Mobile Number:</label>
            <html:text property="mobile" styleId="mobile"/>
        </div>
        <div class="form-group">
            <label for="email">Email ID:</label>
            <html:text property="email" styleId="email"/>
        </div>
        <html:submit value="Login" styleClass="submit-btn"/>
    </html:form> </div>
</body>
</html>
```

success.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8" pageEncoding="UTF-8"%>
<%@ taglib uri="http://struts.apache.org/tags-html" prefix="html" %>
<%@ page language="java" %>
<!DOCTYPE html>
<html>
<head>
    <meta charset="UTF-8">
    <title>Success</title>
    <link rel="stylesheet" href="style.css">
</head>
<body>
    <div class="container success-container">
        <div class="success-icon">✓</div>
        <h2>Welcome, <span class="user-name">${user}</span>!</h2>
        <p>You have successfully logged in.</p>
    </div>
</body>
</html>
```

