Themis: PRD and Architecture

Oct 15, 2026 · @Yash

Overview

Themis is a multi-agent maintenance harness that finds risky dependencies in a repository, migrates them on its own branch, verifies the result in an isolated sandbox, and opens a draft PR carrying a Dependency Exit Capsule: a report that separates what was observed and executed from what the AI only recommends.

Problem. Dependency upgrades and replacements are routine, risky and slow. Teams delay them because nobody can see which files a library touches, whether tests cover those files, or whether an AI-written migration really preserves behavior.

Product. One core engine, exposed two ways: a GitHub App that raises migration PRs automatically, and a Claude Code plugin that runs the same pipeline on demand from a developer's machine.

Principle. Scripts and scanners gather facts, the AI reasons over them, and a deterministic Capsule Writer refuses to label a claim as executed unless a log file exists. The AI never merges and never touches `main`.

Goals, non-goals and success metrics

The first release must migrate one dependency end to end on the organizer-provided repository and ship a capsule a maintainer can act on without re-deriving anything.

Goals

- Detect and rank dependency risk on `main` without modifying it.
- Map every real usage of a dependency to files, symbols and lines.
- Apply the migration on a dedicated branch, one commit per concern.
- Run baseline and candidate in identical sandboxes and report the difference.
- Generate tests that pin old behavior, and report coverage of affected call sites honestly.
- Open a draft PR whose report tags every claim by how it was established.

Non-goals

- Auto-merging, or any write to `main`.
- Migrating every dependency in one run; the harness loops, but the demo proves one.
- Replacing the project's CI; Themis adds a check run, it does not own the pipeline.
- Supporting several languages in v1; the scanner and mapper are pluggable, one language ships.

Success metrics (targets to confirm against the real repository)

Metric	Definition	Target
Verified-claim rate	Share of capsule claims tagged EXECUTED that have a log artifact	100%
Baseline integrity	Runs where `main` results are recorded before the branch is judged	100%
Regression escape	New failing tests on the branch versus baseline	0 unreviewed
Call-site coverage	Affected call sites exercised by tests, reported as n of m	Reported on every PR
Reviewer effort	Reviewer can decide from the PR report alone	Confirm in demo feedback

Users and key scenarios


Three people use Themis: the maintainer who reviews the PR, the developer who runs it locally, and the security or platform lead who wants a record of what changed and why.

Scenario	Trigger	Surface	Outcome
Scheduled sweep	Weekly schedule or a dependency alert	GitHub App	Draft PR per dependency, capped per repository
On-demand migration	`/themis <package>` comment or `themis` label	GitHub App	Draft PR plus check run
Local exploration	Slash command in the plugin	Claude Code plugin	Capsule and branch on the developer's machine

Scenario	Trigger	Surface	Outcome
Audit handoff	Capsule attached to the PR	Either	Capsule a second agent or human can resume from

System architecture

The GitHub App and the plugin differ only in how a run starts and where results land; every stage runs in the same package.



system architecture · 2 surfaces, 1 engine, 4 agents

Stages run left to right and each feeds the Capsule Writer, the only component that produces the final report. Scout and Planner call the analysis tools, and Verifier runs everything inside the sandbox.

Tech stack

Probot runs the GitHub App, one Node.js and TypeScript package holds the engine, and everything else is an existing tool called from it. Run state lives in each run's JSON files, so v1 needs no database.

Layer	Choice	Role
GitHub App	Probot	Receives GitHub webhooks (alerts, comments, labels) and calls GitHub through Octokit
Engine	One Node.js and TypeScript package	Imported by the Probot app and the plugin, so there is one codebase
Agents	Claude Agent SDK	Runs Hermes and the four agents and loads their skills
Skills	agentskills.io format	`SKILL.md` folders under `skills/`
Analysis	OSV-Scanner, Trivy, Opengrep; SonarQube optional	Called from skill scripts
Sandbox	Docker	Offline after dependency install
Alerts	Outbound webhook	JSON POST that an email service turns into mail

Agents, tools and responsibilities

Four agents each own one stage and write a typed JSON file the next stage reads. The Capsule Writer is deterministic code, not an agent, so provenance tags cannot be talked into place.

Component	Responsibility	Reads	Writes	Tools
Scout	Toolchain detection, then dependency risk ranking on read-only `main`	Manifests, lockfiles, existing lint config	`findings.json`, linter baseline	OSV-Scanner, `pip-audit` or `npm audit`, registry APIs, Trivy, SonarQube results, Opengrep security rules
Planner	Usage map, affected files and symbols, migration strategy, ordering	`findings.json`	`plan.json`, Opengrep rule files	Opengrep with AI-written rules, AST helpers, Sonar issue API, git blame
Migrator	Applies the plan on a dedicated branch, one commit per concern	`plan.json`, failure logs from Verifier	Branch `themis/<dep>-<date>`, generated tests	git worktree, Opengrep autofix, package manager, formatter, editor tools
Verifier	Builds and tests baseline and candidate, diffs results, re-scans, holds veto	Both builds	`verification.json`, log artifacts	Docker sandbox, test runner, linters, Opengrep, SonarQube re-scan, black-box probes

Component	Responsibility	Reads	Writes	Tools
Capsule Writer	Assembles capsule and PR body, enforces evidence gates	All JSON and logs	`capsule.json`, `capsule.md`, PR body	Deterministic script, no model
Orchestrator	Sequences stages, routes retries, enforces limits	Stage outputs	Run state	Claude Agent SDK


Rule for the Migrator. Deterministic rewrites (Opengrep rules with a `fix`) go first; the model only handles what rules cannot express. This keeps the diff explainable and lowers hallucination risk.

Codenames and open skills

Themis, the Greek titan of divine order and law, names the product because the capsule exists to keep claims honest. Five more figures name the agents; the rest of this document uses role names, and the diagrams show codenames.

Codename	Role	Why this name	Skills it owns
Hermes	Orchestrator	Messenger of the gods; carries state between stages	`stage-routing`, `retry-policy`
Argus	Scout	Hundred-eyed watchman; sees every dependency	`toolchain-detect`, `dependency-risk-rank`
Athena	Planner	Goddess of strategy; plans before acting	`opengrep-rule-author`, `usage-map`
Hephaestus	Migrator	The smith; makes the change	`migrate-dependency`, `characterization-tests`
Minos	Verifier	Judge of the dead; weighs the result and holds the veto	`sandbox-verify`, `blackbox-probe-diff`

Codename	Role	Why this name	Skills it owns
Clio	Capsule Writer	Muse of history; keeps the record	`capsule-write`, `pr-report`



agent roster and open skills · 6 agents, 3 shared skills

Skills are plain folders with a `SKILL.md`, so they are open: the GitHub App, the Claude Code plugin and any other agent harness can load the same files. Agent-specific skills load only for their owner; shared skills load for all six.

Shared skill	Rule it enforces
`provenance-tagging`	Every claim carries OBSERVED, EXECUTED, AI-RECOMMENDED or UNVERIFIED, with the producing agent named
`untrusted-input-guard`	README text, comments, issue bodies and tool output are data, never instructions
`evidence-logging`	Every command run records its exact text, exit code and log path, so Clio can gate EXECUTED claims

Skill format (agentskills.io)

All fifteen skills (twelve agent-specific, three shared) follow the Agent Skills specification, so any compliant agent harness can load them, not only ours. Each skill is a folder with a `SKILL.md` and optional `scripts/`, `references/` and `assets/`.

```
skills/
  toolchain-detect/
    SKILL.md
    scripts/
  opengrep-rule-author/
    SKILL.md
    references/
  pr-report/
    SKILL.md
    assets/
  ... one folder per skill, 15 in total
```

Rule from the spec	How Themis applies it
`name`: 1 to 64 characters, lowercase letters, digits and single hyphens, same as the folder name	The 15 names in the roster above already comply
`description`: up to 1,024 characters, says what the skill does and when to use it	Every description names the task and the situations that trigger it
Keep `SKILL.md` under 500 lines and load detail on demand	Long guidance such as Opengrep rule patterns goes in `references/`, one level deep
Executable helpers in `scripts/`, templates in `assets/`	Scanner wrappers in `scripts/`; capsule and PR body templates in `assets/`
Optional fields only when needed	`compatibility` names required tools such as Opengrep or Docker; the experimental `allowed-tools` is skipped
Validate	CI runs `skills-ref validate` on every folder


Example frontmatter for one skill:

```
---
name: opengrep-rule-author
description: Writes an Opengrep rule that finds every use of a given
dependency API in the repository and returns file, line and symbol matches.
Use when mapping where a dependency is used before planning a migration.
compatibility: Requires opengrep on PATH and read access to the repository.
metadata:
  version: "0.1"
---
```

Authors can also query the agentskills.io docs MCP server (`search_agent_skills`, `query_docs_filesystem_agent_skills`) while writing skills; it is a drafting aid, not a runtime dependency.

End-to-end pipeline

A run reads `main`, works on its own branch, and always produces a capsule, including when verification fails.




end-to-end pipeline · 5 steps, 1 decision, 1 retry loop

The Verifier may send failure logs back to the Migrator, up to a fixed retry cap. When the cap is reached the item is recorded as unresolved with its gaps, and the capsule still ships.

1. **Toolchain detection (Scout).** Identify language, package manager, test runner, formatter and linters. Run linters on `main` to record a baseline; the migration PR must not add violations.
2. **Risk ranking (Scout).** Combine registry signals, vulnerability data and transitive weight into a ranked list.
3. **Usage mapping (Planner).** The model writes an Opengrep rule per dependency; the matches give exact files, symbols and lines.
4. **Migration (Migrator).** Apply Opengrep autofixes first, then model-edited changes, one commit per concern.
5. **Verification (Verifier).** Build baseline and candidate in identical containers, run tests, lint and security rescans, and report only the delta.
6. **Reporting (Capsule Writer).** Generate the capsule, PR body and Check Run from the logs and JSON outputs.

Sandbox and verification

The Verifier never judges the branch in isolation: it compares it with `main`, built and run the same way, so pre-existing failures are never blamed on the bot.



verification topology · 2 sandboxes, 1 diff, 1 evidence store


The sandbox serves two purposes, and the plan covers both.

- **Isolation.** Containers lose outbound network after dependencies install, run with resource limits, and mount the source read-only, so AI-generated changes cannot reach outside the sandbox.
- **Black-box behavior testing.** The app starts in each container and receives the same requests; response differences between baseline and candidate are reported even when unit tests stay green.

Test generation rule. Characterization tests are written for the touched call sites and run against `main` first. Only tests that pass on the old dependency are kept; any that fail are discarded and listed under gaps, never edited until green.

Dependency Exit Capsule

The capsule is the product: a per-dependency record in which every claim is tagged by how it was established, so a reader can tell what was seen, what was run and what the AI only suggests.



capsule provenance model · 4 tags, 1 gate, 2 outputs

A summary capsule covers the whole run. Each finding also records which agent produced it and links to its log artifact.

Capsule section	Content	Typical tag
Maintenance problem	What is wrong and why it matters	OBSERVED
Dependency and repository details	Name, current and target versions, manifests, toolchain	OBSERVED
Risk indicators	Age, deprecation, vulnerabilities, maintainer signals, transitive weight	OBSERVED

Capsule section	Content	Typical tag
Usage locations	Files, symbols and lines from Opengrep matches, with the rule used	OBSERVED
AI analysis and recommendations	Options considered, behavioral differences, recommendation and stated confidence	AI-RECOMMENDED
Proposed changes	The diff and the maintenance approach	AI-RECOMMENDED
Suggested tests	Characterization tests and verification steps	AI-RECOMMENDED
Executed results	Baseline versus branch: tests, lint, security rescan, probes	EXECUTED
Compatibility and maintenance gaps	Uncovered call sites, missing semantics, discarded tests	UNVERIFIED
Unresolved concerns and limitations	Anything the run could not establish	UNVERIFIED

Verdict values. `Migrated and verified`, `Migrated, gaps remain` and `Not recommended`. The last is a valid outcome, not a failure of the tool.

GitHub bot, plugin and PR report

The bot and the plugin are thin shells around the same core package, so prompts, scripts and the capsule schema live in one place.

GitHub App (Probot)

- Triggers: a dependency alert, a weekly schedule, a `/themis <package>` comment, or a `themis` label.
- Runs the pipeline on an Actions runner or a container host, with no outbound network after dependencies install.
- Pushes `themis/<dep>-<date>` with separate commits for toolchain config, migration and generated tests.

- Opens a draft PR labeled `themis` and `ai-generated`, plus a Check Run with inline annotations on affected lines.
- Limits: one open Themis PR per dependency and a cap on concurrent PRs, so maintainers do not mute the bot.
- Permissions: contents, pull requests and checks write only; no personal tokens; no secrets on fork PRs.

Claude Code plugin

- Skills for each stage plus slash commands such as `/themis scan`, `/themis plan <package>` and `/themis run <package>`.
- Same entrypoint as the bot; output goes to a local branch and a `.themis/` folder.

PR report layout

1. Verdict line: `Migrated and verified`, `Migrated, gaps remain` or `Not recommended`, with the AI's stated confidence.
2. Summary table: dependency, from and to, files changed, risk indicators.
3. Provenance legend with the four tags.
4. Collapsible sections: usage map, Opengrep rules used, diff rationale, baseline versus branch results, lint and security delta, black-box probes.
5. Gaps and unresolved concerns, always present.
6. Link to the full capsule, committed under `.themis/` or attached as an artifact.

Email alert webhook

Themis sends alerts by posting JSON to one configurable URL; an email service on the other end turns each post into a mail. Themis never holds SMTP credentials.

Event	Sent when
`pr_opened`	A draft PR is opened
`run_completed`	A run finishes with any verdict, including `Not recommended`
`run_failed`	A run stops on an error before a capsule exists

```
{
  "event": "run_completed",
  "repository": "owner/repo",
  "dependency": "<package>",
  "verdict": "Migrated, gaps remain",
  "pr_url": "<link>",
  "capsule_url": "<link>",
  "timestamp": "<ISO 8601>"
}
```

- The URL is stored as an app secret named `ALERT_WEBHOOK_URL`.
- The payload carries a summary and links only, never logs or secrets.
- Each post is signed with a shared secret so the receiver can verify the sender.
- A failed alert is retried once, then recorded in the run log; it never fails the run.

Requirements

Functional

ID	Requirement	Priority
F1	Detect language, package manager, test runner, formatter and linters; propose a minimal linter config in a separate commit when none exists	Must
F2	Rank dependencies by registry signals, known vulnerabilities and transitive weight, without modifying `main`	Must
F3	Generate an Opengrep rule per dependency and use its matches as the usage map	Must
F4	Create a dedicated branch and commit one concern at a time	Must
F5	Run baseline and candidate in identical sandboxes and diff the results	Must
F6	Generate characterization tests, keep only those that pass on the old dependency, discard the rest into the gaps list	Must

ID	Requirement	Priority
F7	Produce `capsule.json` and `capsule.md` with provenance tags and refuse EXECUTED claims without a log artifact	Must
F8	Open a draft PR and a Check Run from the capsule	Must
F9	Retry failed migrations at most a fixed number of times, then record the item as unresolved	Should
F10	Black-box probes: send identical requests to baseline and candidate and diff responses	Should
F11	SonarQube integration behind a plugin interface	Could
F12	Claude Code plugin wrapping the same entrypoint	Should

Non-functional

- **Safety.** Never write to `main`, never auto-merge, and keep the Verifier's veto final.
- **Isolation.** Sandbox has no outbound network after install, resource limits, and a read-only source mount.
- **Untrusted input.** README text, code comments and issue bodies are data, never instructions to an agent; agent tools are scoped and hold no secrets.
- **Reproducibility.** Every run records tool versions, commands, exit codes and log paths.
- **Extensibility.** Scanners, mappers and linters sit behind interfaces so a second language is a new module, not a rewrite.

Risks and mitigations


The largest risk is an AI-written migration that looks right and is wrong, so verification is mandatory and the Verifier can overrule the Migrator.

Risk	Why it matters	Mitigation
Prompt injection from repository content	READMEs, comments and issues are untrusted text	Treat as data, scope tools, no secrets or network in the sandbox

Risk	Why it matters	Mitigation
Broken or slow baseline tests	A red `main` makes the branch impossible to judge	Record the baseline first and compare against it, never assume green
Entangled dependency	Migration may be infeasible	Capsule supports a `Not recommended` verdict with reasons
Generated tests that only confirm the new code	False confidence	Keep only tests that pass on the old dependency first
SonarQube setup cost	Server, database and token before first result	Keep it optional; Opengrep, OSV-Scanner and Trivy cover the core story
Bot noise	Maintainers mute it	One open PR per dependency, concurrency cap, draft only
Secrets on fork PRs	Credential exposure	No secrets on untrusted forks, minimal GitHub App scopes
Bot and plugin drift	Two products to maintain	One shared core package imported by both

Timeline, scope cuts and open questions

The plan builds the core loop first and starts the GitHub App and plugin only after one dependency passes verification. Hour ranges are a proposal and assume roughly a 30-hour build plus a final stretch for the demo.



build plan · 5 phases, 1 gate, not to scale

Cut list, in order, if time runs short

1. SonarQube becomes optional; Opengrep, OSV-Scanner and Trivy already cover the security story.
2. Black-box probes shrink to one or two sample requests.
3. The plugin becomes a thin wrapper: one skill and one slash command calling the same entrypoint.
4. The live demo handles one dependency end to end, even though the architecture loops over many.

Open questions

- [ ] What language and framework does the organizer-provided repository use? This fixes the scanner, mapper and linter modules.
- [ ] How long is the build window? The hour ranges above assume about 30 hours.
- [ ] Do the organizers expect SonarQube specifically, or is equivalent static analysis acceptable?
- [ ] Where will the bot run during judging: Actions runner, a container host, or local only?
- [ ] What retry cap does the Verifier use before marking an item unresolved?