

SCAN REPORT

Aurionpro Payment Solutions Pte. Ltd.

DETAILED PCI REPORT

Audited on Thu Mar 16 2023 17:19:42

CONFIDENTIAL

ASV Scan Report Vulnerability Details

Part 1. Scan Information			
Scan Customer Company:	Aurionpro Payment Solutions Pte. Ltd.	ASV Company:	Clone Systems, Inc.
Date scan was completed:	Thu Mar 16 2023 17:19:42	Scan expiration date:	Wed Jun 14 2023 17:19:42

Part 2. Vulnerability Details

Component	Detected Open Ports, Services/ Protocols	Vulnerability	Severity Level	CVE Number	CVSS Score	Compliance Status	
						Pass	Fail
18.142.9.39	general/tcp	This check tries to determine whether a remote host is up (alive). Several methods are used for this depending on configuration of this check. Whether a host is up can be detected in 3 different ways: - A ICMP message is sent to the host and a response is taken as alive sign. - An ARP request is sent and a response is taken as alive sign. - A number of typical TCP services (namely the 20 top ports of nmap) are tried and their presence is taken as alive sign. None of the methods is failsafe. It depends on network and/or host configurations whether they succeed or not. Both, false positives and false negatives can occur. Therefore the methods are configurable. If you select to not mark unreachable hosts as dead, no alive detections are executed and the host is assumed to be available for scanning. In case it is configured that hosts are never marked as dead, this can cause considerable timeouts and therefore a long scan duration in case the hosts are in fact not available. The available methods might fail for the following reasons: - ICMP: This might be disabled for a environment and would then cause false negatives as hosts are believed to be dead that actually are alive. In contrast it is also possible that a Firewall between the scanner and the target host is answering to the ICMP message and thus hosts are believed to be alive that actually are dead. - TCP ping: Similar to the ICMP case a Firewall between the scanner and the target might answer to the sent probes and thus hosts are believed to be alive that actually are dead.	low	NOCVE	0.0	☒	☐
	Vulnerability Detection Result: *1 (Click here to access the vulnerability details) Detection Reliability: Remote banner check of applications that offer patch level in version. Many proprietary products do so.		Details: Ping Host (NVT: 1.3.6.1.4.1.25623.1.0.100315) Version used: 2019-05-15T10:07:01+0000 References: CVSS v2 Vector: (AV:N/AC:L/Au:N/C:N/I:N/A:N) CVE: NOCVE BID: NOBID CERT: XREF: NOXREF				

Component	Detected Open Ports, Services/ Protocols	Vulnerability	Severity Level	CVE Number	CVSS Score	Compliance Status	
						Pass	Fail
18.141.50.187	general/tcp	This check tries to determine whether a remote host is up (alive). Several methods are used for this depending on configuration of this check. Whether a host is up can be detected in 3 different ways: - A ICMP message is sent to the host and a response is taken as alive sign. - An ARP request is sent and a response is taken as alive sign. - A number of typical TCP services (namely the 20 top ports of nmap) are tried and their presence is taken as alive sign. None of the methods is failsafe. It depends on network and/or host configurations whether they succeed or not. Both, false positives and false negatives can occur. Therefore the methods are configurable. If you select to not mark unreachable hosts as dead, no alive detections are executed and the host is assumed to be available for scanning. In case it is configured that hosts are never marked as dead, this can cause considerable timeouts and therefore a long scan duration in case the hosts are in fact not available. The available methods might fail for the following reasons: - ICMP: This might be disabled for a environment and would then cause false negatives as hosts are believed to be dead that actually are alive. In contrast it is also possible that a Firewall between the scanner and the target host is answering to the ICMP message and thus hosts are believed to be alive that actually are dead. - TCP ping: Similar to the ICMP case a Firewall between the scanner and the target might answer to the sent probes and thus hosts are believed to be alive that actually are dead.	low	NOCVE	0.0	☒	☐
	Vulnerability Detection Result: *2 (Click here to access the vulnerability details) Detection Reliability: Remote banner check of applications that offer patch level in version. Many proprietary products do so.		Details: Ping Host (NVT: 1.3.6.1.4.1.25623.1.0.100315) Version used: 2019-05-15T10:07:01+0000 References: CVSS v2 Vector: (AV:N/AC:L/Au:N/C:N/I:N/A:N) CVE: NOCVE BID: NOBID CERT: XREF: NOXREF				

Component	Detected Open Ports, Services/ Protocols	Vulnerability	Severity Level	CVE Number	CVSS Score	Compliance Status	
						Pass	Fail
54.169.47.206	general/tcp	This check tries to determine whether a remote host is up (alive). Several methods are used for this depending on configuration of this check. Whether a host is up can be detected in 3 different ways: - A ICMP message is sent to the host and a response is taken as alive sign. - An ARP request is sent and a response is taken as alive sign. - A number of typical TCP services (namely the 20 top ports of nmap) are tried and their presence is taken as alive sign. None of the methods is failsafe. It depends on network and/or host configurations whether they succeed or not. Both, false positives and false negatives can occur. Therefore the methods are configurable. If you select to not mark unreachable hosts as dead, no alive detections are executed and the host is assumed to be available for scanning. In case it is configured that hosts are never marked as dead, this can cause considerable timeouts and therefore a long scan duration in case the hosts are in fact not available. The available methods might fail for the following reasons: - ICMP: This might be disabled for a environment and would then cause false negatives as hosts are believed to be dead that actually are alive. In contrast it is also possible that a Firewall between the scanner and the target host is answering to the ICMP message and thus hosts are believed to be alive that actually are dead. - TCP ping: Similar to the ICMP case a Firewall between the scanner and the target might answer to the sent probes and thus hosts are believed to be alive that actually are dead.	low	NOCVE	0.0	☒	☐
	Vulnerability Detection Result: *3 (Click here to access the vulnerability details) Detection Reliability: Remote banner check of applications that offer patch level in version. Many proprietary products do so.		Details: Ping Host (NVT: 1.3.6.1.4.1.25623.1.0.100315) Version used: 2019-05-15T10:07:01+0000 References: CVSS v2 Vector: (AV:N/AC:L/Au:N/C:N/I:N/A:N) CVE: NOCVE BID: NOBID CERT: XREF: NOXREF				

Component	Detected Open Ports, Services/ Protocols	Vulnerability	Severity Level	CVE Number	CVSS Score	Compliance Status	
						Pass	Fail
52.74.76.35	general/tcp	This check tries to determine whether a remote host is up (alive). Several methods are used for this depending on configuration of this check. Whether a host is up can be detected in 3 different ways: - A ICMP message is sent to the host and a response is taken as alive sign. - An ARP request is sent and a response is taken as alive sign. - A number of typical TCP services (namely the 20 top ports of nmap) are tried and their presence is taken as alive sign. None of the methods is failsafe. It depends on network and/or host configurations whether they succeed or not. Both, false positives and false negatives can occur. Therefore the methods are configurable. If you select to not mark unreachable hosts as dead, no alive detections are executed and the host is assumed to be available for scanning. In case it is configured that hosts are never marked as dead, this can cause considerable timeouts and therefore a long scan duration in case the hosts are in fact not available. The available methods might fail for the following reasons: - ICMP: This might be disabled for a environment and would then cause false negatives as hosts are believed to be dead that actually are alive. In contrast it is also possible that a Firewall between the scanner and the target host is answering to the ICMP message and thus hosts are believed to be alive that actually are dead. - TCP ping: Similar to the ICMP case a Firewall between the scanner and the target might answer to the sent probes and thus hosts are believed to be alive that actually are dead.	low	NOCVE	0.0	☒	☐
Vulnerability Detection Result: Host is alive (successful TCP SYN service ping), Method: nmap nmap command: nmap --reason -sP -T3 -PS21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,587,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,311,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000 52.74.76.35 Starting Nmap 7.91 (https://nmap.org) at 2023-03-16 11:58 utc Nmap scan report for ec2-52-74-76-35.ap-southeast-1.compute.amazonaws.com (52.74.76.35) Host is up, received syn-ack ttl 106 (0.23s latency). Nmap done: 1 IP address (1 host up) scanned in 31.72 seconds Detection Reliability: Remote banner check of applications that offer patch level in version. Many proprietary products do so.			Details: Ping Host (NVT: 1.3.6.1.4.1.25623.1.0.100315) Version used: 2019-05-15T10:07:01+0000 References: CVSS v2 Vector: (AV:N/AC:L/Au:N/C:N/I:N/A:N) CVE: NOCVE BID: NOBID CERT: XREF: NOXREF				

***1 Vulnerability Detection Result for Host 18.142.9.39 () - general/tcp**

The remote host 18.142.9.39 was considered as dead. Used/configured checks:

Host is down (failed ARP/ICMP ping), Method: nmap

nmap command: nmap --reason -sP -T3 -PE 18.142.9.39

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 2.34 seconds

Host is down (failed TCP service ping), Method: nmap

nmap command: nmap --reason -sP -T3

-PA21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,5
87,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,3
11,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,
990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1
049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1
494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2
107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3
703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5
432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7
485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9
999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000
18.142.9.39

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 43.36 seconds

Host is down (failed TCP SYN service ping), Method: nmap

nmap command: nmap --reason -sP -T3

-PS21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,5
87,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,3
11,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,
990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1
049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1
494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2
107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3
703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5
432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7
485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9
999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000
18.142.9.39

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 43.34 seconds

*2 Vulnerability Detection Result for Host 18.141.50.187 () - general/tcp

The remote host 18.141.50.187 was considered as dead. Used/configured checks:

Host is down (failed ARP/ICMP ping), Method: nmap

nmap command: nmap --reason -sP -T3 -PE 18.141.50.187

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 2.34 seconds

Host is down (failed TCP service ping), Method: nmap

nmap command: nmap --reason -sP -T3

-PA21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,5
87,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,3
11,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,
990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1
049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1
494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2
107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3
703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5
432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7
485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9
999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000
18.141.50.187

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 43.36 seconds

Host is down (failed TCP SYN service ping), Method: nmap

nmap command: nmap --reason -sP -T3

-PS21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,5
87,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,3
11,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,
990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1
049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1
494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2
107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3
703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5
432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7
485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9
999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000
18.141.50.187

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 43.44 seconds

*3 Vulnerability Detection Result for Host 54.169.47.206 () - general/tcp

The remote host 54.169.47.206 was considered as dead. Used/configured checks:

Host is down (failed ARP/ICMP ping), Method: nmap

nmap command: nmap --reason -sP -T3 -PE 54.169.47.206

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 2.33 seconds

Host is down (failed TCP service ping), Method: nmap

nmap command: nmap --reason -sP -T3

-PA21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,5
87,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,3
11,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,
990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1
049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1
494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2
107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3
703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5
432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7
485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9
999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000
54.169.47.206

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 43.36 seconds

Host is down (failed TCP SYN service ping), Method: nmap

nmap command: nmap --reason -sP -T3

-PS21,22,23,25,53,80,110,111,135,139,143,443,445,993,995,1723,3306,3389,5900,8080,137,5
87,3128,8081,1,3,7,9,13,17,19,26,37,79,81,82,88,100,106,113,119,144,179,199,254,255,280,3
11,389,427,444,464,465,497,513,515,543,544,548,554,593,625,631,636,646,787,808,873,902,
990,1000,1022,1024,1025,1026,1027,1028,1029,1030,1031,1032,1033,1035,1041,1044,1048,1
049,1050,1053,1054,1056,1058,1059,1064,1065,1066,1069,1071,1074,1080,1110,1234,1433,1
494,1521,1720,1755,1761,1801,1900,1935,1998,2000,2001,2002,2003,2005,2049,2103,2105,2
107,2121,2161,2301,2383,2401,2601,2717,2869,2967,3000,3001,3002,3003,3268,3689,3690,3
703,3986,4000,4001,4045,4899,5000,5001,5003,5009,5050,5051,5060,5101,5120,5190,5357,5
432,5555,5631,5666,5800,5901,6000,6001,6002,6004,6112,6646,6666,6868,7000,7070,7475,7
485,7937,7938,8000,8002,8008,8009,8010,8031,8443,8453,8888,9000,9001,9090,9100,9102,9
999,10000,10001,10010,32768,32771,49152,49153,49154,49155,49156,49157,50000
54.169.47.206

Starting Nmap 7.91 (<https://nmap.org>) at 2023-03-16 11:58 utc

Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn

Nmap done: 1 IP address (0 hosts up) scanned in 43.37 seconds