



Configuration of Jenkins

Introduction

Jenkins is a **powerful automation server** used for **Continuous Integration (CI)** and **Continuous Deployment (CD)**.

- **How do you configure Jenkins after installation?**
- **What are the key settings required for Jenkins?**
- **How can you secure Jenkins for production use?**

This guide provides a **step-by-step approach to configuring Jenkins** after installation.

Section 1: Learn

Why Configure Jenkins?

- **Ensures Jenkins is secure and optimized** for development workflows.
- **Allows integration with other tools** like Git, Docker, AWS, and Kubernetes.
- **Improves performance and reliability** by setting up system configurations.

Key Areas of Jenkins Configuration

Configuration Area	Purpose
Global Security	Sets user roles and access permissions



Configuration Area	Purpose
Jenkins URL	Defines how users access Jenkins
System Configuration	Manages Jenkins behavior and settings
Plugin Management	Adds integrations with external tools
Email Notifications	Sends automated build reports
Backup and Restore	Ensures data safety and recovery

Interesting Fact

Jenkins has **over 1,500+ plugins** that allow seamless integration with **cloud platforms, databases, and DevOps tools**.

Section 2: Practice

1. Configuring Global Security in Jenkins

Step 1: Open Security Settings

1. Login to **Jenkins Dashboard**.
2. Click **Manage Jenkins** → **Configure Global Security**.



Step 2: Enable Authentication

1. Select **"Jenkins Own User Database"** under **Security Realm**.
2. Check **"Allow users to sign up"**.
3. Click **Save**.

Step 3: Set Role-Based Access Control (RBAC)

1. Install **Role-Based Authorization Strategy Plugin**.
2. Go to **Manage Jenkins → Manage and Assign Roles**.
3. Define roles like **Admin, Developer, Tester** and assign permissions.

Why is this useful?

- Prevents unauthorized access and improves security.
-

2. Configuring Jenkins URL

1. Click **Manage Jenkins → Configure System**.
2. Scroll down to **Jenkins Location**.
3. Set Jenkins URL to:

`http://your-server-ip:8080`

2. Click **Save**.

Why is this important?

- Ensures users and plugins connect properly to Jenkins.
-

3. Installing and Managing Plugins

Step 1: Open Plugin Manager

1. Click **Manage Jenkins → Manage Plugins**.
2. Go to the **Available Plugins** tab.



Step 2: Install Essential Plugins

- Git Plugin – Enables Git integration.
- Pipeline Plugin – Enables Jenkins Pipelines.
- Email Extension Plugin – Sends build notifications.
- Role-Based Authorization Plugin – Manages user roles.

Click Install and Restart Jenkins.

Why is this useful?

- Plugins extend Jenkins functionality for different use cases.
-

4. Configuring Email Notifications

Step 1: Set Up SMTP Server

1. Click Manage Jenkins → Configure System.
2. Scroll down to E-mail Notification.
3. Set SMTP Server:

`smtp.gmail.com`

2. Click Advanced and enter credentials:
 - SMTP Username: Your email ID
 - SMTP Password: Your app password (if using Gmail)

Step 2: Test Email Notification

1. Enter a test email address.
2. Click Test Configuration.

Why is this useful?

- Sends automated build failure notifications.
-



5. Setting Up Jenkins Backup

Step 1: Backup Jenkins Data Manually

```
sudo tar -czf /backup/jenkins_backup.tar.gz /var/lib/jenkins/
```

Step 2: Automate Daily Backups

1. Create a backup script:

```
nano /usr/local/bin/jenkins_backup.sh
```

2. Add the following script:

```
#!/bin/bash

BACKUP_DIR="/backup/jenkins_backup_$(date +%F)"

sudo systemctl stop jenkins

sudo cp -r /var/lib/jenkins $BACKUP_DIR

tar -czf $BACKUP_DIR.tar.gz $BACKUP_DIR

sudo systemctl start jenkins
```

3. Schedule the script in **crontab**:

```
crontab -e
```

4. Add:

```
0 2 * * * /usr/local/bin/jenkins_backup.sh
```

Why is this useful?

- Prevents data loss in case of system failure.
-



Section 3: Know More

Frequently Asked Questions

1. Where is Jenkins data stored?
 - In `/var/lib/jenkins/` on Linux and `C:\ProgramData\Jenkins` on Windows.
2. How do I reset the Jenkins admin password?
 - Delete the `initialAdminPassword` file and restart Jenkins:

```
sudo rm /var/lib/jenkins/secrets/initialAdminPassword  
sudo systemctl restart jenkins
```

3. How do I change Jenkins' default port?

- Edit Jenkins configuration file:

```
sudo nano /etc/default/jenkins
```

- Change `HTTP_PORT=8080` to another port, e.g., `9090`, and restart Jenkins:

```
sudo systemctl restart jenkins
```

4. What happens if a plugin update breaks Jenkins?

- Disable the faulty plugin by running:

```
sudo rm -rf /var/lib/jenkins/plugins/plugin-name*  
sudo systemctl restart jenkins
```

5. Where can I learn more about Jenkins configurations?

- Visit [Jenkins Documentation](#).
-



Conclusion

Jenkins configuration is essential for security, performance, and integration with DevOps tools.

Start by setting up security, managing plugins, configuring email alerts, and enabling backups, and soon you'll be optimizing Jenkins workflows like a pro!