INTERNAL SPECIFICATION FOR **CERAMIC FLOOR TILES(Monocottura)**

Sr. No	CHARACTERISTICS	Swimming Pool Tile 12.0X24.5x0.9 cm		Floor Tiles 15.0x15.0x0.9 cm	
1	Nominal size **(mm)**	120.0x245.0x9.0 mm		150.0x150.0x9.0 mm	
2	Work size **(mm)**	120.5.0x245.5X9.0		150.5 x 150.5X9.0	
		ISO 13006	**SCC. spec.**	**ISO 13006**	**SCC. spec.**
3.1	Size variation from work Size **(%)**	± 0.60	± 0.60	± 0.60	± 0.60
	In **mm** L W	± 1.47 ± 0.90	± 1.47 ± 0.90	± 0.90	± 0.90
3.2	Size range in **mm**	119.6-121.4 244.0-247.0	119.6-121.4 244.0-247.0	149.6-151.4	149.6-151.4
3.3	Size code 01	-	119.6-120.0 244.1-245.0	-	149.6-150.0
	Size code 00 **(Normal)**	-	120.1-121.0 245.1-246.0	-	150.1-151.0
	Size code 02	-	121.1-121.4 246.1-247.0	-	151.1-151.4
4	Thickness deviation **mm**	± 5.0	± 5.0	± 5.0	± 5.0
5	Thickness Range mm	8.55 - 9.45		8.55 - 9.45	
6	Centre Curvature	mm	mm.	mm	mm
6.1	a) Convex **(+)**	+ 1.37	+ 0.80	+ 1.06	+ 0.60
6.2	b) Concave **(-)**	- 1.37	- 0.40	- 1.06	- 0.30
7	Warpage	± 1.37	± 0.60	± 1.06	± 0.60
8	Edge Curvature				
8.1	a) Convex **(+)**	+ 1.23	+ 0.60	+ 0.75	+ 0.40
8.2	b) Concave **(-)**	- 1.23	- 0.40	- 0.75	- 0.30
9	Max deviation from Straightness (**mm)**	± 1.23	± 0.60	± 0.75	± 0.40
10	Max deviation from Rectangularity (**mm)**	± 1.23	± 0.80	± 0.75	± 0.60
11	Water Absorption **(%)**	3 - 6	3 - 6	3 – 6	3 - 6
12	Coefficient to Linear thermal expansion **($x10^{-6}K^{-1}$)**	-	≤ 9	-	≤ 9
13	Resistance to surface abrasion **(Class)**	Manufacturer to state class	2 to 5	Manufacturer to state class	2 to 5
14	Breaking strength **(N)**	≥ 1000	≥ 1100	≥ 1000	≥ 1100
15	Modulus of Rupture (N/mm^2)	Min 22	Min 22	Min 22	Min 22
16	Crazing resistance **(5bar/2 hr cycle)**	Required	Resistant	Required	Resistant
17	Scratch resistance **(Moh's Scale)**	-	Min .6	-	Min. 6(Floor)
18	Staining resistance **(Min.Class)**	3	3	3	3
19	Chemical resistance to Acids and alkalis **(Min.Class)**	Required if agreed	B	Required if agreed	B
20	Resistance to household Chemicals **(Min.Class)**	B	B	B	B