Internal Specification for Glazed Rectified Porcelain tiles.

Sr#	Characteristics / Size	20x120X1.0 cm	
1	Nominal Size in mm	200.0x1200.0x10	
2	Work size in mm	196.0x1200.0x10	
	Standard	ISO 13006	SCC
3	Max Length & width mm		195.9 - 196.4 1199.9 – 1200.4
4	Max deviation in diagonal mm		0.8
5	Thickness deviation %	± 5.0	± 5.0
5.1	Thickness Range mm		9.5 – 10.5
6	Centre curvature	mm	mm
6.1	a) Convex +	+ 1.80	+ 1.80
6.2	b) Concave-	- 1.80	- 0.80
7	Warpage mm	± 1.80	± 1.80
8	Edge curvature mm		
8.1	a) Convex +	+ 1.80	+ 1.60
8.2	b) Concave-	- 1.80	- 0.80
9	Max deviation from straightness mm	± 0.80	± 0.50
10	Max deviation from rectangularity mm	± 1.50	± 1.50
11	Group	B1a	B1a
12	Water absorption %	≤0.5	≤0.5
13	Breaking strength N	≥1300	≥1300
14	Modulus of rupture N/mm^2	≥35	≥35
15	Resistance to surface abrasion class	Manufacturer to state	3 - 5
16	Coefficient of linear thermal expansion ($x10^{-6}K^{-1}$)	-	≤ 9
17.1	Scratch resistance Moh's scale (Glossy)	-	≥ 3
17.2	Scratch resistance Moh's scale (Matt)	-	≥ 6
18	Resistance to thermal shock	Required	Resistant
19	Crazing resistance (5bar / 2hr cycle)	Required	Resistant
20	Frost resistance	Required	Resistant
21	Staining resistance G (min class)	3	3
22	Chemical resistance to acid & alkalis (min Class)	Required if agreed	B
23	Color resistance to UV light	-	No change in color
24	Resistance to household chemicals (minimum class)	B	B