Internal Specification for Glazed, Rectified Porcelain tiles.

Sr#	Characteristics / Size	30x60X0.9 cm	
1	Nominal Size in mm	300.0x600.0x09	
2	Work size in mm	300.0x600.0x09	
	Standard	ISO 13006	SCC
3	Max Length & width mm	-	299.9 – 300.4 599.9 – 600.4
4	Max deviation in diagonal mm	-	0.5
5	Thickness deviation %	± 5.0	± 5.0
5.1	Thickness Range mm	-	8.5 – 9.5
6	Centre curvature	mm	mm
6.1	a) Convex +	+ 1.80	+ 1.40
6.2	b) Concave-	- 0.80	- 0.50
7	Warpage mm	± 1.80	± 1.40
8	Edge curvature mm		
8.1	a) Convex +	+ 1.40	+1.0
8.2	b) Concave-	- 0.60	- 0.40
9	Max deviation from straightness mm	± 0.80	± 0.50
10	Max deviation from rectangularity mm	± 1.50	± 1.20
11	Group	B1a	B1a
12	Water absorption %	≤ 0.5	≤ 0.5
13	Breaking strength (N)	≥ 1300	≥ 1400
14	Modulus of rupture N/mm^2	≥ 35	≥ 35
15	Resistance to surface abrasion class	Manufacturer to state	3 - 5
16	Coefficient of linear thermal expansion ($x10^{-6}K^{-1}$)	-	≥ 3
17.1	Scratch resistance Moh's scale (Glossy)	-	≥ 6
17.2	Scratch resistance Moh's scale (Matt)	-	≤ 9
18	Resistance to thermal shock	Required	Resistant
19	Crazing resistance (5bar / 2hr cycle)	Required	Resistant
20	Staining resistance G (min class)	Required	Resistant
21	Frost Resistance	3	3
22	Chemical resistance to acid & alkalis (min.Class)	Required if agreed	B
23	Color resistance to UV light	-	No change in color
24	Resistance to household chemicals (minimum class)	B	B