

Tribhuvan University  
**Institute of Engineering**  
Pulchowk Campus



**Lab Report on :**  
CONVOLUTION OF SIGNALS

**Submitted By:**  
Saugat Kafley (075BCT099)

**Submitted To:**  
**Ganesh Gautam**  
Department of Electronics and Computer Engineering

**Submission Date:**  
August 24 , 2022


## DSAP Lab2 Convolution of signals

a) Convolution of  $x = [1.2 \ 2.3 \ 4.6 \ -5 \ -11.6]$  and  $h = [2 \ 4 \ 1.7 \ 2.9]$ ;

**Code :**

```
x = [1.2 2.3 4.6 -5 -11.6];  
h = [2 4 1.7 2.9];  
y = conv(x,h);  
subplot(3,1,1);  
stem(x);  
xlabel("x");  
title('075bct099');  
subplot(3,1,2);  
stem(h);  
xlabel("h");  
title("");  
subplot(3,1,3);  
stem(y);  
xlabel("Convolution");  
title('Convolution ');
```

**Output :**



b) Convolution of signals


$x = \{1 \text{ for } 0 \leq n \leq 5 ; \text{otherwise } 0\}$  and  
 $H = \{0.1 \text{ for } -1 \leq n \leq 3 ; \text{otherwise } 0\}$

**Code :**

```
clc;
n= -10:1:10;
% Empty vector x and h
x = [];
h = [];
for(n = -10:10)
    if(n>= 0 & n<=5)
        x = [x 1];
    else
        x = [x 0];
    end
    if (-1<= n & n<=3)
        h = [h 0.1];
    else
        h = [h 0];
    endif
end

y = conv(x,h);
subplot(311);
stem(x);
title("075bct099");
subplot(312);
stem(h);
subplot(313);
stem(y);
```

**Output :**



### c) Convolution of

$$x=a^n$$

$$h=u[n]$$

**Code :**

```
clc;
n = -10:10;
x = [];
h = [];
pow = [];

a = input("Input for constant value a bwt 0 and 1 :");
for(n = -10:10)

    if(n >= 0)
        h = [h 1];
    else
        h = [h 0];
    end
    pow = [pow a.^n];
end


x = pow.*h;
y = conv(x,h);
subplot(311);
```

```

stem(x);
title("Power signal 075bct099");
subplot(312);
stem(h);
title("h ");
subplot(313);
stem(y);
title("convolution ");

```

## Output:



d)

## Code:

```

clc;
clear all ;

t = -10: 0.01:10;

h= t>=0;

```

```
x = h - t >= 3;
```


```
y = conv(x,h , "same");  
subplot(311);
```

```
plot(t,x , 'g');  
title("x");
```

```
subplot(312);  
plot(t,h , 'r');  
title("h");
```

```
subplot(313);  
plot(t,y);  
title("convolution");
```

## Output:



e)  $x = [1.2 \ 2.3 \ 4.6 \ -5 \ -11.6]$ ;  $h = [2 \ 4 \ 1.7 \ 2.9]$ ;

Code :

```

clc;
clear ;

x = [1.2 2.3 4.6 -5 -11.6];
h = [2 4 1.7 2.9];


% convolution
m=length(x);
n=length(h);
X=[x,zeros(1,n)];
H=[h,zeros(1,m)];
for i=1:n+m-1
    y(i)=0;
    for j=1:m
        if(i-j+1>0)
            y(i)=y(i)+X(j)*H(i-j+1);
        else
            end
        end
    end
end
subplot(3,1,1);
stem(x);
xlabel("x");

subplot(3,1,2);
stem(h);
xlabel("h");

subplot(3,1,3);
stem(y);
xlabel("Convolution");

```

**Output :**




#### f) Convolution of exponential signal

##### Code:

```
t= 0:0.01:10;
x = exp(0.5*t);
h = ones(1 , length(x));
y = conv(h,x);
subplot(311);
plot(t,x);
title('Exponential signal');
subplot(312);
plot(t,h);
title("");
subplot(313);
plot(y);
title('Convolution of exponential');
```

##### Output:





## Conclusion:

Thus in this lab we performed convolution of two signals using inbuilt octave command 'conv'. The convolution of both continuous as well as discrete signals were performed and their output after convolution were observed in a plot.