

Import required libraries, fetch data from database into pandas.DataFrame and format data type for PCA

```

In [18]: import numpy as np
import sqlite3
import matplotlib.pyplot as plt
import datetime as DT
import seaborn as sns
np.set_printoptions(precision=5)
import pandas as pd # data processing, CSV file I/O (e.g. pd.read_csv)
#### import the PCA library from scikit learn library
from sklearn.decomposition import PCA
from mpl_toolkits.mplot3d import Axes3D # didn't get to use this
%matplotlib inline

# Normalizing (scaling) the data is VERY important - indeed can be important to many machine
# learning algorithms. Take the original features and scale them so that they all have zero
# mean and unit variance
from sklearn import preprocessing

## pandas actually has a command to read_sql or read_sql_query and return a pandas.DataFrame
## coerce_float=True argument to force float data type
## Need to FIRST connect to the database by creating a connection object called conn.
conn = sqlite3.connect('database.sqlite')

# create a cursor object using the conn object method
# The cursor object has methods for accessing the data
# c = conn.cursor() # this is not needed for the pd.read_sql IO tool

# Get the database table list from information in the sqlite_master table
# Follow convention to type SQL commands in all caps

# preview all tables in the database
print ('=====')
print ('Tables in the database')
# Set the execute SQL command, Fetch and print all table names and info, and
# return a pandas DataFrame
df_tables = pd.read_sql("""SELECT * FROM sqlite_master WHERE type='table';""", conn)
print('df_tables shape: ', df_tables.shape)
print(df_tables)
print ('=====')
print('Player_Attributes table:')
print(df_tables.sql[1]) # get sql that CREATE the Player_Attribtues table
print ('=====')
print('Player table:')
print(df_tables.sql[2]) # get sql that CREATE the Player table
print ('=====')
print ('Player table')
df_Player = pd.read_sql("""SELECT * FROM Player """, conn)
print('df_Player.shape:', df_Player.shape)
print(df_Player.columns)
print(df_Player.head())
print ('=====')
print ('Player_Attributes table')
df_Player_Attributes = pd.read_sql("""SELECT * FROM Player_Attributes""", conn)
print('df_Player_Attributes.shape:', df_Player_Attributes.shape)
print(df_Player_Attributes.columns)
print(df_Player_Attributes.head())
print ('=====')

# acquire data from database using pd.read_sql_query(sql, , ,)
# build SQL to SELECT all columns from both Player and Player_Attributes tables
# for rows reocrds w/ matching player_fifa_api_id
sql="SELECT * FROM Player INNER JOIN Player_Attributes ON Player.player_fifa_api_id=Player_A
ttributes.player_fifa_api_id;"
df_all_col=pd.read_sql_query(sql, conn, coerce_float=True, params=None, parse_dates=['birthd
ay','date'], chunksize=None)
# calculate age of player at the time attributes were collected
df_all_col['age'] = (df_all_col.date - df_all_col.birthday).astype('timedelta64[Y]')

#Tally total score per player attribute category
df_all_col['total_attack'] = df_all_col.crossing + df_all_col.finishing + df_all_col.heading
accuracy + \

```

=====

Tables in the database

df_tables shape: (8, 5)

	type	name	tbl_name	rootpage	\
0	table	sqlite_sequence	sqlite_sequence	4	
1	table	Player_Attributes	Player_Attributes	11	
2	table	Player	Player	14	
3	table	Match	Match	18	
4	table	League	League	24	
5	table	Country	Country	26	
6	table	Team	Team	29	
7	table	Team_Attributes	Team_Attributes	2	

sql

```

0      CREATE TABLE sqlite_sequence(name,seq)
1 CREATE TABLE "Player_Attributes" (\n\t`id`\tIN...
2 CREATE TABLE `Player` (\n\t`id`\tINTEGER PRIMA...
3 CREATE TABLE `Match` (\n\t`id`\tINTEGER PRIMAR...
4 CREATE TABLE `League` (\n\t`id`\tINTEGER PRIMA...
5 CREATE TABLE `Country` (\n\t`id`\tINTEGER PRIM...
6 CREATE TABLE "Team" (\n\t`id`\tINTEGER PRIMARY...
7 CREATE TABLE `Team_Attributes` (\n\t`id`\tINTE...

```

=====

Player_Attributes table:

```

CREATE TABLE "Player_Attributes" (
  `id`      INTEGER PRIMARY KEY AUTOINCREMENT,
  `player_fifa_api_id`  INTEGER,
  `player_api_id`  INTEGER,
  `date`  TEXT,
  `overall_rating`  INTEGER,
  `potential`  INTEGER,
  `preferred_foot`  TEXT,
  `attacking_work_rate`  TEXT,
  `defensive_work_rate`  TEXT,
  `crossing`  INTEGER,
  `finishing`  INTEGER,
  `heading_accuracy`  INTEGER,
  `short_passing`  INTEGER,
  `volleys`  INTEGER,
  `dribbling`  INTEGER,
  `curve`  INTEGER,
  `free_kick_accuracy`  INTEGER,
  `long_passing`  INTEGER,
  `ball_control`  INTEGER,
  `acceleration`  INTEGER,
  `sprint_speed`  INTEGER,
  `agility`  INTEGER,
  `reactions`  INTEGER,
  `balance`  INTEGER,
  `shot_power`  INTEGER,
  `jumping`  INTEGER,
  `stamina`  INTEGER,
  `strength`  INTEGER,
  `long_shots`  INTEGER,
  `aggression`  INTEGER,
  `interceptions`  INTEGER,
  `positioning`  INTEGER,
  `vision`  INTEGER,
  `penalties`  INTEGER,
  `marking`  INTEGER,
  `standing_tackle`  INTEGER,
  `sliding_tackle`  INTEGER,
  `gk_diving`  INTEGER,
  `gk_handling`  INTEGER,
  `gk_kicking`  INTEGER,
  `gk_positioning`  INTEGER,
  `gk_reflexes`  INTEGER,
  FOREIGN KEY(`player_fifa_api_id`) REFERENCES `Player`(`player_fifa_api_id`),
  FOREIGN KEY(`player_api_id`) REFERENCES `Player`(`player_api_id`)
)

```

data cleaning

```
In [19]: df_all_col.replace(r'\s+', np.nan, regex=True, inplace = True)
df_all_col.dropna(axis=0, how='any', inplace=True) #drop row (sample) with any NA entry
df_all_col.sort_values('player_name',axis=0, inplace=True)
df_all_col.drop_duplicates(inplace=True)
df_all_col.to_csv('df_all_col.csv')

print ('df_all_col.shape: ', df_all_col.shape)
print(df_all_col.shape)
print(df_all_col.info())
print(df_all_col.head())
print(df_all_col.tail())
print(df_all_col['defensive_work_rate'][0:60]) # need more data cleaning for col before plotting
print ('=====')

df_unscaled_data = df_all_col[numeric_col]
print('df_unscaled_data.columns:', df_unscaled_data.columns)
print('df_unscaled_data.shape:', df_unscaled_data.shape)
print('df_unscaled_data.info: ', df_unscaled_data.info())
```

```

df_all_col.shape: (10898, 57)
(10898, 57)
<class 'pandas.core.frame.DataFrame'>
Int64Index: 10898 entries, 1045 to 183615
Data columns (total 57 columns):
id                10898 non-null int64
player_api_id     10898 non-null int64
player_name       10898 non-null object
player_fifa_api_id 10898 non-null int64
birthday          10898 non-null datetime64[ns]
height            10898 non-null float64
weight            10898 non-null int64
id                10898 non-null int64
player_fifa_api_id 10898 non-null int64
player_api_id     10898 non-null int64
date              10898 non-null datetime64[ns]
overall_rating     10898 non-null float64
potential          10898 non-null float64
preferred_foot     10898 non-null object
attacking_work_rate 10898 non-null object
defensive_work_rate 10898 non-null object
crossing           10898 non-null float64
finishing          10898 non-null float64
heading_accuracy   10898 non-null float64
short_passing      10898 non-null float64
volleys            10898 non-null float64
dribbling          10898 non-null float64
curve              10898 non-null float64
free_kick_accuracy 10898 non-null float64
long_passing       10898 non-null float64
ball_control       10898 non-null float64
acceleration       10898 non-null float64
sprint_speed       10898 non-null float64
agility            10898 non-null float64
reactions          10898 non-null float64
balance            10898 non-null float64
shot_power         10898 non-null float64
jumping            10898 non-null float64
stamina            10898 non-null float64
strength           10898 non-null float64
long_shots         10898 non-null float64
aggression         10898 non-null float64
interceptions      10898 non-null float64
positioning        10898 non-null float64
vision             10898 non-null float64
penalties          10898 non-null float64
marking            10898 non-null float64
standing_tackle    10898 non-null float64
sliding_tackle     10898 non-null float64
gk_diving          10898 non-null float64
gk_handling        10898 non-null float64
gk_kicking         10898 non-null float64
gk_positioning     10898 non-null float64
gk_reflexes        10898 non-null float64
age                10898 non-null float64
total_attack       10898 non-null float64
total_skill        10898 non-null float64
total_movement     10898 non-null float64
total_power        10898 non-null float64
total_mentality    10898 non-null float64
total_defending    10898 non-null float64
total_goalkeeping  10898 non-null float64
dtypes: datetime64[ns](2), float64(44), int64(7), object(4)
memory usage: 4.8+ MB
None

```

	id	player_api_id	player_name	player_fifa_api_id	birthday	height	\
1045	67	40938	Abel	17880	1978-12-22	177.8	
1046	67	40938	Abel	17880	1978-12-22	177.8	
1047	67	40938	Abel	17880	1978-12-22	177.8	
1048	67	40938	Abel	17880	1978-12-22	177.8	
----	--	-----	--	-----	-----	----	--

Preprocess data and conduct PCA - principal component analysis

```
In [9]: scaled_data = preprocessing.scale(df_unscaled_data) #center and scale the data
print('scaled data:')
print (scaled_data)  # preview scaled data

# create a PCA object.
# sklearn uses this PCA object that can be trained using one dataset and applied to another d
ataset
pca = PCA()
print(type(pca))
# do PCA math, calculate loading scores and the variation each PCA accounts for
pca.fit(scaled_data)
# generate coordinates for a PCA graph based on the loading scores and the scaled data
pca_data = pca.transform(scaled_data)

scaled data:
[[ 1.20435 -0.50782 -0.12955 ... -0.64338 -0.19821 -0.36672]
 [ 1.20435 -0.50782 -0.12955 ...  2.36822  0.20348  0.18149]
 [ 0.98217 -0.50782 -0.12955 ...  2.36822  0.20348  0.18149]
 ...
 [-1.68402 -0.88666 -1.24685 ... -0.64338 -0.31297 -0.47637]
 [-1.68402 -0.88666 -1.24685 ... -0.64338 -0.31297 -0.47637]
 [-3.2393  -0.88666 -1.24685 ... -0.64338 -0.31297 -0.47637]]
<class 'sklearn.decomposition.pca.PCA'>
```

Present Explained Variance, Scree Plot and Principal Components Scatter Matrix

```
In [11]: # pca.explained_variance_ratio_ is <class 'numpy.ndarray'>.
# It calculates the percentage of variance that each principal component accounts for
per_var = np.round(pca.explained_variance_ratio_*100, decimals=1)
print('=====')
print('percent of explained variance: ')
print(per_var)
PC_labels = ['PC'+ str(x) for x in range(1,len(per_var)+1)] # labels for the Scree Plot: PC1
, PC2 ...
print(' ')
print('=====')

# create Scree Plot
plt.figure(figsize=(18, 6))
plt.bar(x=range(1, len(per_var)+1), height=per_var, tick_label=PC_labels)
plt.ylabel('Percentage of Explained Variance', fontsize='14')
plt.xlabel('Principal Component', fontsize='14')
plt.title('Scree Plot', fontsize='18')
plt.show()
plt.close()

# put pca_data with DataFrame with PC_labels
pca_df = pd.DataFrame(pca_data, index=None, columns=PC_labels)
print(pca_df.head()) # preview transformed and scaled
print('=====')


print('Principal Components Scatter Matrix')
df_pc_matrix= pca_df[['PC'+ str(x) for x in range(1,21)]] # scatter matrix for PC1, PC2, ...
, PC15
pd.plotting.scatter_matrix(df_pc_matrix, alpha=0.1, figsize=(14, 14), diagonal='kde',range_p
adding =0.1)
plt.tight_layout()
plt.show()
plt.close()
```


=====

percent of explained variance:

```
[43.9 15.7  8.9  6.8  3.9  3.   2.2  1.7  1.3  1.1  1.   1.   0.9  0.7
  0.7  0.7  0.6  0.6  0.5  0.5  0.5  0.4  0.4  0.4  0.3  0.3  0.3  0.3
  0.2  0.2  0.2  0.2  0.1  0.1  0.1  0.1  0.1  0.1]
```

=====



	PC1	PC2	PC3	PC4	PC5	PC6	PC7	\
0	-2.640114	1.968095	0.650296	-1.085030	0.432893	-0.997913	-0.036752	
1	-1.974144	1.547071	1.945571	-1.698880	0.785256	-0.431110	2.178955	
2	-1.998243	1.632706	1.964671	-1.818000	0.655679	-0.269227	2.168876	
3	-1.777293	1.508709	1.666837	-1.760435	0.469343	-0.019567	2.297794	
4	-2.056297	0.869395	0.466741	-1.179464	0.879790	-0.124301	2.485314	

	PC8	PC9	PC10	...	PC29	PC30	PC31	\
0	-0.345769	-0.212905	0.717640	...	-0.243024	-0.082784	-0.287740	
1	-0.524871	0.683914	0.138753	...	-0.313755	-0.136859	-0.142348	
2	-0.553466	0.642269	0.157086	...	-0.304040	0.008732	-0.030220	
3	-0.364947	0.543994	0.246732	...	-0.335973	0.075856	0.170031	
4	0.184533	0.201187	-0.439294	...	-0.316171	0.099965	0.113237	

	PC32	PC33	PC34	PC35	PC36	PC37	PC38
0	-0.044248	-0.119196	-0.127400	-0.024028	0.054763	0.303422	0.202196
1	-0.096422	-0.082920	0.120610	0.091425	-0.042255	0.005217	-0.040199
2	-0.022378	-0.068867	0.080547	0.128276	0.035120	0.007889	-0.050469
3	0.044900	-0.031943	0.052600	0.120342	0.048383	0.012409	-0.034910
4	0.045786	-0.056746	0.502708	0.322174	-0.167724	-0.178028	-0.046963

[5 rows x 38 columns]

=====

Principal Components Scatter Matrix



Take a Look at the Loading Scores of PC1, PC2 and PC3 to determine which feature has the largest influence in each principal component

```
In [12]: loading_scores_PC1 = pd.Series(pca.components_[0],index=numeric_col)
loading_scores_PC1_sorted = loading_scores_PC1.abs().sort_values(ascending=False)
print('Sorted PC1 Loading Scores (abs)')
print('PC1 sorted components: ', loading_scores_PC1_sorted.index)
print(loading_scores_PC1_sorted)
print('=====')

loading_scores_PC2 = pd.Series(pca.components_[1],index=numeric_col)
loading_scores_PC2_sorted = loading_scores_PC2.abs().sort_values(ascending=False)
print('Sorted PC2 Loading Scores (abs)')
print('PC2 sorted components: ', loading_scores_PC2_sorted.index)
print(loading_scores_PC2_sorted)
print('=====')

loading_scores_PC3 = pd.Series(pca.components_[2],index=numeric_col)
loading_scores_PC3_sorted = loading_scores_PC3.abs().sort_values(ascending=False)
print('Sorted PC3 Loading Scores (abs)')
print('PC3 sorted components: ', loading_scores_PC3_sorted.index)
print(loading_scores_PC3_sorted)
```

Sorted PC1 Loading Scores (abs)

```
PC1 sorted components: Index(['ball_control', 'dribbling', 'short_passing', 'crossing', 'curve',
                             'long_shots', 'positioning', 'shot_power', 'vision', 'gk_diving',
                             'free_kick_accuracy', 'gk_reflexes', 'gk_handling', 'gk_positioning',
                             'volleys', 'finishing', 'acceleration', 'penalties', 'sprint_speed',
                             'long_passing', 'agility', 'stamina', 'balance', 'height',
                             'heading_accuracy', 'weight', 'gk_kicking', 'reactions', 'aggression',
                             'overall_rating', 'potential', 'interceptions', 'standing_tackle',
                             'sliding_tackle', 'marking', 'strength', 'age', 'jumping'],
                             dtype='object')
ball_control      0.233895
dribbling         0.226609
short_passing     0.220168
crossing          0.213529
curve            0.211442
long_shots       0.211257
positioning      0.204851
shot_power       0.199655
vision           0.197614
gk_diving        0.196600
free_kick_accuracy 0.196366
gk_reflexes      0.195234
gk_handling      0.195011
gk_positioning   0.193662
volleys          0.193077
finishing        0.191773
acceleration     0.185480
penalties        0.183370
sprint_speed     0.182038
long_passing     0.177636
agility          0.168734
stamina          0.158548
balance          0.153811
height           0.134852
heading_accuracy 0.132158
weight           0.125473
gk_kicking       0.121982
reactions        0.105162
aggression       0.087644
overall_rating   0.083033
potential        0.080174
interceptions    0.071469
standing_tackle  0.065230
sliding_tackle   0.059237
marking          0.052163
strength         0.028138
age              0.005573
jumping          0.001561
dtype: float64
=====
```

Sorted PC2 Loading Scores (abs)

```
PC2 sorted components: Index(['marking', 'standing_tackle', 'sliding_tackle', 'interceptions',
                             'aggression', 'strength', 'heading_accuracy', 'agility', 'height',
                             'weight', 'finishing', 'stamina', 'volleys', 'balance',
                             'gk_positioning', 'gk_handling', 'acceleration', 'gk_reflexes',
                             'positioning', 'gk_diving', 'jumping', 'dribbling', 'age', 'curve',
                             'gk_kicking', 'sprint_speed', 'long_passing', 'penalties', 'long_shots',
                             'vision', 'short_passing', 'free_kick_accuracy', 'overall_rating',
                             'shot_power', 'crossing', 'reactions', 'potential', 'ball_control'],
                             dtype='object')
marking           0.360160
standing_tackle   0.357693
sliding_tackle    0.351805
interceptions     0.323485
aggression        0.310414
strength          0.269961
heading_accuracy  0.231016
agility           0.172402
. . . . .
. . . . .
```

Present graphs pertinent to the first three principal componets:

Note: When plotting PC1 versus PC2 AND PC1 versus PC3, two clusters are displayed.







Next, we will visualize further in PC1, PC2 and PC3.







```
In [13]: # draw PCA 2D plot: PC1 Vs PC2 and PC1 Vs PC3
def color_plot (i):
    plt.figure(figsize=(10, 5))
    plt.subplot(1,2,1)







    plt.scatter(pca_df.PC1, pca_df.PC2, c=scaled_data[:,i], alpha=0.1)
    plt.title("PCA Graph: PC1 Versus PC2 - color by " + numeric_col[i], fontsize='12')
    plt.xlabel('PC1 - {0}%'.format(per_var[0]), fontsize='12')
    plt.ylabel('PC2 - {0}%'.format(per_var[1]), fontsize='12')
    plt.tight_layout()







    plt.subplot(1,2,2)
    plt.scatter(pca_df.PC1, pca_df.PC3, c=scaled_data[:,i], alpha=0.1)
    plt.title("PCA Graph: PC1 Versus PC3 - color by " + numeric_col[i], fontsize='12')
    plt.xlabel('PC1 - {0}%'.format(per_var[0]), fontsize='12')
    plt.ylabel('PC3 - {0}%'.format(per_var[2]), fontsize='12')
    plt.tight_layout()
    plt.show()
    plt.close()


for j in range(0,38):
    color_plot (j)
```









































































```

In [17]: # 'attacking_work_rate', 'defensive_work_rate']
# plt.title('players with gk_diving > 40', loc='center')
def plot(df_all, df_sub, hue_col):
    # first plot
    vis1=sns.lmplot(x='ball_control', y='marking', hue=hue_col, sharex=False, data=df_all,
scatter=True, fit_reg=False, units=None, order=1, legend=True)
    plt.title('all players')
    plt.xlim(0,100)
    plt.ylim(0,100)
    plt.show()
    plt.close()
    # second plot: goalkeepers only
    vis2=sns.lmplot(x='ball_control', y='marking', hue=hue_col, sharex=False, data=df_sub,
scatter=True, fit_reg=False, units=None, order=1, legend=True)
    plt.title('players with gk_diving > 40 (goalkeepers)')
    plt.xlim(0,100)
    plt.ylim(0,100)
    plt.show()
    plt.close()

print('gk_diving > 40 (goalkeepers)')
df_goalkeepers=df_all.loc[df_all_col['gk_diving']>40]
#print(df_goalkeepers.head())
plot(df_all_col, df_goalkeepers, None)

# color by lefty and righty
plot(df_all_col, df_goalkeepers, 'preferred_foot')
# plot lefty only
print('plot preferred left foot')
df1=df_all_col.loc[df_all_col['preferred_foot']=='left']
df2=df_goalkeepers.loc[df_goalkeepers['preferred_foot']=='left']
plot(df1,df2,None)




# color by 'attaching_work_rate'
df3=df_all_col[df_all_col['attaching_work_rate'].isin(['low','medium','high'])]
df4=df_goalkeepers[df_goalkeepers['attaching_work_rate'].isin(['low','medium','high'])]
plot(df3, df4, 'attaching_work_rate')


#plot jointplot with goal keeper attributes:
# 'gk_diving', 'gk_handling', 'gk_kicking', 'gk_positioning', 'gk_reflexes'
def joint_plot(df, title):
    vis=sns.jointplot(x='ball_control',y='gk_diving', data=df, xlim=(0,100), ylim=(0,100), s
tat_func=None)
    plt.title(title, loc='left')
    plt.show()
    plt.close()
    vis=sns.jointplot(x='ball_control',y='gk_handling', data=df, xlim=(0,100), ylim=(0,100),
stat_func=None)
    plt.title(title, loc='left')
    plt.show()
    plt.close()
    vis=sns.jointplot(x='ball_control',y='gk_kicking', data=df, xlim=(0,100), ylim=(0,100),
stat_func=None)
    plt.title(title, loc='left')
    plt.show()
    plt.close()
    vis=sns.jointplot(x='ball_control',y='gk_positioning', data=df, xlim=(0,100), ylim=(0,10
0), stat_func=None)
    plt.title(title, loc='left')
    plt.show()
    plt.close()
    vis=sns.jointplot(x='ball_control',y='gk_reflexes', data=df, xlim=(0,100), ylim=(0,100),
stat_func=None)
    plt.title(title, loc='left')
    plt.show()
    plt.close()

    vis=sns.jointplot(x='marking',y='gk_diving', data=df, xlim=(0,100), ylim=(0,100), stat_f
unc=None)



```




```
gk_diving > 40 (goalkeepers)
```











plot preferred left foot





































```
In [42]: import seaborn as sns
df1=df_all_col[df_all_col['defensive_work_rate'].isin(['low','medium','high'])]
df2=df_all_col[df_all_col['defensive_work_rate'].isin(['high'])]
df3=df_all_col[df_all_col['defensive_work_rate'].isin(['medium'])]
df4=df_all_col[df_all_col['defensive_work_rate'].isin(['low'])]




def lmplot(df):
    vis=sns.lmplot(x='marking', y='overall_rating', hue='defensive_work_rate', sharex=False,
    , data=df, \
                    scatter=True, fit_reg=False, units=None, order=1, legend=True)
    plt.title('Colored By Defensive Work Rate')
    plt.show()
    plt.close()




    vis=sns.lmplot(x='standing_tackle', y='overall_rating', hue='defensive_work_rate', sharex=False, data=df, \
                    scatter=True, fit_reg=False, units=None, order=1, legend=True)
    plt.title('Colored By Defensive Work Rate')
    plt.show()
    plt.close()




    vis=sns.lmplot(x='sliding_tackle', y='overall_rating', hue='defensive_work_rate', sharex=False, data=df, \
                    scatter=True, fit_reg=False, units=None, order=1, legend=True)
    plt.title('Colored By Defensive Work Rate')
    plt.show()
    plt.close()




    vis=sns.lmplot(x='interceptions', y='overall_rating', hue='defensive_work_rate', sharex=False, data=df, \
                    scatter=True, fit_reg=False, units=None, order=1, legend=True)
    plt.title('Colored By Defensive Work Rate')
    plt.show()
    plt.close()




lmplot(df1) #color by 'defensive_work_rate'.isin(['low','medium','high'])
lmplot(df2) #color by 'defensive_work_rate'.isin(['high'])
lmplot(df3) #color by 'defensive_work_rate'.isin(['medium'])
lmplot(df4) #color by 'defensive_work_rate'.isin(['low'])
```
















```
In [4]: df_totals=df_all_col[numeric_few_col]
pd.plotting.scatter_matrix(df_totals, alpha=0.1, figsize=(16, 16), diagonal='kde',range_padd
ing =0.01)
plt.tight_layout()
plt.show()
plt.close()

total_cols = numeric_few_col + ['player_fifa_api_id', 'player_name']
df_t=df_all_col[total_cols]
df_t.to_csv('player_total_score_per_attributes_category.csv')
print(df_t.shape)
print (df_t.head())
```



```
(10898, 15)
```

```
   age  height  weight  overall_rating  potential  total_attack  \  
1045  31.0   177.8    165             73.0      75.0         311.0  
1046  31.0   177.8    165             72.0      75.0         307.0  
1047  30.0   177.8    165             73.0      75.0         305.0  
1048  28.0   177.8    165             73.0      75.0         298.0  
1049  28.0   177.8    165             70.0      72.0         288.0
```

```
   total_skill  total_movement  total_power  total_mentality  \  
1045         319.0           375.0       355.0         351.0  
1046         318.0           375.0       355.0         372.0  
1047         316.0           377.0       357.0         372.0  
1048         311.0           372.0       355.0         370.0  
1049         335.0           366.0       346.0         356.0
```

```
   total_defending  total_goalkeeping  player_fifa_api_id  \  
1045             219.0              42.0             17880  
1046             216.0             143.0             17880  
1047             221.0             143.0             17880  
1048             221.0             141.0             17880  
1049             212.0             102.0             17880
```

```
   player_fifa_api_id  player_name  
1045             17880         Abel  
1046             17880         Abel  
1047             17880         Abel  
1048             17880         Abel  
1049             17880         Abel
```

```
In [16]: # Total Goalkeeping
vis=sns.lmplot(x='total_goalkeeping', y='overall_rating', hue = None, sharex=False, data=df_totals, \
              scatter=True, fit_reg=False, units=None, order=1, legend=True)
plt.title('Total Goalkeeping Versus Overall Rating')
plt.show()
plt.close()

df_totals_gk = df_totals[df_totals['total_goalkeeping'] > 250]
corr_gk=df_totals_gk[['total_goalkeeping','overall_rating']].corr()
print ('A Closer Look at the Goalkeeper Subgroup on the Far Right')
print(' total_goalkeeping > 250 ')
print(' ')
print('Strong Positive Linear Correlation: ')
print(corr_gk)

vis=sns.lmplot(x='total_goalkeeping', y='overall_rating', hue = None, sharex=False, data=df_totals_gk, \
              scatter=True, fit_reg=True, units=None, order=1, legend=True)
plt.title('Goalkeeper Subgroup: Total Goalkeeping Versus Overall Rating')
plt.show()
plt.close()

# Total Mentality
vis=sns.lmplot(x='total_mentality', y='overall_rating', hue = None, sharex=False, data=df_totals, \
              scatter=True, fit_reg=False, units=None, order=1, legend=True)
plt.title('Total Mentality Versus Overall Rating')
plt.show()
plt.close()


df_totals_non_gk = df_totals[df_totals['total_goalkeeping'] < 250]
corr_mentality=df_totals_non_gk[['total_mentality','overall_rating']].corr()
print ('A Closer Look at the Non_goalkeeper Subgroup on the Far Right')
print(' total_goalkeeping < 250')
print(' ')
print ('Moderate Positive Linear Correlation: ')
print(corr_mentality)

vis=sns.lmplot(x='total_mentality', y='overall_rating', hue = None, sharex=False, data=df_totals_non_gk, \
              scatter=True, fit_reg=True, units=None, order=1, legend=True)
plt.title('Non_Goalkeeper Subgroup: Total Mentality Versus Overall Rating')
plt.show()
plt.close()

# Total Attack
vis=sns.lmplot(x='total_attack', y='overall_rating', hue = None, sharex=False, data=df_totals, \
              scatter=True, fit_reg=False, units=None, order=1, legend=True)
plt.title('Total Attack Versus Overall Rating')
plt.show()
plt.close()

df_totals_non_gk = df_totals[df_totals['total_goalkeeping'] < 250]
corr_attack=df_totals_non_gk[['total_attack','overall_rating']].corr()
print ('A Closer Look at the Non_goalkeeper Subgroup on the Far Right')
print(' total_goalkeeping < 250')
print(' ')
print ('Moderate Positive Linear Correlation: ')
print(corr_attack)


vis=sns.lmplot(x='total_attack', y='overall_rating', hue = None, sharex=False, data=df_totals_non_gk, \
              scatter=True, fit_reg=True, units=None, order=1, legend=True)
plt.title('Non_Goalkeeper Subgroup: Total Attack Versus Overall Rating')
plt.show()
plt.close()
```




A Closer Look at the Goalkeeper Subgroup on the Far Right
total_goalkeeping > 250

Strong Positive Linear Correlation:

	total_goalkeeping	overall_rating
total_goalkeeping	1.000000	0.978269
overall_rating	0.978269	1.000000







A Closer Look at the Non_goalkeeper Subgroup on the Far Right
total_goalkeeping < 250

Moderate Positive Linear Correlation:

	total_mentality	overall_rating
total_mentality	1.00000	0.67607
overall_rating	0.67607	1.00000

Non_Goalkeeper Subgroup: Total Mentality Versus Overall Rating






A Closer Look at the Non_goalkeeper Subgroup on the Far Right
total_goalkeeping < 250

Moderate Positive Linear Correlation:

	total_attack	overall_rating
total_attack	1.000000	0.628757
overall_rating	0.628757	1.000000



Interpret correlation coefficient

Exactly -1. A perfect downhill (negative) linear relationship

- -0.70. A strong downhill (negative) linear relationship
- -0.50. A moderate downhill (negative) relationship
- -0.30. A weak downhill (negative) linear relationship
- 0. No linear relationship


```
In [21]: # save correlation coefficient for dataset to csv
df_corr = df_unscaled_data.corr()
df_corr.to_csv('df_corr.csv')

df_gk=df_unscaled_data.loc[df_unscaled_data['gk_diving']>40]
df_gk_corr = df_gk.corr()
df_gk_corr.to_csv('df_gk_corr.csv')


df_non_gk=df_unscaled_data.loc[df_unscaled_data['gk_diving']<40]
df_non_gk_corr = df_non_gk.corr()
df_non_gk_corr.to_csv('df_non_gk_corr.csv')
```

```
In [31]: print('Unscaled Data Scatter Matrix 1')
print('PC1 sorted components: ', loading_scores_PC1_sorted.index[0:19])
#col_of_interest = ['ball_control', 'dribbling', 'short_passing', 'crossing', 'curve', 'long_shots', 'positioning', 'shot_power', 'vision', 'gk_diving', 'free_kick_accuracy', 'gk_reflexes', 'gk_handling']
col_of_interest = loading_scores_PC1_sorted.index[0:19]
df_col_of_interest= df_unscaled_data[col_of_interest] # scatter matrix for columns of interest

pd.plotting.scatter_matrix(df_col_of_interest, alpha=0.1, figsize=(16, 16), diagonal='kde', range_padding =0.01)
plt.tight_layout()
plt.show()
plt.close()
```

Unscaled Data Scatter Matrix 1

PC1 sorted components: Index(['ball_control', 'dribbling', 'short_passing', 'crossing', 'curve', 'long_shots', 'positioning', 'shot_power', 'vision', 'gk_diving', 'free_kick_accuracy', 'gk_reflexes', 'gk_handling', 'gk_positioning', 'volleys', 'finishing', 'acceleration', 'penalties', 'sprint_speed'], dtype='object')




```
In [39]: print('Unscaled Data Scatter Matrix 2')
print('PC1 sorted components: ', loading_scores_PC1_sorted.index[19:38])
#col_of_interest = ['ball_control', 'dribbling', 'short_passing', 'crossing', 'curve', 'long_shots', 'positioning', 'shot_power', 'vision', 'gk_diving', 'free_kick_accuracy', 'gk_reflexes', 'gk_handling']
col_of_interest = loading_scores_PC1_sorted.index[19:38]
df_col_of_interest= df_unscaled_data[col_of_interest] # scatter matrix for columns of interest

pd.plotting.scatter_matrix(df_col_of_interest, alpha=0.1, figsize=(16, 16), diagonal='kde', range_padding =0.01)
plt.tight_layout()
plt.show()
plt.close()
```

Unscaled Data Scatter Matrix 2

PC1 sorted components: Index(['long_passing', 'agility', 'stamina', 'balance', 'height', 'heading_accuracy', 'weight', 'gk_kicking', 'reactions', 'aggression', 'overall_rating', 'potential', 'interceptions', 'standing_tackle', 'sliding_tackle', 'marking', 'strength', 'age', 'jumping'], dtype='object')



```
In [36]: # create distribution plot for all features

final_col = ['player_fifa_api_id', 'preferred_foot', 'attacking_work_rate', 'defensive_work_rate'] + numeric_col
print(final_col)
df_final=df_all_col[final_col]
'''
df_final=df_all_col['player_fifa_api_id', 'preferred_foot', 'attacking_work_rate', 'defensive_work_rate', 'age', \
                    'height', 'weight', 'overall_rating', 'potential', 'crossing', 'finishing', 'heading_accuracy', \
                    'short_passing', 'volleys', 'dribbling', 'curve', 'free_kick_accuracy', 'long_passing', \
                    'ball_control', 'acceleration', 'sprint_speed', 'agility', 'reactions', 'balance', 'shot_power', \
                    'jumping', 'stamina', 'strength', 'long_shots', 'aggression', 'interceptions', 'positioning', \
                    'vision', 'penalties', 'marking', 'standing_tackle', 'sliding_tackle', 'gk_diving', 'gk_handling', \
                    'gk_kicking', 'gk_positioning', 'gk_reflexes']
'''
print(df_final.head())
print(len(final_col))
df_final.to_csv("df_final.csv")

# distplot for goalkeeping attributes
fig = plt.figure(figsize=(24,18))
ax1 = fig.add_subplot(321)
ax2 = fig.add_subplot(322)
ax3 = fig.add_subplot(323)
ax4 = fig.add_subplot(324)
ax5 = fig.add_subplot(325)
vis1=sns.distplot (df_all_col['gk_diving'], bins=30, ax=ax1)
vis2=sns.distplot (df_all_col['gk_handling'], bins=30, ax=ax2)
vis3=sns.distplot (df_all_col['gk_kicking'], bins=30, ax=ax3)
vis4=sns.distplot (df_all_col['gk_positioning'], bins=30, ax=ax4)
vis5=sns.distplot (df_all_col['gk_reflexes'], bins=30, ax=ax5)
plt.show()
plt.close()

# distplot for defending attributes
fig = plt.figure(figsize=(18,5))
ax6 = fig.add_subplot(131)
ax7 = fig.add_subplot(132)
ax8 = fig.add_subplot(133)
vis6=sns.distplot (df_all_col['marking'], bins=30, ax=ax6)
vis7=sns.distplot (df_all_col['standing_tackle'], bins=30, ax=ax7)
vis8=sns.distplot (df_all_col['sliding_tackle'], bins=30, ax=ax8)
plt.show()
plt.close()

# distplot
for i in range (4,42) :
    sns.distplot (df_all_col[final_col[i]], bins=30)
    plt.title('Distribution Plot')
    plt.show()
    plt.close()
```

```
[ 'player_fifa_api_id', 'preferred_foot', 'attacking_work_rate', 'defensive_work_rate', 'age', 'height', 'weight', 'overall_rating', 'potential', 'crossing', 'finishing', 'heading_accuracy', 'short_passing', 'volleys', 'dribbling', 'curve', 'free_kick_accuracy', 'long_passing', 'ball_control', 'acceleration', 'sprint_speed', 'agility', 'reactions', 'balance', 'shot_power', 'jumping', 'stamina', 'strength', 'long_shots', 'aggression', 'interceptions', 'positioning', 'vision', 'penalties', 'marking', 'standing_tackle', 'sliding_tackle', 'gk_diving', 'gk_handling', 'gk_kicking', 'gk_positioning', 'gk_reflexes' ]
```

```

player_fifa_api_id player_fifa_api_id preferred_foot \
1045                17880                17880      right
1046                17880                17880      right
1047                17880                17880      right
1048                17880                17880      right
1049                17880                17880      right

```

```

attacking_work_rate defensive_work_rate age height weight \
1045                None                o 31.0 177.8 165
1046                None                o 31.0 177.8 165
1047                None                o 30.0 177.8 165
1048                None                o 28.0 177.8 165
1049                None                o 28.0 177.8 165

```

```

overall_rating potential ... vision penalties marking \
1045                73.0                75.0 ...      75.0        66.0      73.0
1046                72.0                75.0 ...      75.0        75.0      72.0
1047                73.0                75.0 ...      75.0        75.0      74.0
1048                73.0                75.0 ...      75.0        76.0      74.0
1049                70.0                72.0 ...      75.0        83.0      70.0

```

```

standing_tackle sliding_tackle gk_diving gk_handling gk_kicking \
1045                74.0                72.0      7.0         5.0         7.0
1046                72.0                72.0      9.0        20.0        74.0
1047                75.0                72.0      9.0        20.0        74.0
1048                75.0                72.0      9.0        20.0        72.0
1049                70.0                72.0      9.0        10.0        63.0

```










```





gk_positioning gk_reflexes
1045                13.0        10.0
1046                20.0        20.0
1047                20.0        20.0
1048                20.0        20.0
1049                8.0         12.0





```





```
[5 rows x 43 columns]
```





```
42
```












































```
In [40]: print('A Closer Look at Overall Rating Versus Reactions Attributes')
print(' ')
corr1=df_all_col[['reactions','overall_rating']].corr()
print(corr1)
vis1=sns.lmplot( x='reactions', y='overall_rating', hue=None, sharex=False, data=df_all_col,
scatter=True, fit_reg=True, units=None, order=1, legend=True)
plt.show()

df11=df_all_col[df_all_col['attacking_work_rate'].isin(['low','medium','high'])]
corr11=df11[['reactions','overall_rating']].corr()
print(corr11)
vis11=sns.lmplot( x='reactions', y='overall_rating', hue='attacking_work_rate', sharex=False
, data=df11, scatter=True, fit_reg=True, units=None, order=1, legend=True)
plt.show()


df12=df_all_col[df_all_col['defensive_work_rate'].isin(['low','medium','high'])]
corr12=df12[['reactions','overall_rating']].corr()
print(corr12)
vis12=sns.lmplot( x='reactions', y='overall_rating', hue='defensive_work_rate', sharex=False
, data=df12, scatter=True, fit_reg=True, units=None, order=1, legend=True)
plt.show()

df13=df_all_col[df_all_col['gk_diving'] > 40]
corr13=df13[['reactions','overall_rating']].corr()
print('gk_diving > 40 ')
print(corr13)
vis13=sns.lmplot( x='reactions', y='overall_rating', hue=None, sharex=False, data=df13, scat
ter=True, fit_reg=True, units=None, order=1, legend=True)
plt.show()
plt.close()


df14=df_all_col[df_all_col['gk_diving'] < 41]
corr14=df14[['reactions','overall_rating']].corr()
print('gk_diving < 41')
print(corr14)
vis14=sns.lmplot( x='reactions', y='overall_rating', hue=None, sharex=False, data=df14, scat
ter=True, fit_reg=True, units=None, order=1, legend=True)
plt.show()
plt.close()
```

A Closer Look at Overall Rating Versus Reactions Attributes


	reactions	overall_rating
reactions	1.00000	0.72483
overall_rating	0.72483	1.00000



	reactions	overall_rating
reactions	1.00000	0.72456
overall_rating	0.72456	1.00000




	reactions	overall_rating
reactions	1.000000	0.725001
overall_rating	0.725001	1.000000



```
gk_diving > 40
```

	reactions	overall_rating
reactions	1.00000	0.56092
overall_rating	0.56092	1.00000



```
gk_diving < 41
```

	reactions	overall_rating
reactions	1.000000	0.759507
overall_rating	0.759507	1.000000

