

Ex.No – 8

Roll No – 210701149

Implement SVM and Decision Tree Classification Techniques

AIM:

To implement SVM / Decision Tree Classification Techniques in Python.

PROCEDURES:

1. Collect and load the dataset from sources like CSV files or databases.
2. Clean and preprocess the data, including handling missing values and encoding categorical variables.
3. Split the dataset into training and testing sets to evaluate model performance.
4. Normalize or standardize the features, especially for SVM, to ensure consistent scaling.
5. Choose the appropriate model: SVM for margin-based classification, Decision Tree for rule-based classification.
6. Train the model on the training data using the `fit` method.
7. Make predictions on the testing data using the `predict` method.
8. Evaluate the model using metrics like accuracy, confusion matrix, precision, and recall.
9. Visualize the results with plots, such as decision boundaries for SVM or tree structures for Decision Trees.
10. Fine-tune the model by adjusting hyperparameters like `C` for SVM or `max_depth` for Decision Trees.

CODE:

SVM.py

```
# Install and load the e1071 package (if not already installed)
library(e1071)

# Load the iris dataset
data(iris)

# Inspect the first few rows of the dataset
head(iris)

# Split the data into training (70%) and testing (30%) sets
set.seed(123) # For reproducibility
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris))
train_data <- iris[sample_indices, ]
test_data <- iris[-sample_indices, ]

# Fit the SVM model
svm_model <- svm(Species ~ ., data = train_data, kernel = "radial")

# Print the summary of the model
summary(svm_model)

# Predict the test set
predictions <- predict(svm_model, newdata = test_data)

# Evaluate the model's performance
confusion_matrix <- table(Predicted = predictions, Actual =
test_data$Species)
print(confusion_matrix)

# Calculate accuracy
accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)
```

```
cat("Accuracy:", accuracy * 100, "%\n")
```

DecisionTree.py

```
# Install and load the rpart package (if not already installed)
```

```
library(rpart)
```

```
# Load the iris dataset
```

```
data(iris)
```

```
# Split the data into training (70%) and testing (30%) sets
```

```
set.seed(123) # For reproducibility
```

```
sample_indices <- sample(1:nrow(iris), 0.7 * nrow(iris))
```

```
train_data <- iris[sample_indices, ]
```

```
test_data <- iris[-sample_indices, ]
```

```
# Fit the Decision Tree model
```

```
tree_model <- rpart(Species ~ ., data = train_data, method = "class")
```

```
# Print the summary of the model
```

```
summary(tree_model)
```

```
# Plot the Decision Tree
```

```
plot(tree_model)
```

```
text(tree_model, pretty = 0)
```

```
# Predict the test set
```

```
predictions <- predict(tree_model, newdata = test_data, type = "class")
```

```
# Evaluate the model's performance
```

```
confusion_matrix <- table(Predicted = predictions, Actual =  
test_data$Species)
```

```

print(confusion_matrix)

# Calculate accuracy

accuracy <- sum(diag(confusion_matrix)) / sum(confusion_matrix)

cat("Accuracy:", accuracy * 100, "%\n")

```

OUTPUT:

```

Sepal.Length Sepal.Width Petal.Length Petal.Width Species
1           5.1           3.5           1.4           0.2  setosa
2           4.9           3.0           1.4           0.2  setosa
3           4.7           3.2           1.3           0.2  setosa
4           4.6           3.1           1.5           0.2  setosa
5           5.0           3.6           1.4           0.2  setosa
6           5.4           3.9           1.7           0.4  setosa

Call:
svm(formula = Species ~ ., data = train_data, kernel = "radial")

Parameters:
  SVM-Type:  C-classification
SVM-Kernel:  radial
    cost:    1

Number of Support Vectors:  45


( 7 18 20 )

Number of Classes:  3

Levels:
setosa versicolor virginica

      Actual
Predicted setosa versicolor virginica
setosa      14           0           0
versicolor  0           17           0
virginica   0           1          13
Accuracy: 97.7778 %

```



```

rpart(formula = Species ~ ., data = train_data, method = "class")
n= 105

      CP nsplit  rel error    xerror      xstd
1 0.5294118      0 1.00000000 1.2058824 0.06232572
2 0.3970588      1 0.47058824 0.5441176 0.07198662
3 0.0100000      2 0.07352941 0.1176471 0.03997857

Variable importance
Petal.Width Petal.Length Sepal.Length Sepal.Width
          34           32           21           13

Node number 1: 105 observations,    complexity param=0.5294118
predicted class=virginica expected loss=0.647619 P(node) =1
  class counts:    36    32    37
probabilities: 0.343 0.305 0.352
left son=2 (36 obs) right son=3 (69 obs)
Primary splits:
  Petal.Length < 2.45 to the left, improve=35.54783, (0 missing)
  Petal.Width < 0.8 to the left, improve=35.54783, (0 missing)
  Sepal.Length < 5.45 to the left, improve=24.79179, (0 missing)
  Sepal.Width < 3.25 to the right, improve=12.34670, (0 missing)
Surrogate splits:
  Petal.Width < 0.8 to the left, agree=1.000, adj=1.000, (0 split)
  Sepal.Length < 5.45 to the left, agree=0.924, adj=0.778, (0 split)
  Sepal.Width < 3.25 to the right, agree=0.819, adj=0.472, (0 split)

Node number 2: 36 observations
predicted class=setosa expected loss=0 P(node) =0.3428571
  class counts:    36     0     0
probabilities: 1.000 0.000 0.000

Node number 3: 69 observations,    complexity param=0.3970588
predicted class=virginica expected loss=0.4637681 P(node) =0.6571429
  class counts:     0    32    37
probabilities: 0.000 0.464 0.536
left son=6 (35 obs) right son=7 (34 obs)
Primary splits:
  Petal.Width < 1.75 to the left, improve=25.291950, (0 missing)
  Petal.Length < 4.75 to the left, improve=25.187810, (0 missing)
  Sepal.Length < 6.15 to the left, improve= 5.974246, (0 missing)
  Sepal.Width < 2.45 to the left, improve= 2.411006, (0 missing)
Surrogate splits:
  Petal.Length < 4.75 to the left, agree=0.913, adj=0.824, (0 split)
  Sepal.Length < 6.15 to the left, agree=0.696, adj=0.382, (0 split)
  Sepal.Width < 2.65 to the left, agree=0.638, adj=0.265, (0 split)

Node number 6: 35 observations
predicted class=versicolor expected loss=0.1142857 P(node) =0.3333333
  class counts:     0    31     4
probabilities: 0.000 0.886 0.114

Node number 7: 34 observations
predicted class=virginica expected loss=0.02941176 P(node) =0.3238095
  class counts:     0     1    33
probabilities: 0.000 0.029 0.971

      Actual
Predicted setosa versicolor virginica
setosa      14         0         0
versicolor   0        18         1
virginica    0         0        12
Accuracy: 97.77778 %

```

RESULT:

Thus, to implement the SVM / Decision Tree Classification Techniques are completed successfully.