



IMAGE COLORIZATION

Group 28:

Abhinav Mishra (160101005)

Namit Kumar (160101046)

Ritik Agrawal (160101055)

Saurabh Bazari (160101061)

G. Sharath Kumar (150101023)



Contents

- Introduction
- Literature Survey
 - Image Colorization using CNNs and Inception-Resnet-v2
 - Automatic Temporally Coherent Video Colorization
 - Infrared Image Colourization Using an S-Shape Network
 - Learning To Color From Language
 - NIR to RGB Domain Translation Using Asymmetric Cyclic Generative Adversarial Networks
 - Near-Infrared Imagery Colorization

Introduction

- What is Image Colorization ?
- Possible problem scenarios
- Different architectures





Image Colorization using CNNs and Inception-Resnet-v2:






Image Colorization using CNNs and Inception-Resnet-v2:

- Mapping L^* to a^*b^*
- Pre-trained model used



Automatic Temporally Coherent Video Colorization:

- Convert Grayscale or line sketch images to colored images using pervious coloured image.
- Using a U-net based GAN(Baseline).
- Use Style Loss, Content Loss, L1 Loss, etc.



Automatic Temporally Coherent Video Colorization:


- Effect of Losses



- When any new character is introduced
- Repetition of incorrect colourization

Infrared Image Colourization Using an S-Shape Network:

- Architecture
 - ColorNet
 - EdgeNet



Learning To Color From Language:


- Benefits of using caption for colourization



An orange dog
sitting on a blue
couch

A grey dog sitting on
a green couch

Example



Architecture

Learning To Color From Language:

- Limitation
- Scope of Improvement




Ground-truth image

FCNN output

FILM conditioned on
"a school bus driving on
the road"

NIR to RGB Domain Translation Using Asymmetric Cycle GAN:

- NIR to RGB Conversion
- Use of Asymmetric Cyclic GAN



NIR to RGB Domain Translation Using Asymmetric Cycle GAN:





FIGURE 1. NIR to RGB domain translation using asymmetric cycle GAN, redrawn from [14]. Single directional model often calculates L_1 norm $L(fake B, real B)$ as training loss. When *real A* is not registered with *real B*, the training loss is confused by unregistration but the cyclic loss $L(real A, F(G(real A)))$ is unaffected by unregistration.



Near-Infrared Imagery Colorization:

Conditional Generative Adversarial Network Model :




Fig. 1. Illustration of the proposed triplet GAN architecture used for NIR image colorization.