

```
# Start MongoDB server (in terminal)
mongod
```

```
# Open MongoDB shell (new terminal)
mongo
```

```
use studentDB // Switches to/create studentDB
```

```
db.createCollection("students") // Creates 'students' collection
```

```
// Single document
db.students.insertOne({
  rollno: 1,
  name: "Ravi",
  marks: 85
})
```

```
// Multiple documents
db.students.insertMany([
  {rollno: 2, name: "Sneha", marks: 90},
  {rollno: 3, name: "Amit", marks: 75},
  {rollno: 4, name: "Priya", marks: 82},
  {rollno: 5, name: "Karan", marks: 60, status: "pass"}
])
```

```
// All documents
db.students.find()
```

```
// Specific rollno
db.students.find({rollno: 2})
```

```
// Marks > 80
db.students.find({marks: {$gt: 80}})
```

```
// Status = "pass"
db.students.find({status: "pass"})
```

```
// Update one document
db.students.updateOne(
  {rollno: 3},
  {$set: {marks: 80}}
```

)

// Update multiple documents

db.students.updateMany(
 {marks: {\$lt: 65}},
 {\$set: {status: "fail"}}
)

// Delete one document

db.students.deleteOne({rollno: 1})

// Delete multiple documents

db.students.deleteMany({status: "fail"})

[

{ "_id": ObjectId("..."), "rollno": 1, "name": "Ravi", "marks": 85 },

{ "_id": ObjectId("..."), "rollno": 2, "name": "Sneha", "marks": 90 },

{ "_id": ObjectId("..."), "rollno": 3, "name": "Amit", "marks": 75 },

{ "_id": ObjectId("..."), "rollno": 4, "name": "Priya", "marks": 82 },

{ "_id": ObjectId("..."), "rollno": 5, "name": "Karan", "marks": 60, "status": "pass" }

]