



Experiment No.6
Data Stream Algorithms: Implement Bloom filter algorithm using any programming language
Date of Performance: 06/09/23
Date of Submission: 13/09/23



**AIM :**

Data Stream Algorithms:

Implement bloom filter algorithm using any programming language

**THEORY :**

Bloom filter algorithm approximates the number of unique objects in a stream or a database in one pass. If the stream contains  $n$  elements with  $m$  of them unique, this algorithm runs in  $O(n)$  time and needs  $O(\log(m))$  memory.

**Algorithm :**

1. Create a bit vector (bit array) of sufficient length  $L$ , such that  $2L > n$ , the number of elements in the stream. Usually a 64-bit vector is sufficient since 264 is quite large for most purposes.
2. The  $i$ -th bit in this vector/array represents whether we have seen a hash function value whose binary representation ends in  $0i$ . So initialize each bit to 0.
3. The  $i$ -th bit in this vector/array represents whether we have seen a hash function value whose binary representation ends in  $0i$ . So initialize each bit to 0.
4. The  $i$ -th bit in this vector/array represents whether we have seen a hash function value whose binary representation ends in  $0i$ . So initialize each bit to 0.
5. Once input is exhausted, get the index of the first 0 in the bit array (call this  $R$ ). By the way, this is just the number of consecutive 1s (i.e. we have seen  $0, 00, \dots, 0R-1$  as the output of the hash function) plus one.
6. Calculate the number of unique words as  $2R/\phi$ , where  $\phi$  is 0.77351. A proof for this can be found in the original paper listed in the reference section.
7. The standard deviation of  $R$  is a constant:  $\sigma(R) = 1.12$ . (In other words,  $R$  can be off by about 1 for 1 - 0.68 = 32% of the observations, off by 2 for about 1 - 0.95 = 5% of the observations, off by 3 for 1 - 0.997 = 0.3% of the observations using the Empirical rule of statistics). This implies that our count can be off by a factor of 2 for 32% of the observations, off by a factor of 4 for 5% of the observations, off by a factor of 8 for 0.3% of the observations and so on.



**CODE :**

```
n = 20 #no of items to add
p = 0.05 #false positive probability

bloomf = BloomFilter(n,p)
print("Size of bit array:{ }".format(bloomf.size))
print("False positive Probability:{ }".format(bloomf.fp_prob))
print("Number of hash functions:{ }".format(bloomf.hash_count))

# words to be added
word_present = ['abound','abounds','abundance','abundant','accessible',
                'bloom','blossom','bolster','bonny','bonus','bonuses',
                'coherent','cohesive','colorful','comely','comfort',
                'gems','generosity','generous','generously','genial']

# word not added
word_absent = ['bluff','cheater','hate','war','humanity',
               'racism','hurt','nuke','gloomy','facebook',
               'geeksforgeeks','twitter']

for item in word_present:
    bloomf.add(item)

shuffle(word_present)
shuffle(word_absent)

test_words = word_present[:10] + word_absent
shuffle(test_words)
for word in test_words:
    if bloomf.check(word):
        if word in word_absent:
            print("{} is a false positive!".format(word))
        else:
            print("{} is probably present!".format(word))
    else:
        print("{} is definitely not present!".format(word))
```



## Output:

```
ubuntu@ubuntu-HP-Elite-Tower-600-G9-Desktop-PC:~/bloomfilter$ python3 bloom_test.py
Size of bit array:124
False positive Probability:0.05
Number of hash functions:4
'gloomy' is definitely not present!
'cohesive' is probably present!
'geeksforgeeks' is definitely not present!
'hate' is definitely not present!
'bluff' is definitely not present!
'abundant' is probably present!
'nuke' is definitely not present!
'twitter' is a false positive!
'cheater' is definitely not present!
'accessible' is probably present!
'bonus' is probably present!
'generosity' is probably present!
'comely' is probably present!
'genial' is probably present!
'humanity' is a false positive!
'comfort' is probably present!
'war' is definitely not present!
'generous' is probably present!
'bolster' is probably present!
'facebook' is definitely not present!
'hurt' is definitely not present!
'racism' is definitely not present!
ubuntu@ubuntu-HP-Elite-Tower-600-G9-Desktop-PC:~/bloomfilter$
```



### **CONCLUSION:**

The Bloom filter stands out as a compact data structure designed for membership testing. It comes into its own when working with substantial data sets, where allowing for occasional false positives is tolerable. Nevertheless, it does come with the caveat of potential false positives, which means it can incorrectly identify an element as part of the set when it isn't. The delicate balance between space efficiency and the likelihood of false positives hinges on the number of hash functions and the size of the bit array used. Bloom filters find common application in scenarios like network routers, spell checkers, and distributed systems, particularly when memory resources are constrained, and there's a need for swift membership tests.