

▼ Principal Component Analysis (PCA)

▼ Importing the libraries

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

▼ Importing the dataset

```
dataset = pd.read_csv('Wine.csv')
X = dataset.iloc[:, :-1].values
y = dataset.iloc[:, -1].values
```

▼ Splitting the dataset into the Training set and Test set

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.2, random
```

▼ Feature Scaling

```
from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)
```

▼ Applying PCA

```
from sklearn.decomposition import PCA
pca = PCA(n_components = 2)
X_train = pca.fit_transform(X_train)
X_test = pca.transform(X_test)
```

▼ Training the Logistic Regression model on the Training set

```
from sklearn.linear_model import LogisticRegression
classifier = LogisticRegression(random_state = 0)
classifier.fit(X_train, y_train)
```

```
↳ LogisticRegression(C=1.0, class_weight=None, dual=False, fit_intercept=True,
                    intercept_scaling=1, l1_ratio=None, max_iter=100,
                    multi_class='auto', n_jobs=None, penalty='l2',
                    random_state=0, solver='lbfgs', tol=0.0001, verbose=0,
                    warm_start=False)
```

▼ Making the Confusion Matrix

```
from sklearn.metrics import confusion_matrix, accuracy_score
y_pred = classifier.predict(X_test)
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)
```


```
↳ [[14  0  0]
    [ 1 15  0]
    [ 0  0  6]]
0.9722222222222222
```

▼ Visualising the Training set results

```
from matplotlib.colors import ListedColormap
X_set, y_set = X_train, y_train
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].
                          np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()])).T).res
               alpha = 0.75, cmap = ListedColormap(('red', 'green', 'blue')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green', 'blue'))(i), label = j)
plt.title('Logistic Regression (Training set)')
plt.xlabel('PC1')
plt.ylabel('PC2')
plt.legend()
plt.show()
```

```
↳
```

```
*c* argument looks like a single numeric RGB or RGBA sequence, which should be avoided :
*c* argument looks like a single numeric RGB or RGBA sequence, which should be avoided :
*c* argument looks like a single numeric RGB or RGBA sequence, which should be avoided :
```



▼ Visualising the Test set results

```
from matplotlib.colors import ListedColormap
X_set, y_set = X_test, y_test
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].
                        np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).res
              alpha = 0.75, cmap = ListedColormap(('red', 'green', 'blue')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green', 'blue'))(i), label = j)
plt.title('Logistic Regression (Test set)')
plt.xlabel('PC1')
plt.ylabel('PC2')
plt.legend()
plt.show()
```



```
*c* argument looks like a single numeric RGB or RGBA sequence, which should be avoided :  
*c* argument looks like a single numeric RGB or RGBA sequence, which should be avoided :  
*c* argument looks like a single numeric RGB or RGBA sequence, which should be avoided :
```

