# Natural Language Processing

### ▼ Importing the libraries

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

## Importing the dataset

```
dataset=pd.read csv('/content/Restaurant Reviews.tsv', delimiter='\t', quoting=3 )
```

## Cleaning the texts

```
import re
import nltk
nltk.download("stopwords")
from nltk.corpus import stopwords
from nltk.stem.porter import PorterStemmer
corpus= []
for i in range(0,1000):
 review=re.sub('[^a-zA-Z]',' ',dataset['Review'][i])
 review=review.lower()
 review=review.split()
 ps=PorterStemmer()
 all_stopwords=stopwords.words('english')
 all stopwords.remove('not')
 review=[ps.stem(word) for word in review if not word in set(all_stopwords)]
 review=" ".join(review)
 corpus.append(review)
    [nltk data] Downloading package stopwords to /root/nltk data...
     [nltk data] Package stopwords is already up-to-date!
print(corpus)
    ['wow love place', 'crust not good', 'not tasti textur nasti', 'stop late may bank holic
```

## Creating the Bag of Words model

```
from sklearn.feature_extraction.text import CountVectorizer
cv=CountVectorizer(max_features=1500)
X=cv.fit_transform(corpus).toarray()
y=dataset.iloc[:, -1].values
len(X[0])
```

Splitting the dataset into the Training set and Test set

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.20, random_state = 0)
```

▼ Training the Naive Bayes model on the Training set

```
from sklearn.naive_bayes import GaussianNB
classifier = GaussianNB()
classifier.fit(X_train, y_train)

□→ GaussianNB(priors=None, var_smoothing=1e-09)
```

Predicting the Test set results

```
y_pred = classifier.predict(X_test)
print(np.concatenate((y_pred.reshape(len(y_pred),1), y_test.reshape(len(y_test),1)),1))
```

Making the Confusion Matrix

```
from sklearn.metrics import confusion_matrix, accuracy_score
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)

[55 42]
     [12 91]]
0.73
```