

▼ Decision Tree Classification

▼ Importing the libraries

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

▼ Importing the dataset

```
dataset = pd.read_csv('Social_Network_Ads.csv')
X = dataset.iloc[:, -3:-1].values
y = dataset.iloc[:, -1].values
```

▼ Splitting the dataset into the Training set and Test set

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_state = 0)

print(X_train)

print(y_train)

print(X_test)

print(y_test)
```

▼ Feature Scaling

```
from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)

print(X_train)

print(X_test)
```

▼ Training the Decision Tree Classification model on the Training set

```
from sklearn.tree import DecisionTreeClassifier
classifier=DecisionTreeClassifier(criterion='entropy',random_state=0)
classifier.fit(X_train,y_train)
```

```
↳ DecisionTreeClassifier(ccp_alpha=0.0, class_weight=None, criterion='entropy',
                          max_depth=None, max_features=None, max_leaf_nodes=None,
                          min_impurity_decrease=0.0, min_impurity_split=None,
                          min_samples_leaf=1, min_samples_split=2,
                          min_weight_fraction_leaf=0.0, presort='deprecated',
                          random_state=0, splitter='best')
```

▼ Predicting a new result

```
print(classifier.predict(sc.transform([[30,87000]])))
```

```
↳ [0]
```

▼ Predicting the Test set results

```
y_pred = classifier.predict(X_test)
print(np.concatenate((y_pred.reshape(len(y_pred),1), y_test.reshape(len(y_test),1)),1))
```

▼ Making the Confusion Matrix

```
from sklearn.metrics import confusion_matrix, accuracy_score
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)
```

```
↳ [[62  6]
     [ 3 29]]
0.91
```

▼ Visualising the Training set results


```
from matplotlib.colors import ListedColormap
X_set, y_set = sc.inverse_transform(X_train, y_train)
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 10, stop = X_set[:, 0].max() + 10,
                              np.arange(start = X_set[:, 1].min() - 1000, stop = X_set[:, 1].max() + 1
```

```

plt.contourf(X1, X2, classifier.predict(sc.transform(np.array([X1.ravel(), X2.ravel()]).T)).r
            alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1], c = ListedColormap(('red', 'greer
plt.title('Decision Tree Classification (Training set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()

```

→ 'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided a
 'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided a



▼ Visualising the Test set results

```

from matplotlib.colors import ListedColormap
X_set, y_set = sc.inverse_transform(X_test), y_test
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 10, stop = X_set[:, 0].max() + 10,
                           np.arange(start = X_set[:, 1].min() - 1000, stop = X_set[:, 1].max() + 1
plt.contourf(X1, X2, classifier.predict(sc.transform(np.array([X1.ravel(), X2.ravel()]).T)).r
            alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1], c = ListedColormap(('red', 'greer
plt.title('Decision Tree Classification (Test set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()

```

↳ 'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided a
'c' argument looks like a single numeric RGB or RGBA sequence, which should be avoided a

