



## ▼ Grid Search

## ▼ Importing the libraries

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd
```

## ▼ Importing the dataset

```
dataset = pd.read_csv('Social_Network_Ads.csv')
X = dataset.iloc[:, 2:-1].values
y = dataset.iloc[:, -1].values
```

## ▼ Splitting the dataset into the Training set and Test set

```
from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size = 0.25, random_state = 0)
```

## ▼ Feature Scaling

```
from sklearn.preprocessing import StandardScaler
sc = StandardScaler()
X_train = sc.fit_transform(X_train)
X_test = sc.transform(X_test)
```

## ▼ Training the Kernel SVM model on the Training set

```
from sklearn.svm import SVC
classifier = SVC(kernel = 'rbf', random_state = 0)
classifier.fit(X_train, y_train)
```



Filter

3

User ID

156245

158109

156685

156032

158040

157287

155980

156948

156005

157273

Show

10 ▼

per

page

1

2

10

30

40

```
SVC(C=1.0, break_ties=False, cache_size=200, class_weight=None, coef0=0.0,
```

## ▼ Making the Confusion Matrix

```
from sklearn.metrics import confusion_matrix, accuracy_score
y_pred = classifier.predict(X_test)
cm = confusion_matrix(y_test, y_pred)
print(cm)
accuracy_score(y_test, y_pred)
```

```
↳ [[64  4]
    [ 3 29]]
0.93
```

## ▼ Applying k-Fold Cross Validation

```
from sklearn.model_selection import cross_val_score
accuracies = cross_val_score(estimator = classifier, X = X_train, y = y_train, cv
print("Accuracy: {:.2f} %".format(accuracies.mean()*100))
print("Standard Deviation: {:.2f} %".format(accuracies.std()*100))
```

```
↳ Accuracy: 90.33 %
   Standard Deviation: 6.57 %
```

## ▼ Applying Grid Search to find the best model and the best parameters

```
from sklearn.model_selection import GridSearchCV
parameters = [{'C': [0.25, 0.5, 0.75, 1], 'kernel': ['linear']},
               {'C': [0.25, 0.5, 0.75, 1], 'kernel': ['rbf'], 'gamma': [0.1, 0.2,
grid_search = GridSearchCV(estimator = classifier,
                           param_grid = parameters,
                           scoring = 'accuracy',
                           cv = 10,
                           n_jobs = -1)
grid_search.fit(X_train, y_train)
best_accuracy = grid_search.best_score_
best_parameters = grid_search.best_params_
print("Best Accuracy: {:.2f} %".format(best_accuracy*100))
print("Best Parameters:", best_parameters)
```

```
↳ Best Accuracy: 90.67 %
   Best Parameters: {'C': 0.5, 'gamma': 0.6, 'kernel': 'rbf'}
```


## ▼ Visualising the Training set results

```

from matplotlib.colors import ListedColormap
X_set, y_set = X_train, y_train
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1, step = 0.5),
                      np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1, step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
             alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())
plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('Kernel SVM (Training set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')

```

✖ `*c*` argument looks like a single numeric RGB or RGBA sequence, which should be  
 ✖ `*c*` argument looks like a single numeric RGB or RGBA sequence, which should be



## ▼ Visualising the Test set results

```

from matplotlib.colors import ListedColormap
X_set, y_set = X_test, y_test
X1, X2 = np.meshgrid(np.arange(start = X_set[:, 0].min() - 1, stop = X_set[:, 0].max() + 1, step = 0.5),
                      np.arange(start = X_set[:, 1].min() - 1, stop = X_set[:, 1].max() + 1, step = 0.5))
plt.contourf(X1, X2, classifier.predict(np.array([X1.ravel(), X2.ravel()]).T).reshape(X1.shape),
             alpha = 0.75, cmap = ListedColormap(('red', 'green')))
plt.xlim(X1.min(), X1.max())

```

```

plt.ylim(X2.min(), X2.max())
for i, j in enumerate(np.unique(y_set)):
    plt.scatter(X_set[y_set == j, 0], X_set[y_set == j, 1],
                c = ListedColormap(('red', 'green'))(i), label = j)
plt.title('Kernel SVM (Test set)')
plt.xlabel('Age')
plt.ylabel('Estimated Salary')
plt.legend()
plt.show()

```

☞ \*c\* argument looks like a single numeric RGB or RGBA sequence, which should be  
 \*c\* argument looks like a single numeric RGB or RGBA sequence, which should be

