

Question - 1

Kubernetes Two or More Instructions

You are composing a Kubernetes scenario file in YAML format. You want to put more than one instruction inside one file. How can this be achieved?

- ☐ # namespace creation instruction
(one or more space)
pod creation instruction
- ☐ # namespace creation instruction

pod creation instruction
- ☐ # namespace creation instruction
pod creation instruction
- ☐ There is no way to put more that one instruction per file.

Question - 2

Kubernetes Run Command

After setting up a Kubernetes cluster, you want to run the package manager update process in a particular pod. How this can be achieved?

- ☐ kubectl run pod/frontend-controller-01 --cmd="apt-get update"
- ☐ kubectl exec pod/frontend-controller-01 --cmd="apt-get update"
- ☐ kubectl run pod/frontend-controller-01 -- apt-get update
- ☐ kubectl exec pod/frontend-controller-01 -- apt-get update

Question - 3

Kubernetes Pod Logs

After a rollback to the previous deployment of a Kubernetes service, you need to fetch the last log entries of all the pods marked with a specific "publisher" label. What is the correct way to do this?

- ☐ kubectl logs --last=10 -l publisher=hacker-company
- ☐ kubectl get logs --count=10 --selector="publisher=hacker-company"
- ☐ kubectl logs --tail=10 -l publisher=hacker-company
- ☐ kubectl get logs --count=-10 -l publisher=hacker-company

Question - 4

Kubernetes Find Documentation

While refactoring an existing Kubernetes cluster, you want to create a new service but you have forgotten the resource schema. How can you get a short explanation of a specific resource definition?

- ☐ kubectl explain service
- ☐ kubectl help service
- ☐ kubectl describe service
- ☐ kubectl expose service

Question - 5

Kubernetes Get Deployment Information

While optimizing an existing Kubernetes cluster, you need to get extended information about the deployment named "hacker-application". How can you do this?

- ☐ kubectl describe deployment hacker-application
- ☐ kubectl expose deployment hacker-application
- ☐ kubectl explain deployment hacker-application
- ☐ none of the above

Question - 6

Kubernetes Pods Query

As part of your Kubernetes cluster maintenance process, you need to find out all the pods working in the staging environment. You know each pod has a specific label named "environment" which refers to a particular environment name. How can you get all the pods with the label "environment=staging"?

- ☐ kubectl get pods --label environment=staging
- ☐ kubectl get pods --selector=environment=staging
- ☐ kubectl label environment=staging
- ☐ kubectl expose pods environment=staging

Question - 7

Kubernetes Labels & Annotations

You are replicating an existing production deployment on staging. As part of this process, you have decided to attach an environment-oriented label and set annotation. How can you do this?

- ☐ kubectl attach label deployment hacker-application environment=staging
kubectl set annotation deployment hacker-application url="https://staging.hacker-company.com"

- ☐ kubect! set label deployment hacker-application environment=staging
kubect! set annotation deployment hacker-application url="https://staging.hacker-company.com"
- ☐ kubect! label deployment hacker-application environment=staging
kubect! annotate deployment hacker-application url="https://staging.hacker-company.com"
- ☐ kubect! create label deployment hacker-application environment=staging
kubect! create annotation deployment hacker-application url="https://staging.hacker-company.com"

Question - 8

Kubernetes Basic Pod

As the next part of your Kubernetes cluster maintenance, you want to test that everything still works properly. For a quick check, you want to execute a test image run. What is the right command?

- ☐ kubect! exec --image=hello-world test
- ☐ kubect! exec --rm -i --image=hello-world --restart=Never test
- ☐ kubect! create image hello-world
- ☐ kubect! run --rm -i --image=hello-world --restart=Never test

Question - 9

Kubernetes Deployment Scale

While maintaining your company's Kubernetes cluster, you found that Redis deployment should be scaled according to the metrics you see. What command should be executed to scale operation up to 3 (increase the number of ReplicaSets)?

- ☐ kubect! scale --replicas=3 -n hacker-company ReplicaSet/redis
- ☐ kubect! scale --number=3 -n hacker-company ReplicaSet/redis
- ☐ kubect! scale --to=3 -n hacker-company ReplicaSet/redis
- ☐ kubect! patch --set="replicas=3" -n hacker-company ReplicaSet/redis

Question - 10

Kubernetes Pods Status

You are working on one of your company's existing Kubernetes clusters. You want to retrieve information about all the pods you have for a specific namespace. Which of these commands will achieve this?

- ☐ kubect! explain pods hacker-company
- ☐ kubect! explain pods -n hacker-company
- ☐ kubect! get pods -n hacker-company
- ☐ kubect! expose pods -n hacker-company