



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

| |
|--|
| Experiment No. 8 |
| Single Source Shortest Path using Dynamic Programming (Bellman-Ford Algorithm) |
| Date of Performance: |
| Date of Submission: |

Experiment No: 8

Title: Single Source Shortest Path: Bellman Ford

Aim: To study and implement Single Source Shortest Path using Dynamic Programming: Bellman Ford

Objective: To introduce Bellman Ford method

Theory:

Given a graph and a source vertex source in graph, find shortest paths from src to all vertices in the given graph. The graph may contain negative weight edges. We have discussed Dijkstra's algorithm for this problem. Dijkstra's algorithm is a Greedy algorithm and time complexity is $O(V \log V)$ (with the use of Fibonacci heap). Dijkstra doesn't work for Graphs with negative weight edges, Bellman-Ford works for such graphs. Bellman-Ford is also simpler than Dijkstra and suites well for distributed systems. But time complexity of Bellman-Ford is $O(VE)$, which is more than Dijkstra.

Example:


Let the given source vertex be 0. Initialize all distances as infinite, except the distance to the source itself. Total number of vertices in the graph is 5, so all edges must be processed 4 times.



Vidyavardhini's College of Engineering and Technology


Department of Artificial Intelligence & Data Science

| A | B | C | D | E |
|---|----------|----------|----------|----------|
| 0 | ∞ | ∞ | ∞ | ∞ |



Let all edges are processed in the following order: (B, E), (D, B), (B, D), (A, B), (A, C), (D, C), (B, C), (E, D). We get the following distances when all edges are processed the first time. The first row shows initial distances. The second row shows distances when edges (B, E), (D, B), (B, D) and (A, B) are processed. The third row shows distances when (A, C) is processed. The fourth row shows when (D, C), (B, C) and (E, D) are processed.

| A | B | C | D | E |
|---|----------|----------|----------|----------|
| 0 | ∞ | ∞ | ∞ | ∞ |
| 0 | -1 | ∞ | ∞ | ∞ |
| 0 | -1 | 4 | ∞ | ∞ |
| 0 | -1 | 2 | ∞ | ∞ |
| 0 | -1 | 2 | ∞ | 1 |
| 0 | -1 | 2 | 1 | 1 |
| 0 | -1 | 2 | -2 | 1 |




The second iteration guarantees to give all shortest paths which are at most 2 edges long. The algorithm processes all edges 2 more times. The distances are minimized after the second iteration, so third and fourth iterations don't update the distances.



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science



Algorithm:

```
function Bellman_Ford(list vertices, list edges, vertex source, distance[], parent[])
```

```
// Step 1 – initialize the graph. In the beginning, all vertices weight of  
// INFINITY and a null parent, except for the source, where the weight is 0
```

```
for each vertex v in vertices  
    distance[v] = INFINITY  
    parent[v] = NULL
```

```
distance[source] = 0
```

```
// Step 2 – relax edges repeatedly  
for i = 1 to V-1 // V – number of vertices  
    for each edge (u, v) with weight w  
        if (distance[u] + w) is less than distance[v]  
            distance[v] = distance[u] + w  
            parent[v] = u
```

```
// Step 3 – check for negative-weight cycles
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
for each edge (u, v) with weight w
    if (distance[u] + w) is less than distance[v]
        return "Graph contains a negative-weight cycle"
```

```
return distance[], parent[]
```

Output:

Shortest path from source (5)

Vertex 5 -> cost=0 parent=0

Vertex 1 -> cost=6 parent=2

Vertex 2 -> cost=3 parent=4

Vertex 3 -> cost =3 parent =4

Vertex 4 -> cost =2 paren=5

Implementation: `#include <stdio.h>`

`#include <stdlib.h>`

`#include <limits.h>`

`// Structure to represent a weighted edge in the graph`

`struct Edge {`

`int src, dest, weight;`

`};`

`// Structure to represent a directed, weighted graph`

`struct Graph {`

`int V, E;`

`struct Edge* edge;`



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
};
```

```
// Create a graph with V vertices and E edges
```

```
struct Graph* createGraph(int V, int E) {  
    struct Graph* graph = (struct Graph*)malloc(sizeof(struct Graph));  
    graph->V = V;  
    graph->E = E;  
    graph->edge = (struct Edge*)malloc(E * sizeof(struct Edge));  
    return graph;  
}
```

```
// Bellman-Ford algorithm function
```

```
void BellmanFord(struct Graph* graph, int src) {  
    int V = graph->V;  
    int E = graph->E;  
    int dist[V];  
  
    // Initialize distances from source to all other vertices as INFINITE  
    for (int i = 0; i < V; i++)  
        dist[i] = INT_MAX;  
    dist[src] = 0;  
  
    // Relax all edges V-1 times  
    for (int i = 1; i <= V - 1; i++) {  
        for (int j = 0; j < E; j++) {  
            int u = graph->edge[j].src;  
            int v = graph->edge[j].dest;  
            int weight = graph->edge[j].weight;  
            if (dist[u] != INT_MAX && dist[u] + weight < dist[v])  
                dist[v] = dist[u] + weight;  
        }  
    }  
}
```



```
    }
}

// Check for negative weight cycles
for (int i = 0; i < E; i++) {
    int u = graph->edge[i].src;
    int v = graph->edge[i].dest;
    int weight = graph->edge[i].weight;
    if (dist[u] != INT_MAX && dist[u] + weight < dist[v]) {
        printf("Graph contains negative weight cycle\n");
        return;
    }
}

// Print shortest distances
printf("Vertex  Distance from Source\n");
for (int i = 0; i < V; ++i)
    printf("%d \t\t %d\n", i, dist[i]);
}

int main() {
    int V, E, src;
    printf("Enter number of vertices and edges: ");
    scanf("%d %d", &V, &E);

    struct Graph* graph = createGraph(V, E);

    printf("Enter source vertex: ");
    scanf("%d", &src);
```



Vidyavardhini's College of Engineering and Technology

Department of Artificial Intelligence & Data Science

```
printf("Enter edge details (source destination weight):\n");  
for (int i = 0; i < E; i++)  
    scanf("%d %d %d", &graph->edge[i].src, &graph->edge[i].dest,  
&graph->edge[i].weight);  
  
BellmanFord(graph, src);  
  
return 0;  
}
```

Conclusion: Single Source Shortest Path: Bellman Ford has been successfully implemented.