# Embedded Software Essentials


Makefiles Part 2

C1 M2 V8

## Copyright

 Copyright (C) 2017 by Alex Fosdick. Redistribution, modification or use of this presentation is permitted as long as the files maintain this copyright. Users are permitted to modify this and use it to learn about the field of embedded software. Alex Fosdick and the University of Colorado are not liable for any misuse of this material.

# Build System [S1]



#### Makefile Variables [S2]

- Makes Makefile dynamic & eliminates text duplication
  - Variables can use other variables

```
CPU=cortex-m0plus
ARCH=thumb
SPECS=nosys.specs
```

Recursively expanded variables (=)

Variables are expanded when variable is substituted in

```
PLATFORM_FLAGS:=-m$(ARCH) \
-mcpu=$(CPU) \
-specs=$(SPECS)
```

**Simply Expanded Variables (:=)** 

Variables are expanded once at time of the variable definition

#### Pattern Matching [S3]

- Pattern Matching Operator %
  - Pattern matches a target object rule with an associated source file

```
%.o: %.c
$ (CC) -c $^ -o $@ $ (CFLAGS)

$ make main.o → Make uses a pattern match rule to match a target
```

main.o: main.c
\$(CC) -c main.c -o main.o \$(CFLAGS)

#### Pattern Matching [S4]

Pattern Matches are dynamic




 Can use source variables (SRCS) to generate a list of object files variable (OBJS)

```
SRCS:= main.c \
    my_file.c \
    my_memory.c
OBJS:= main.o \
    my_file.o \
    my_memory.o
```

## Target Suggestions [S5]

- Targets do NOT have to be a file
  - Need to have a .PHONY directive



all – Builds final executable binary

clean – Removes all generated and object files

debug – Builds a debug image with debug symbols enabled

→ Whatever you want!!!

#### Functions & Dynamic Variables [S6]

- Can use make functions to process info
  - Output goes into variables
  - shell, file, origin, conditional, etc
- Shell functions are one form command expansion that can gather data from the system outside of make
  - Use the syntax \$(shell command)

Use conditional statements to change flags

```
$(function arguments)
```

#### **Shell Command Variables**

```
ARCH:=$(shell arch)
CWD:=$(shell pwd)
OS:=$(shell uname)
```

#### **Example Conditional**

#### Overriding Variables [S7]

- Pass input parameters into make to alter build
  - Architecture to build for
  - CPU
  - Platform/Board
  - Compiler Instance
  - Compiler/Linker Options

```
$ make all PLATFORM=msp432
$ make all CPU=cortex-m4
$ make all ARCH=arm
```

```
Input can set variables or be used conditionally
```



```
ifeq ($(PLATFORM),MSP)
    CPU=cortex-m4
endif
```

```
ifeq($(PLATFORM),FRDM)
    CPU=cortex-m0plus
endif
```

#### Overriding Variables [S8]

 By making a target variable based, you can change/alter flags for linker or compiler

```
main.elf: main.o file.o foo.o uart.o
    gcc -Wall -I./inc -Wl,-Map=main.map -o main.elf $^

$(TARGET): $(OBJS)
    $(CC) $(CFLAGS) $(INCLUDES) $(LDFLAGS) -o $(TARGET) $(OBJS)
```

Can make our target rules extremely generic yet dynamic!

## Special Variables [S9]

- Variables implicitly used by make
  - CC Compiler
  - CPP Preprocessor Program
  - AS Assembler Program
  - LD -Linker
  - CFLAGS C program Flags
  - CPPFLAGS C Preprocessor Flags
  - ASFLAGS Flags for Assembler
  - LDFLAGS C program Linker Flags
  - LDLIBS Extra flags for Llbraries

Make has internal rules it uses for targets not defined You provide the flags

## Version Controlled Build System [S10]

