




```
temp.setNext(start.getNext());
start.setNext(temp);
```

Introduction to Graphs :→

Binary Search Applications :

(I) First Occurrence
(II) Last Occurrence
(III) Total Occurrence $(L - F + 1)$

[1, 2, 2, 2, 3, 4, 5]
0 1 2 3 4 5 6

3 → F 0 → 2
3 → L 0 → 4 — L-F+1
3 → T 0 → 4 - 2 + 1
2 + 1 = 3

* Find the missing element inside a sorted array using Binary Search :-

Note : 1 to n

arr[8] = [1, 2, 3, 5, 6, 7, 8] → 4
arr[8] = [1, 2, 3, 4, 5, 6, 7] → 8

[len + 1]
7 + 1 = 8

Binary Search



if left part :

(I) mid == 0
return mid + 1

(II) arr[mid - 1] == mid
return mid + 1

e = mid - 1 ;

arr[m] = m + 1
Right side s = m + 1

Graph Data Structure : → Un Weighted graph

(I) Nodes, Vertex
(II) Edges

Node → Entity whose we can store data as value.
Edge → It is the connection between two nodes/vertices







Components





Graph Representation :

(I) Adjacency Matrix
(II) Adjacency List



Adjacency Matrix

	0	1	2	3	4	5
0		1	0	1	0	
1	0		1	1	0	
2	1	0		0	1	1
3	0	1	0		1	
4	1	1	0	1		1
5		0	1	1	0	

Adjacency List

Nodes → List of Neighbours

0 →
1 → 2, 4
2 → 1, 3, 4
3 → 2, 4, 5
4 → 1, 2, 3, 5
5 → 2, 4

Set <> , unordered map
AD

C++, OOPs, Exception Handling
Arrays, quick sort → Heap Sort
Searching & Sorting
Stacks & queues → STL
Linked List → S, D, C
Trees → LT, BST, AVL, Heaps → CBT
Priority Queues

Graphs → Representations → AM, AL
Traversal → DFS, BFS
Cycle Detection → DFS, BFS
Algos → Dijkstra's, MST → Kruskal's

XXXX
2018
2018

Recursion → Back Tracking → (4) Training
TM 50 → Dynamic Programming
(I) (II) (III) → Bit Masking (5 - 6)
→ Problem Solving
30 questions