

Over-riding : $\rightarrow$ Parent $\rightarrow$ add() $\rightarrow$ logic

child $\rightarrow$ add() $\rightarrow$ changing the logic

Employee:

work() $\rightarrow$ checking mail, attend meetings, etc

Lecturer: work() $\rightarrow$ conducting classes, lectures, seminars.

Developer: work() $\rightarrow$ making apps, fixing bugs, etc.

"virtual" keyword helps in method over-riding because the compiler understands that the particular method is being over-riden.

Over-riding can be defined as inheriting the base class method but with a slight different implementation logic.

RBI $\rightarrow$ Rate of Interest $\rightarrow$ 6.2% (virtual)

ICICI 7.2
HDFC 6.9
AXIS 7.5
values 1 2 3

Over-riding

Mahalakshmi Sweets				
Mysoore Pak		50 years		
1 children		1 variety		
Cedew	Honey	Chnee	Milk	M P

Base Recipe

Extra Ingredients:

Abstraction:

Anvitha $\rightarrow$ Phone $\rightarrow$ [Friend] $\rightarrow$ 16, 26, 36, 46, 56

Chaitanya $\rightarrow$ Remote $\rightarrow$ TV $\rightarrow$ Technology? Infra-red Implementation

Abstraction $\rightarrow$ Hiding $\rightarrow$ How it is done.
Displaying $\rightarrow$ What is being done.
 $\rightarrow$ Functionality

Abstraction or Data Abstraction:

Hiding the implementation details & only showing the functionality to the end-user, is known as abstraction.

In C++, we don't have the similar concepts of abstract classes & interfaces like Java, therefore we use "Pure Virtual Functions" to achieve abstraction.

When a "Virtual Function" is initialized to '0', it is called a "Pure Virtual Functions".

* Exception Handling & Association:
(Learn) Templates:
Generics: