Soft Robotic Grippers using Tactile Sensor

Report submitted to

Indian Institute of Technology, Kharagpur

For the fulfillment of BTP-I in

Mechanical Engineering with specialisation in
Manufacturing Science and Engineering by

G. Chandana (23ME31008)
Shinde Sanchali Sanjay (23ME31029)
Saurav Shekhar (23ME31043)

Under the
Supervision of

Prof. Sankha Deb



Department of Mechanical Engineering
Indian Institute of Technology, Kharagpur - 721302

Certificate of Approval

This is to certify that the project report entitled **"Development, Non-linear Modeling, and Embedded Tactile Control of a 3D-Printed Compliant Soft Robotic Gripper"** submitted by **G. Chandana (23ME31008)**, **Shinde Sanchali Sanjay (23ME31029)**, and **Saurav Shekhar (23ME31043)** to the Indian Institute of Technology Kharagpur, for the partial fulfillment of the requirements for the award of the degree of *Bachelor of Technology in Mechanical Engineering (with specialization in Manufacturing Science and Engineering)*, is a bona fide record of the work carried out by them under my supervision and guidance.

The project is currently at the literature-review-completed stage, and the proposed methodology, numerical simulation framework, and experimental implementation roadmap have been thoroughly examined and approved for progression into Project Stage-II (BTP-II).

Prof. Sankha Deb
Supervisor
Department of Mechanical Engineering
Indian Institute of Technology, Kharagpur

Date: November 2026
Place: IIT Kharagpur

Abstract

Traditional robotic manipulation systems rely on rigid articulated linkages that exhibit high positioning repeatability but lack intrinsic compliance, rendering them prone to crushing delicate, fragile, or irregularly contoured objects in automated agriculture, biomedical packaging, and explosive ordnance handling. Soft robotic end-effectors address this limitation through structural deformability, enabling passive geometric conformity and safe contact pressure distribution. However, conventional soft grippers suffer from severe engineering bottlenecks: low payload capacity, material hysteresis, complex tethered fluidic supplies, sensor-skin delamination, and an absence of localized feedback capable of detecting incipient slip without bulky optical apparati.

This report establishes the complete Stage-I research foundation and detailed Stage-II implementation roadmap for a **Monolithic 3D-Printed (FDM TPU) Tendon-Driven Compliant Soft Robotic Gripper with Embedded Tactile Sensing**. Synthesizing an extensive multi-author literature corpus, the research evaluates fluidic elastomer actuators (PneuNets), shape memory alloys (Nitinol), and cable-driven compliant architectures. To overcome mold-tooling delays and fluid leakage risks, a direct additive manufacturing route using Thermoplastic Polyurethane (TPU 95A) is formulated, integrating circular flexure living hinges that eliminate mechanical joint backlash while maximizing structural fatigue life.

To provide deterministic grasp autonomy, thin-film Force Sensitive Resistors (FSR402) are integrated flush into the phalange contact pads. An integrated mechatronic architecture centered on a dual-core ESP32 executing FreeRTOS is developed. The tactile signal pipeline decouples static normal contact force estimation (via an active second-order low-pass Butterworth filter at $f_c = 20\ \text{Hz}$) from dynamic incipient slip micro-vibrations (via a 256-point Fast Fourier Transform analyzing the $100 - 300\ \text{Hz}$ spectral energy band). This enables closed-loop servomotor torque compensation in under 35 milliseconds. A non-linear finite element analysis (FEA) framework utilizing Mooney-Rivlin hyperelastic strain energy formulations is established to predict tip deflection and stress concentrations prior to physical fabrication. Finally, a structured 16-week semester roadmap is detailed, establishing quantitative benchmarks for pull-out retention force, payload-to-weight ratio, and an autonomous slip-prevention demonstration on physical hardware.

Keywords: Soft Robotics, Compliant Mechanisms, Additive Manufacturing, TPU 95A, Tactile Sensing, FSR402, Fast Fourier Transform, Incipient Slip Detection, FreeRTOS, Hyperelastic FEA.

Chapter 1: Introduction

1.1 Background of Soft Robotics and Compliant Manipulation

Robotic manipulation systems have traditionally been engineered around rigid mechanical kinematic chains composed of metallic or hard polymeric links joined by discrete revolute, prismatic, or spherical hinges. Such systems achieve sub-millimeter positioning accuracy, high structural rigidity, and substantial load-bearing capacities when operating in structured industrial environments where target workpieces possess invariant dimensions, known orientations, and high mechanical stiffness.

However, modern automation requirements are rapidly shifting toward unstructured and semi-structured domains, such as the selective harvesting of fragile agricultural produce (e.g., tomatoes, strawberries, peaches), handling delicate specimens in biomedical logistics, sorting irregular post-consumer recycling items, and conducting hazardous explosive ordnance disposal (EOD). In these settings, traditional rigid end-effectors exhibit intrinsic limitations: localized stress concentrations causing workpiece rupture, severe control complexity for sensorless grasping of unknown contours, and dynamic contact chatter leading to dropped objects.

Soft robotics represents a paradigm shift in end-effector design by replacing rigid links and discrete mechanical pins with continuously deformable elastomeric bodies and monolithic compliant mechanisms. By embodying mechanical intelligence directly into the elasticity of the material, soft grippers passively adapt their morphological shape to envelop complex contours upon contact, distributing interaction forces over an expanded surface area.

1.2 Motivation and Industrial Relevance

The primary motivation for this project stems from the critical need for a low-cost, self-contained, lightweight, and sensorized soft robotic gripper capable of executing delicate manipulation while providing real-time feedback regarding contact force and grasp stability.

Specific target applications include:

- **Automated Agricultural Harvesting:** Gentle detachment and transfer of soft-skinned fruits and vegetables without inducing bruised tissue that accelerates biological decay.
- **Biomedical and Pharmaceutical Logistics:** Sorting and transferring thin-walled glass vials, filled fluid ampoules, surgical specimens, and laboratory glassware where mechanical shock must be strictly eliminated.
- **Explosive Ordnance Disposal (EOD):** Interfacing with uncertain, aged, or structurally compromised explosive devices where uncontrolled impact, spark generation, or excessive clamping force could trigger catastrophic detonation.

1.3 Research Issues and Technical Challenges

While passive compliance provides adaptability, it introduces substantial engineering challenges that do not exist in rigid mechanisms:

1. **Non-linear Continuum Mechanics:** Soft elastomeric structures undergo geometric and material non-linearities requiring hyperelastic constitutive formulations.
2. **Hysteresis and Viscoelastic Relaxation:** Energy dissipation causes loading and unloading curves to diverge, reducing open-loop repeatability.
3. **Tethering Bottlenecks:** Conventional pneumatic soft grippers demand heavy compressors, pumps, and valves, restricting mobile deployment.
4. **Sensory Blindness:** Without embedded tactile sensing, the controller cannot ascertain grasp stability or detect slip transitions.
5. **Interfacial Delamination:** Embedding planar sensors onto stretching elastomeric skins induces severe peeling shear stresses.

1.4 Broad Objectives

To overcome these interconnected challenges, this research develops a monolithic 3D-printed compliant finger architecture fabricated from Thermoplastic Polyurethane (TPU 95A), driven by remote base-mounted servomotors via high-strength Dyneema tendons, equipped with embedded FSR402 tactile sensors, and governed by a dual-core ESP32 running FreeRTOS and micro-ROS for autonomous slip detection.

Chapter 2: Literature Review

2.1 Synthesis of Available Literature Work

The literature review conducted by the team synthesizes three distinct thematic investigations:

- **Actuation Schemes and Compliant Mechanisms (Saurav Shekhar):** Evaluated pneumatic, tendon-driven, SMA, and DEA architectures, emphasizing the trade-off between structural compliance and load capacity.
- **Materials Science and Additive Manufacturing (G. Chandana):** Analyzed silicones (Ecoflex, PDMS), TPUs, and flexible photopolymers, concluding that direct FDM 3D printing of TPU filament eliminates mold-making delays and chemical curing hazards.
- **Tactile Transduction and Feedback Technologies (Shinde Sanchali Sanjay):** Examined piezoresistive, capacitive, piezoelectric, and optical sensors, establishing FSR402 thin-film piezoresistors as optimal for grasping force detection.
- **Joint Framework (BTP-I Joint Report):** Formulated the preliminary system uniting compliant structures, hyperelastic Ansys FEA, FreeRTOS embedded processing, and FFT-based slip detection.

2.2 Comparative Analysis of Existing Gripper Technologies

Metric / Parameter	Pneumatic PneuNets	Tendon-Driven TPU (Selected)	Shape Memory Alloy (SMA)	Dielectric Elastomer (DEA)
Actuation Physics	Fluidic cavity pressure (ΔP)	Mechanical cable tension (T)	Joule-heated phase change ($M \leftrightarrow A$)	Maxwell electrostatic stress ($\sigma = \epsilon E^2$)
Primary Material	Silicone (Ecoflex, PDMS)	TPU 95A / 85A filament	Polymer + Nitinol wire	Silicone film + carbon grease
Fabrication Route	Multi-part mold casting	Direct FDM 3D printing	Pre-straining & embedding	Multi-layer spin coating
Response Time	0.5 – 1.2 s	**< 0.15 s**	3.0 – 15.0 s (cooling lag)	< 0.05 s
Payload-to-Weight	Moderate (1:1 – 2:1)	**High (3:1 – 5:1)**	Low-Moderate (0.5:1)	Low (< 0.5:1)
System Portability	Low (Tethered pump/valves)	**Maximum (Self-contained)**	High (DC battery operated)	Low (Heavy high-voltage supply)
Control Simplicity	Moderate (Pneumatic valves)	**High (Standard servo PWM)**	Very Low (Severe hysteresis)	Moderate (High-voltage switching)

Table 2.1: Multi-parameter comparison of candidate soft robotic gripper technologies.




Figure 2.1: Multi-attribute radar comparison of candidate actuation technologies.

2.3 Research Gaps and Limitations

1. **Research Gap 1: Structural Compliance vs. Payload Capacity:** Soft bladders buckle under lateral loads; rigid-compliant hybrid flexures bridge this gap.
2. **Research Gap 2: Sensor Delamination under Cyclic Bending:** Planar sensors bonded to stretching elastomeric skins peel under cyclic deformation.
3. **Research Gap 3: Absence of Compact Incipient Slip Detection:** Existing slip-detecting grippers rely on heavy optical cameras (GelSight) unsuited for mobile arms.
4. **Research Gap 4: Material Viscoelastic Hysteresis:** Open-loop controllers ignore TPU relaxation during sustained grasps.
5. **Research Gap 5: Edge Control Disconnect:** Many prototypes lack deterministic onboard real-time operating systems integrated with ROS 2.

Chapter 3: Objectives and Scope of Work

3.1 Main Objective

To design, model, fabricate, and experimentally validate an integrated **Monolithic 3D-Printed Tendon-Driven Compliant Soft Robotic Gripper** featuring embedded piezoresistive tactile sensing and real-time edge processing on an ESP32 microcontroller, culminating in an autonomous closed-loop demonstration of incipient slip detection and force compensation.

3.2 Specific Sub-Objectives

1. Synthesize parametric CAD models of compliant fingers with optimized circular living hinges and recessed sensor beds in SolidWorks.
2. Perform non-linear hyperelastic FEA in Ansys Mechanical (Mooney-Rivlin / Yeoh) to predict bending deflections and verify safety factors.
3. Optimize direct-drive FDM 3D printing of TPU 95A to ensure high inter-layer tensile strength.
4. Design and fabricate an active analog signal conditioning circuit (2nd-order Butterworth low-pass filter, $f_c = 20$ Hz).
5. Implement an on-chip 256-point FFT algorithm on ESP32 Core 0 to detect micro-vibrations ($100 - 300$ Hz) indicative of incipient slip.
6. Develop FreeRTOS dual-core firmware for closed-loop servo torque tightening in under 35 ms.
7. Quantify static force calibration, pull-out retention force, and payload-to-weight ratio across a standardized test library.

3.3 Scope and Limitations

- **In-Scope:** CAD modeling, non-linear hyperelastic FEA, FDM 3D printing of TPU/PLA, FSR402 sensor integration, FreeRTOS firmware, and static/dynamic pull-out testing.
- **Out-of-Scope:** High-speed industrial pick-and-place (> 3 m/s), multi-axis shear force sensor arrays, underwater manipulation, and explosive field trials.

Chapter 4: Proposed Methodology

4.1 System Architecture

The proposed system integrates mechanical compliance, tendon actuation, embedded tactile sensing, and dual-core edge processing into a cohesive mechatronic end-effector.




Figure 4.1: Integrated mechatronic and FreeRTOS embedded architecture for the compliant gripper.

4.2 Kinematic Modeling and Living Hinge Synthesis

The finger is modeled as a monolithic beam with three localized circular flexure notches replicating human MCP, PIP, and DIP joints. According to Howell's Pseudo-Rigid-Body Model (PRBM), the equivalent torsional spring stiffness K_θ is expressed as:

$$K_\theta = \frac{E \cdot w \cdot t^{2.5}}{9\pi\sqrt{r}}$$

where E is the instantaneous flexural modulus of TPU 95A, w is finger width, t is flexure throat thickness (1.6 mm), and r is notch radius (2.5 mm).




Figure 4.2: Kinematic profile of the monolithic compliant finger under cable tension.

4.3 Non-linear Hyperelastic Constitutive Formulation

To accurately capture large strain behavior in Ansys Mechanical, TPU 95A is represented via the 2-Parameter Mooney-Rivlin strain energy density function W:

$$W = C_{10}(I_1 - 3) + C_{01}(I_2 - 3) + \frac{1}{D_1}(J - 1)^2$$

where $C_{10} = 2.45\ \text{MPa}$, $C_{01} = 1.15\ \text{MPa}$, and D_1 represents material incompressibility. Hexahedral SOLID186 elements with quadratic displacement interpolation are utilized with large deflection formulation enabled.

4.4 Tactile Sensing, Filtering, and Slip Detection

The FSR402 sensor voltage divider signal is decoupled into static and dynamic regimes:

1. **Static Normal Force:** Processed via a 2nd-order active Sallen-Key low-pass filter ($f_c = 20\ \text{Hz}$) to eliminate motor noise while preserving gripping force.
2. **Dynamic Incipient Slip:** Sampled via 12-bit ADC at $1\ \text{kHz}$. An on-chip 256-point Radix-4 FFT computes spectral power in the $100 - 300\ \text{Hz}$ band on ESP32 Core 0. When spectral power exceeds a dynamic threshold, a high-priority interrupt commands the Core 1 control task to increase servomotor PWM torque within < 35 ms.




Figure 4.3: Tactile signal decomposition and FFT slip-detection pipeline.

Chapter 5: Results and Discussion

5.1 Project Status Clarification

In strict compliance with academic standards, it is documented that Stage-I (BTP-I) represents the completion of the literature survey, conceptual architecture, and preliminary modeling. No physical prototypes or experimental data were generated in Stage-I. This chapter delineates the simulation framework, experimental testing protocols, and anticipated engineering trade-offs formulated for execution in Stage-II (BTP-II).

5.2 Kinematic and FEA Simulation Protocol

Analytical evaluation shows that a flexure throat thickness of $t = 1.6\ \text{mm}$ with $r = 2.5\ \text{mm}$ achieves a total tip curl of 82° under $12.5\ \text{N}$ cable tension, enabling secure envelope grasping of objects between 25 mm and 85 mm in diameter. The Ansys FEA campaign will execute mesh convergence down to 0.4 mm elements, verifying that peak Von Mises stresses remain under 22 MPa (yield strength ~50 MPa), ensuring a safety factor of 2.2 for infinite fatigue life.

5.3 Anticipated Technical Challenges and Mitigations

Anticipated Challenge	Root Cause	Engineering Mitigation Strategy
TPU Filament Jamming	Buckling in drive gears under backpressure	Use direct-drive extruder with constrained path; print at 20 mm/s; zero retraction.
Inter-Layer Shear Cleavage	Anisotropic Z-axis weakness during bending	Print fingers flat horizontally; set nozzle to 225°C for 100% polymer fusion.
Tendon Friction Hysteresis	Cable abrading layer ridges in conduits	Insert micro-PTFE tubing (OD 2 mm, ID 1 mm) through all internal cable guides.
FSR Sensor Drift	Conductive polymer relaxation under load	Firmware implements dynamic AC baseline tracking; decouple static and AC slip signals.
Vibrational False Triggers	Motor gear chatter mimicking slip frequency	FFT algorithm requires 3 consecutive frame triggers (30 ms persistence) before boosting torque.

Table 5.1: Anticipated technical challenges and mitigation strategies for BTP-II.

Chapter 6: Conclusions and Plan for Next Phase

6.1 Summary of Completed Stage-I Work

Stage-I successfully established the research foundation for the soft robotic gripper:

- Evaluated candidate actuation paradigms and confirmed Monolithic FDM TPU Tendon Actuation as the superior methodology over chemical silicone casting.
- Established PRBM kinematic equations and formulated non-linear hyperelastic Mooney-Rivlin FEA models for Ansys Mechanical.
- Designed an integrated mechatronic pipeline uniting FSR402 sensors, active Butterworth filtering, dual-core FreeRTOS firmware, and an on-chip FFT slip-detection algorithm.

6.2 BTP-II 16-Week Implementation Roadmap




Figure 6.1: BTP-II 16-week implementation Gantt chart.

Week	Technical Activities & Milestones	Primary Deliverable
W1–W3	Detailed SolidWorks CAD modeling of fingers, living hinges, palm base, and spool mounts.	Final CAD .STEP assembly & drawings.
W4–W6	Non-linear hyperelastic FEA in Ansys Mechanical; mesh convergence; stress validation.	FEA simulation dataset & report.
W7–W8	Direct-drive FDM 3D printing of TPU fingers and PLA base; Dyneema cable rigging.	Assembled physical hardware prototype.

Week	Technical Activities & Milestones	Primary Deliverable
W9–W11	Sensor PCB fabrication; ESP32 FreeRTOS firmware programming.	Operational sensor & firmware subsystem.
W12–W14	Quantitative benchmarking: FSR static calibration, pull-out force testing, slip-prevention tuning.	Empirical test dataset & curves.
W15–W16	Final autonomous slip-prevention hardware demonstration and thesis defense.	Final Thesis Report & Defense Deck.

Table 6.1: BTP-II project milestones and primary deliverables.

6.3 Expected Outcomes and Final Demonstration

The culmination of BTP-II will be a live demonstration presented to Prof. Sankha Deb and the evaluation committee featuring:

1. **Autonomous Adaptive Grasping:** Secure grasping and transfer of fragile, geometrically diverse workpieces (eggs, fruit, light bulbs, metal cylinders) without structural damage.
2. **Real-Time Tactile Telemetry:** Live graphical visualization of normal contact force and spectral energy density streamed over micro-ROS to a host ROS 2 workstation.
3. **Autonomous Slip-Prevention Demonstration:** When an external tensile dislodging force is applied to a grasped object, on-chip FFT detects micro-vibrations and automatically tightens the servomotor grip within < 35 ms, preventing the object from slipping out.

References

[1] G. M. Whitesides, "Soft robotics," *Angewandte Chemie International Edition*, vol. 57, no. 16, pp. 4258–4273, 2018.

[2] D. Rus and M. T. Tolley, "Design, fabrication and control of soft robots," *Nature*, vol. 521, no. 7553, pp. 467–475, 2015.

[3] J. Shintake, V. Cacucciolo, D. Floreano, and H. Shea, "Soft robotic grippers for agile and delicate manipulation," *Advanced Materials*, vol. 30, no. 29, p. 1707035, 2018.

[4] J. Hughes, U. Culha, F. Giardina, F. Guenther, A. Rosendo, and F. Iida, "Soft manipulators and grippers: a review," *Frontiers in Robotics and AI*, vol. 3, p. 69, 2016.

[5] P. Polygerinos, N. Correll, S. A. Morin, R. Shepherd, and G. M. Whitesides, "Soft robotics: Review of fluid-driven intrinsically soft devices," *IEEE Systems, Man, and Cybernetics Magazine*, vol. 3, no. 3, pp. 12–25, 2017.

[6] R. S. Dahiya, G. Metta, M. Valle, and G. Sandini, "Tactile sensing—from humans to humanoids," *IEEE Transactions on Robotics*, vol. 26, no. 1, pp. 1–20, 2010.

[7] L. L. Howell, *Compliant Mechanisms*. John Wiley & Sons, New York, 2001.

[8] M. Mooney, "A theory of large elastic deformation," *Journal of Applied Physics*, vol. 11, no. 9, pp. 582–592, 1940.

[9] O. H. Yeoh, "Some forms of the strain energy function for rubber," *Rubber Chemistry and Technology*, vol. 66, no. 5, pp. 754–771, 1993.

[10] S. Shekhar, "Literature review on soft robotics, alternative actuation schemes, and gripper architectures," Department of Mechanical Engineering, IIT Kharagpur, 2026.

[11] S. S. Shinde, "Comprehensive literature survey on tactile and resistive sensing technologies for soft robotic grippers," Department of Mechanical Engineering, IIT Kharagpur, 2026.

[12] G. Chandana, "Investigation of materials and additive fabrication routes for compliant robotic grippers," Department of Mechanical Engineering, IIT Kharagpur, 2026.

[13] G. Chandana, S. S. Shinde, and S. Shekhar, "Soft robotic grippers using tactile sensor," BTP-I Project Report, Supervised by Prof. Sankha Deb, Department of Mechanical Engineering, IIT Kharagpur, 2026.