HipMRI Segmentation: Spatial Continuity, Boundary Errors and Computational Cost

COMP3710 Final Assessment | Student ID: s4906923 | Updated 22 October 2026

Abstract

Ten 50-epoch U-Net runs were compared on HipMRI using patient-disjoint splits: 26 Train, 6 Validation and 6 Test patients. Each run was evaluated at its best measured Validation checkpoint. Improved v3 had the highest Validation small-organ Dice, 0.8564, compared with 0.8502 for Standard 3D. On the existing Test cohort, their small-organ Dice values were 0.8145 and 0.7851, and prostate Dice values were 0.7485 and 0.7433. Relative to the supplementary 2D configuration, both 3D models had higher prostate base/apex slice Dice and fewer visits with internal prediction gaps. Relative to Standard, however, v3 had lower mean base/apex slice Dice and more adjacent-organ confusion. Its median prostate HD95 was lower, 6.65 versus 7.98 mm, but its maximum was higher, 115.37 versus 19.23 mm. Reference peak allocated inference memory was 0.3458 GiB for v3, 0.2460 GiB for Standard and 0.0761 GiB for 2D. These measurements support retaining v3 for the original Validation endpoint while retaining Standard for boundary comparison. They do not establish autonomous contouring performance. Test had already been inspected, and only six patients contributed to each evaluation split; no external-cohort or independent-seed replication was completed.

1. Introduction

The COMP3710 segmentation specification asks whether volumetric continuity or multiscale context reduces local boundary and slice-transition errors that whole-organ Dice can conceal. For HipMRI, it identifies prostate base/apex contours, bladder/rectum interfaces, disconnected predictions and computational cost as the investigation. This report implements the 3D Improved U-Net route with residual units and multiscale outputs, using Standard 3D U-Net as the main baseline and a separately trained 2D U-Net as a supplementary context comparison. These choices follow the baseline allowance and Hard-route description on pages 5-6 of the supplied specification.

Course investigation	Research question measured in this study	Results and corresponding discussion
Volumetric continuity versus slice-wise processing	Do the tested 3D configurations improve prostate base/apex overlap and slice continuity over the supplementary 2D configuration?	Regional overlap, gaps and adjacent-slice area change; interpretation of the 2D/3D comparison
Local boundary errors concealed by global overlap	Does Improved v3 improve prostate ends, adjacent-organ separation and surface-error extremes over Standard 3D, in addition to whole-organ Dice?	Per-class overlap, surface errors and five MRI cases; boundary comparison
Anatomical benefit versus computation	What additional inference memory and latency accompany the measured 3D results, and which uses remain unsupported by the observed errors?	Measured resources; cost interpretation and engineering recommendation

The first question corresponds to the course's 2D/3D context comparison. The second applies its local-boundary requirement to the submitted Improved-versus-Standard comparison. The third corresponds to its resource table and manager recommendation. The 2D run changes sampling, width and class weights as well as dimensionality, so the study cannot attribute the whole 2D/3D difference to 3D convolution alone. The measured adjacent-organ statistic counts GT Bladder/Rectum voxels labelled Prostate; it does not measure rectal-wall or bladder-mucosa invasion. No radiation-dose or treatment-outcome evaluation was performed.

Supplementary material. Appendix A gives the recorded software environment and commands for training, fixed-checkpoint evaluation, example export and PDF generation. Appendix B lists the submitted files, saved experiment evidence and coursework actions that require confirmation. Appendix C retains the one-page feasibility review within this README, as required on page 14 of the specification. The source specification's SHA-256 and page mapping are retained in `evidence/provenance.json`.

Checkpoint selection used Validation. Test was inspected during the research process and is reported as an existing descriptive cohort, not a new blind evaluation. Sections 2-4 separate the implemented methods, measured results and interpretation.

2. Materials and methods

2.1 Dataset audit and preprocessing

Audit sequence. The recorded pretraining checks covered source pairs, the factor-two preprocessing path, delivered samples and two-patch optimiser behaviour. The initial audit decoded Train arrays only; Validation/Test filenames were inventoried to check the split, without using their label distributions to design the recipe.

Check before formal cohort training	Recorded evidence and decision
Cohort and mechanical integrity	All 143 Train MRI/mask pairs from 26 patients were audited; no inventory/case errors, non-finite values or illegal labels were found. All six labels occurred in every Train volume; no identical-file hash groups were found within Train.
Geometry and gross alignment	Every MRI/mask affine matched exactly. All Train MRI used LPS orientation and millimetres; 142 volumes were 256x256x128 and one was 256x256x144. Two axial overlays per volume showed no obvious gross displacement. This screen did not certify every local contour.
Documented metadata warning	All 143 mask headers left spatial units unspecified. Matching grids, affines and spacings supported using the paired MRI geometry, with this limitation retained rather than silently correcting the source.
Distribution and supervision	Train-only counts showed Background 59.99%, Body 35.75%, Bones 3.41%, Bladder 0.60%, Rectum 0.15% and Prostate 0.11%. Visit counts varied from 1 to 8 per patient. This motivated patient-balanced sampling and Train-derived CE weights, rather than treating correlated visits as independent patients.
Actual preprocessing	The factor-two pipeline processed 143/143 Train cases without errors; all small organs survived. Prostate physical label volume after/before resampling ranged from 0.9383 to 1.0423. Normalised nonzero MRI values had mean approximately 0 and standard deviation approximately 1. Organ survival did not prove thin-boundary preservation.
Delivered samples and learning checks	Patient-balanced CPU sampling/tensor checks preceded a paired GPU optimiser smoke and full-volume capacity probe. In a controlled two-patch, 500-update check, unweighted CE left Standard predicting no Bladder, Rectum or Prostate voxels. Weighted CE produced same-patch Dice of 0.9843, 0.9796 and 0.9722 for these organs, respectively. This justified a weighted learning protocol, not a claim about unseen-patient accuracy.

Training acceptance. Zero unresolved mechanical errors, matching paired geometry, preserved labels through the actual transform, finite model inputs, verified sampling and a working optimiser/inference path supported proceeding to controlled training. These checks did not include expert certification of every contour or a clinical suitability assessment. The unspecified mask units and downsampling's potential loss of millimetre-scale detail remained explicit limitations. The numerical summaries and original audit hashes are retained under `pretraining_review` in `evidence/provenance.json`.

Split	Patients	Volumes	Purpose
Train	26	143	Optimisation and Train-derived weights
Validation	6	38	Checkpoint selection and diagnosis
Existing Test	6	30	Descriptive fixed-checkpoint evaluation

`config/patient_split.json` records the fixed patient lists and their provenance: the previously approved split was preserved for comparability with the pre-restart experiments, rather than drawn again for this submission. Train contains 26 of 38 patients (68.4%); Validation and Test each contain six (15.8%). Keeping all visits from a patient together prevents within-patient visits from crossing the optimisation/evaluation boundary. Retaining this split also permits the ten runs to be compared on the same patients. The retained record does not document the original randomisation procedure or clinical stratification, so neither is claimed here. Six patients per evaluation split limits population-level conclusions.

Files are paired by patient/week. `dataset.py` checks matching 3D shape, affine and voxel spacing, finite arrays and integer labels 0-5. MRI must declare millimetres; matching masks with unknown spatial units are accepted as a documented source-metadata limitation. Metadata agreement is not expert confirmation of anatomy.

MRI and mask are jointly downsampled by (2,2,2). Output centre j samples source centre `(j+0.5)*2-0.5`; the affine uses the same transform. MRI interpolation is linear, mask nearest-neighbour; lost labels trigger failure. Image-only nonzero Z-score preserves outside zeros. The ground-truth mask (GT) never defines the region used for prediction.

Arrays use X/Y/Z voxel order until conversion to channel/depth/height/width (CDHW) model input. High-end zero padding makes dimensions divisible by 16 and is removed before metrics/export. Evaluation is on the downsampled physical grid, not original resolution. Cross-entropy (CE) takes integer labels; Dice converts them to six-channel one-hot internally; `one_hot()` is also available.

Keep raw files outside Git:

```
HipMRI_Study_open/
  semantic_MRs/PatientID_WeekN_LFOV.nii.gz
  semantic_labels_only/PatientID_WeekN_SEMANTIC.nii.gz
```

2.2 Network architectures

Architecture specification. Standard uses volumetric convolution and encoder-decoder skips, with U-Net and 3D U-Net cited as architectural references [1,2]. The Improved implementation uses residual context blocks and multiscale outputs, with Isensee et al. cited as its reference [3]. Both implemented models start at eight channels. Their recorded reference inference-memory measurements are given in Section 3.4; no width-search experiment was completed. The layer definitions below describe this project's implementations rather than an exact reproduction of the papers.

Property	Standard 3D U-Net	Improved 3D U-Net v3
Input and output	One MRI channel; six class logits	One MRI channel; six combined class logits
Feature hierarchy	Five resolutions, channels 8,16,32,64,128; four downsampling steps	Same five resolutions and channel widths
Encoder stage	Two 3x3x3 convolutions, each followed by GN1 and ReLU	3x3x3 stem; a residual context block at every resolution
Downsampling	2x2x2 max pooling, stride 2	3x3x3 convolution, stride 2, padding 1; channels double
Decoder step	2x2x2 transposed convolution, stride 2; concatenate matching encoder features; two-convolution block	Nearest-neighbour upsampling to the skip grid, 3x3x3 channel reduction and LeakyReLU; concatenate matching context features; localisation block
Localisation / block details	3x3x3 convolutions use padding 1 and no bias	Localisation: 3x3x3 convolution on 2C channels, GN1 and LeakyReLU, then 1x1x1 reduction to C
Normalisation and activation	GN(1,C), epsilon 1e-5, learned scale/offset; ReLU	Fourteen GN(1,C) sites, epsilon 1e-5, learned scale/offset; LeakyReLU slope 0.01
Residual and regularisation	No residual blocks or dropout	Five identity residual blocks; Dropout3d probability 0.3 between each block's two convolutions, active during training
Segmentation heads	One 1x1x1 convolution at full resolution	1x1x1 heads at full, half and quarter resolution; resize the latter two and sum the logits
Trainable parameters	1,412,550	2,366,946

For a training patch, both encoders follow this spatial/channel schedule. Sizes are X/Y/Z voxels; the implementation receives Bx1x32x64x64 after conversion to depth/height/width order. B is batch size.

Encoder level	Channels	Patch feature size X/Y/Z
Full resolution	8	64x64x32
Half resolution	16	32x32x16
Quarter resolution	32	16x16x8
One eighth	64	8x8x4
Bottleneck, one sixteenth	128	4x4x2

The decoder reverses this hierarchy, using four feature-concatenation skips, and ends with Bx6x32x64x64 logits for a training patch. Evaluation accepts a larger padded whole volume with the same channel hierarchy; this is not a fixed patch-size inference model.

The v3 residual block. For feature tensor x with C channels, the branch applies GN1 -> LeakyReLU -> 3x3x3 convolution -> Dropout3d -> GN1 -> LeakyReLU -> 3x3x3 convolution, then adds the original x. The spatial convolutions use stride 1 and padding 1. GN1 normalises across channels and spatial positions within each sample, not across the batch. v1 instead used

per-channel InstanceNorm. The input-context and head-output experiments are reported in Section 4.4; the normalisation definition alone does not identify the cause of a prediction error.

Output fusion and supervision. The full-resolution head sees eight decoder channels; the half- and quarter-resolution heads see 16 and 32. Auxiliary logits are resized to the main grid by trilinear interpolation with `align_corners=False`. Training and inference both use `combined = main + resized_half + resized_quarter`; one loss is applied to this sum, so all three heads receive gradients. This is additive multiscale supervision, not the independent head losses of v2. Class order is Background, Body, Bones, Bladder, Rectum, Prostate. Softmax supplies probabilities for the Dice loss; inference uses the largest combined logit per voxel.




Figure 1. Implemented preprocessing and Standard/v3 network paths. GN1 denotes one-group GroupNorm; crop sizes are X/Y/Z voxels.

2.3 Loss function, training and checkpoint selection

Both models use random seed 371017 and the Adam optimiser, with a fixed learning rate of 0.001 and no weight decay. One shuffled/cycled visit per Train patient supplies ten uniform 64x64x32 XYZ patches per epoch: 260 patches, batch size 2, 130 updates; 50 epochs yield 6,500 updates. The submission preserves the deterministic visit/crop/batch schedule. Exact GPU rerun weights are not guaranteed across kernels, hardware and library versions.

Loss is `0.5 *weighted_cross_entropy* + 0.5 foreground_soft_Dice_loss`. Background remains in CE but is excluded from Dice. CE weights derived from Train data are `[1.453871, 1, 2.617199, 4.498586, 8.893215, 9.699950]` in label order. The selected weights came from Train patch exposure and the controlled two-patch learning check described in Section 2.1. The v5-L comparison tests a change to the three small-organ weights; its observed Validation and Test scores are reported in Section 3.1. Training loss and evaluation Dice are reported separately.

Validation runs every five epochs. Pool confusion matrices across visits within each patient; compute Bladder/Rectum/Prostate Dice, average within patient, then average six patients equally. Choose the highest score at measured epochs 5,10,...,50, with earlier ties. The intermediate epochs were not all evaluated. Both selected checkpoints happen to be epoch 50.




Figure 2. Standard/v3 training objective and patient-equal Validation small-organ Dice over the recorded 50-epoch runs.

2.4 Experimental development and model selection

Completed runs and evaluation budget. The study completed ten formal 50-epoch runs: Standard, supplementary 2D, v1, v2, v3, A0, A1 and v5-C/L/S. Tiny-batch checks, inference probes and sampler audits were diagnostics, not additional successful cohort models. The sequence used Train exposure records and Validation predictions to decide what to test next. Recorded configuration changes below describe intended mechanisms; they are not by themselves proof of the cause of an error. The complete numerical comparisons are in Section 3. Standard, v1 and the supplementary 2D run were extended from the initial 40-epoch budget to 50; the final comparison uses the same 50-epoch total budget for every run. Earlier v2/v3 mechanism plans also specified fixed-epoch checks. Those historical checks are distinct from the final benchmark, which consistently reports each model's best measured Validation checkpoint.

Initial comparison and subsequent diagnostics. Standard and the first Improved network, subsequently called v1, were given the same patient-balanced 3D crops, loss, split and optimisation recipe. The residual context, InstanceNorm, dropout and additive output heads in v1 were intended to add contextual representation and regularisation. After training, review moved from loss curves to per-class Validation confusion counts, precision/recall, physical Body surfaces and MRI overlays. Reproducing the fixed predictions before calculating new measurements prevented a change of checkpoint or preprocessing from masquerading as a diagnostic finding.

The recorded v1 investigation examined four candidate mechanisms: boundary/background exposure, output-head coupling, imbalance weights and normalisation/input extent. These were diagnostic questions, not established causes. Train geometry/exposure audits tested what the sampler supplied. Fixed-weight Validation probes compared full-volume and sliding-window inputs and inspected the individual output heads. Neither inference-context changes nor removal of auxiliary outputs was treated as a retrained architecture comparison. Small numerical differences caused a head-replay control to fail; that control was not used as causal proof. v2, v3 and the later optimisation branches changed the factors specified in the table below.

Run / parent	Design decision and question tested	Comparison logic
Standard / initial reference	Basic 3D U-Net, GN1, one head; establish a volumetric baseline under the verified pipeline	Same 3D split, patch schedule, objective and update budget as v1
v1 / initial Improved	Residual context, InstanceNorm, dropout 0.3 and summed multiscale logits; test the contextual Hard architecture	Several components differ from Standard, so the aggregate contrast cannot identify one causal component
2D / supplementary branch	Width-16 slice U-Net; four uniform plus two crops per small organ per patient, with its own Train-derived weights	Slice-only context and lower resource use provide an engineering reference; different width/sampling/weights prevent a pure dimensionality ablation
v2 / v1	Train main, half and quarter heads independently: `(Lmain + 0.5 Lhalf + 0.25 Lquarter) / 1.75`; use the main head at inference	Tests whether individually useful heads avoid reliance on summed predictions; keeps v1's backbone and InstanceNorm. Training supervision and inference output change together
v3 / v1	Replace all 14 InstanceNorm sites with GN1; retain v1's residual blocks, dropout, additive heads and loss	Normalisation is the only declared recipe change from v1; the comparison uses a historical single-run reference. v2's independent losses are not used

Run / parent	Design decision and question tested	Comparison logic
A0 / v3	AdamW, decay 1e-5 excluding bias/normalisation, cosine learning rate from 0.001 towards 1e-5 over 6,500 updates	Tests a conventional optimisation/regularisation package; the combined changes cannot isolate decay from optimiser or schedule
A1 / A0	With probability 0.3, apply paired physical-axis rotations up to 10 degrees and isotropic scaling 0.9-1.1; linear MRI and nearest-neighbour mask interpolation	A1-A0 tests this specific spatial augmentation under the AdamW/cosine recipe. A Train-only 26-patient geometry/exposure audit and real previews preceded training
v5-C / v3	Concurrent run using the original v3 settings and nominal seed	Provides a contemporary control for L/S and reveals same-recipe run variation; this is not an independent-seed replication
v5-L / C	Compress only the three small-organ CE weights by square root: 4.498586/8.893215/9.699950 become 2.120987/2.982149/3.114474	Tests a less aggressive imbalance penalty while retaining Adam, constant learning rate, architecture and sampling
v5-S / C	Retain Adam and zero decay; change only the learning-rate rule to cosine over 6,500 updates, towards 1e-5	Separates the schedule question from A0's additional optimiser/decay changes

Sequence of revisions. v2 changed head supervision and inference output after the v1 head-output diagnostic. Its best Validation small-organ score was below v1's, as recorded in Section 3.1. v3 therefore retained v1's additive outputs while replacing InstanceNorm with GN1. A0/A1 then tested optimiser/decay/schedule changes and paired spatial augmentation around the v3 architecture. The A1 Train-only audit covered 26 patients and six real previews, with gates for small-organ exposure and out-of-volume sampling; it preceded A1 training and did not measure segmentation accuracy. C/L/S subsequently separated the learning-rate schedule and small-organ CE weights under a concurrent v3-recipe control. The Train edge-sampling candidate was audited but never trained as a formal segmentation run and is not counted among the ten models.

Selection of the submitted model pair. The original selection endpoint remained patient-equal Validation Dice for Bladder, Rectum and Prostate, measured every five epochs. Each run first contributes its best measured checkpoint; comparing those checkpoints places v3 first under this rule. v3 scored 0.8564, compared with 0.8502 for Standard and 0.8542 for C. Its Validation Body HD95 median was 4.58 mm, compared with 76.61 mm for v1 (Section 3.3). None of the later branches exceeded v3's original primary Validation score. Standard is retained as the baseline; it has fewer parameters and lower recorded peak inference memory, and its Test boundary results differ from v3's as reported in Sections 3.3-3.5. C's higher existing Test prostate score does not justify changing the rule after seeing Test; v3 is the selected research candidate, not the winner of every metric or a clinically approved model. Section 3 quantifies those gains and regressions; Section 4 weighs their practical importance.

2.5 Evaluation protocol and study limitations

All models use identical patient splits and evaluation grids. 3D inference processes the complete downsampled volume once, not sliding windows. The supplementary 2D model processes slices and reconstructs a volume. A 3D training patch contains 131,072 voxels (64x64x32), whereas a 2D crop contains 4,096 pixels (64x64); equal epoch/update counts do not equalise processed input elements or computation. No GT-dependent post-processing is used. Taking the largest class logit gives the same class as applying softmax first.

TP, FP and FN denote true positives, false positives and false negatives. Dice=$2TP/(2TP+FP+FN)$, intersection over union (IoU)=$TP/(TP+FP+FN)$, precision=$TP/(TP+FP)$, recall=$TP/(TP+FN)$. If a class is absent from both prediction and GT, its overlap is recorded as unavailable rather than perfect. Primary overlap tables pool visits within patients before averaging patients. The foreground mean gives equal weight to labels 1-5; Background remains in the six-class table. The supplementary post-hoc 50% prostate-weighted score is not a selection rule or official course criterion.

The 95th-percentile Hausdorff distance (HD95) and average symmetric surface distance (ASSD) use concatenated directed distances between six-connected mask surfaces, in physical millimetres. HD95 is the 95th percentile; ASSD here is their combined mean. Empty-mask statuses are explicit and null, never zero distance. All five foreground masks were present in all 680 fixed-audit case/model entries. Surface medians/maxima below summarise volumes, unlike patient-equal overlap. The saved distances use this surface convention. The evaluation code rejects sheared grids rather than applying spacing-only Euclidean distances to them.

Test has already been repeatedly inspected. Checkpoints were chosen using Validation. Because Test has already been examined, it is not a fresh blind holdout and should not guide further tuning. Six patients, not 30 correlated visits, are the independent Test units. No external cohort or independent multi-seed replication was completed.

3. Results

3.1 Validation-selected checkpoints across ten runs

Every model in the table completed 50 training epochs. Only Standard/v3 runtime implementations are retained here; the other experiments are retained as comparisons, including changes that did not improve performance.

Model	Best epoch	Validation small organs	Test small organs	Test foreground five	Test Prostate
2D	50	0.7757	0.7082	0.7883	0.6611
Standard	50	0.8502	0.7851	0.8370	0.7433
v1	50	0.8420	0.8078	0.8502	0.7520
v2	45	0.8362	0.7959	0.8422	0.7478
v3	50	0.8564	0.8145	0.8631	0.7485
A0	45	0.8450	0.7836	0.8400	0.7318
A1	45	0.8298	0.7801	0.8362	0.7273
v5-C	50	0.8542	0.8040	0.8557	0.7633
v5-L	45	0.8426	0.7858	0.8388	0.7361
v5-S	45	0.8465	0.7788	0.8350	0.7281

A1 augmentation result (design in Section 2.4). The best Validation small-organ Dice decreased from 0.8450 to 0.8298, and existing Test Dice from 0.7836 to 0.7801. Validation distant Background-to-Body voxel counts decreased from 9,572 to 1,171; the corresponding Test counts decreased from 9,636 to 535. These are sums over volumes, not patient-equal rates. The lower counts occurred alongside the lower small-organ Dice values. This result concerns one tested augmentation scheme and training budget; it does not show that data augmentation is generally ineffective.

v3's Test small-organ gain over Standard is +0.0294, but only 3/6 patients improve; excluding influential M015 changes the contrast to approximately -0.0050. Validation improves for 5/6 patients. These descriptive sensitivities do not establish population superiority. C's higher Test prostate Dice is reported without switching the primary selection rule after seeing Test.

3.2 Per-class Test overlap and precision/recall

Class	Std Dice	v3 Dice	Std IoU	v3 IoU	Precision Std / v3	Recall Std / v3
Background	0.9904	0.9885	0.9814	0.9778	0.9952 / 0.9961	0.9858 / 0.9814
Body	0.9677	0.9732	0.9384	0.9484	0.9748 / 0.9664	0.9610 / 0.9807
Bones	0.8619	0.8988	0.7578	0.8168	0.7868 / 0.8793	0.9543 / 0.9205
Bladder	0.7993	0.8539	0.7455	0.7768	0.7871 / 0.8807	0.8229 / 0.8598
Rectum	0.8128	0.8410	0.6918	0.7280	0.7898 / 0.8086	0.8414 / 0.8784
Prostate	0.7433	0.7485	0.6081	0.6193	0.7189 / 0.6983	0.8415 / 0.8516




Figure 3. Standard/v3 patient-equal foreground Dice on Validation and the existing Test cohort.

v3 improves all five Test foreground mean Dice values here, but prostate gains only about 0.0052 while precision decreases from 0.7189 to 0.6983. In this comparison, the higher mean Dice occurs alongside lower patient-equal precision; the W029_Week6 example below also has lower whole-volume prostate Dice for v3.

3.3 Surface distances and distant Body predictions

Class	Median HD95 Std / v3 mm	Worst HD95 Std / v3 mm	Median ASSD Std / v3 mm
Body	4.86 / 4.50	18.72 / 22.23	1.21 / 1.66
Bones	7.46 / 4.58	18.97 / 19.02	2.69 / 1.83
Bladder	3.36 / 3.89	109.49 / 72.36	1.38 / 1.51
Rectum	7.06 / 7.28	38.56 / 109.19	2.46 / 2.09
Prostate	7.98 / 6.65	19.23 / 115.37	3.45 / 2.73

Median prostate HD95 improves 7.98 to 6.65 mm, while the worst value worsens 19.23 to 115.37 mm. Maximum Body HD95 was 18.72/22.23 mm and maximum Rectum HD95 was 38.56/109.19 mm for Standard/v3. The Hard-route stated Dice target of 0.7 is exceeded by v3's Test prostate (0.7485), small-organ (0.8145) and foreground (0.8631) means. The specification does not define the aggregation of that target; one of six Test patients still has prostate Dice below 0.7. These averages therefore do not establish either per-patient attainment or local contour safety.

The following additional Body measurements come from the selected-checkpoint records. Distant false predictions count GT Background voxels labelled Body at least 20 mm from GT Body. Counts are summed over the 38 Validation or 30 Test volumes; they are not patient-equal scores.

Model	Validation median Body HD95 (mm)	Validation distant Body FP voxels	Test distant Body FP voxels
Standard	4.75	1,007	2,804
v1	76.61	1,358,516	667,239
v3	4.58	73,204	81,145

v3 has a much lower Validation median and fewer distant Body false predictions than v1, but its distant-voxel counts remain above Standard on both splits. This separates the improvement over v1 from the comparison with the baseline. The unrounded counts and source-bundle identity are retained under `report_diagnostic_summaries` in `evidence/provenance.json`.

3.4 Parameter count, GPU memory and inference time

Model	Parameters	Peak inference GiB	Reference latency s
2D	1,942,374	0.0761	0.1395
Standard	1,412,550	0.2460	0.1552
v3	2,366,946	0.3458	0.1452

NVIDIA A100-PCIE-40GB, prepared Validation case K008_Week0, three warm-ups and five repetitions, one resident model. Latency includes transfer, execution, argmax and conversion, excluding decoding/preprocessing/metrics/IO. Peak figures are allocated inference memory, not training memory or device utilisation. The five recorded reference repetitions, per-case timings and patient records are retained in `evidence/experiments.json`.

The following cohort summary uses the separate, single recorded inference pass for each volume in the same historical audit. Each Validation row contains 38 volumes from six patients; each Test row contains 30 volumes from six patients. Quartiles and P95 are calculated across volumes with linear interpolation, not across repeated benchmark passes. These timing summaries weight volumes equally; segmentation summaries elsewhere weight patients equally.

Model	Split	Median latency s	Q1-Q3 s	P95 s	Maximum peak allocated GiB
2D	Validation	0.1412	0.1406-0.1415	0.1417	0.0761
2D	Test	0.1401	0.1394-0.1410	0.1414	0.0761
Standard	Validation	0.1733	0.1722-0.1737	0.1744	0.2460
Standard	Test	0.1740	0.1700-0.1744	0.1747	0.2460
v3	Validation	0.1669	0.1665-0.1671	0.1675	0.3458
v3	Test	0.1666	0.1665-0.1668	0.1670	0.3458

Inputs were prepared in RAM before each recorded pass; execution was GPU-synchronised and peak allocated memory was reset per case. The model remained resident. Thus these values exclude file loading, preprocessing and metrics, and do not measure an end-to-end service. The cohort and five-repeat reference protocols must not be combined into one latency estimate. Unrounded values and the source identity are in `evidence/cohort_inference_summary.json`.

The supplementary 2D model segments slices independently and uses 0.0761 GiB in this reference inference measurement. The 3D models process the full downsampled volume. Their end-region, continuity and distant-component measurements are reported separately, rather than inferred from the convolution dimensionality. The supplementary 2D arm differs in sampling, weights and width; it is not a clean dimension-only ablation and does not claim to meet the separate Easy-route dataset/target. Measurements of prostate end regions, nearby organs at risk (OAR) and changes between adjacent slices remain in `evidence/experiments.json`.

3.5 Prostate regions, slice continuity and adjacent-organ confusion

These diagnostics were calculated from the predictions and geometry records already saved for the 30 Test volumes. They do not involve new inference, tuning or checkpoint selection.

Existing Test diagnostic	2D	Standard 3D	Improved v3
Apex mean slice Dice	0.5186	0.7544	0.7523
Central mean slice Dice	0.7125	0.7824	0.7931
Base mean slice Dice	0.3473	0.5097	0.5069
Visits with an internal predicted prostate gap (%)	43.75	0.00	8.33
Adjacent-area transition error (dimensionless)	0.1953	0.0685	0.0720
GT Bladder/Rectum voxels labelled Prostate (%)	0.386	0.485	0.580

End-region values average GT-positive slice Dice within each visit, then visits within each patient, and finally the six patients equally. Base and apex are the physically superior and inferior 20% of GT-positive slices: geometric proxies rather than clinician-defined regions. These slice averages differ from the pooled whole-organ Dice in Section 3.2.

The gap statistic is the patient-equal mean fraction of visits with an empty predicted Z slice between nonempty predicted prostate slices. The GT has no such gaps in this cohort. It counts missing intermediate predicted slices, not correct anatomical placement. The area-transition error is the absolute difference between prediction and GT mean normalized adjacent-area changes on GT-positive adjacent slice pairs. It is a descriptive shape-change measure, not a validated anatomical quality score.

The adjacent-organ percentage pools counts within each patient before averaging patients. Its denominator is all GT Bladder/Rectum voxels, and its numerator is those labelled as Prostate. It measures class confusion, not specifically wall invasion, mucosal dose or clinical harm. No wall-specific region or clinical severity threshold was annotated for this measurement. Definitions and unrounded values are retained in `evidence/spatial_context_summary.json`.

Regional comparison. Standard/v3 improve apex and base overlap over this 2D configuration and show fewer internal gaps. However, v3's gains over Standard are concentrated in central slices; its apex and base means are slightly lower, its continuity measures are not better, and its adjacent-organ confusion percentage is higher. The central slice mean increased from 0.7824 to 0.7931, whereas the internal-gap fraction increased from 0.00% to 8.33%.

3.6 Case-level error analysis

These panels use real MRI and the selected Standard/v3 checkpoints. A read-only replay (job 686318) reproduced all ten historical whole-volume confusion matrices before drawing them. No training, checkpoint selection or new Test-case selection was performed. The original multi-model panels are retained in the research archive; the figures below separate the submitted pair for readability.

Each upper row shows full-field MRI, the GT mask in cyan, Standard prediction and v3 prediction in orange. The lower row shows MRI, GT and red FP/blue FN overlays in the same display region. That region is the 2D GT bounding box plus ten voxels; if GT is absent on the plane, the full field is retained. Cropping affects display only, never inference or metrics. Physical pixel aspect is preserved. Voxel axis 2 is the axial Z direction here; indices are zero-based on the downsampled grid.

The fixed slices were taken from the previously documented cases: M015 z=47, W029 base z=41 and apex z=32, K018 z=0, J026 z=49, and B040 z=63. They were not reselected to favour v3. The Body, Rectum and Bones views retain earlier A1-error-selected planes; this remains purposive rather than random sampling. Prostate base/apex uses physical superior/inferior ordering as a geometric proxy, not expert end-region annotation.

3.6.1 M015_Week7, Test: bladder localisation




Figure 4. M015_Week7 Test Bladder at z=47: full-field masks and a shared enlarged error region.

Standard includes distant non-bladder tissue and misses much of the bladder; v3 reduces distant predictions but still undersegments the target. Whole-volume bladder Dice is 0.0676 Standard versus 0.5224 v3; HD95 is 109.49 versus 58.84 mm. The v3 bladder Dice in this visit remained 0.5224 despite the increase over Standard. The saved evaluation did not isolate anatomy, intensity or annotation effects as the cause. Section 4.5 reports the Test comparison with and without patient M015.

3.6.2 W029_Week6, Test: prostate ends and adjacent tissue




Figure 5. W029_Week6 Test Prostate base at z=41: both predictions extend beyond the small GT cross-section.




Figure 6. W029_Week6 Test Prostate apex at z=32: the same full-field and enlarged error layout.

Both displayed base predictions extend beyond GT; their base-region mean slice Dice values are below 0.22. Whole-volume prostate Dice is 0.4623 Standard versus 0.4377 v3; base-region mean slice Dice is 0.2111 versus 0.2158. Slight end-region improvement does not imply whole-organ improvement. HD95 increases 19.23 to 20.59 mm. No controlled test established why this visit failed; no radiation-dose evaluation or expert clinical adjudication was performed.

3.6.3 K018_Week4, Validation: Body and distant components




Figure 7. K018_Week4 Validation Body at z=0: full-field masks retain distant predictions outside the local display region.

The full-field v3 prediction includes small regions outside the main Body prediction, and the enlarged overlay retains both FP and FN. Standard/v3 whole-volume Body Dice is almost equal (0.9740/0.9742); HD95 is 4.75/6.24 mm, and distant Background-to-Body voxels are 5/3,128. The near-equal Dice values therefore coexist with different surface distances and distant-error counts. This case does not isolate normalisation or input context as the cause.

3.6.4 J026_Week4, Validation: rectum extent




Figure 8. J026_Week4 Validation Rectum at z=49: GT is absent on this plane, while both predictions contain Rectum FP. The lower row therefore retains the full field.

The empty GT mask and nonempty predicted masks expose a false-positive Rectum cross-section in both models. This is one selected slice, not a claim that the whole-volume Rectum is absent. Whole-volume Dice improves 0.8110 to 0.8437, ASSD improves 2.00 to 1.73 mm, but HD95 remains 6.24 mm. The lower ASSD and higher Dice do not remove the displayed false-positive extent or change the recorded HD95. The records do not isolate why either network predicts Rectum on this plane.

3.6.5 B040_Week1, Validation: bone coverage




Figure 9. B040_Week1 Validation Bones at z=63: separate masks and the same-region FP/FN overlays.

The selected plane contains both missing bone and extra predicted regions. v3 improves whole-volume Bones Dice 0.8607 to 0.9026 and HD95 7.41 to 4.58 mm, but the enlarged error views retain FP and FN. The displayed FP/FN and the whole-volume metrics are reported for Bones separately from the three-small-organ selection score. No controlled test attributes these residual errors to a specific tissue-intensity or anatomical trigger.

4. Discussion

4.1 Spatial continuity in the tested 2D and 3D configurations

The first research question is addressed by the whole-prostate and axial-region measurements. Standard/v3 had Test whole-prostate Dice 0.7433/0.7485, compared with 0.6611 for 2D. Apex slice Dice was 0.7544/0.7523 versus 0.5186, and base slice Dice was 0.5097/0.5069 versus 0.3473. The patient-equal fraction of visits with an internal predicted prostate gap was 0.00%/8.33%, compared with 43.75% for 2D. Thus the tested 3D configurations differed from the 2D configuration at prostate ends and intermediate slices, not only in the central-region score.

Those differences do not isolate dimensionality: 2D also changed width, sampling and class weights. Base Dice remained approximately 0.51 for both 3D models, and the W029_Week6 panel retained end-region FP/FN. The existing records support a comparison of these configurations, not a causal estimate for adding 3D kernels alone.

4.2 Mean overlap gains and persistent boundary errors

The second research question separates whole-organ overlap from local errors. v3 had higher Test mean Dice for all five foreground classes than Standard. For Prostate, Dice changed from 0.7433 to 0.7485, precision from 0.7189 to 0.6983 and recall from 0.8415 to 0.8516. Its median prostate HD95 was lower by about 1.33 mm, while its maximum was 115.37 mm rather than 19.23 mm.

The spatial diagnostics did not show an additional v3 advantage over Standard: apex/base means were slightly lower, the internal-gap fraction was higher, and the GT Bladder/Rectum-to-Prostate fraction was 0.580% rather than 0.485%. Test distant Body false predictions also remained higher: 81,145 versus 2,804 voxels. These measurements answer the boundary question with different outcomes for different metrics; higher mean foreground Dice did not coincide with fewer errors on all boundary measures. No clinical outcome can be inferred from the adjacent-organ proxy.

4.3 Measured inference cost and profiling scope

For K008_Week0 on the recorded A100, Standard and v3 used 3.23 and 4.54 times the 2D model's peak allocated inference memory. v3 used 1.41 times Standard's memory. Median resident-model latency over five repetitions was 0.1452 s for v3 and 0.1552 s for Standard. These measurements establish the memory/latency values for this case and protocol; they do not establish a general speed advantage.

The course's cost question is only partly measured. The controlled table concerns inference on factor-two-downsampled volumes, not a matched training-memory/time experiment. It therefore neither demonstrates a 5-10-fold training penalty nor estimates full-resolution deployment cost. v3 completed its recorded 50-epoch training job in 02:02:48, including Validation and checkpoint IO; that job wall time is not a controlled comparison of architecture-only training speed.

4.4 Validation diagnostics and limits of causal attribution

The earlier v1 had worse Body HD95 than Standard in all 38 Validation volumes; their medians were 76.61 and 4.75 mm. With v1 weights fixed, replacing the combined output by the main head alone changed patient-equal Validation small-organ Dice from 0.8420 to 0.2414 and median Body HD95 from 76.61 to 108.96 mm. The result documents dependence on the trained combined output; it does not show what a separately trained main-head architecture would achieve.

The fixed-weight four-case inference experiment also had nonuniform organ outcomes. On K018_Week4, sliding windows reduced distant Body FP from 58,078 to 18,650 voxels while the within-volume mean of the three small-organ Dice values fell from 0.7610 to 0.7158. The corresponding small-organ means also fell on K008_Week0 but rose on B040_Week4 and J026_Week4. These were four selected Validation cases, not an all-38 protocol comparison. A separate head-replay control failed its numerical-equivalence threshold, so its replay outputs were not accepted as mechanistic evidence.

v3 changed InstanceNorm to GN1 within the v1 architecture. Its selected Validation Body median decreased to 4.58 mm and its small-organ score increased to 0.8564. This is the outcome of the recorded training comparison; without independent-seed replication or a successful mechanism-isolating control, it does not establish a unique causal explanation for v1's distant predictions. The exposure audit was not followed by an edge-sampling training run. A1/L/S were trained, but none exceeded the original v3 Validation score. Consequently, the report does not attribute the remaining errors to untested anatomy, loss, padding or data-exposure causes. Original head/window JSON hashes and the reported diagnostic values are retained under `report_diagnostic_summaries` in `evidence/provenance.json`.

4.5 Patient-level variation and evaluation limitations

v3 exceeded Standard's primary Validation score for five of six patients, but exceeded its existing Test score for only three of six. Removing M015 changed the Test small-organ contrast from +0.0294 to approximately -0.0050. The same-recipe C run had Validation Dice 0.8542 rather than v3's 0.8564, while its Test prostate Dice was higher, 0.7633 rather than 0.7485. These recorded differences prevent ranking v3 first for every patient, metric or repeated run.

Checkpoints were selected using Validation, but Test was subsequently inspected repeatedly. No new holdout, external cohort or independent-seed study was completed. The Test set contains six patient units with 30 correlated visits; the report's patient-equal summaries avoid counting those visits as 30 independent patients. The current data do not estimate reliability in a different hospital or patient population.

4.6 Engineering recommendation for the recorded prototype

For the coursework prototype, retain v3 under the original Validation small-organ selection rule and retain Standard as the implemented baseline. The observed v3 advantages are higher average Test foreground Dice and a lower median prostate HD95. The observed regressions include worse maximum prostate/rectum HD95, more internal prostate gaps than Standard and more distant Body FP. A decision based only on the average Dice would omit those regressions.

Do not use these results as evidence for unattended radiotherapy contouring. If the prototype is used to generate contours for research review, explicitly inspect superior/inferior prostate slices, predictions entering labelled bladder/rectum regions, and disconnected/distant predictions. This is a recommendation based on the recorded errors; correction time, clinician agreement and dose effects were not measured. Any further model experiment should use Train/Validation, retain a new patient-independent final assessment and repeat the comparison across seeds. No performance improvement from those future actions is claimed here.

Recorded error	Consequence for this prototype	Review action before accepting a research contour
Base-region mean slice Dice about 0.51; W029_Week6 below 0.22 for both models	Whole-prostate Dice does not describe end-slice placement	Inspect physical superior/inferior extent and each end-region contour against MRI
v3 labels 0.580% of GT Bladder/Rectum voxels as Prostate versus 0.485% for Standard	The measured class confusion persists despite higher average prostate Dice	Inspect the prostate boundary next to bladder and rectum; the recorded proxy cannot certify wall separation
v3 maximum prostate HD95 115.37 mm and 81,145 distant Body FP voxels in Test	Typical surface scores omit large individual errors and distant components	Inspect the full 3D field and disconnected predictions, rather than only a central slice
M015_Week7 bladder Dice remains 0.5224 with v3	Improvement over Standard does not make this case a reliable automatic draft	Review target localisation and missing bladder extent; manual correction burden is unmeasured

5. Artificial Intelligence Usage Disclosure

ChatGPT/Codex assisted with scaffolding/refactoring, debugging, audits, metric checks, literature interpretation, plotting and report drafting, including the standalone submission packaging. Verification included source/weight hashes, historical initialization and actual-weight CPU logit parity, paired geometry/metric tests, all-head gradients, recovery equivalence and recomputation from integer confusion counts. Historical GPU audits reproduced fixed predictions; the standalone migration replay also reproduced all 76 Validation matrices with matching input/weight/source identities. No new training or Test decoding was performed for that migration check. Failed controls and negative experiments were not converted into positive findings. The student remains personally responsible for every formula/code line, understanding the work and responding to reviewers; this disclosure is not independent certification of all AI output.

References

1. Ronneberger, Fischer and Brox. *U-Net: Convolutional Networks for Biomedical Image Segmentation*. 2015. https://arxiv.org/abs/1505.04597

2. Cicek et al. *3D U-Net: Learning Dense Volumetric Segmentation from Sparse Annotation*. 2016. https://arxiv.org/abs/1606.06650

3. Isensee et al. *Brain Tumor Segmentation and Radiomics Survival Prediction: Contribution to the BRATS 2017 Challenge*. 2018. https://arxiv.org/abs/1802.10508

The project attributes its encoder-decoder/skip design to [1], volumetric U-Net context to [2], and residual context/multiscale supervision to [3]. GroupNorm, width, objective and preprocessing are project-specific choices; this implementation is not an exact reproduction or an empirical validation of the papers' original systems. The package refactors this project's own verified implementation, not an externally pretrained model. Retain attribution when reusing components.

Appendix A. Software environment and reproduction commands

A.1 Dependencies and installation

The tested local CPU environment is Python 3.11.16, PyTorch 2.13.0+cpu, NumPy 2.4.6, SciPy 1.17.1, nibabel 5.4.2 and Matplotlib 3.11.0. `requirements.txt` pins core packages. Historical GPU records specify Python 3.11.15, PyTorch 2.13.0+cu130 and NumPy 2.4.6 on A100; not all historical auxiliary versions were recorded. These CPU package versions are not a complete record of the historical GPU environment. Install the official CUDA PyTorch wheel compatible with your compute environment; numerical replay is separately verified. The installation command below is the documented procedure, not evidence that a fresh isolated CUDA installation was tested.

The imported local versions and nine-test result are recorded in evidence/local_environment.json. This CPU check validates the package's tests and count-recalculation example; the separate GPU replay in A.4 validates agreement with the historical Validation predictions.

The documentation replay on 22 October captured the following environment directly. It is an exact record of that replay environment, not a reconstruction of every earlier training environment.

Component	Local CPU verification	GPU documentation replay, job 686318
Python	3.11.16	3.11.15
PyTorch	2.13.0+cpu	2.13.0+cu130
CUDA build / GPU	Not available	13.0 / NVIDIA A100-PCIE-40GB
NumPy / SciPy	2.4.6 / 1.17.1	2.4.6 / 1.17.1
nibabel / Matplotlib	5.4.2 / 3.11.0	5.4.2 / 3.11.2
Pillow	Not captured in the local verification record	12.3.0

GPU versions, source hashes, the actual command and prediction checks are retained in evidence/documentation_replay.json. Library differences are recorded rather than treated as interchangeable proof of a fresh installation.

```
cd recognition/HipMRI_UNet_s4906923
python -m pip install -r requirements.txt
python -B -m unittest discover -s tests -v
```

In the existing Windows Conda environment, `MKL_THREADING_LAYER=SEQUENTIAL` and `OMP_NUM_THREADS=1` avoided an OpenMP runtime conflict; do not use a duplicate-runtime override. Run GPU training on allocated compute nodes, not the login node. The recorded v3 submission requested one A100, two CPU cores and a six-hour job limit; the job completed in 02:02:48. The requested limit is not an observed runtime.

A.2 Training, checkpoint storage and recovery

```
python -B train.py train --model standard --dataset-root /path/to/HipMRI_Study_open --run-dir
/path/to/new_standard --device cuda
python -B train.py train --model v3 --dataset-root /path/to/HipMRI_Study_open --run-dir /path/to/new_v3 --device
 cuda
```

Training only decodes Train/Validation. Test filenames are enumerated for cohort validation but Test arrays are not loaded. Each completed batch atomically saves `latest.pt` with optimizer, RNG and position. Validation improvements save `best.pt`; epoch JSON and `training.png` are retained. `--keep-epoch-weights` additionally retains all epoch weights if space permits. Compact default storage differs from historical retention, not the mathematical recipe.

```
python -B train.py train --model v3 --dataset-root /path/to/HipMRI_Study_open --run-dir /path/to/new_v3 --device
 cuda --resume
```

Resume requires the same source/config/runtime identity and submission-format recovery files. It does not mutate historical research runs. Two writers are rejected by `.writer.lock`; after a force-kill, confirm no writer remains before removing that stale lock. New 50-epoch training is not required to evaluate existing selected weights.

A.3 Fixed-checkpoint evaluation and prediction export

Supply trusted local checkpoints explicitly; weights are excluded from Git. The selected checkpoint hashes appear in `evidence/experiments.json`. Existing private backups can be used in place without copying into this folder. Historical files contain Python optimizer/RNG objects: load only trusted checkpoints.

```
python -B train.py evaluate --model v3 --dataset-root /path/to/HipMRI_Study_open --checkpoint
/path/to/v3/best.pt --split validation --output /path/to/new_validation.json --device cuda
python -B train.py evaluate --model v3 --dataset-root /path/to/HipMRI_Study_open --checkpoint
/path/to/v3/best.pt --split test --output /path/to/new_fixed_test.json --device cuda
python -B predict.py --model v3 --checkpoint /path/to/v3/best.pt --dataset-root /path/to/HipMRI_Study_open
--split validation --case K008_Week0 --output-dir /path/to/new_example --device cuda
```

Use `--model standard` with Standard weights for the baseline. Outputs: `metrics.json`, `overlay.png`, `prediction_downsampled.nii.gz`. Inference uses MRI only; paired GT is used afterwards for metrics/illustration. The exported NIfTI uses the downsampled affine, not original-resolution geometry. Outputs refuse overwrite. Without authorised MRI/weights, use the synthetic tests and inspect the recorded metrics; random weights must not be substituted for experimental results.

Executed example. Job 686318 ran the `predict.py` command above with the recorded v3 `best.pt`, the authorised HipMRI root and Validation case K008_Week0. The process returned 0 and its six-class confusion matrix exactly matched the historical record. Its real outputs were:

```
cli_example_K008_v3/
  metrics.json                   Six-class counts, overlap, physical surfaces and source hashes
  overlay.png                    GT/prediction contours and FP/FN views for five foreground classes
  prediction_downsampled.nii.gz   Predicted labels on the downsampled physical grid
```

The submitted metrics example and actual output panel are copied from this execution. The label volume remains outside Git. For this one volume, Body/Bones/Bladder/Rectum/Prostate Dice are 0.978729/0.891083/0.925819/0.754756/0.824233; these values are not patient-equal cohort scores. The panel selects each class's GT-largest-area and maximum-error axial slices after prediction, rather than using GT to constrain inference. This example verifies executable output and historical agreement; it is not a new generalisation test or a latency benchmark.

A.4 Standalone Validation replay

Before submission, the standalone implementation reproduced all 76 Standard/v3 Validation confusion matrices, input and weight identities, and physical surface measurements. Job 682858 completed in 00:04:49 with exit 0:0 on 21 October 2026, using PyTorch 2.13.0+cu130. All seven package tests passed before that check. The Validation scores were 0.8502228594450512 (Standard) and 0.8563563984705311 (v3). Verification scripts, backup receipts and editorial checks are stored in the separate research archive; they are not needed to run the submitted models. This check establishes agreement with the earlier implementation, not new generalisation or clinical safety.

The later documentation replay, job 686318, completed in 00:00:26 with exit 0:0 on 22 October 2026. It separately ran the submitted prediction CLI on K008_Week0 and reproduced ten fixed Standard/v3 case matrices before rendering Section 3.6. Two of those cases are from the previously inspected Test cohort; their weights, identities and slices were fixed before replay. The operation refreshed presentation and verified the example command; it did not select a new model or add independent Test evidence.

A.5 Report export

```
python -m pip install reportlab==5.0.1
python -B export_report.py
```

`REPORT.pdf` is generated directly from this README and its figures. The feasibility review in Appendix C occupies one dedicated page. Review the export before submitting; this command does not upload to Turnitin.

A.6 Worked example without MRI or weights

The saved K008_Week0 Validation record can be recalculated locally with the submitted command below. This reads the historical confusion counts; it does not rerun the network or generate a new mask.

```
python -B train.py inspect-record --model v3 --split validation --case K008_Week0 --output
/path/to/new_record.json
```

The actual exported example is evidence/example_K008_v3_record.json. It identifies epoch 50, the input/checkpoint hashes, a 128x128x64 downsampled XYZ grid and spacings 3.515625, 3.515625, 3.1199951171875 mm. Prostate TP=1,034, FP=242 and FN=199 give `Dice = 2068/2509 = 0.8242327621` and `IoU = 1034/1475 = 0.7010169492`. These are one-volume values, not the patient-equal cohort score. The command recalculates overlap and copies the recorded surface distances; surface distances cannot be reconstructed from a confusion matrix alone. It refuses to overwrite an existing export. The separate MRI/weight-based command in A.3 is required to create a new prediction volume and panel.

Appendix B. Evidence files and assessment checklist

```
HipMRI_UNet_s4906923/
  modules.py             PyTorch-only Standard/v3 components
  dataset.py             Fixed patient split, paired preprocessing and sampling
  train.py               Direct model imports, training, Validation and fixed evaluation
  predict.py             Saved-model example, metrics, overlay and NIfTI export
  utils.py               Loss, inference, overlap and physical boundaries
  config/                Fixed patient split and training settings
  tests/                 Synthetic data, geometry, model and recovery tests
  evidence/              Ten-model count records, CSVs and source identities
  figures/               Method, curves, comparison, five real case studies and CLI example
  README.md              This report, with a companion PDF export
```

The runtime has no import/path dependency on `20261017`, 2D or retired models. `evidence/experiments.json` preserves 500 epoch summaries and 680 best-model/case entries; the stored confusion counts allow readers to recalculate overlap metrics. The archived research checks verified 400 foreground metric values, checkpoint selection and five original

figure hashes. Those original multi-model panels now reside in the research archive; six focused Standard/v3 panels cover the same five cases in this report. The documentation receipt records their fixed-prediction replay, the CLI example and exact GPU environment. Source/checkpoint identities preserve research provenance without submitting MRI volumes or parameter files. Packaging does not overwrite historical metrics.

The current nine-test suite covers split leakage rejection, NIfTI pairing, spatial resampling, label retention, padding/crop inversion, patient aggregation, anisotropic distances/empty masks, both models' gradients/loading, direct model construction in the trainer, interrupted-versus-uninterrupted optimizer recovery, and MRI-free count export with known metrics and overwrite rejection. A synthetic 211-case file-list fixture ran the predict CLI end to end; it is not a research cohort or a performance result. Earlier tests also checked actual downloaded best-weight logits against historical implementations. The separate real-MRI GPU verification step passed for all 76 Validation model/case comparisons. The replayed model/data/metric files subsequently received prose-only edits; their executable syntax trees remain unchanged. The new `inspect-record` mode in the trainer is separately tested and does not alter training or inference calculations. Comparison records are retained with the research archive.

Coursework requirement	Included evidence or remaining action
Hard volumetric residual model and deep supervision	Model code, architecture explanation, all-head gradients and six-class results
Implemented baseline, same split	Standard/v3, fixed split and input/weight identities
Per-class DSC/IoU and resource profiling	Six-class table, boundaries, parameters/VRAM/latency
Boundary/context dilemma and 3-5 failures	Five original MRI cases, prostate ends, OAR/slice diagnostics, recommendation
Modular code and reproducibility	Five required files, dependencies, commands and tests
Progressive originality	Existing staged Git history; adapted literature listed in References
No datasets/model files in Git	Code, count records and selected report visuals only
Feasibility hurdle	Student confirmed completion on 22 October 2026; original written version lost; Appendix C is a retrospective reconstruction
Upstream PR and code-review response	Lodge to upstream topic-recognition before the applicable deadline; respond during later feedback window
Turnitin	Submit PDF export of this README; confirm it matches the final committed report

The student confirmed that the practical check-off had already been completed, describing it as "last Tuesday" in the confirmation received on 22 October 2026. An exact check-off date and tutor feedback are not reconstructed from that relative date. Before submission, complete the course PR and Turnitin upload and check the applicable Blackboard deadline. The requirements above follow the local 21-page COMP3710 draft specification; follow any later teaching-team instructions.

Appendix C. Feasibility review

Status and provenance. This is a retrospective reconstruction and update, not the lost original one-page review. On 22 October 2026 the student confirmed that the practical check-off had already been completed (described as "last Tuesday"). The original direction was retained, but the planned maximum of five models expanded to ten completed runs. No exact consultation date, original wording, tutor feedback or original numerical budget is inferred from that confirmation.

User need and scope. Evaluate a six-class improved 3D contouring prototype against an implemented baseline on supplied downsampled HipMRI. The comparison records patient-level splits, prostate precision, base/apex overlap, surface errors and disconnected predictions alongside whole-organ overlap.

Five review criteria and current evidence. (1) Patient-disjoint lists and paired geometry/labels pass checks: 143/143 Train volumes passed the recorded pipeline audit. (2) Implement residual volumetric context and multiscale outputs; report the Hard-route Dice target of 0.7 with explicit aggregation: v3 Test prostate/small-organ means are 0.7485/0.8145, without per-patient attainment. (3) Compare per-class Dice/IoU, physical boundaries and 3-5 failures: Sections 3.2-3.6 provide these, including regressions. (4) Check compute feasibility within the recorded one-A100, two-CPU, six-hour training allocation: v3 completed in 02:02:48; inference peaked at 0.3458 GiB on K008_Week0. Training peak VRAM was not recorded, so inference memory does not substitute for it. (5) Provide executable commands and fixed-checkpoint reproducibility: the standalone code reproduced all 76 Validation confusion matrices. These are present review criteria, not a claim to reproduce the lost original criteria or clinical safety thresholds.

Choice and course concepts. Standard provides volumetric encoder-decoder skip connections. v3 adds residual context, dropout and summed multiscale outputs. Normalisation uses one-group GroupNorm, written GroupNorm(1,C), where C is the number of channels. The work applies 3D convolution, multiclass supervised learning, imbalance weighting and patient-level generalisation analysis. It adapts the three cited papers rather than claiming full reproduction.

Measured outcome. There are 26/6/6 patients and 143/38/30 volumes. Ten formal models completed 50 epochs. Standard/v3 Validation small-organ scores are 0.8502/0.8564; Test scores are 0.7851/0.8145. The reference v3 inference latency was 0.1452 s on K008_Week0. Job wall time includes Validation/checkpoint IO, and neither it nor the one-case profile establishes an architecture-only training-speed comparison.

Risks, budget and fallback. Each evaluation split contains six patients, Test was inspected repeatedly and no independent-seed or external-cohort comparison was completed. Saving every epoch exhausted HPC storage during A0/A1; both runs resumed and completed 50 epochs. The submission trainer saves latest/best by default, with optional epoch weights. Keep Standard as the comparison model. The edge-sampling candidate passed a Train exposure audit but was not trained; no segmentation gain is attributed to that audit. Further evaluation should use new, independent patients rather than reusing Test for tuning.

Next decision. Retain the Validation-selected v3 and Standard baseline for the coursework comparison. Further performance claims require an independent patient assessment; the existing Test cohort cannot provide a new blind selection test. This reconstruction documents the present evidence and the student's consultation confirmation; it is not a replacement copy of the original check-off document.