

API Specification Doc

(Sawit: The Lasy Chance)

Version	Date	Author	Description
1.0		SawitDev	Initial project
1.1	5-Mei-2026	SawitDev	Added version number in response
1.2	23-Mei-2026	SawitDev	Add Vehicle
1.3	8-Juni-2026	SawitDev	Final Version

Methods

1. Client-to-Server API (Gameplay Networking)

Komunikasi antara Klien (COMP-01) dan Server (COMP-02) menggunakan sistem *Remote Event* (satu arah) dan *Remote Function* (dua arah / meminta timbal balik).

RequestHarvestSawit

Method	Request
POST	<pre>{ "TreeID": "String (ID unik objek pohon di map)" }</pre>

Dipicu ketika pemain mengayunkan *Scythe* ke pohon sawit biasa. Server akan memvalidasi jarak dan status *cooldown* pohon sebelum memberikan hasil.

Response

Status	Response
200	<pre>{ "Success": "Boolean (true jika pohon siap dipanen)", "AddedSawit": "Integer (24 jika sukses, 0 jika gagal)", "TotalSawit": "Integer (Jumlah sawit terbaru di leaderstat)", "ErrorMessage": "String (Kosong jika sukses, atau 'Pohon dalam masa cooldown')" }</pre>

2. RequestSellSawit

Dipicu ketika pemain berinteraksi dengan NPC Muis dan memilih opsi dialog untuk menjual seluruh buah sawit yang dibawa.

Request

Method	Request
POST	None

Response

Status	Response
200	<pre>{ "Success": "Boolean (true jika pemain memiliki sawit > 0)", "SawitCleared": "Integer (Jumlah sawit yang dikurangkan menjadi 0)", "CashEarned": "Integer (Jumlah uang yang didapat, hasil panen x 10)", "TotalCash": "Integer (Total uang terbaru di leaderstat pemain)" } "Now you can eat."], "remarks": "serves 2 people" }], "version": "4" }</pre>

3. RequestSpawnCar

Dipicu ketika pemain menahan tombol 'E' pada area *Car Spawner* untuk membeli atau memunculkan mobil sedan seharga 20.000.

Request

Method	URL
POST	None

Response

Status	Response
200	<pre>{ "Success": "Boolean (true jika uang cukup dan area spawn kosong)", "TotalCash": "Integer (Sisa uang pemain setelah dikurangi 20.000)", "ErrorMessage": "String (Kosong jika sukses, atau 'Uang tidak cukup' / 'Area spawn terhalang')"</pre>

4. RequestLogProtectedTree

Dipicu ketika pemain berhasil merobohkan 1 pohon di hutan lindung menggunakan *Chainsaw*. Server akan memperbarui konter bencana secara global.

Request

Method	Request
GET	<pre>{ "TreeID": "String (ID unik pohon lindung)" }</pre>

Type	Params	Values
HEAD URL_PARAM	auth_key <recipe_id>	string number

Response

Status	Response
200	None

Glossary

Conventions

- **Client** - Client application.
- **Status** - HTTP status code of response.
- All the possible responses are listed under 'Responses' for each method. Only one of them is issued per request server.
- All response are in JSON format.
- All request parameters are mandatory unless explicitly marked as [optional]
- The type of values accepted for a *request* parameter are shown the the values column like this [**10**|<any number>] .The | symbol means OR. If the parameter is [optional], the default value is shown in blue bold text, as **10** is written in [**10**|<any number>].

Status Codes

All status codes are standard HTTP status codes. The below ones are used in this API.

2XX - Success of some kind

4XX - Error occurred in client's part

5XX - Error occurred in server's part

Status Code	Description
200	OK
201	Created
202	Accepted (Request accepted, and queued for execution)
400	Bad request
401	Authentication failure
403	Forbidden
404	Resource not found
405	Method Not Allowed
409	Conflict
412	Precondition Failed

413	Request Entity Too Large
500	Internal Server Error
501	Not Implemented
503	Service Unavailable