Assignment 4: Create a private bucket in AWS. Upload a file and check by presigned URL that you can access the file or not.

1. Go to **Search** and search S3.
2. Click on **Create Bucket** and give unique **Bucket Name.**
3. Check **ACLs Disabled(recommended)**.







4. Check **Block all public access** and keep other options as it is**.**
5. Click **Create Bucket.**
6. Click on Bucket name to enter into our bucket.
7. Choose **upload** and **'add files'** or **'add folders'** upload the required files or folders.
8. Click **Upload**, after upload completion click **Close**. Click on the file, copy **object URL** and open it to see if access is denied or not (denied).









9. Go back and select the document, click **Actions** and select **share with a presigned URL**.
10. Set the time limit and click **Create presigned URL**. Now copy the presigned URL and paste on another browser.





Assignment 5: Create a public bucket in AWS. Upload a file and give the necessary permission to check the file URL is working or not.



1. Go to **Search** and search S3.
2. Click on **Create Bucket** and give unique **Bucket Name.**
3. Check **ACLs Enabled**.
4. Uncheck **Block all public access** and check the acknowledgement box. Leave other options as it is.



5. Click **Create Bucket**.
6. Click on Bucket name to enter into our bucket.
7. Choose **upload** and **'add files'** or **'add folders'** upload the required files or folders.



8. Click **Upload**, after upload completion click **Close**. Click on the file, copy **object URL** and open it to see if access is denied or not (denied).





9. Again click on the document, go to **Permissions** and in Access Control List click **Edit**. Click the both checkboxes in **Everyone (public access)**. Check the **I Understand** and click **Save Changes**.
10. Again open the Object URL or refresh it.