# **Amazon S3:**

1. Create a bucket in **Amazon Simple Storage Service (Amazon S3)**. Give a unique bucket name. In object ownership, select **ACLs enabled**. Untick '*Block all public access*'. Select *disabled* in bucket versioning. Select encryption type as server-side encryption with Amazon S3 managed keys. Select *enabled* in bucket key. Select *disable* in object lock.
2. Create a folder. In server-side encryption, do not specify an encryption key.
3. Upload files in the folder. Note the **S3 URI** for the file. Go to the permissions. Edit **Access Control List (ACL)**. Add ***grantee*** to give access for other AWS accounts. Enter *canonical ID* in grantee and select read permission for objects.
4. Go to **Identity and Access Management (IAM)**. Select the user. Go to permissions. Give ***AmazonS3FullAccess*** in permissions policies. Go to security credentials. Create an ***access key***. Download the .csv file having the access key.
5. Install ***AWS CLI*** on your local system.
6. Open a terminal in your local system. Enter the following commands:
    a. **aws configure**

       Here, give your access key details (read from the .csv file downloaded in step 4).
    b. **aws s3 cp s3://<bucket_name>/<filename1>  <filename2>**

       This command is used to download a file from S3.
7. Take necessary screenshots. Delete the file, folder and bucket in S3 after your work is done.