

Computer Science and Engineering
IIIT Kalyani, West Bengal

Compilers Design Laboratory (Spring: 2017 - 2018)

3rd Year CSE: 6th Semester

Assignment - 6

Marks: 15

Assignment Out: 16th March, 2018

Report on or before: 23rd March, 2018

1. Consider the following *context-free grammar*:

Terminals:

```
and (AND) := (ASSIGN) : (COLON) , (COMMA) def (DEF) / (DIV)
. (DOT) else (ELSE) end (END) = (EQ) exit (EXITLOOP) float (FLOAT)
(FLOAT\_CONST) (FORMAT) from (FROM) fun (FUN) >= (GE) global (GLOBAL)
> (GT) (ID) if (IF) int (INT) (INT\_CONST) ( (LEFT\_PAREN)
[ (LEFT\_SQ\_BKT) <= (LE) < (LT) - (MINUS) mod (MOD) * (MULT) <> (NE)
not (NOT) null (NUL) or (OR) + (PLUS) print (PRINT) product (PRODUCT)
read (READ) return (RETURN) -> (RETURNS) ) (RIGHT\_PAREN)
] (RIGHT\_SQ\_BKT) ; (SEMICOLON) skip (SKIP) step (STEP) (STRING) to (TO)
while (WHILE)
```

Note: ID, INT_CONST, FLOAT_CONST are identifier, integer constant and floating point constant. STRING is a string constant. FORMAT are %d %f %s

Non-terminals:

```
prog declList decl typeList varList var sizeList0 sizeList type
typeDef funDef funID fparamList0 pList idP funBody stmtList stmtList0
stmt assignmentStmt dotId readStmt printStmt ifStmt elsePart whileStmt
loopStmt stepPart callStmt returnStmt exp0 exitLoop skip id indxList0
indxList bExp relOP exp actParamList0 actParamList
```

Start symbol: prog

Production Rules

prog	→	GLOBAL declList stmtListO END
declList	→	decl declList
	→	ε
decl	→	DEF typeList END
	→	FUN funDef END
typeList	→	typeList SEMICOLON varList COLON type
	→	varList COLON type
	→	typeDef
varList	→	var COMMA varList
	→	var
var	→	ID sizeListO
sizeListO	→	sizeList
	→	ε
sizeList	→	sizeList LEFT_SQ_BKT INT_CONST RIGHT_SQ_BKT
	→	LEFT_SQ_BKT INT_CONST RIGHT_SQ_BKT
type	→	INT
	→	FLOAT
	→	STRING
	→	NUL
	→	typeDef
	→	ID
typeDef	→	ID ASSIGN PRODUCT typeList END
funDef	→	funID fparamListO RETURNS type funBody
funID	→	ID
fparamListO	→	fparamList
	→	ε
fparamList	→	fparamList SEMICOLON pList COLON type
	→	pList COLON type
pList	→	pList COMMA idP
	→	idP

idP	→	ID sizeListO
funBody	→	declList stmtListO
stmtListO	→	stmtList
	→	ε
stmtList	→	stmtList SEMICOLON stmt
	→	stmt
stmt	→	assignmentStmt
	→	readStmt
	→	printStmt
	→	ifStmt
	→	whileStmt
	→	loopStmt
	→	callStmt
	→	returnStmt
	→	exitLoop
	→	skip
assignmentStmt	→	dotId ASSIGN exp
dotId	→	id
	→	id DOT dotId
readStmt	→	READ FORMAT exp
printStmt	→	PRINT STRING
	→	PRINT FORMAT exp
ifStmt	→	IF bExp COLON stmtList elsePart END
elsePart	→	ELSE stmtList
	→	ε
whileStmt	→	WHILE bExp COLON stmtList END
loopStmt	→	FROM id ASSIGN exp TO exp stepPart COLON stmtListO END
stepPart	→	STEP exp
	→	ε
callStmt	→	LEFT_PAREN ID COLON actParamList RIGHT_PAREN
returnStmt	→	RETURN expO
expO	→	exp
	→	ε
exitLoop	→	EXITLOOP

```

skip    →  SKIP

id      →  ID indxListO

indxListO  →  indxList
           →  ε

indxList  →  indxList LEFT_SQ_BKT exp RIGHT_SQ_BKT
           →  LEFT_SQ_BKT exp RIGHT_SQ_BKT

bExp     →  bExp OR bExp
           →  bExp AND bExp
           →  NOT bExp
           →  LEFT_PAREN bExp RIGHT_PAREN
           →  exp relOP exp

relOP    →  EQ
           →  LE
           →  LT
           →  GE
           →  GT
           →  NE

exp      →  exp PLUS exp
           →  exp MINUS exp
           →  exp MULT exp
           →  exp DIV exp
           →  exp MOD exp
           →  MINUS exp
           →  PLUS exp
           →  exp DOT exp
           →  LEFT_PAREN exp RIGHT_PAREN
           →  id
           →  LEFT_PAREN ID COLON actParamListO RIGHT_PAREN
           →  INT_CONST
           →  FLOAT_CONST

actParamListO  →  actParamList
                →  ε

actParamList   →  actParamList COMMA exp
                →  exp

```

2. Comment in the language is `//`, up to the end of the line.
3. Operator precedence: $\{+-\} < \{*/ \text{ mod} \} < \{-u+u\} < \cdot$.
4. Write *flex-bison* specification for parsing the complete language. There should not be any reported conflict. The precedence of the operators are usual.
5. You have three files: `<roll-no>.6.1`, `<roll-no>.6.y++` and `Makefile`. The name of the executable file should be `myParser`.
6. Prepare a `tar`-archive with the name `<roll-no>.6.tar` containing the `Makefile`, `<roll-no>.6.y++`, `<roll-no>.6.1`. As an example,
`$ tar cvf 13CS01026.6.tar 13CS01026.6.1 13CS01026.6.y++ Makefile`
 Send the `tar`-archive as a report.