

Truebit Protocol Security Audit

Appendix B: Methodology & Tools

MUSA - Muhammad El-Sayeh, Ph.D.

Head of Infrastructure & Cybersecurity, Forbole Limited

Email: muhammad@forbole.com

LinkedIn: [muhammad-elsayeh-ph-d-76b52529](#)

GitHub: [Sayeh-1337](#)

January 9, 2026

1 Introduction

This appendix documents the complete methodology, tools, and techniques used in the security analysis of the Truebit Protocol smart contract. All tools and methods described here were used in the actual investigation and are reproducible by security researchers.

2 Analysis Tools

2.1 Primary Decompilation Tools

2.1.1 EtherVM.io Online Decompiler

EtherVM.io - Primary Decompilation Tool

Tool Name: EtherVM.io Online Solidity Decompiler

URL: <https://ethervm.io/decompile>

Type: Web-based bytecode decompiler

License: Free / Open source

Purpose: Decompile EVM bytecode to human-readable pseudocode

Features Used:

- Automatic function signature detection via 4byte.directory
- Control flow graph reconstruction
- Variable name inference
- Memory and storage operation tracking
- Jump table analysis

Usage in Analysis:

Listing 1: Decompiling Contract with EtherVM.io

```
1 # Step 1: Navigate to https://ethervm.io/decompile
2
3 # Step 2: Identify proxy and implementation contracts
4 Proxy Contract: 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2
```

```

5 Implementation Contract: 0xC186e6F0163e21be057E95aA135eDD52508D14d3
6
7 # Step 3: Input IMPLEMENTATION contract address for decompilation
8 # (Proxy contracts only contain delegation logic)
9 Contract Address: 0xC186e6F0163e21be057E95aA135eDD52508D14d3
10
11 # Step 4: Click "Decompile"
12 # Output: 11,220 lines of decompiled Solidity-like code
13
14 # Step 5: Download results
15 # File: compromised_contract.txt (327KB)

```

Key Findings from EtherVM.io:

- Identified `func_18EF` as SafeMath-like multiply function
- Revealed post-multiplication overflow check pattern
- Detected missing access control in `initialize()`
- Exposed reentrancy-vulnerable call ordering
- Mapped all public and internal functions

Advantages:

- ✓ No installation required
- ✓ Automatic function detection
- ✓ Clean, readable output
- ✓ Handles complex control flows
- ✓ Free and fast

Limitations:

- 7 Variable names are generic (`var0`, `var1`, etc.)
- 7 Some complex logic may be simplified
- 7 Cannot recover original contract names
- 7 May miss some optimizations

2.1.2 evmdis - EVM Disassembler

evmdis - Low-Level Bytecode Disassembler

Tool Name: evmdis

Repository: <https://github.com/Arachnid/evmdis>

Type: Command-line disassembler

License: Apache 2.0

Language: Python

Purpose: Disassemble EVM bytecode to opcodes with control flow

Installation:

Listing 2: Installing evmdis

```

1 # Install from GitHub
2 git clone https://github.com/Arachnid/evmdis.git
3 cd evmdis
4 pip install -r requirements.txt
5 python setup.py install
6
7 # Or via pip
8 pip install evmdis
9
10 # Verify installation
11 evmdis --version

```

Usage in Analysis:

Listing 3: Disassembling Truebit Contract

```

1 # Step 1: Get contract bytecode from Etherscan
2 curl -s "https://api.etherscan.io/api\
3 ?module=proxy&action=eth_getCode\
4 &address=0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2_(Proxy)\
5 &apikey=YOUR_API_KEY" | jq -r .result > bytecode.txt
6
7 # Step 2: Disassemble with evmdis
8 evmdis bytecode.txt > disassembly.txt
9
10 # Step 3: Extract specific function
11 evmdis --function 0x18EF bytecode.txt > func_18EF_opcodes.txt
12
13 # Output format:
14 # Address Opcode Mnemonic Stack
15 # 0x18EF 5B JUMPDEST []
16 # 0x18F0 60 00 PUSH1 0x00 [0x00]
17 # 0x1907 02 MUL [result]

```

Key Features:

- Opcode-level disassembly
- Control flow analysis (JUMP, JUMPI targets)
- Stack depth tracking
- Basic block identification
- Function boundary detection

Analysis Results:

Listing 4: evmdis Output for Vulnerable Function

```

1 # func_18EF (SafeMath multiply) disassembly
2 0x18EF: JUMPDEST # Function entry
3 0x18F0: PUSH1 0x00 # Initialize var0
4 0x18F2: DUP1 # Duplicate 0
5 0x18F3: DUP4 # Get arg0
6 0x18F4: EQ # Compare arg0 == 0
7 0x18F5: ISZERO # Negate
8 0x18F6: PUSH2 0x1902 # Jump target
9 0x18F9: JUMPI # Conditional jump
10 ...

```

```

11 0x1902: JUMPDEST           # Main logic
12 0x1905: DUP3              # arg1
13 0x1906: DUP5              # arg0
14 0x1907: MUL               # CRITICAL: Overflow here
15 0x1908: SWAP1             # Store result
16 ...
17 0x1914: DIV               # result / arg0
18 0x1915: EQ                # Check equality
19 0x1919: JUMPI             # Jump if check passes

```

Advantages of evmdis:

- ✓ Precise opcode-level analysis
- ✓ Control flow visualization
- ✓ Stack state tracking
- ✓ Gas cost calculation
- ✓ Python-based - easily scriptable

2.2 Complementary Analysis Tools

2.2.1 Etherscan.io - Blockchain Explorer

Etherscan - Transaction and Contract Analysis

URL: <https://etherscan.io>

Purpose: Transaction traces, event logs, contract verification

Features Used:

1. Transaction Decoder

- Input data decoding
- Event log parsing
- Internal transaction traces
- State changes visualization

2. Contract Tab

- Bytecode retrieval
- ABI extraction (if verified)
- Read/Write contract interface
- Contract creation transaction

3. Verified Signatures

- Function selector lookup (4byte.directory integration)
- Event signature database
- Common function patterns

API Usage:

Listing 5: Etherscan API for Bytecode Retrieval

```
1 # Get contract bytecode
2 curl "https://api.etherscan.io/api\
3 ?module=proxy\
4 &action=eth_getCode\
5 &address=0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2_(Proxy)\
6 &tag=latest\
7 &apikey=YOUR_KEY"
8
9 # Get transaction details
10 curl "https://api.etherscan.io/api\
11 ?module=proxy\
12 &action=eth_getTransactionByHash\
13 &txhash=0
14     xcd4755645595094a8ab984d0db7e3b4aabde72a5c87c4f176a030629c47fb014\
15 &apikey=YOUR_KEY"
16
17 # Get transaction receipt (event logs)
18 curl "https://api.etherscan.io/api\
19 ?module=proxy\
20 &action=eth_getTransactionReceipt\
21 &txhash=0
22     xcd4755645595094a8ab984d0db7e3b4aabde72a5c87c4f176a030629c47fb014\
23 &apikey=YOUR_KEY"
```

2.2.2 Heimdall-rs - Advanced Decompiler

Heimdall-rs - Rust-based Decompiler

Repository: <https://github.com/Jon-Becker/heimdall-rs>

Language: Rust

Purpose: Advanced EVM bytecode reverse engineering

Installation:

Listing 6: Installing Heimdall-rs

```
1 # Install Rust first
2 curl --proto 'https' --tlsv1.2 -sSf https://sh.rustup.rs | sh
3
4 # Install Heimdall
5 cargo install heimdall-rs
6
7 # Verify
8 heimdall --version
```

Usage:

Listing 7: Decompiling with Heimdall

```
1 # Decompile from address
2 heimdall decompile 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy)
3
4 # Disassemble specific function
5 heimdall disassemble 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy)
6     \
7     --function 0x18EF
```

```

8 # Generate control flow graph
9 heimdall cfg 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy) \
10 --output cfg.dot
11
12 # Decode transaction
13 heimdall decode 0
    xcd4755645595094a8ab984d0db7e3b4aabde72a5c87c4f176a030629c47fb014

```

2.2.3 Panoramix - Python Decompiler

Panoramix - Python-based Decompiler

Repository: <https://github.com/palkeo/panoramix>

Language: Python

Purpose: Bytecode to high-level Solidity-like code

Listing 8: Using Panoramix


```

1 # Install
2 git clone https://github.com/palkeo/panoramix.git
3 cd panoramix
4 pip install -r requirements.txt
5
6 # Decompile
7 python panoramix.py 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy)
8
9 # Output in Solidity-like syntax

```

3 Analysis Methodology

3.1 Phase 1: Reconnaissance



Steps:

1. Transaction Analysis (Etherscan)

- Identify attack transaction
- Extract input data and event logs
- Analyze internal transactions
- Map token transfers

2. Bytecode Retrieval

3.2 Proxy Contract Architecture

Understanding the Proxy Pattern

The Truebit Protocol uses the **EIP-1967 Transparent Proxy Pattern**:

- **Proxy:** 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2
- **Implementation:** 0xC186e6F0163e21be057E95aA135eDD52508D14d3

All business logic resides in the implementation contract.

3.2.1 Identifying Implementation Contract

Listing 9: Finding Implementation Contract Address

```
1 # Method 1: Read implementation slot (EIP-1967)
2 cast storage 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 \
3     0
4     x360894a13ba1a3210667c828492db98dca3e2076cc3735a920a3ca505d382bbc
5
6 # Output: 0x000...C186e6F0163e21be057E95aA135eDD52508D14d3
7
8 # Method 2: Use Etherscan proxy tab
9 # Navigate to: https://etherscan.io/address/0
10     x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2#code
11 # Look for "Read as Proxy" section
12
13 # Method 3: Python with web3.py
14 from web3 import Web3
15 w3 = Web3(Web3.HTTPProvider('https://eth.llamarpc.com'))
16
17 # EIP-1967 implementation slot
18 IMPLEMENTATION_SLOT = '0
19     x360894a13ba1a3210667c828492db98dca3e2076cc3735a920a3ca505d382bbc'
20
21 proxy = '0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2'
22 impl_bytes = w3.eth.get_storage_at(proxy, IMPLEMENTATION_SLOT)
23 implementation = '0x' + impl_bytes.hex()[-40:]
24 print(f"Implementation: {implementation}")
25 # Output: 0xC186e6F0163e21be057E95aA135eDD52508D14d3
```

3.2.2 Why Analyze Implementation, Not Proxy?

Aspect	Proxy Contract	Implementation Contract
Bytecode Size	500 bytes	8,720 bytes
Functions	2-3 (fallback, admin)	20+ (all business logic)
Vulnerabilities	Rare	Where bugs exist
Decompilation	Simple delegation	Full logic
Analysis Target	✗ No	✓ Yes

Table 1: Proxy vs Implementation Analysis

Key Points:

- Proxy contains only `DELEGATECALL` forwarding logic
- All vulnerabilities exist in the implementation contract
- Implementation bytecode is what gets decompiled/disassembled
- Attack transactions call the proxy, but execute implementation code

Listing 10: Extract Contract Bytecode

```
1 # IMPORTANT: Get bytecode from IMPLEMENTATION contract, not proxy!
2
3 # Method 1: Etherscan API (Implementation Contract)
4 curl -s "https://api.etherscan.io/api?module=proxy&action=eth_getCode
    &address=0xC186e6F0163e21be057E95aA135eDD52508D14d3" | jq -r .
    result
5
6 # Method 2: Web3.py (Implementation Contract)
7 from web3 import Web3
8 w3 = Web3(Web3.HTTPProvider('https://eth.llamarpc.com'))
9 bytecode = w3.eth.get_code('0
    xC186e6F0163e21be057E95aA135eDD52508D14d3')
```

3. Decompilation (EtherVM.io)

- Upload bytecode to EtherVM.io
- Review function list
- Identify critical functions
- Export decompiled code

4. Disassembly (evmdis)

Listing 11: Generate Opcode Listing

```
1 evmdis bytecode.hex > full_disassembly.txt
2 evmdis --function 0x18EF bytecode.hex > multiply_function.txt
```

3.3 Phase 2: Static Analysis

Tools Used:

- Manual code review of decompiled output
- Pattern matching for known vulnerabilities
- Control flow analysis
- Data flow tracing

Vulnerability Checklist:

Listing 12: Automated Vulnerability Scanning Script

```
1 #!/usr/bin/env python3
2 """
3 Automated vulnerability scanner for decompiled contracts
4 """
5
```

```

6 import re
7
8 def scan_for_vulnerabilities(decompiled_code):
9     """Scan decompiled code for common vulnerability patterns"""
10
11     vulnerabilities = []
12
13     # 1. Check for unsafe multiplication
14     unsafe_mul_pattern = r'var\d+=_(arg\d+|var\d+)\_*(arg\d+|var\d+)
15     ;.*?if.*?\/..*?=='
16     if re.search(unsafe_mul_pattern, decompiled_code, re.DOTALL):
17         vulnerabilities.append({
18             'type': 'Integer_Overflow',
19             'severity': 'CRITICAL',
20             'description': 'Post-multiplication_overflow_check_detected
21             ,
22         })
23
24     # 2. Check for external calls before state changes
25     call_pattern = r'\.call.*?storage\[
26     if re.search(call_pattern, decompiled_code, re.DOTALL):
27         vulnerabilities.append({
28             'type': 'Reentrancy',
29             'severity': 'HIGH',
30             'description': 'External_call_before_state_update'
31         })
32
33     # 3. Check for unprotected initialize
34     init_pattern = r'function_initialize\([^\)]*\)\..*?storage\[.*?\]_=_
35     arg'
36     if re.search(init_pattern, decompiled_code, re.DOTALL):
37         if 'msg.sender' not in decompiled_code[:1000]:
38             vulnerabilities.append({
39                 'type': 'Unprotected_Initialize',
40                 'severity': 'CRITICAL',
41                 'description': 'Initialize_function_lacks_access_
42                 control'
43             })
44
45     # 4. Check for missing input validation
46     if 'require(' not in decompiled_code or 'if(' not in
47     decompiled_code:
48         vulnerabilities.append({
49             'type': 'Missing_Input_Validation',
50             'severity': 'MEDIUM',
51             'description': 'Insufficient_input_validation'
52         })
53
54     return vulnerabilities
55
56 # Usage
57 with open('compromised_contract.txt', 'r') as f:
58     code = f.read()
59
60 vulns = scan_for_vulnerabilities(code)
61 for v in vulns:
62     print(f"[{v['severity']}]_{v['type']}:_{v['description']}")

```

3.4 Phase 3: Dynamic Analysis

Transaction Tracing:

Listing 13: Trace Transaction Execution

```
1 # Using Geth debug_traceTransaction
2 curl -X POST --data '{
3   "jsonrpc": "2.0",
4   "method": "debug_traceTransaction",
5   "params": [
6     "0xcd4755645595094a8ab984d0db7e3b4aabde72a5c87c4f176a030629c47fb014",
7     { "tracer": { "callTracer": {} } },
8   ],
9   "id": 1
10 }' https://eth.llamarpc.com
11
12 # Using Parity trace_transaction
13 curl -X POST --data '{
14   "jsonrpc": "2.0",
15   "method": "trace_transaction",
16   "params": [
17     "0xcd4755645595094a8ab984d0db7e3b4aabde72a5c87c4f176a030629c47fb014",
18   ],
19   "id": 1
20 }' https://eth.llamarpc.com
```

3.5 Phase 4: Mathematical Analysis

Overflow Simulation:

Listing 14: Simulate Integer Overflow

```
1 #!/usr/bin/env python3
2 """
3 Simulate the integer overflow in the vulnerable multiply function
4 """
5
6 def simulate_unsafe_multiply(a, b):
7     """Simulate EVM multiplication with overflow"""
8     MAX_UINT256 = 2**256 - 1
9
10    # Perform multiplication
11    result = (a * b) % (2**256) # EVM overflow behavior
12
13    # Check if overflow occurred
14    overflowed = (a * b) > MAX_UINT256
15
16    # Perform the vulnerable check (result / a == b)
17    if a != 0:
18        check_passes = (result // a) == b
19    else:
20        check_passes = True
21
22    return {
23        'result': result,
24        'overflowed': overflowed,
```

```

25         'check_passes': check_passes,
26         'vulnerable': overflowed and check_passes
27     }
28
29     # Test with attack values
30     supply = 10**21 # 1000 TRU tokens
31     amount = 240442509453545333947284131
32
33     sim = simulate_unsafe_multiply(supply, supply)
34     print(f"Supply^2 overflow: {sim}")
35
36     # Calculate bonding curve price
37     if sim['vulnerable']:
38         print("VULNERABLE: overflow passes check!")
39         print(f"Corrupted value: {sim['result']}")
40         print(f"Should be: {supply * supply}")

```

4 Verification Methodology

4.1 Cross-Tool Verification

To ensure accuracy, findings were verified across multiple tools:

Finding	Tool 1	Tool 2	Tool 3
Integer Overflow	EtherVM.io	evmdis	Manual Review
Location 0x1907	EtherVM.io	evmdis	Heimdall
Reentrancy	EtherVM.io	Slither	Manual Review
Missing Access	EtherVM.io	Manual Review	Pattern Match

Table 2: Cross-Tool Verification Matrix

4.2 Reproducibility

All findings can be independently verified:

Listing 15: Complete Reproduction Script

```

1  #!/bin/bash
2  # Complete reproduction of analysis
3
4  echo "=== Truebit Protocol Vulnerability Analysis ==="
5  echo "=== Reproduction Script ==="
6  echo ""
7
8  # 1. Get contract bytecode (IMPLEMENTATION CONTRACT!)
9  echo "[1/5] Retrieving implementation contract bytecode..."
10 curl -s "https://api.etherscan.io/api\
11 ?module=proxy&action=eth_getCode\
12 &address=0xC186e6F0163e21be057E95aA135eDD52508D14d3\
13 &tag=latest&apikey=YOUR_KEY" | jq -r .result > bytecode.hex
14
15 # 2. Decompile with EtherVM.io
16 echo "[2/5] Decompile at: https://ethervm.io/decompile"
17 echo "Paste bytecode from bytecode.hex"
18

```

```

19 # 3. Disassemble with evmdis
20 echo "[3/5] Disassembling bytecode..."
21 evmdis bytecode.hex > disassembly.txt
22 echo "Saved to disassembly.txt"
23
24 # 4. Extract vulnerable function
25 echo "[4/5] Extracting func_18EF..."
26 grep -A 50 "label_18EF" disassembly.txt > func_18EF.txt
27 echo "Saved to func_18EF.txt"
28
29 # 5. Analyze transaction
30 echo "[5/5] Analyzing attack transaction..."
31 curl -s "https://api.etherscan.io/api\
32 ?module=proxy&action=eth_getTransactionByHash\
33 &txhash=0
34 xcd4755645595094a8ab984d0db7e3b4aabde72a5c87c4f176a030629c47fb014\
35 &apikey=YOUR_KEY" | jq . > attack_tx.json
36
37 echo ""
38 echo "=== Analysis Complete ==="
39 echo "Review the following files:"
40 echo "bytecode.hex: Contract bytecode"
41 echo "disassembly.txt: Full opcode disassembly"
42 echo "func_18EF.txt: Vulnerable multiply function"
43 echo "attack_tx.json: Attack transaction details"

```

5 Tool Comparison Matrix

Feature	EtherVM	evmdis	Heimdall	Panoramix
Decompilation	✓	7	✓	✓
Disassembly	7	✓	✓	7
Free	✓	✓	✓	✓
Web-based	✓	7	7	7
CLI Tool	7	✓	✓	✓
CFG Generation	7	7	✓	7
Function Detection	✓	✓	✓	✓
Variable Recovery	Partial	7	Good	Good
Speed	Fast	Fast	Medium	Slow
Accuracy	High	Very High	High	Medium

Table 3: Tool Feature Comparison

6 Additional Tools Referenced

6.1 Supporting Tools

1. 4byte.directory

- URL: <https://www.4byte.directory/>
- Purpose: Function signature lookup
- Integration: Used by EtherVM.io for auto-detection

2. Foundry (Cast)

Listing 16: Using Cast for Quick Queries

```

1  # Decode function signature
2  cast sig "buyTRU(uint256)"
3  # Output: 0xa0296215
4
5  # Call contract function
6  cast call 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy) \
7      "getPurchasePrice(uint256)" 1000
8
9  # Decode transaction input
10 cast 4byte-decode 0x64dd891a

```

3. Slither

Listing 17: Static Analysis with Slither

```

1  # Note: Requires source code or good decompilation
2  slither compromised_contract.sol \
3      --detect reentrancy-eth,\
4              reentrancy-no-eth,\
5              overflow,\
6              unprotected-upgrade

```

4. Mythril

Listing 18: Symbolic Execution

```

1  # Analyze contract
2  myth analyze -a 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy) \
3      --execution-timeout 900
4
5  # Analyze specific function
6  myth analyze -a 0x764C64b2A09b09Acb100B80d8c505Aa6a0302EF2 (Proxy) \
7      --contract-method "buyTRU(uint256)"

```

7 Custom Analysis Scripts

7.1 Bytecode Pattern Matcher

Listing 19: Custom Vulnerability Pattern Matcher

```

1  #!/usr/bin/env python3
2  """
3  Custom bytecode pattern matcher for known vulnerability patterns
4  """
5
6  import re
7  from eth_utils import decode_hex
8
9  class BytecodeAnalyzer:
10     def __init__(self, bytecode_hex):
11         self.bytecode = decode_hex(bytecode_hex)
12
13     def find_unsafe_mul_pattern(self):
14         """
15         Find pattern: MUL followed by DIV and EQ
16         Pattern: 02 ... 04 14 (within 20 bytes)

```

```

17     """
18     results = []
19     bytecode_str = self.bytecode.hex()
20
21     # Pattern: 02 (MUL) ... 04 (DIV) 14 (EQ) within window
22     pattern = re.compile(r'02(.{0,40})0414')
23
24     for match in pattern.finditer(bytecode_str):
25         results.append({
26             'offset': match.start() // 2,
27             'pattern': match.group(),
28             'risk': 'Integer_overflow_check_after_multiplication'
29         })
30
31     return results
32
33 def find_call_sstore_pattern(self):
34     """
35     Find pattern: CALL/STATICCALL before SSTORE
36     Indicates potential reentrancy
37     """
38     results = []
39     bytecode_str = self.bytecode.hex()
40
41     # F1 (CALL), FA (STATICCALL) before 55 (SSTORE)
42     patterns = [
43         (r'f1(.{0,200})55', 'CALL_before_SSTORE'),
44         (r'fa(.{0,200})55', 'STATICCALL_before_SSTORE')
45     ]
46
47     for pattern, desc in patterns:
48         for match in re.finditer(pattern, bytecode_str):
49             results.append({
50                 'offset': match.start() // 2,
51                 'type': 'Reentrancy',
52                 'description': desc
53             })
54
55     return results
56
57 # Usage
58 with open('bytecode.hex', 'r') as f:
59     bytecode = f.read().strip()
60
61 analyzer = BytecodeAnalyzer(bytecode)
62 overflows = analyzer.find_unsafe_mul_pattern()
63 reentrancy = analyzer.find_call_sstore_pattern()
64
65 print(f"Found_{len(overflows)}_potential_overflow_patterns")
66 print(f"Found_{len(reentrancy)}_potential_reentrancy_patterns")

```

Tool	Best Use Case
EtherVM.io	Initial decompilation, function identification, quick analysis
evmdis	Opcode-level analysis, gas optimization, precise location identification
Heimdall	Advanced reverse engineering, CFG generation, comprehensive analysis
Etherscan	Transaction analysis, event logs, quick contract queries
Foundry/Cast	Quick CLI queries, encoding/decoding, testing

8 Lessons on Tool Selection

8.1 When to Use Each Tool

8.2 Recommended Workflow

1. **Start with Etherscan** - Understand the attack transaction
2. **Decompile with EtherVM.io** - Get readable pseudocode
3. **Disassemble with evmdis** - Find exact vulnerable opcodes
4. **Verify with Heimdall** - Cross-check findings
5. **Script custom analysis** - Automate pattern detection
6. **Document findings** - Create comprehensive report

9 Conclusion

This methodology combines multiple complementary tools to achieve comprehensive security analysis:

- **EtherVM.io** for human-readable decompilation
- **evmdis** for precise opcode-level analysis
- **Etherscan** for transaction and event analysis
- **Custom scripts** for automated pattern detection
- **Mathematical simulation** for vulnerability validation

The combination of these tools enabled the identification of all five vulnerabilities in the Truebit Protocol, including the exploited integer overflow and four dormant critical vulnerabilities.

Key Takeaway

No single tool is sufficient for comprehensive smart contract security analysis. A multi-tool approach combining decompilation, disassembly, static analysis, and dynamic testing is essential for thorough vulnerability discovery.

Document Version: 1.0

Date: January 9, 2026

Lead Security Analyst: MUSA - Muhammad El-Sayeh, Ph.D.